

# Package ‘optimalcausalities’

March 23, 2021

**Title** Optimal Stochastic Interventions in High-dimensional Data

**Version** 2.0

**Authors**

'Kosuke Imai <imai@harvard.edu> [aut], Rohit <rohitchaudhuri@g.harvard.edu> [aut, cre], Connor Jerzak <cjerzak@g.harvard.edu> [aut, cre]'

**Description** Description here.

**Depends** R (>= 3.3.3)

**License**

Creative Commons Attribution-Noncommercial-No Derivative Works 4.0, for academic use only.

**Encoding** UTF-8

**LazyData** true

**Maintainer** 'Connor Jerzak' <connor.jerzak@gmail.com>

**Imports** Rsolnp, keyATM

**RoxygenNote** 7.1.1

## R topics documented:

analyze_fixedStrategy . . . . .	1
computeQse_conjoint . . . . .	2
computeQse_lda . . . . .	3
computeQ_conjoint . . . . .	4
computeQ_lda . . . . .	5
find_optimalStrategy . . . . .	6
plot_optimalStrategy . . . . .	7
specify_treatmentMechanism . . . . .	7

<b>Index</b>	<b>9</b>
--------------	----------

---

analyze\_fixedStrategy *analyze\_fixedStrategy*

---

## Description

Implements ...

```
analyze_fixedStrategy(  
    specifiedAssignmentMechanism = NULL,  
    hypotheticalAssignmentMechanism = NULL  
)
```

dfm 'document-feature matrix'. A list ...

- Items.

```
#set seed
set.seed(1)

#Generate data
x <- rnorm(100)
```

computeQse_conjoint	<i>computeQse_conjoint</i>
---------------------	----------------------------

```
computeQse_conjoint(  
  FactorsMat,  
  Yobs,  
  hypotheticalProblList,  
  assignmentProblList,  
  log_pr_w = NULL,  
  hajek = T,  
  returnLog = T,  
  log_treatment_combs = NULL  
)
```

dfm 'document-feature matrix'. A list ...

**Value**

A list consiting of

- Items.

**References**

- Kosuke, Rohit, Connor. Working Paper.

**Examples**

```
#set seed
set.seed(1)

#Geneate data
x <- rnorm(100)
```

---

computeQse\_lda

*computeQse\_lda*


---

**Description**

Implements ...

**Usage**

```
computeQse_lda(
  THETA__,
  INDICES_,
  DOC_INDICES_U,
  D_INDICES_U,
  PI_MAT_INPUT,
  MARGINAL_BOUNDS,
  DOC_LIST,
  MODAL_DOC_LEN,
  TERMS_MAT_INPUT,
  LOG_TREATCOMBS,
  YOBS,
  returnLog = T,
  LOG_PR_W = NULL
)
```

**Arguments**

dfm                    'document-feature matrix'. A list ...

**Value**

A list consiting of

- Items.

## References

- Kosuke, Rohit, Connor. Working Paper.

## Examples

```
#set seed
set.seed(1)

#Generate data
x <- rnorm(100)
```

---

computeQ_conjoint	<i>computeQ_conjoint</i>
-------------------	--------------------------

---

## Description

Implements ...

## Usage

```
computeQ_conjoint(
  FactorsMat,
  Yobs,
  assignmentProbList,
  hypotheticalProbList = NULL,
  se_ub = NULL,
  split1_indices = NULL,
  split2_indices = NULL,
  computeSEs = F,
  openBrowser = F,
  hajek = T,
  findMax = T,
  quiet = T
)
```

## Arguments

dfm                    'document-feature matrix'. A list ...

## Value

A list consiting of

- Items.

## References

- Kosuke Imai, Rohit, Connor

**Examples**

```
#set seed
set.seed(1)

#Generate data
x <- rnorm(100)
```

computeQ\_lda

*computeQ\_lda***Description**

Implements ...

**Usage**

```
computeQ_lda(
  DTM_MAT,
  n_fold = 3,
  Yobs,
  topicProportions,
  document_list,
  wordTopicDistributions,
  se_ub = sd(Yobs)/10,
  split2_indices = NULL,
  split1_indices = NULL,
  computeSEs = T,
  findMax = T,
  nboot = 10,
  trim_q = 1,
  maxWt = 1e+10,
  maxWt_hajek = NULL,
  alphaLevel = 0.05,
  openBrowser = F
)
```

**Arguments**

dfm                    'document-feature matrix'. A list ...

**Value**

A list consiting of

- Items.

**References**

- Kosuke Imai, Rohit, Connor

## Examples

```
#set seed
set.seed(1)

#Generate data
x <- rnorm(100)
```

---

find_optimalStrategy	<i>find_optimalStrategy</i>
----------------------	-----------------------------

---

## Description

Implements ...

## Usage

```
find_optimalStrategy(specifiedAssignmentMechanism = NULL, cubeConstraint = F)
```

## Arguments

dfm                    'document-feature matrix'. A list ...

## Value

A list consiting of

- Items.

## References

- Kosuke Imai, Rohit, Connor

## Examples

```
#set seed
set.seed(1)

#Generate data
x <- rnorm(100)
```



**Value**

A list consisting of

- Items.

**References**

- Kosuke Imai, Rohit, Connor

**Examples**

```
#set seed  
set.seed(1)
```

```
#Generate data  
x <- rnorm(100)
```



# Index

`analyze_fixedStrategy`, [1](#)

`computeQ_conjoint`, [4](#)

`computeQ_lda`, [5](#)

`computeQse_conjoint`, [2](#)

`computeQse_lda`, [3](#)

`find_optimalStrategy`, [6](#)

`plot_optimalStrategy`, [7](#)

`specify_treatmentMechanism`, [7](#)