

Package ‘optimalcausalities’

March 23, 2021

Title Optimal Stochastic Interventions in High-dimensional Data

Version 2.0

Authors

'Kosuke Imai <imai@harvard.edu> [aut], Rohit <rohitchaudhuri@g.harvard.edu> [aut, cre], Connor Jerzak <cjerzak@g.harvard.edu> [aut, cre]'

Description Description here.

Depends R (>= 3.3.3)

License

Creative Commons Attribution-Noncommercial-No Derivative Works 4.0, for academic use only.

Encoding UTF-8

LazyData true

Maintainer 'Connor Jerzak' <connor.jerzak@gmail.com>

Imports Rsolnp, keyATM

RoxygenNote 7.1.1

R topics documented:

analyze_fixedStrategy	2
computeQse_conjoint	2
computeQse_lda	3
computeQ_lda	4
find_optimalStrategy	5
optimizeQ_conjoint	6
optimizeQ_lda	7
plot_optimalStrategy	8
specify_treatmentMechanism	9

Index	10
--------------	-----------

`analyze_fixedStrategy` *analyze_fixedStrategy*

Description

Implements ...

Usage

```
analyze_fixedStrategy(  
  specifiedAssignmentMechanism = NULL,  
  hypotheticalAssignmentMechanism = NULL  
)
```

Arguments

`dfm` 'document-feature matrix'. A list ...

Value

A list consiting of

- Items.

References

- Kosuke Imai, Rohit, Connor

Examples

```
#set seed  
set.seed(1)  
  
#Geneate data  
x <- rnorm(100)
```

`computeQse_conjoint` *computeQse_conjoint*

Description

Implements ...

Usage

```
computeQse_conjoint(
  FactorsMat,
  Yobs,
  hypotheticalProbList,
  assignmentProbList,
  log_pr_w = NULL,
  hajek = T,
  returnLog = T,
  log_treatment_combs = NULL
)
```

Arguments

dfm 'document-feature matrix'. A list ...

Value

A list consiting of

- Items.

References

- Kosuke, Rohit, Connor. Working Paper.

Examples

```
#set seed
set.seed(1)

#Geneate data
x <- rnorm(100)
```

computeQse_lda

computeQse_lda

Description

Implements ...

Usage

```
computeQse_lda(
  THETA__,
  INDICES_,
  DOC_INDICES_U,
  D_INDICES_U,
  PI_MAT_INPUT,
  MARGINAL_BOUNDS,
  DOC_LIST,
```

```

    MODAL_DOC_LEN,
    TERMS_MAT_INPUT,
    LOG_TREATCOMBS,
    YOBS,
    returnLog = T,
    LOG_PR_W = NULL
  )

```

Arguments

dfm 'document-feature matrix'. A list ...

Value

A list consiting of

- Items.

References

- Kosuke, Rohit, Connor. Working Paper.

Examples

```

#set seed
set.seed(1)

#Geneate data
x <- rnorm(100)

```

computeQ_lda

computeQ_lda

Description

Implements ...

Usage

```

computeQ_lda(
  theta = NULL,
  term_mat,
  Yobs,
  doc_words,
  dtm = NULL,
  pi_mat = NULL,
  alpha_mat = NULL,
  log_pr_w = NULL,
  computeSE = F,
  trim_q = 1,
  quiet = T,
  iters = 100,

```

```

    smoothWts = F,
    TreatFxn = NULL,
    maxWt = 1e+10,
    maxWt_hajek = NULL,
    term_mat_TRUE = NULL,
    doc_indices_u = NULL,
    d_indices_u = NULL,
    diagnostics = F
  )

```

Arguments

dfm 'document-feature matrix'. A list ...

Value

A list consiting of

- Items.

References

- Kosuke, Rohit, Connor. Working Paper.

Examples

```

#set seed
set.seed(1)

#Geneate data
x <- rnorm(100)

```

find_optimalStrategy *find_optimalStrategy*

Description

Implements ...

Usage

```
find_optimalStrategy(specifiedAssignmentMechanism = NULL, cubeConstraint = F)
```

Arguments

dfm 'document-feature matrix'. A list ...

Value

A list consiting of

- Items.

References

- Kosuke Imai, Rohit, Connor

Examples

```
#set seed
set.seed(1)

#Generate data
x <- rnorm(100)
```

optimizeQ_conjoint	<i>computeQ_conjoint</i>
--------------------	--------------------------

Description

Implements ...

Usage

```
optimizeQ_conjoint(
  FactorsMat,
  Yobs,
  assignmentProbList,
  hypotheticalProbList = NULL,
  se_ub,
  INDICES_SPLIT1 = NULL,
  INDICES_SPLIT2 = NULL,
  computeSEs = F,
  openBrowser = F,
  hajek = T,
  doMax = T,
  quiet = T
)
```

Arguments

dfm 'document-feature matrix'. A list ...

Value

A list consisting of

- Items.

References

- Kosuke Imai, Rohit, Connor

Examples

```
#set seed
set.seed(1)

#Geneate data
x <- rnorm(100)
```

optimizeQ_lda

*computeQ_lda***Description**

Implements ...

Usage

```
optimizeQ_lda(
  INDICES_SPLIT1 = NULL,
  INDICES_SPLIT2 = NULL,
  DTM_MAT,
  n_fold = 3,
  YOBS,
  PI_MAT,
  DOC_LIST,
  TERMS_MAT,
  SE_UB = sd(YOBS)/10,
  nboot = 10,
  trim_q = 1,
  maxWt = 1e+10,
  maxWt_hajek = NULL,
  computeSEs = T,
  doMax = T,
  alphaLevel = 0.05,
  openBrowser = F
)
```

Arguments

dfm 'document-feature matrix'. A list ...

Value

A list consiting of

- Items.

References

- Kosuke Imai, Rohit, Connor

Examples

```
#set seed
set.seed(1)

#Generate data
x <- rnorm(100)
```

plot_optimalStrategy *plot_optimalStrategy*

Description

Implements ...

Usage

```
plot_optimalStrategy(
  specifiedAssignmentMechanism = NULL,
  hypotheticalAssignmentMechanism = NULL
)
```

Arguments

dfm 'document-feature matrix'. A list ...

Value

A list consiting of

- Items.

References

- Kosuke Imai, Rohit, Connor

Examples

```
#set seed
set.seed(1)

#Generate data
x <- rnorm(100)
```

specify_treatmentMechanism
specify

Description

Implements ...

Usage

```
specify_treatmentMechanism(Yobs, W, PrW_parameters = list())
```

Arguments

dfm 'document-feature matrix'. A list ...

Value

A list consiting of

- Items.

References

- Kosuke Imai, Rohit, Connor

Examples

```
#set seed
set.seed(1)

#Geneate data
x <- rnorm(100)
```

Index

`analyze_fixedStrategy`, [2](#)

`computeQ_lda`, [4](#)

`computeQse_conjoint`, [2](#)

`computeQse_lda`, [3](#)

`find_optimalStrategy`, [5](#)

`optimizeQ_conjoint`, [6](#)

`optimizeQ_lda`, [7](#)

`plot_optimalStrategy`, [8](#)

`specify_treatmentMechanism`, [9](#)