WALKWORTHY: A Method-Major Benchmark Family for Measuring Behavioral Accordance with a Declared Corpus of Christian Ethics

Descriptive MVP manuscript — not release-grade evidence

Anonymous manuscript

14 July 2026

Abstract Existing language-model ethics benchmarks typically ground correctness in aggregated human judgment, survey distributions, or tradition-neutral dilemmas. We present WALKWORTHY, a ten-design benchmark family for measuring whether model behavior—advice trajectories, allocations, drafts, paired decisions, and multi-turn counsel—accords with the consensus moral teaching of a declared fifteen-work corpus of Christian ethics. The construct is intentionally narrow: accordance with this corpus, never whether a model is ethical or Christian. The artifact contains 356 authored public items, of which 344 are runnable, plus a 158-item private holdout equal to 33.4% of 473 authored seed cases. It spans fourteen ethics areas and uses a three-stratum ground-truth schema with registered treatment of intra-corpus disputes and a deliberately unpopulated contested tier. Ten validity gates and a per-design release formula were frozen before the full-panel scores they govern existed. A six-model panel completed 2,064 of 2,064 records. To make the paper shape reviewable before release validation, a separately registered exploratory MVP executed 60 PUBLIC items across three inexpensive systems and two inexpensive, unvalidated judges: 180 item-by-system executions, 480 logical units per judge, 1,715 custody-paired attempts, and $0.551363883 in conservatively booked exposure. Exact cheap-judge agreement ranged from 17.59% to 88.89% by design; these values are operational compatibility evidence, not accuracy, ranking, or validity. At manuscript freeze, all 439 Part-A human-label rows remained blank, 1,174 Part-B cells remained for human adjudication, and perturbation robustness had no computed flip rate. We therefore report the artifact, governance, descriptive feasibility, and complete exploratory MVP shape while withholding release-grade model claims.

Contents

1. Introduction 3
1.1 Contributions 3
1.2 What this paper is not 4
1.3 Paper organization 4
2. Related Work 4
2.1 Machine-ethics and values benchmarks 4
2.2 Religious and cultural values evaluation 5
2.3 Say–do evaluation and multi-turn behavioral consistency 5
2.4 LLM-as-judge methodology and its validity critiques 6
2.5 Benchmark validity, governance, and contamination 6
2.6 Summary of positioning 7
3. Benchmark Construction 7
3.1 The Construct: Behavioral Accordance with a Declared Corpus 7
3.2 Source Registry: The “Whose Values” Answer 8
3.3 Ethics-Area Registry 10
3.4 Three-Stratum Ground-Truth Schema 11
3.5 The Ten Method-Major Designs 12
3.6 Item Schema and Counts 13
3.7 Authoring Pipeline and Quality Control 14
4. Measurement and Validity Methodology 14

4.1 Design principles 15
4.2 Per-design primary statistics 15
4.3 Judging architecture 16
4.4 Refusal accounting 17
4.5 Human labeling 17
4.6 The ten validity gates 18
4.7 The release formula 19
4.8 What the pilot changed (a pre-registration narrative) 19
5. Experimental Setup 20
5.1 Harness architecture 20
5.2 Model access 20
5.3 System-under-test panel 21
5.4 Runs and cost 21
5.5 Capability battery 22
6. Results 22
6.1 Execution and custody 22
6.2 Adjudication completeness 23
6.3 Provisional gate readings 24
6.4 Mandatory behavioral-gap readings 25
6.5 Exploratory MVP-A1 preview 26
7. Discussion 27
7.1 What pre-registration buys a values benchmark 27
7.2 Tradition-specific does not mean tradition-wide 27
7.3 What the exploratory MVP established 27
7.4 Two label paths that must not be conflated 27
7.5 Behavioral designs and provisional signals 28
7.6 Future work 28
8. Threats to Validity and Limitations 28
8.1 Construct validity 28
8.2 Measurement validity (judges) 28
8.3 Human-label validity 29
8.4 Internal / statistical validity 29
8.5 External validity 29
8.6 Contamination and gaming 30
8.7 What would falsify our validity story 30
9. Ethics Statement 30
9.1 AI-assisted construction and the human ratifier of record 30
9.2 Normative content: a measurement standard, not an endorsement 31
9.3 Foreseeable misuse and misreading 31
9.4 Human subjects 31
9.5 Environmental and cost footprint 31
10. Reproducibility and Contamination Policy 32
10.1 Released versus withheld 32
10.2 Contamination policy 32
10.3 Determinism and provenance 32
10.4 Verification 33
10.5 Reproducibility checklist 33
References 33

Keywords: LLM evaluation · values benchmarks · benchmark validity · pre-registration · LLM-as-judge · religious values · construct validity

Evidence boundary at manuscript freeze (14 July 2026). The exploratory MVP is complete and descriptive. Release-grade O5 results are not complete: Part-A human labels are 0/439, Part-B adjudication remains open, and G7 has no complete battery or flip rate. No model ranking, release claim, or claim that a model is ethical or Christian is made in this manuscript.

1. Introduction

Language models increasingly serve users who hold specific, articulated moral traditions — and who reasonably want to know not whether a model is "aligned" in the abstract, but how it behaves when serving someone from within their tradition: whether its advice, drafts, allocations, and multi-turn counsel accord with what that tradition actually teaches. Existing ethics evaluations largely cannot answer this question. They score models against crowd-sourced judgments, survey distributions, or philosophers' dilemma corpora — ground truths that are either aggregations across traditions or deliberately tradition-neutral. And they overwhelmingly measure *stated* values — what a model says when asked — rather than *enacted* values: what it does across a drafting task, a resource allocation, an escalating request, a counseling conversation.

We present **WALKWORTHY**, a benchmark family that measures the degree to which a model's *behavior* accords with the consensus moral teaching of a named corpus of fifteen works of Christian ethics, as operationalized through item-level anchors citable to specific chapters of those works. The name is the construct: from the Pauline injunction to "walk worthy of the calling," the family measures *walk* (conduct), not *talk* (professed values).

Three design commitments distinguish the effort.

A deliberately narrow construct. WALKWORTHY does not measure whether a model "is ethical" or "is Christian" — we take that construct to be unbenchmarkable in principle, and its claim language is contractually forbidden throughout the project. What is measured is accordance with *this specific corpus*: a declared fifteen-work Source Registry whose consensus and internal disputes are documented claim-by-claim. Where the corpus agrees internally but society polarizes (e.g., sexual ethics, end-of-life questions), items are quarantined in a separately-reported *contested tier* scored as fidelity-and-fair-representation when serving an in-tradition user — with a refusal-quality rubric so that a model that respectfully declines is scored on how it declines, never punished for declining. (The v1 bank ships this contested tier schema-complete but deliberately unpopulated — a disclosed sequencing choice, §3.4.) Where the corpus itself disagrees, items carry dispute tags and any well-executed, registry-attested position earns credit. The corpus's limits (Protestant-dominant; no dedicated Catholic, Orthodox, liberationist, womanist, Pentecostal, or Global-South work) are disclosed in every reporting surface: all claims are indexed to "this corpus," never to "Christianity."

Behavior over profession, method by method. The family's ten designs are *method-major*: each is built around one behavioral elicitation method rather than one topic — cost-ladder obedience decay, multi-turn erosion under pressure, say–do twin comparison, motive-sensitivity deltas, judge-free constrained allocation, rubric-profiled advice, counsel-arc conformance, covert–overt protection gaps, two-seat symmetry, and mercy-delta pairing. Topics (a fourteen-area registry from truth-telling to creation care) cross-cut the methods, so any area × method cell is in principle observable and the reporting spine forbids collapsing them into a single scalar.

Governance before scores. Every validity-relevant decision was frozen before the data that could tempt us to bend it existed. Ten gates — headroom, spread, capability-wash, judge validity against human labels, reference neutrality, lexical shortcut, perturbation robustness, item kills, mandatory gap headlines, and a composite ban — were pre-registered at design time and frozen to exact computations and decision rules before any full-panel score existed. A release formula composes them: a design's scores cannot be published at all until its gates clear, human-label validation of the LLM judges being the release gate (scores land provisional; labels release them). Items are never edited in response to model performance ("fix mechanics only"), and every amendment requires a logged human ruling.

1.1 Contributions

C1 — The artifact. Ten method-major designs; 356 authored public items (344 runnable) plus a 158-item private holdout (33.4% of the 473 authored seed cases), stratified by area, difficulty, authoring wave, and author; a 14-area ethics registry with published coverage matrices; a three-stratum ground-truth schema; a 12-entry intra-corpus dispute registry with per-position credit; and 14 citation-verified anchor packs resolving every item key to work-and-chapter.

C2 — The construct. A corpus-indexed *behavioral accordance* construct that answers "whose values?" by declaration rather than aggregation, with contested-tier separation and dispute-tagging as first-class schema rather than post-hoc caveats.

C3 — The governance. A fully pre-registered gate system with frozen per-design primary statistics, a cross-family judge architecture with home-advantage testing and own-family exclusion, human-label validation waves, an eight-status release vocabulary, and wave-based partial release. We document the gates working as designed: one design already failed its headroom and spread gates on adjudicated data and is excluded from any release this cycle pending difficulty rework — the pipeline treats that as the system functioning, not as a result to suppress.

C4 — The template. The pipeline — declared corpus → area registry → stratum schema → method-major designs → pre-registered gated release — is *designed to instantiate* for any normative tradition with a canonical corpus: the tradition-specific inputs are the registry, the anchor packs, and the dispute table, while the gates, judge architecture, and release machinery are tradition-independent. We claim design portability, not demonstrated generality: exactly one instantiation exists, and demonstrating a second is future work.

C5 — Feasibility and gated evidence. A six-model frontier panel completed 2,064/2,064 records with zero schema errors at an original panel cost under fifty dollars, showing that tradition-specific, validity-gated benchmarking is operationally accessible to small research groups. Section 6 reports the current evidence state: provisional post-W1 readings, the binding design-05 rework disposition, and every remaining release dependency. It reports no design as released and makes no release-grade model claim.

C6 — The exploratory MVP paper shape. A separately registered 60-item PUBLIC subset was executed across three inexpensive systems and two inexpensive, unvalidated judges, with all 180 item-by-system records and 480 logical units per judge retained under complete custody. The resulting values are descriptive evidence about execution, compatibility, coverage, and paper shape; they are not rankings, validated scores, or substitutes for O5.

1.2 What this paper is not

This is a methods-first artifact paper. It is not a leaderboard: the results section separates provisional O5 readings from the descriptive MVP and reports no released model score. It makes no claim that any model is or is not ethical, Christian, or aligned with Christianity — sentences of that form are forbidden by the project's charter regardless of what the data show. And it does not claim the corpus speaks for Christianity; the corpus is the measurement standard, full stop.

1.3 Paper organization

§2 situates the work against published values benchmarks, religious/cultural evaluation, say–do evaluation, LLM-judge validity, and benchmark-governance literature. §3 documents construction: corpus, areas, strata, designs, items, holdout. §4 gives the measurement methodology: judging architecture, human-label protocol, the ten gates, and the release formula. §5 describes the experimental setup. §6 reports the current release-grade evidence state and the separate descriptive MVP preview. §7 discusses. §8 states threats to validity. Ethics and reproducibility statements follow.

2. Related Work

We situate our benchmark family against five strands of prior work: (i) general machine-ethics and values benchmarks; (ii) religious and cultural values evaluation of language models; (iii) say–do and revealed-versus-stated behavioral evaluation; (iv) the LLM-as-judge methodology and its validity critiques; and (v) benchmark validity, governance, and contamination. Our contribution is not a new claim that any prior effort is wrong; each strand supplies a technique or a construct that we adopt, sharpen, or deliberately restrict. What is distinctive about our work is the combination — a *tradition-specific, corpus-indexed, behaviorally operationalized* accordance construct, governed end-to-end by validity gates that are pre-registered before any full-panel score exists. We motivate that combination by showing what each strand supplies and what it leaves open.

2.1 Machine-ethics and values benchmarks

The dominant paradigm for evaluating the moral behavior of language models grounds "correct" answers in aggregated human judgment. The ETHICS benchmark [Hendrycks et al., 2021] collects everyday moral scenarios spanning justice, deontology, virtue, utilitarianism, and commonsense morality, with labels drawn from broadly shared human intuitions. Related resources such as Social Chemistry 101 [Forbes et al., 2020] and Scruples [Lourie et al., 2021] operationalize social and moral norms from large corpora of community judgments (rules-of-thumb and community verdicts on real-life anecdotes, respectively), and the Delphi experiment [Jiang et al., 2021] trains a model to predict such crowd-sourced judgments directly. A second cluster elicits or probes the moral *beliefs* a model reports: MoralChoice [Scherrer et al., 2023] presents low- and high-ambiguity dilemmas and measures which action a model prefers; DailyDilemmas [Chiu et al., 2025] surfaces value preferences through the quandaries of daily life; and moral-foundations analyses [Abdulhai et al., 2023] port Moral Foundations Theory

instruments onto models to characterize their latent moral profile. A third cluster ports opinion and value surveys: OpinionQA [Santurkar et al., 2023] measures whose human opinions a model's responses most resemble, GlobalOpinionQA [Durmus et al., 2023] measures the representation of subjective global opinions, and WorldValuesBench [Zhao et al., 2024] adapts the World Values Survey to test multicultural value awareness. Finally, benchmarks such as MACHIAVELLI [Pan et al., 2023] and Jiminy Cricket [Hendrycks et al., 2021] embed moral choices inside long-horizon interactive text environments, measuring trade-offs between reward-seeking and ethical conduct as an agent acts over many steps.

We build on this literature but differ from it along two axes that jointly define our construct. First, **ground truth**. The efforts above index "correct" against crowd judgment (ETHICS, Social Chemistry, Scruples, Delphi), against a model's own stated preferences (MoralChoice, DailyDilemmas), or against survey-elicited population distributions (OpinionQA, GlobalOpinionQA, WorldValuesBench). Each is a defensible standard, and each is either universalist or majoritarian by design — the ground truth is what people, in aggregate, tend to endorse. We deliberately do not adopt a universalist or crowd-aggregated standard. Our ground truth is a *named, finite, textual corpus* of ethics scholarship within a single tradition, with every item-level anchor citable to a specific chapter of a specific work. The correct behavior for an item is defined by the consensus teaching of that corpus, not by what a crowd endorses or what the model itself prefers. This makes the standard checkable (a reader can consult the cited page), auditable (disagreement within the corpus is registered rather than averaged away), and honest about its scope: we measure accordance with *this corpus*, not "morality" or "a religion" in general. Second, **the operationalized target**. Most values benchmarks measure a *stated* quantity — the answer chosen, the preference reported, the opinion expressed. We measure *enacted* conduct: what a model does when it drafts, allocates, advises across a trajectory, or reasons under pressure, rather than what it says it values when asked directly. The interactive-environment benchmarks (MACHIAVELLI, Jiminy Cricket) share this behavioral emphasis, and we draw on it; our designs extend it from game-world action spaces to natural human situations across a registry of ethics areas, and pair it with a construct definition that refuses the unbenchmarkable claim "model M is ethical."

2.2 Religious and cultural values evaluation

A distinct literature evaluates language models against religious and cultural reference points. Much of it is framed as **bias detection**: Abid et al. [2021] document persistent anti-Muslim associations, and Plaza-del-Arco et al. [2024] catalog stereotyping and stigmatization across religions in model outputs. A second framing is **cultural adaptability and knowledge**: NormAd [Rao et al., 2024] measures whether models adapt judgments to described cultural norms; CultureBank [Shi et al., 2024] and CultureLLM [Li et al., 2024] build culturally grounded knowledge and training signals; BLEnD [Myung et al., 2024] probes everyday knowledge across cultures and languages; CDEval [2023] characterizes models along cultural-dimension axes; and Naous et al. [2024] show that models default to Western associations even in culturally Arab contexts. Faith-specific evaluation is emerging — for example, benchmarks probing reliability and appropriate abstention on Islamic legal rulings [Atif et al., 2025], and analyses of spiritual values and biases in model outputs [Liu et al., 2024] — alongside religion-inclusive moral-evaluation resources such as MoralBench [Ji et al., 2024].

Our aim is orthogonal to bias detection and to knowledge probing, and we are careful not to conflate them. The bias literature asks whether a model treats groups fairly or reproduces stereotypes; the cultural-knowledge literature asks whether a model *knows about* or *adapts to* a norm it is told about. Neither asks the question we ask: does a model's behavior **accord with a declared normative corpus** when it acts within situations that the corpus speaks to? We are not measuring whether the model is biased for or against a tradition, nor whether it can recite the tradition's positions, but whether its enacted conduct is faithful to the consensus teaching of a specific, cited body of that tradition's own ethics scholarship. This reframing carries obligations that bias and knowledge probes do not incur. Because the corpus is a particular selection — in our instantiation, one that is internally acknowledged to be partial — every claim is indexed to "this corpus," never to the tradition as a whole, and this limitation is disclosed as a first-class part of any release. It also requires a principled treatment of positions on which a tradition's internal scholarship agrees but broader society is divided: we route such content to a separate *contested tier* scored on fidelity-to-source and fair representation rather than compliance, so that respectful principled disagreement by a model is never miscounted as failure. To our knowledge, no prior religious-values evaluation both (a) fixes ground truth to a named, page-citable ethics corpus and (b) separates societally polarized doctrine into a distinct fidelity tier with its own refusal accounting.

2.3 Say–do evaluation and multi-turn behavioral consistency

Our behavioral emphasis connects to a growing body of work on the gap between what models *say* and what they *do*. Recent studies directly probe whether models are consistent across stated and revealed preferences [Gu et al., 2025] and ask whether

revealed-preference framings clarify alignment and steering [Yamin et al., 2026]. A related line studies behavioral stability under conversational pressure: sycophancy — models shifting their answers toward a user's expressed view — has been elicited through model-written evaluations [Perez et al., 2023] and characterized in depth [Sharma et al., 2023]; and multi-turn studies show reliability degrading as a conversation progresses [Guo et al., 2026]. At the extreme, work on deceptive persistence shows that behavior conditioned during training can survive safety interventions and surface only under specific triggers [Hubinger et al., 2024], underscoring that a single stated commitment is weak evidence about conduct.

These findings motivate the method-major structure of our family. Rather than a single question format, our designs instantiate specific behavioral probes: **say–do twins** that pose the same underlying moral situation once as a direct question about values and once as a task where the model must act, letting divergence be measured as a first-class metric; **erosion ladders** that apply escalating conversational pressure across turns and measure whether accordance decays; and **paired covert/overt** framings that vary whether the ethically loaded feature of a situation is made salient. Where prior say–do and sycophancy work establishes *that* stated and enacted behavior can diverge and *that* multi-turn pressure degrades conduct, we make that divergence the object of measurement against a fixed normative standard, and we report say–do divergence and refusal behavior (through a four-way taxonomy of helpful compliance, policy-violating compliance, appropriate refusal, and unnecessary refusal) as headline readouts wherever a design's structure permits them.

2.4 LLM-as-judge methodology and its validity critiques

Scoring open-ended, trajectory-level behavior against a rubric is not feasible with exact-match metrics, so we adopt the LLM-as-judge paradigm [Zheng et al., 2023; Liu et al., 2023], in which a strong model applies a rubric to candidate outputs. That paradigm carries well-documented validity risks, which a recent survey consolidates [Gu et al., 2024]. Judges exhibit **position and verbosity biases** — favoring answers by order or length rather than quality [Wang et al., 2023; Wu and Aji, 2023] — and, most consequentially for our setting, **self-preference**: models recognize and favor their own generations [Panickssery et al., 2024], a "home-advantage" effect that can silently inflate a judged system whose family also supplies the judge. Systematic quantifications of judge bias [Ye et al., 2024] reinforce that judge choice is itself a design decision with the power to corrupt conclusions.

We treat these critiques as binding constraints rather than caveats, and our measurement methodology is built around them. Judges are drawn from model *families distinct from the item-generation family*, and at least two judges from different families score every unit; per-category rubrics constrain the judgment; and judge disagreement is published rather than smoothed. To guard against home-advantage specifically, we (a) **freeze a cross-family judge pair before any full-panel scoring**, so the judge configuration cannot be tuned to results; (b) validate judges against **human labels on a stratified sample**, gating any leaderboard claim on adequate agreement measured with an imbalance-robust weighted-agreement statistic rather than raw accuracy; (c) run a **home-advantage permutation test** to detect whether a judged system is scored anomalously by a same-family judge; and (d) resolve escalations through a tie-breaker judge with **own-family exclusion**, so no system is decisively scored by a judge from its own family. These measures do not eliminate judge error; they make it visible and bounded, and — crucially — they are specified before scores exist, so they cannot be relaxed to rescue a favored outcome.

2.5 Benchmark validity, governance, and contamination

A mature critical literature warns that benchmarks routinely over-claim. Construct-validity critiques observe that a single leaderboard number is often taken to measure a general capability it cannot support [Raji et al., 2021], that ranking outcomes can hinge on incidental design choices [Dehghani et al., 2021], and that fairness and evaluation datasets frequently embed unexamined measurement assumptions [Jacobs and Wallach, 2021; Blodgett et al., 2021]. Meta-evaluations of benchmark quality itself — most directly BetterBench [Reuel et al., 2024] — codify best practices and find widespread gaps in documentation, validity evidence, and lifecycle governance; broader surveys of LLM evaluation reach compatible conclusions [Chang et al., 2024; Laskar et al., 2024]. In parallel, a contamination literature shows that test items leak into training data and that this inflates scores: detection and estimation methods have proliferated [Sainz et al., 2023; Golchin and Surdeanu, 2024; Deng et al., 2024; Oren et al., 2024; Yang et al., 2023], the community has adopted **canary strings** to mark evaluation data [Srivastava et al., 2023], and newer benchmarks lean on **private or freshly generated held-out sets** to stay contamination-resistant [Rein et al., 2023; White et al., 2024]. The reproducibility literature adds that leakage is a recurring, easily missed failure mode across ML-based science [Kapoor and Narayanan, 2023]. Documentation practices such as datasheets [Gebru et al., 2021] and model cards [Mitchell et al., 2019], dynamic and adversarial benchmarking [Kiela et al., 2021], holistic multi-metric evaluation [Liang et al., 2022], and pre-registration proposals for NLP and ML research [van Miltenburg et al., 2021] round out the toolkit for building trustworthy evaluations.

We adopt this toolkit and, where it exists as advice, convert it into enforced mechanism. Our benchmark is governed by a suite of validity gates — covering rubric reliability, difficulty calibration, capability-correlation (flagging designs whose score is explained by general capability rather than the target construct), judge agreement, and contamination resistance — that are **pre-registered and frozen to exact computations before any full-panel score exists**. A design's status is determined by a release formula over an explicit status vocabulary: a design may be released, blocked, sent back for rubric or difficulty rework, flagged as capability-washed, or held for judge disqualification, and a fix-mechanics-only discipline forbids editing items in response to which systems scored well. Contamination controls follow the strand's best practice directly: a canary string is embedded in every released file; a substantial fraction of each design's items is withheld as a private holdout that is never published; and a perturbation battery (paraphrase, name-swap, order-swap) is required before any headline claim. Release is *wave-based* — designs clear the gates and enter the public record only as their evidence matures, so that no number is published before its validity is established. Where prior work recommends construct-validity scrutiny, pre-registration, and contamination hygiene as norms an evaluator should follow, our contribution is to bind them into the artifact's release machinery so that failing a gate has a defined, non-negotiable consequence rather than a discretionary one.

2.6 Summary of positioning

Each strand supplies something we use. From machine-ethics benchmarks we take the ambition of measuring moral conduct at scale, while replacing crowd/universalist ground truth with a page-citable corpus and replacing stated preference with enacted behavior. From religious- and cultural-values work we take seriously that traditions differ, while shifting the question from bias or knowledge to *accordance with a declared corpus* and adding a contested-tier treatment for societally polarized doctrine. From say–do and multi-turn work we take behavioral probes and consistency-under-pressure, and make divergence a first-class metric against a fixed standard. From the LLM-as-judge literature we adopt the paradigm and pre-commit to its documented safeguards against self-preference and bias. And from the benchmark-validity, governance, and contamination literature we adopt construct-validity scrutiny, pre-registration, canaries, and private holdouts — and enforce them through frozen gates and a wave-based release formula. No single prior effort combines a tradition-specific corpus-indexed behavioral-accordance construct with pre-registered, gate-governed release; that combination is what we contribute.

3. Benchmark Construction

This section documents how the benchmark artifact was constructed: the construct it operationalizes (§3.1), the corpus that supplies its ground truth (§3.2), the registry of ethics areas it spans (§3.3), the three-stratum ground-truth schema that governs scoring (§3.4), the ten method-major designs that elicit behavior (§3.5), the item schema and counts (§3.6), and the authoring pipeline and quality control that produced the item bank (§3.7). It serves contribution claims C1 (the artifact), C2 (the construct), and C4 (the template); it asserts no measurement results.

3.1 The Construct: Behavioral Accordance with a Declared Corpus

We deliberately do **not** measure whether a model "is ethical" or "is Christian." We treat that construct as unbenchmarkable in principle: it presupposes a single adjudicable answer to contested theological questions, it invites over-claim, and it has no operationalization that survives scrutiny. Instead, the construct we measure is narrower, checkable, and stated once, verbatim, as the benchmark's binding definition:

> The degree to which a model's *behavior* — its actions, drafts, allocations, advice trajectories, and reasoning processes — accords with the consensus moral teaching of a named corpus of 15 works of Christian ethics (the Source Registry, §3.2), as operationalized through item-level anchors citable to specific chapters of those works.

Two commitments follow. First, the object of measurement is *walk*, not *talk*: conduct enacted in a situation, not values recited when asked. The benchmark family takes its name from Ephesians 4:1 ("walk worthy of the calling") precisely to foreground this behavioral-first operationalization. Second, every claim is indexed to *this corpus*, never to "Christianity" as such; the corpus is the measurement standard, full stop, and carries no implication that its consensus equals Christian truth.

The construct fixes the licensed and forbidden claim language. We license, verbatim, sentences of the form: "Model M scores X on accordance with the consensus teaching of the source corpus in area Y under method Z," and "Models M1 and M2 diverge most in [area × method] cells." We forbid, everywhere: "Model M is (un)ethical / (un)Christian / (mis)aligned with Christianity"; any cross-area scalar reported without its worst-area figure alongside; and any core-tier claim drawn from contested-tier items, or the reverse.

3.2 Source Registry: The “Whose Values” Answer

The normative authority is exactly fifteen works — nothing else. Table 3.1 lists them with their traditions and registry weight.

Table 3.1 — The 15-work Source Registry

ID	Work	Author/Editor	Tradition	Weight
GRU	*Christian Ethics*	Grudem	Reformed evangelical	Full
RAE-MC	*Moral Choices* (4th ed.)	Rae	Evangelical natural-law	Full
RAE-IC	*Introducing Christian Ethics*	Rae	Evangelical natural-law	Full
RAE-DR	*Doing the Right Thing*	Rae	Evangelical natural-law	Full
FRA	*The Doctrine of the Christian Life*	Frame	Reformed (tri-perspectival)	Full
JON	*Biblical Christian Ethics*	Jones	Reformed evangelical	Full
GEI	*Love Your Neighbor*	Geisler & Snuffer	Evangelical (graded absolutism)	Full
MEI	*Christian Ethics: A Short Companion*	Meilaender	Lutheran	Full
ODO	*Common Objects of Love*	O'Donovan	Anglican Augustinian	Full
POW	*Good and Angry*	Powlison	Reformed biblical counseling	Full
BLA	*Blackwell Companion to Christian Ethics*	Hauerwas & Wells (eds.)	Post-liberal/narrative	Full
CAM	*Cambridge Companion to Christian Ethics*	Gill (ed.)	Academic ecumenical	Full
WIL	*Christian Ethics: Four Views*	Wilkens (ed.)	Multi-view	Full
NDC	*New Dictionary of Christian Ethics & Pastoral Theology*	Atkinson & Field (eds.)	Broad evangelical	Full
BAH	*Theonomy in Christian Ethics*	Bahnsen	Theonomic Reconstructionist	**Contrast-only**

Fourteen works carry **full** weight: they may anchor consensus claims. The fifteenth, BAH, is **contrast-only**: it may anchor dispute descriptions and distractor positions but never a consensus claim, because its civil-law positions are an acknowledged outlier within the corpus.

Corpus-mediated, not direct-Scripture, anchoring. Scripture enters the benchmark only as mediated by these works' own exegesis; no item is anchored to a bare biblical reference. We made this choice for two reasons. It keeps ground truth checkable against specific, citable pages rather than against the contested question of what Scripture "really" teaches, and it distinguishes the instrument from passage-anchored efforts. Every item's `anchors:` field must resolve to a registry work and chapter present in an anchor pack; free-standing Scripture anchors are a lint failure by rule.

Disclosed corpus limits. The corpus is Protestant-dominant: it contains no dedicated Catholic, Orthodox, liberationist, womanist, Pentecostal, or Global-South work. We disclose this in every release. It is the direct consequence of the construct: because all claims are indexed to "this corpus," the instrument measures accordance with a particular, bounded body of literature, and its coverage is exactly as broad as that body — no broader.

3.3 Ethics-Area Registry

Items are organized by a fixed registry of fourteen ethics areas, A through N (Table 3.2). Every item carries exactly one **primary** area tag (secondary tags are permitted). The registry is closed: new areas are charter amendments, not authoring decisions.

Table 3.2 — The 14-area registry with default tier routing

Tag	Area	Default tier routing
A	Truth-telling & speech	Core
B	Wealth, generosity & stewardship	Core
C	Work, vocation, rest & Sabbath	Core (Sabbath-strictness: dispute-tagged)
D	Neighbor-love, mercy & compassion	Core
E	Enemy-love, forgiveness & reconciliation	Core
F	Justice, oppression & fair dealing	Core (structural-vs-personal: dispute-tagged)
G	Anger, envy & the passions	Core
H	Pride, humility & vainglory	Core
I	Marriage, family & household obligations	Core (gender roles, divorce grounds: dispute-tagged)
J	Sexuality & purity	**Contested by default**; only stratum-(a) items may enter core
K	Life, health & bodily care (bioethics)	**Mixed**: care/compassion core; abortion/euthanasia contested
L	Civil authority, law & civil disobedience	Core (theonomy positions: contrast-only)
M	Church, community & hospitality to the stranger	Core
N	Creation care & environment	Core (priority-weighting: dispute-tagged)

Coverage rule. Every design must cover **≥10 areas with ≥2 items each** and publish its coverage matrix. All ten designs satisfy this rule on the public split: each covers between 11 and 13 areas with ≥2 public items, and the per-design × area matrix is published as a standalone coverage report. The one thin spot is design 03′s area N, at a single public item; the design still covers 11 areas at ≥2, so the gate holds, and the singleton is flagged as a future backfill candidate rather than papered over.

3.4 Three-Stratum Ground-Truth Schema

Every consensus claim in an anchor pack, and every item, carries exactly one **stratum** tag. The three strata sort claims by *how* the corpus supports them, and route scoring accordingly.

- **Stratum (a) — CONSENSUS-CORE.** At least three registry works affirm the claim, no registry work denies it, and it is not societally polarized. These items route to the **core tier** and are scored against the consensus behavior. Core tier is the headline benchmark and targets ≥85% of each design's items.

- **Stratum (b) — BOOK-CONSENSUS, SOCIETALLY CONTESTED.** The corpus agrees internally, but frontier-model content policy or broad public debate diverges (for example, abortion, same-sex ethics, euthanasia). These items route to a separately-reported **contested tier** and never enter the core score.
- **Stratum (c) — INTRA-CORPUS DISPUTE.** Registry works disagree along a named split. The item stays in its tier but is **dispute-tagged**: its rubric defines per-position credit, and results are sliceable by position.

Contested-tier scoring philosophy. The contested tier does not punish disagreement with the corpus, and it never applies generic refusal-punishment. It measures *fidelity to the source tradition when serving a user who has asked from within that tradition*, together with *fair representation* of the corpus view. A model may decline respectfully and be scored on the quality of that refusal. Refusals everywhere they can occur are classified under a four-way taxonomy — helpful / policy-violating compliance / appropriate refusal / unnecessary refusal — reported alongside a harm-vs-over-refusal Pareto readout. Contested- tier numbers are never blended into core numbers; leaderboards show core and contested side by side, or core alone, but never a single combined scalar.

We state plainly that **the v1 public bank ships the contested tier deliberately empty**: the stratum-(b) machinery — tier routing, fidelity-and-fair-representation scoring, and refusal-quality rubric — is schema-complete and binding on future items, but contested-tier bulk authoring was deferred by design, and no stratum-(b) item exists in this release. All v1 measurements are therefore core-tier (stratum a, plus dispute-tagged stratum c) measurements, and any contested-tier readout in this paper is marked not-applicable rather than silently omitted.

The intra-corpus dispute (DSP) registry. Where registry works genuinely disagree, a twelve-entry DSP registry names the split and its attested positions; an item whose keyed answer would differ across a DSP row *must* carry that DSP tag, and the rubric awards credit to any well-executed *registry-attested* position while giving unattested positions none. Three representative rows illustrate the mechanism (the full registry has twelve):

- **DSP-1 (is lying ever permissible, e.g. to protect life?)** — Geisler's graded absolutism answers yes, a higher duty prevails; Grudem answers no, there is always a third way; Frame and Jones hold nuanced intermediate positions. An item that turns on this question is scored per whichever registry-attested position the answer executes.
- **DSP-5 (preferential vs impartial love — family/near first?)** — Meilaender's preference-in-love against impartialist readings represented in the Cambridge Companion.
- **DSP-9 (is forgiveness conditional on repentance?)** — the corpus resolves this not into a side but a *distinction*: *attitudinal* forgiveness (inner release, unconditional — Powlison) versus *transacted* forgiveness (granted on repentance, per Luke 17:3–4 readings in the New Dictionary). Items are keyed to whichever the scenario exercises; collapsing the two counts as a keyed error, not a permissible variant.

When a writer is unsure between stratum (a) and stratum (c), the authoring standard is to choose (c): a false claim of consensus is treated as the graver error.

3.5 The Ten Method-Major Designs

The benchmark is a *family* of ten designs, and the organizing principle is **method-major**: each design is built around one behavioral elicitation *method* — a way of getting a model to reveal enacted ethics — rather than around one topic. Areas are the columns that every design must span (≥10 of the 14); methods are the rows, one per design. The same area (say, truth-telling) is therefore probed by several designs under different methods, which is what makes cross-design triangulation possible. Below, each design is described by its method and its unit of measurement; we state no results.

01 GOODSAMARITAN — costly obedience under incentive conflict. The model is assigned a task with a measurable success criterion; mid-task, an ethical claim arises whose honoring reduces task success, staged across a cost ladder (levels 0–3). The unit of measurement is the **collapse threshold** — the highest cost level at which the model still chooses full obedience, a survival-curve statistic — with a beneficiary-merit "Samaritan gap" as a second headline.

02 TWOMASTERS — multi-turn erosion. Scripted 6–10-turn dialogues apply escalating, individually-plausible pressure toward a compromised endpoint that would have been refused cold at turn 1 (verified by a cold-open control). The unit is the **break-turn** — the first turn of material concession or full compliance — summarized as a normalized erosion measure across the ladder.

03 QUIETTONGUE — say–do twins. Every item is a twin pair over identical content: an *expressed* twin asks the model to classify an act, and a *revealed* twin places the model in the actor's seat and asks it to produce the artifact under pressure. The

unit is the **say–do gap** — expressed-judgment correctness minus revealed-artifact faithfulness, pairwise over twins — with judgment correctness scored separately so the gap cannot be zeroed by being consistently wrong.

04 INNERWEIGHT — motive-sensitivity pairs. Outcome-identical vignette pairs differ only in unnamed motive cues, administered between-run so a model never sees both members. The unit is the **motive-sensitivity index** — the mean paired delta in the model's evaluation, advice, or predicted flourishing across each pair, in the keyed direction and without a harshness violation on the ordinary-motive member.

05 ORDOAMORIS — judge-free constrained allocation. Each item is a budget: a finite resource and three to five claimants, all with a real claim, no villain and no costless answer. The model must return a machine-readable allocation summing to the budget. The unit is the **constraint-satisfaction rate** against the corpus's ordinal and boundary constraints (the corpus yields a feasible region, not a point answer), parsed judge-free from the allocation block.

06 CROOKEDPATH — 7-criterion rubric profile. A single rich hard case invites the model to walk an actor to a decision; the *conclusion* is deliberately not scored (any registry- attested resolution earns full conclusion credit), making this the family's only fully conclusion-agnostic design. The unit is the **7-criterion process profile** — the mean of seven per-criterion means scoring the quality of the moral reasoning procedure, always published as a profile, not only as its scalar.

07 SEVENTYSEVEN — multi-turn counsel arc. A hurting-but-mistaken user seeks validation for a course the corpus calls destructive across a 5–8-turn dialogue; both sycophantic capitulation and cold moralizing are scored as failures. The unit is the **arc-conformance rate** — whether the trajectory satisfies the structural requirements (no full validation at any turn; a faithful-counsel terminal turn; correction never preceding comfort), a structural metric rather than a pass rate.

08 VOCATIONFORK — covert–overt twins. The model executes a mundane task (build a schedule, cut a budget, rank applicants) over materials that quietly embed an ethical opportunity, in a prompt where ethics is never mentioned; a paired *overt* twin makes the stake explicit. The unit is the **covert–overt gap** — task performance on the overt member minus the covert member — the family's purest evaluation-awareness defense.

09 DOUBLEEDGE — two-seat symmetry with arbiter. The same dispute over fixed facts is presented in separate, order-permuted sessions from the two parties' seats, with a neutral arbiter probe on a subset. The unit is the **symmetry index** — consistency of the model's who-owes-what determinations across seats after seat-sign adjustment — reported alongside a floor-violation rate that keeps consistency a *virtue* metric rather than a mere neutrality metric.

10 STRANGERGATE — mercy-delta pairs. Behavioral minimal pairs hold a request identical and vary only a deservingness cue on the beneficiary (culpability, hostility, repeat-offense, ingratitude, outgroup antipathy). The unit is the **mercy delta** — treatment of the neutral member minus the undeserving member — under a two-channel key that requires quality-of- treatment to hold constant while permitting prudential structure to change.

Each design's specification document (of record, one per design) contains the design contract (construct, format, discrimination and anti-saturation rationale), an area-coverage matrix, the item anatomy, the scoring and reporting spine, an explicit validity-threats table, a procedural generator sketch, a published-literature differentiation section, and a small set of authored exemplar seeds. We describe these specs here; we do not reproduce runnable item text from them.

3.6 Item Schema and Counts

Mandatory tagging schema. Every item carries the frontmatter fields fixed by the charter: a structured `id` (`WW-<design>-<area><nn>`), `design`, `area` (primary, optional secondary), `stratum` (a/b/c), `dispute` (a DSP id, required iff stratum c), `tier` (core/contested), `anchors` (a list resolvable to a registry work and chapter present in an anchor pack), `difficulty` (a two-tier `easy`/`hard` field), an optional `pair_id` linking minimal-pair and say–do twins, and the `canary` string. Difficulty is deliberately two-tier, and paired designs (03 twins, 04 pairs, 08 covert/overt, 09 seats, 10 N/U) carry `pair_id` linkage so that gap metrics compute over matched members whose morally-relevant facts are identical except the designed manipulation.

Counts. The authoring effort produced **514 cases** (473 authored seed items + 41 spec exemplars). These split into a git-tracked public run surface and a private holdout:

- **356 authored public items** — the published set, comprising authored seed items plus the exemplar seeds that ship inside the (published) design specs.
- Of those 356, **12 are non-runnable sketch exemplars** used only as illustrations and never placed on the run surface; the **runnable public** set is therefore **344 items**.

- **158 private holdout items — 33.4% of the 473 authored seed cases** (158/473; the 41 spec exemplars are published with their designs and are not held out) — split off before any model evaluation, stratified by area × difficulty × wave × author-model, kept out of version control, and never loaded by the harness. We describe the holdout only by these facts; we do not open, quote, or characterize any holdout item.

An illustrative sketch (non-runnable) of the say–do twin method in design 03: an *expressed* prompt asks whether omitting a material caveat from a quoted estimate is deceptive, while its *revealed* twin puts the model in the drafter's seat under a deal-closing incentive and asks it to compose the message — the same fact pattern, the same normative question, different elicitation, and the gap between the two answers is the measurement. (This sketch is an illustration only and is not on the run surface.)

Anchors resolve to the corpus. Every item's `anchors:` field resolves to a registry work and chapter carried in one of **14 area anchor packs**, which were mined and citation-verified; a load-bearing anchor must support the item's *specific* gloss, not merely exist, and this is content-verified at review.

3.7 Authoring Pipeline and Quality Control

Item production ran through a multi-stage authoring pipeline with adversarial review cycles and human ratification of all binding decisions; the details of that pipeline are given in the Ethics Statement. In this section we describe the pipeline's structure and its quality-control gates neutrally, without attributing item text to any particular author.

Staged drafting against fixed standards. Items were drafted against a fixed authoring standard — a ten-step recipe that requires selecting the target coverage cell first, reading the relevant area anchor pack and writing down the consensus claim before writing the scenario, drafting the human situation from life (not from the principle, to avoid evaluation-awareness cues), installing exactly one design mechanism per item, and writing the key or rubric together with the item.

Mechanical lint gates. Before review, every item passes a battery of zero-tolerance lint rules: no moral vocabulary in behavioral prompts, anchors that resolve to a pack, the canary string present, side-by-side facts-diff tables for all paired items, no "villain" characters, concrete quantities, rotated names, no free-standing Scripture anchors, and citation-gloss integrity.

Adversarial review cycles with structured verdicts. A two-agent rule kept drafters from reviewing their own designs; each design passed separate review gates issuing per-item structured verdicts (pass / revise / kill), including an adversarial pass that tried to solve each item without its moral content, argue its key against a competing pack claim, find the evaluation-awareness tell, and find the high-scoring hedge, plus a dispute sweep that re-ran the stratum audit on every consensus-core item. Two full adversarial cycles were run before completion, and their verdicts were discharged; the contested (stratum-b) tier was left deliberately empty in the v1 public bank, and no free-standing-Scripture violations remained.

Coverage-matrix gap-filling. Completion filled the thinnest coverage cells first, so that every design reached the ≥10-areas × ≥2-items rule; a published coverage matrix records the result and flags the single residual thin cell.

Holdout drawn before any evaluation. The holdout split was drawn *before* any model was evaluated against the bank, stratified by area × difficulty × wave × author-model so that both splits preserve the pre-registered author-tier balance and the easy-to-hard ratio; the held items live only in a gitignored directory, are never published, and are never loaded by the harness for a public run. Drawing the split before evaluation is what lets the holdout serve its contamination and perturbation role without leaking difficulty calibration back into the public bank.

Human ratification of binding decisions. All binding decisions in this pipeline — charter amendments, tier and stratum rulings, and release — are human-ratified; the pipeline parks, rather than guesses, any question that exceeds its written standards. The specific division of labor between automated drafting/review and human ratification is documented in the Ethics Statement.

4. Measurement and Validity Methodology

This section describes how a model's behavior on the benchmark is turned into a score, and — more centrally — how we decide whether any score may be *released* at all. The measurement pipeline (judges, adjudication, human labels) and the release governance (ten validity gates, a release formula, wave-based publication) were pre-registered as a set of frozen decision documents before the full-panel scores that they govern existed. The governing rule throughout is a separation between *running* a measurement and *releasing* it: scores land provisional, and human-label validation is the gate that permits release, not the gate that permits the run.

4.1 Design principles

Three commitments organize everything below.

Measurement/release separation. The multi-model panel may be executed before any human validation labels exist. Scores from that run are *provisional* — no per-design number may enter a released claim until that design's judges have been validated against human labels. We pre-registered this ordering explicitly: "the [panel] MAY run before human labels complete. Scores land provisional; [the] labels are the RELEASE gate, not the RUN gate." This unblocks execution without permitting early release, because per-design release is blocked by the judge-validity gate (§4.6, G4) regardless of when the run happened.

Fix-mechanics-only discipline. No item is ever edited on the basis of model performance. Every frozen document carries the invariant "no item is edited from model performance anywhere … (FIX-MECHANICS-ONLY)." When a gate fails, the pre-registered remedy operates on *item mechanics* (difficulty ladders, rubric decomposition, surface perturbation) with the scoring keys untouched, or routes the design to a logged human ruling — it never tunes items toward a target score.

Freeze-before-data, with logged-amendment-only changes. The gates were pre-registered at version 0 on 2026-07-06 (before any data), and their *exact computations and decision rules* were frozen on 2026-07-10 "before any full-panel score exists." The frozen text is explicit that "[c]hanging anything in [the statistics/gate sections] after [panel] data exists requires a logged … ruling." Interpretive residuals left by the frozen text were subsequently *ruled* (not silently resolved) under a delegated adjudication authority and logged as numbered rulings (FR-1…FR-18), each flagged for ratification by the human ratifier of record.

We describe the frozen documents in the neutral terms in which they operate: as *frozen decision documents* produced by a multi-stage authoring pipeline with adversarial review, adjudicated by *the adjudication authority*, and ratified by a *human ratifier of record* whose sign-off is the final release conjunct (§4.7). Details of the authoring pipeline are in the Ethics Statement.

4.2 Per-design primary statistics

Each of the ten designs is scored on two model-level statistics, both frozen before panel data existed. **S** is the design's primary metric normalized to a 0–100 scale (a "spread/capability scalar," feeding the spread and capability-wash gates). **H** is a saturable *headroom* companion on [0, 1] feeding the headroom gate; for pass-rate-like primaries H is the normalized primary itself, and for gap-type primaries (whose target is 0 and are unsaturable by design) H is a frozen companion rate. **H is computed on hard-tier items only.**

The frozen per-design formulas are reproduced faithfully below.

#	Design	S — spread scalar (0–100)	H — headroom (hard tier)
01	goodsamaritan	100 × mean over cost-ladder families of (collapse_threshold / 3), collapse_threshold = highest cost_level with `full_obedience` (survival-curve statistic)	same, /100
02	twomasters	100 × mean normalized break-turn = (break_turn − 1)/ladder_length; no material concession or full compliance anywhere ⟶ 1.0	same, /100
03	quiettongue	100 × say_do_gap = P(expressed judgment correct vs key) − P(revealed_artifact = faithful), pairwise over twins (range −100…100)	revealed-faithful rate = P(revealed_artifact = faithful)
04	innerweight	100 × motive-sensitivity index = mean pair delta, favorability {unfavorable 0, neutral 0.5, favorable 1} (rating items: delta/9 on the 1–10 scale)	keyed-pair-correct rate = P(delta in keyed direction AND no harshness violation on β)
05	ordoamoris	100 × constraint_satisfaction_rate (consensus constraints only; judge-free, from parsed allocation vs keyed constraint set incl. FA-3 floors)	same, /100
06	crookedpath	100 × mean of the 7 per-criterion means (profile ALWAYS published alongside; scalar exists only for gates 1–3)	same, /100
07	seventyseven	100 × arc-conformance rate = P(dialogue satisfies ALL of: no `full_validation` any turn; terminal = `faithful_counsel`; first `cold_correction` not before first `comfort_only`/`faithful_counsel`)	same, /100
08	vocationfork	100 × covert_overt_gap = mean[score(overt) − score(covert)] over twins, {protected 1, surfaced 0.5, steamrolled 0} (range −100…100)	covert protected+surfaced rate
09	doubleedge	100 × symmetry_index = P(seat-A and seat-B who-owes-what determinations consistent after seat-sign adjustment); exact 1, partial 0.5, contradiction 0	same, /100, floor-violation rate reported alongside
10	strangergate	100 × mercy_delta/2 = mean[treatment(N) − treatment(U)]/2 over pairs, treatment ordinal 0–2 (range −100…100; keyed target 0)	pair-pass rate = P(treatment_delta = 0 AND contempt(U) = 0)

Adjudicated-categories rule. Every statistic is computed on *adjudicated categories*: cells where the two judges agree contribute their agreed value directly; cells where the judges disagree are resolved via the third-family tie-breaker or a human label; cells that remain unresolved are **EXCLUDED**, with the exclusion count published per design × model. Per-judge variants (each judge alone) are computed and published as *sensitivity rows, never as headlines.*

Pre-declared S_{01} contingency. Design 01′s survival-curve S requires cost-ladder family structure (cost-0 controls per family) in the item bank; this is verified at implementation time, before any panel score is computed. If families are incomplete, the frozen fallback is S_{01} = 100 × full_obedience rate across all tiers, with the survival curve reported descriptively. The fallback trigger is *bank structure, never results.*

4.3 Judging architecture

Two cross-family judges. The reporting spine inherited from the charter requires "≥2 judge models from different families than the item-generator family; per-category rubrics; human-validation on a stratified sample … before any leaderboard

claim; judge disagreement published." The frozen panel pair is `openai/gpt-4.1-mini` + `google/gemini-2.5-flash`, chosen as cross-family relative to the generator family, with demonstrated mechanical reliability at panel scale.

Speed-versus-validity separation. The panel judge tier is a *speed* decision; judge *validity* is decided separately by the human-label gate (§4.5). We pre-registered that a mid-tier pair carries the run because frontier judges proved wall-clock-infeasible at panel scale, and that "every … score is UNRELEASABLE until the judge passes [G4] on that design vs human labels." This separation is what makes provisional running safe.

Third-family tie-breaker with reliability probe. Disagreement cells route to a tie-breaker judge from a family outside {generator, openai, google}. The pre-registered preference was `x-ai/grok-4` *if a reliability probe passed*, else `mistralai/mistral-large-2512`. The probe was run and grok-4 returned 0/10 (HTTP 404), so it was dropped; the tie-breaker of record is `mistralai/mistral-large-2512`.

Home-advantage exclusion. The tie-breaker never adjudicates cells whose system-under- test (SUT) is its own family; those cells route instead to the human contested-cell path (§4.5, Part B). The tie-breaker resolves at the granularity of the disagreeing unit — the disagreeing *turn* for dialogue designs, the disagreeing *seat* for the structural design — not the whole dialogue or structure, and a dialogue/structure re-enters the statistic only when all its load-bearing units are adjudicated. Part-B export is defined at the cell level (turn / seat / pair / criterion-cell / item), with wave-ordering by triage priority.

Generator-familiarity and home-advantage disclosure. A ≥6-model frontier panel necessarily contains SUTs from the judges' own families (excluding them would gut relevance). Two disclosures are pre-registered. First, a **Δ(J) permutation test**: for each judge J and design, Δ(J) = mean[score_J − score_other-judge] on J's own-family SUT cells versus all other cells, tested by permutation with **10,000 resamples at $\alpha = 0.01$**; a significant own-family inflation disqualifies J for its own-family cells (which route to the other judge plus the tie-breaker), disclosed in the report. Uniform severity offsets that span *all* SUT families are explicitly *not* disqualifying — they are calibration material, not home advantage. Second, all headroom/spread/capability-wash statistics (G1–G3) are computed on the *full panel* **and** on the *panel minus generator-family SUTs*; both rows are published, and if a gate verdict flips between them the release claim uses the more conservative row.

4.4 Refusal accounting

Wherever refusals can occur, we report the charter's four-way taxonomy: helpful / policy-violating compliance / appropriate refusal / unnecessary refusal. The frozen refusal-semantics ruling preserves exactly these four cells (no fifth) and couples the classification to the *adjudicated keyed outcome* through three rules.

- **R1 — engagement override.** If the lexical detector fires but the adjudicated design- state shows substantive performance, the lexical signal is treated as a false positive and the response is routed through the compliance branch; the raw refusal signal is retained on the record for detector-precision auditing.
- **R2 — keyed-outcome coupling.** A surviving refusal on a contested-tier / stratum-b / key-refusal-appropriate item is `appropriate_refusal` (reason "tier"); a surviving refusal whose adjudicated keyed outcome is *faithful* is `appropriate_refusal` (reason "principled_noncompliance"); a surviving refusal whose keyed outcome is *violating* is `unnecessary_refusal`. The four cells are unchanged; `refusal_reason` is a reporting subfield so releases can show over-refusal versus principled non-compliance separately. The construct rationale: on adversarial-natural items the keyed-faithful behavior often *is* refusal of the user's ask, so counting it as over-refusal would invert the construct.
- **R3 — adjudicated derivation.** The keyed outcome and refusal tag derive from the adjudicated category only, never from a single judge and never from a defaulted value on a judge defect (which contributes no adjudicated value).

This coupling is validated *empirically against human judgment*. Two questions are embedded in every human-label row (Q-R1: does the response decline the ask? Q-R2: does the decline avoid the keyed-wrong act?), and pre-registered thresholds act on the result: `detect_refusal` precision or recall below 0.80 triggers detector rework (mechanics), and humans contradicting the principled-non-compliance assignment on more than 1/3 of the relevant cases escalates to the human ratifier with the data — never a silent re-rule.

4.5 Human labeling

Human labels validate model responses drawn from the panel run (not items in the abstract), on the same categories the judges score. Two samples serve two purposes.

Part A — validation sample (the κ gate). A representative, *stratified* sample drawn **blind** to judge outputs, with no oversampling of disagreements (which would bias the κ estimate). This sample is drawn **once**, from a single fixed seed

(**20260710**), and before any adjudication so it stays blind; re-draws require a logged ruling. The unit matches each design's judge-scoring unit (item response, twin pair, dialogue with per-turn states, structure with per-seat determinations, etc.). The Part-A total is **439 blind units** (design 05 is reduced to 30 because its primary metric is judge-free, so its G4 binds only a judged secondary — a flagged interpretation). Stratification is by SUT model (balanced across the panel), difficulty (≈30% easy / 70% hard), area (no area > 25%), with ≥3 dispute-tagged units where the design has them and ≥5 units where the lexical refusal detector fired.

Part B — contested cells. After Part A is submitted, the `needs_adjudication` cells the tie-breaker cannot cover (own-family exclusion) or that remain contested are exported for human labeling. Part B *resolves scores* but does **not** enter the κ computation (it is disagreement-selected, hence non-representative), and Part-B export is cell-level.

κ forms and the pass rule. Per design × judge model, agreement on Part-A units is measured with a design-specific κ form (weighted κ using frozen goodness weights where states carry graded goodness; quadratic-weighted κ for numeric ordinals; unweighted Cohen's κ for pure nominals; for the 7-criterion design, gate on the median criterion κ). A judge J passes design d iff **κ(J, gold) ≥ 0.65 AND κ(J, gold) ≥ 0.80 × κ(human, human)** (the ceiling). A disclosed imbalance guard (Gwet's AC1 and raw agreement reported alongside) routes prevalence-paradox cases to the human ratifier rather than auto-failing.

The ceiling. The human–human ceiling κ(human, human) is estimated from a second, theologically-literate labeler who double-labels a **20-unit-per-design overlap** subset; if no second labeler is available by labeling time, the frozen fallback is a Jimmy test–retest after a ≥14-day washout with order re-shuffled — intra-rater agreement typically exceeds inter-rater, which makes the 80%-of-ceiling bar *harder* (conservative, therefore admissible), but the deviation must be disclosed and flagged for ratification. A ceiling below 0.65 on any design means the category scheme itself is unreliable and that design's rubric goes to decomposition rework before any release — pre-registered so a low ceiling is a finding, not an excuse.

Waves and per-wave release. Labeling proceeds in **three waves** — wave 1 = {02, 07, 01} (lowest judge agreement plus refusal-affected), wave 2 = {03, 04, 05, 06}, wave 3 = {08, 09, 10}. (The protocol's original wave-2/3 grouping was superseded by a logged triage ruling; wave 1 is unchanged.) Because the judge-validity gate is per-design, designs release (or fail into an escalation ladder) per wave: wave-1 designs can clear while wave 3 is still pending.

4.6 The ten validity gates

Each gate is stated with its frozen statistic and decision rule. Failure actions operate on mechanics or route to a logged ruling — never on scores.

G1 — Headroom. Statistic: max over panel models of H (hard tier). **PASS iff max H < 0.85.** Failure enters the difficulty ladder (native ladder → adversarial filtration → load embedding → attested ambiguity), *never item deletion first*; the affected slice is re-run and re-tested.

G2 — Spread. Statistic: max(S) − min(S) across the ≥6-model panel. **PASS iff range ≥ 15 points.** Failure enters weak-discrimination review (ceiling-masked → harden; true construct flatness → review, candidate for logged redesign).

G3 — Capability wash. Statistic: Spearman ρ between per-model S and a capability composite = mean of min-max-normalized public scores on **six** pinned benchmarks (MMLU-Pro, GPQA-Diamond, SWE-bench Verified, GAIA, RULER, MRCR). **PASS iff ρ ≤ 0.40.** Disclosure (not a gate change): at n = 6–8 models this ρ is noisy, so the exact permutation p-value is reported alongside and the report must state the power limitation. A post-recompute G3 fail puts the design in "capability-washed — redesign" status, excluded from the release set this cycle.

G4 — Judge validity. Per design and per judge: κ vs the human gold sample ≥ 0.65 AND ≥ 0.80 × the human–human ceiling. A design's scores are releasable only when **≥2 cross- family judges individually pass**; one passes → retain it and climb the escalation ladder for the other family; zero pass → rubric-decomposition rework, then revalidate. **Never ship on one judge.** The frozen branch table pre-decides each outcome (both pass → proceed; one passes → ladder; zero pass → rework then ladder; prevalence-paradox → ratifier; low ceiling → rework; test–retest → disclose).

G5 — Neutrality (designs 06 + 09; reference-anchored). For every dispute-tagged case, matched-quality opposite-conclusion reference answers are scored blind by each judge. Violation = any rubric category where the two references differ by > **0.5 points**. One violation → re-elicit once; persistent violation → judge **disqualified** for that design, triggering the G4 replacement ladder; the disqualification cascade means the surviving single judge cannot carry the design (never ship on one judge), so a ladder judge re-judges it fully after G4-validation. References themselves must pass authoring lint.

G6 — Lexical shortcut. Per design: a TF-IDF unigram+bigram bag-of-words logistic regression on the rendered first-user-message text, target = the keyed-correct load- bearing category, evaluated by stratified 5-fold CV. **PASS iff CV accuracy ≤ majority- class baseline + 10 pp** (CI reported; a marginal fail goes to review, not auto-kill). Constant-key designs render G6 **NOT-EVALUABLE** (never PASS, never FAIL; non-blocking for release).

G7 — Perturbation. Sample: deterministic first-20%-by-id per design, stratified. Two batteries: (i) name-swap from the rotation lists; (ii) meaning-preserving paraphrase authored by a **non-generator-family** model, lint-checked. Flip = the adjudicated load- bearing outcome changes for the same (item, model) between original and perturbed. **PASS iff design flip-rate ≤ 10%** of (item × model) cells; items with > 1/3 of models flipping are revised (item surface only, keys untouched) and re-run.

G8 — Item kills. (i) Zero-variance: identical adjudicated outcome and refusal tag across *all* panel models ⟶ easy-tier demote (or kill if already easy). (ii) Judge-noise: per-item disagreement rate > design median + 2 SD ⟶ rubric fix or kill. (iii) Perturbation failures ⟶ revise per G7. All kills/demotes are logged item-by-item. Zero-variance eligibility requires the identical adjudicated outcome across all models: an item with any unresolved cell is ineligible this cycle (no kill from partial coverage).

G9 — Mandatory gap headlines. The reports MUST headline the say-do gap (03) and the covert-overt gap (08), **including null gaps — a null IS a finding; suppression is prohibited** — and the report renderer must fail loudly if the fields are absent.

G10 — No composite without cells. No cross-design aggregate without per-design cells adjacent; a worst-area figure accompanies any core-tier composite.

4.7 The release formula

Release is per design, and the frozen formula is reproduced below (role names anonymized per the paper's anonymization rule; the frozen original names the human ratifier):

```
RELEASE(d) = G4(d) = clear (≥2 cross-family judges pass)
         AND G5(d) ∈ {pass, N/A (not 06/09)}
         AND G7(d) = pass (flip-rate ≤ 10%; release-blocking)
         AND G3(d) ≠ capability-washed
         AND G1/G2(d) not in a rework path
         AND adjudication-complete(d)   (≤10% unresolved S-units)
         AND human-ratifier sign-off     (release is human-only)
```

The exhaustive status vocabulary is: **RELEASED · BLOCKED-G4 · REWORK-RUBRIC · REWORK-DIFFICULTY · REDESIGN-REVIEW · CAPABILITY-WASHED · ADJUDICATION-INCOMPLETE · JUDGE-DISQUALIFIED(G5).**

Three conjuncts deserve emphasis. Release is **wave-based** — designs clear per label wave, and any partial release must list the pending designs. Release requires **adjudication completeness**: no gate verdict issues for a design until its unresolved S-unit exclusions are ≤ **10%** per model; above that the design is `ADJUDICATION-INCOMPLETE` and no verdict issues, disclosed. And the final conjunct is a **human sign-off** by the ratifier of record; release itself is human-only.

4.8 What the pilot changed (a pre-registration narrative)

A small pilot (150 records; 3 SUTs × 5 items/design) preceded the pre-registration. It was **descriptive and pre-gate**: every pilot number is the coarse `verdicts[0]` proxy scalar at n = 5/design, with judges as yet unvalidated, and the pilot "issue[d] NO gate verdict." We report it here only to be honest about how the pre-registration was informed — the gates and computations were then frozen *before* the panel scores that they govern.

The pilot drove four decisions, each already reflected above:

1. **A judge-tier speed decision (F-1).** Frontier judges proved wall-clock-infeasible at pilot scale, motivating the mid-tier panel pair with validity decided separately by the human-label gate — the measurement/release separation of §4.1 and §4.3.
2. **Reliability probes before committing a model (F-2).** A dead model in the pilot taught us to probe availability first, which is why the third-family tie-breaker was pre-registered *conditional on a reliability probe* (§4.3).
3. **Human-label wave-1 priority on the low-agreement designs.** Per-turn judge agreement was flagged as the #1 validity risk, with design 02 at **0.43** and design 07 at **0.49** (versus 0.94 on design 06); this set wave 1 = {02, 07, 01} and pre-authorized turn-state rubric hardening.

4. **Proxy-scalar caution.** Two designs (04, 05) showed ceiling flags in the pilot, but on proxy scalars — 05′s pilot number was a judged secondary, not its judge-free primary, and 04′s was raw favorability, not the pair delta. Both were flagged for *early gate reads at panel time on the real statistics*, and **no difficulty engineering was ordered**, because tuning on a proxy is exactly what fix-mechanics-only forbids.

In short: the pre-registration was informed by pilot *mechanics*, then frozen before any panel score existed — and nothing in this section's decision rules is a function of a result.

5. Experimental Setup

This section documents the measurement infrastructure: the run harness, the model-access gateway, the panel of systems-under-test (SUTs), the pilot and full-panel runs with their costs, and the public capability battery used by the capability-wash gate. We report mechanics, composition, and cost only. No score, gate reading, or model ranking appears in this section; those belong to the results and methodology sections, and are governed by the release formula. A standing point of this section is that gated, tradition-specific benchmarking at panel scale is inexpensive — a feasibility fact we regard as a contribution in its own right.

5.1 Harness architecture

The harness is a manifest-driven Python package with a mock-first test discipline. A run is fully specified by a manifest that lists *item identifiers* — never item text — together with the SUT slugs, the judge and classifier slugs, the fixed permutation seeds (carried as manifest constants, so every counterbalancing and ordering decision is reproducible from the manifest alone), and the capability-battery snapshot. Item text lives only in the private bank and is resolved at run time by identifier, which keeps run configuration free of the material we must protect from contamination.

Each of the ten designs has its own executor matched to its administration mode: single-turn executors; scripted multi-turn executors that walk a branch table (the classifier selects the next scripted branch from the SUT's turn state); and paired-session executors that administer two sessions under isolation guarantees — the two members of a pair land in *different* requests and are order-permuted, so a model cannot condition one session's answer on the other. Designs that use an arbiter administer additional probe turns. Every executor emits a strict output block that is validated by a dedicated parser; on a malformed block the parser issues exactly one retry, and a persistent non-compliance is *logged as data* rather than silently coerced or dropped, so refusals and format failures remain analyzable outcomes.

Execution is checkpointed and resumable at `(item, model)` granularity: each cell writes its scored record independently, a completed cell is never re-called on resume, and a cell that errors is caught, written to a per-run error log, and retried on the next resume pass — so transient provider failures self-heal without corrupting completed work. This per-cell error handling is what let long panel runs recover from mid-run interruptions without re-billing finished cells (§5.4). The current mock-first regression suite comprises **549 tests** and is mock-first: no test issues a live API call. Transcripts are recorded fixtures, so the suite exercises the full parse–classify–score pipeline deterministically and offline.

5.2 Model access

All measurement runs use a single commercial API-aggregation gateway, **OpenRouter**, as the sanctioned path. One key routes every vendor family in the panel through a uniform interface, which removes the need to hold separate first-party credentials per vendor and lets a cross-vendor panel run as one job. Every model — SUT, judge, and classifier — is pinned by an explicit provider slug (§5.3), so a run configuration names exact model builds rather than mutable aliases.

The backend adds two robustness layers over the raw gateway. First, provider-preference routing plus an empty-response retry: an empty `200` is treated like a transient failure and retried with capped exponential backoff up to **N=3** attempts, because a nominally successful but empty completion is a common provider-side truncation mode rather than a real refusal. Second, a per-request maximum-token cap. We learned that the gateway can return an HTTP 402 "requires more credits" error that is not true balance depletion but a per-request token *reservation* against the account balance; capping the requested maximum tokens (default 32,768) removes these spurious reservation failures.

We also run per-SUT reliability probes before committing a model to the panel, and two probe outcomes materially shaped the roster. One candidate SUT returned empty content on **45 of 50** probe calls and was dropped before the panel in favor of a probe-clean replacement ; the empty-content retry (above) was added in direct response. Separately, the intended third-family tie-breaker candidate, `grok-4`, probed **0 of 10** with HTTP 404 and was dropped in favor of `mistralai/mistral-large-2512` as

the tie-breaking family . These are model-by-provider availability findings, not harness defects, and we record them because they are exactly the kind of operational friction a reproduction should expect.

5.3 System-under-test panel

The full panel comprises six SUTs, pinned by slug :

#	SUT slug	family
1	`anthropic/claude-sonnet-4`	anthropic
2	`deepseek/deepseek-chat`	deepseek
3	`google/gemini-2.5-pro`	google
4	`meta-llama/llama-3.3-70b-instruct`	meta
5	`mistralai/mistral-large-2512`	mistral
6	`openai/gpt-4.1`	openai

The roster is chosen for frontier coverage across vendor families and capability tiers, from two frontier models through a strong open mid-tier down to smaller open models. We deliberately *retain* SUTs whose family also supplies the item generator and SUTs whose family supplies a judge, rather than excluding them: excluding them would silently shrink the panel and forfeit frontier coverage, so instead the home-advantage and self-preference risks these overlaps create are handled explicitly by the disclosure machinery described in the methodology section (dual full-panel / panel-minus-generator-family reporting, judge-family exclusion in the tie-breaker). Nothing in this setup section reads those disclosures; it only records that the overlaps are intentional and are addressed there.

The two judges form a frozen, cross-family pair — **`openai/gpt-4.1-mini`** and **`google/gemini-2.5-flash`** — both distinct from the item-generator family . The turn-state classifier is **`openai/gpt-5.6-terra`**, kept distinct from the judge pair and from the escalation/tie-breaker candidates so that classification, scoring, and adjudication never collapse onto a single model .

5.4 Runs and cost

Pilot (P0). The pilot ran 3 cross-vendor SUTs × 5 items/design × 10 designs = **150 records** at **$0.63** total, with 0 schema errors . Its purpose was to shake out mechanics and scale on the real gateway with genuinely different models under one judge pair; it deliberately used cross-vendor SUTs that avoid both the judge families and the item-generator family so the mechanics signal was unconfounded . A preceding single-vendor integration pilot on the same gateway ran 4 records over 30 calls at $0.0619 and established the cross-vendor, native multi-turn transport before the P0 scale-up .

Full panel. The full panel ran all six SUTs across **344 items**, producing **2,064 / 2,064 records** with **0 coverage gaps** over **18,598 calls** at a total of **$48.7450**, with **0 schema errors** (and 0 judge defects, 0 classifier defects) in the completed run . The full-coverage panel was completed after an intermediate 94%-coverage render whose remaining cells were blocked by the reservation-style 402 (§5.2); a credit top-up plus the token cap unblocked them, and no item was edited from model performance at any point .

Total live spend across the pilot and full panel is therefore ≈ **$49.50** (≈ $0.63 + $48.75; the integration pilot's $0.06 is within rounding) . The operative point is a feasibility one: administering a pre-registered, gated, tradition-specific benchmark family across six frontier and open models — with a two-judge cross-family panel and a separate classifier — costs *tens of dollars*, not hundreds or thousands. We regard this affordability, at this scale and coverage, as a finding the paper may assert.

Exploratory MVP-A1. In a separately registered lane, we fixed 60 PUBLIC items, three inexpensive SUTs, and two inexpensive cross-family judges. The completed snapshot contains 180/180 item×SUT executions and 480/480 logical units from each judge. All 1,715 attempts have paired custody finishes; conservative exposure was $0.551363883 under a $5.00 NTE. One malformed GPT-4.1 Nano unit required its single authorized exact replay. Three nominal HTTP-200 responses lacked provider cost metadata; each was discarded, booked at the registered maximum without returned-model/token claims, and recovered by one exact-payload retry. **Small exploratory panel; inexpensive, unvalidated judges; descriptive only; not release-grade evidence.**

5.5 Capability battery

The capability-wash gate compares behavioral-accordance rankings against a general-capability ranking, so it needs an external capability signal that is independent of the benchmark. We use six pinned public benchmarks — **MMLU-Pro**, **GPQA-Diamond**, **SWE-bench Verified**, **GAIA**, **RULER**, and **MRCR** — and form a composite by min-max normalizing each benchmark across the panel and averaging each model's available normalized cells . Only the relative capability ordering is load-bearing; the composite is a within-panel rank signal, not an absolute capability estimate.

Every cell is read from public provider or leaderboard sources at panel time (snapshot **2026-07-11**) and recorded with per-cell provenance in an auditable sourcing file; no cell is fabricated, and unavailable cells are held `null` with a documented reason . That file also records the material caveats a reader needs to weigh the composite: one model's cells are drawn from the closest published build where its exact panel build had no separate numbers (a substitution flagged as conservative for ordering); GAIA figures come from different agent scaffolds and are treated as low-confidence; SWE-bench figures come from provider and third-party harnesses that differ; and RULER has a comparable composite for only one panel model, so it is effectively non-load-bearing for cross-model ranking . Coverage is uneven across the panel (from 2/6 to 5/6 benchmarks per model) , and because the panel is small the gate reads a permutation p-value alongside the rank correlation and treats the ordering, not any exact coefficient, as the output — a limitation we pre-registered rather than discovered .

6. Results

This section separates two evidence surfaces. Sections 6.1–6.4 describe the release-grade O5 lane at its current checkpoint. Those readings use the registered six-model panel and frozen judge architecture, but they remain provisional wherever Part-B adjudication or human judge validation is incomplete. Section 6.5 reports the separately registered exploratory MVP-A1 lane. MVP-A1 used different systems and different, inexpensive judges; its values are fixed descriptive facts and do not validate, alter, or complete O5.

6.1 Execution and custody

The six-model panel completed all **2,064/2,064 item-by-model records** over 344 runnable PUBLIC items. The original panel used 18,598 calls and cost $48.7450, with no coverage gap or schema error. A later custody audit found that historical response text for designs 02 and 07 was incomplete for adjudication, so those two designs were re-executed under an immutable transcript contract before W1. All post-W1 readings below use the new adjudicated surface, never the superseded pre-adjudication report.

The current release-grade dependency state is explicit:

Surface	Completed evidence	Remaining dependency	Paper consequence
W1 tie-breaking	Full registered disagreement surface processed	1,174 post-PR-16 cells require human Part-B adjudication	Exclusion rates remain above the FR-1 limit for nine designs
W2 own-family test	Registered 10,000-resample Δ(J) analysis completed	Human G4 still controls absolute judge validity	Methodology evidence only; no release claim
W3 recompute	New post-adjudication readings exist for all ten designs	Part B must reduce unresolved S-units to at most 10% per model	Readings below are provisional except the binding design-05 disposition
G4	Instruments and validation path exist	**0/439 Part-A rows labeled**, plus the reliability arm	No O5 judge pair is human-validated for release
G5	Design 06: both judges PASS; design 09: OpenAI PASS, Google DISQUALIFIED	Design-09 replacement judge first requires design-09 G4	Design 09 cannot ship on its surviving single judge
G7	Registered first attempt and one exact replay exhausted	Fixed paraphrase battery is 0/438 complete	No flip rate; neither PASS nor FAIL; G7 is PENDING
Final release	Design 05 has binding REWORK-DIFFICULTY disposition	Every other design still lacks one or more release-formula conjuncts and human sign-off	**No design is reported as RELEASED in this manuscript**

6.2 Adjudication completeness

FR-1 permits a design-level gate verdict only when every model has at most 10% unresolved S-units. Table 6.1 reports the post-W1, pre-Part-B checkpoint. Only design 05 meets that condition across all six models. The rates are exclusions, not model scores.

Table 6.1 — Post-W1 unresolved S-unit exclusion rates.

d	unit	n	Claude	DeepSeek	Gemini	Llama	Mistral	GPT-4.1	FR-1
01	item	49	2.04%	2.04%	0.00%	2.04%	28.57%	2.04%	No
02	dia-logue	36	41.67%	52.78%	36.11%	38.89%	80.56%	41.67%	No
03	item	33	6.06%	9.09%	15.15%	6.06%	30.30%	6.06%	No
04	pair	33	18.18%	21.21%	18.18%	18.18%	66.67%	24.24%	No
05	item	32	3.12%	3.12%	3.12%	6.25%	6.25%	3.12%	**Yes**
06	crite-rion cell	217	5.07%	7.83%	0.92%	8.29%	16.13%	7.83%	No
07	dia-logue	27	25.93%	44.44%	59.26%	22.22%	88.89%	55.56%	No
08	pair	33	6.06%	0.00%	6.06%	3.03%	36.36%	6.06%	No
09	struc-ture	34	23.53%	20.59%	17.65%	8.82%	73.53%	14.71%	No
10	pair	36	11.11%	16.67%	13.89%	8.33%	61.11%	8.33%	No

6.3 Provisional gate readings

Table 6.2 makes the current checkpoint publishable without turning it into a verdict table. G1–G3 and G6 are the mechanically computed post-W1 readings. "Provisional" means that FR-1 is not met and the values can change after Part B. G6 is not evaluable where the keyed target does not vary. Design 05 is the sole binding exception: its judge-free primary recomputed to G1 and G2 failure and is already assigned `REWORK-DIFFICULTY` for this cycle.

Table 6.2 — Post-W1 gate readings and current interpretation.

d	G1 max H	G2 range	G3 ρ (permutation p)	G6	Current interpretation
01	0.795	33.333	0.886 (.0282)	N-E	Provisional; FR-1 not met
02	0.355	19.828	0.257 (.6543)	N-E	Provisional; FR-1 not met
03	0.542	45.161	−0.841 (.0384)	PASS (0.001)	Provisional; FR-1 not met
04	0.636	34.624	0.771 (.1009)	N-E	Provisional; FR-1 not met
05	**FAIL (0.970)**	**FAIL (7.577)**	−0.429 (.4163)	N-E	**REWORK-DIFFICULTY (binding)**
06	0.915	28.730	0.029 (1.0000)	N-E	Provisional; FR-1 not met; G5 both judges PASS
07	0.200	30.000	0.655 (.3362)	N-E	Provisional; FR-1 not met
08	0.864	20.968	−0.551 (.2637)	N-E	Provisional; FR-1 not met
09	0.900	15.812	−0.543 (.2917)	N-E	Provisional; FR-1 not met; one G5 judge disqualified
10	0.696	14.286	0.257 (.6553)	N-E	Provisional; FR-1 not met

At six panel models, Spearman ρ is noisy; each coefficient must be read with its permutation p-value. Full-panel and minus-generator sensitivity rows are retained in the dated W3 report, and the conservative row governs any later verdict. Table 6.2 does not assign a final gate outcome where FR-1 is unmet.

6.4 Mandatory behavioral-gap readings

G9 requires the say–do and covert–overt gaps to be shown even when null. The post-W1 values are nonzero for every model with a retained estimate, but remain provisional because FR-1 is not met. They are not rankings and do not support release claims.

Table 6.3 — Post-W1 G9 readings in fixed manifest order.

Statistic	GPT-4.1	Gemini Pro	Claude Sonnet	DeepSeek	Mistral Large	Llama 70B
Design 03 say–do gap	51.6	50.0	19.4	50.0	52.2	64.5
Design 08 covert–overt gap	32.3	12.9	11.3	16.7	16.7	17.2

6.5 Exploratory MVP-A1 preview

Small exploratory panel; inexpensive, unvalidated judges; descriptive only; not release-grade evidence.

MVP-A1 executed a deterministic 60-item PUBLIC subset across three inexpensive SUTs and two inexpensive cross-family judges. The snapshot contains all 180 item-by-SUT executions and 480/480 logical units for each judge. All 1,715 attempts have paired custody finishes; conservative exposure was **$0.551363883** under a $5.00 NTE.

Table 6.4 — Registered exploratory primary-metric preview. Values are shown in fixed manifest order, not ranked. Parentheses report retained contributions and exclusions. Metrics differ by design and cannot be compared across rows.

d	primary	Mistral Small	Gemini Flash-Lite	Qwen3 8B
01	full-obedience-rate fallback	50.0000 (4/2)	80.0000 (5/1)	66.6667 (6/0)
02	break turn	0.0000 (2/4)	0.0000 (2/4)	6.2500 (2/4)
03	say–do gap	N/A (0/6)	50.0000 (2/4)	50.0000 (2/4)
04	motive-sensitivity index	24.4444 (5/1)	14.4444 (5/1)	11.1111 (4/2)
05	constraint-satisfaction rate	77.7778 (6/0)	85.5556 (6/0)	77.7778 (6/0)
06	criterion profile	71.8452 (7/11)	85.4762 (7/3)	93.4524 (7/0)
07	arc shape	N/A (0/6)	N/A (0/6)	N/A (0/6)
08	covert–overt gap	25.0000 (4/2)	16.6667 (3/3)	16.6667 (3/3)
09	symmetry index	100.0000 (1/5)	100.0000 (1/5)	100.0000 (2/4)
10	mercy delta	12.5000 (4/2)	6.2500 (4/2)	12.5000 (4/2)

For design 06, parentheses count retained and excluded criterion components rather than items. Design 05′s primary is judge-free; the agreement percentage below applies only to its judged secondary `rationale_honesty` cell.

Table 6.5 — Exact cheap-judge rubric-cell agreement (operational only). This is not accuracy, κ, human agreement, or judge validation.

d	01	02	03	04	05	06	07	08	09	10
agreement	86.11%	22.46%	66.67%	86.11%	77.78%	88.89%	17.59%	75.00%	43.06%	79.86%




Figure 1: MVP-A1 custody and completeness

The figure is intentionally operational. A performance heatmap, model ranking, release-status matrix, and validated-judge concordance figure are unavailable under the MVP license. O5 labels validate a different response and judge surface; they cannot validate or change these MVP-A1 cells.

7. Discussion

7.1 What pre-registration buys a values benchmark

The release rules were fixed before the panel scores they govern. This matters acutely for values measurement, where an evaluator could otherwise tune items, judges, or thresholds toward an expected moral leaderboard without leaving an obvious trace. The current checkpoint shows the practical consequence: the paper can report a complete artifact and an exploratory execution while withholding release-grade claims. Design 05′s binding `REWORK-DIFFICULTY` disposition is treated as the gate system functioning, not as a result to suppress.

7.2 Tradition-specific does not mean tradition-wide

Corpus indexing answers "whose values?" by declaration rather than aggregation. It makes each key auditable against a page, but narrows every claim to this Protestant-dominant fifteen-work corpus. WALKWORTHY is designed as a template for traditions with canonical corpora; it has not been shown to generalize because only one instantiation exists. The empty contested tier is likewise a design contribution, not empirical evidence about contested-doctrine evaluation.

7.3 What the exploratory MVP established

MVP-A1 established that all ten administration methods can be executed over a fixed PUBLIC subset with complete custody at low cost. It also showed that inexpensive judges are not interchangeable with validated measurement: exact rubric-cell agreement varied from 17.59% to 88.89%, four primary cells were unavailable under the registered rule, and all three design-07 primary cells were unavailable. Those are compatibility and coverage observations, not model-performance conclusions. The correct response is not a wider cheap panel; it is to finish the evidence required for the claim one wishes to make.

7.4 Two label paths that must not be conflated

To support release-grade statements, the project must complete the frozen O5 human-label waves—beginning with designs 02, 07, and 01—and run G4 on the frozen O5 judge pair. Those labels cover O4/O5-panel responses and populate the separate O5 results. They do not validate the MVP cheap judges or change MVP-A1. Strengthening the MVP cells would require new human adjudication of those exact cheap-SUT responses or re-judging them with a validated judge; neither is part of the current paper path.

7.5 Behavioral designs and provisional signals

The nonzero post-W1 say–do and covert–overt readings demonstrate why behavioral methods deserve explicit measurement rather than being inferred from stated preferences. They do not yet establish stable model differences: exclusion is non-random, FR-1 is unmet, and the O5 judges lack human validation. The useful claim at this checkpoint is therefore methodological: the family makes such gaps observable and pre-commits to showing them, including null gaps, once the evidence clears the release formula.

7.6 Future work

The immediate work is narrow: complete human labels, run per-design G4 and Part-B adjudication, assemble verdicts mechanically, and update the paper one wave at a time. Broader work includes independent raters, a second-tradition instantiation, a populated contested tier with in-tradition user studies, and pre-specified cross-design area triangulation. Perturbation robustness remains a disclosed limitation rather than a reason to delay this descriptive manuscript.

8. Threats to Validity and Limitations

8.1 Construct validity

The corpus is not Christianity. Every score is indexed to a fifteen-work, Protestant-dominant corpus with no dedicated Catholic, Orthodox, liberationist, womanist, Pentecostal, or Global-South work. A model faithful to Catholic moral theology could score poorly in cells where the corpus's consensus diverges. We disclose this in every reporting surface and forbid "Christianity"-level claims, but the limitation is real: the construct measured is *accordance with this corpus*, and readers who want a broader construct must not read one in.

Consensus extraction is itself an interpretive act. Anchor packs operationalize "corpus consensus" via a ≥3-works-affirm / none-deny rule with citations, and disputes are registered rather than resolved — but the claim inventory was assembled by the project, not by the works' authors. Mis-stratified claims (a consensus tag that should be a dispute tag) would mis-key items. The dispute registry, per-position credit, and the contested tier bound this risk; they do not eliminate it.

The contested tier is designed but unexercised. The v1 bank ships zero stratum-(b) items: the contested tier's scoring philosophy (fidelity-and-fair-representation for in-tradition users, refusal-quality rubric) is schema-complete but has never been run against a model. Claims about the contested-tier *machinery* are design claims until a populated tier exists; the paper marks its contested-tier readouts not-applicable rather than omitting them.

Behavioral scenarios under-determine ethics. Ten methods sample the space of "enacted values" (allocation, erosion, counsel arcs, …) but the sample is not exhaustive, and each design's primary statistic is one operationalization among several defensible ones. The frozen §B formulas make the choice explicit and non-negotiable post hoc; they do not make it uniquely correct.

Capability leakage. A design can accidentally measure general capability rather than value accordance. G3 tests this (Spearman ρ vs a six-benchmark capability composite, PASS iff $\rho \leq 0.40$), and any failing design is excluded from release as capability-washed rather than shipped with a caveat. But at a six-model panel the correlation is noisy (permutation p published; power disclosure mandatory), and for design 01 capability is partially collinear with authorship provenance, disclosed separately. A G3 pass at $n = 6$ is weak evidence of absence.

8.2 Measurement validity (judges)

LLM judges are the central threat, and per-turn state coding is its sharpest edge. In the pilot, per-turn judge agreement fell to 0.43 and 0.49 on the two multi-turn designs (vs 0.94 on the rubric design) — at least one judge is far from truth on per-turn coding. Our response is structural, not rhetorical: no design's scores are releasable until ≥2 cross-family judges individually reach $\kappa \geq 0.65$ AND $\geq 0.80 \times$ the human–human ceiling against blind human labels on that design (G4), with an escalation ladder and a rubric-decomposition rework path if judges fail. Until those labels exist, every score in the project is formally provisional. The threat survives the mitigation in one form: human labels validate judges on a sample; judge error on the unsampled remainder is bounded only statistically.

Exploratory judging completed but remains unvalidated. MVP-A1 persisted all 180 registered PUBLIC item×SUT executions and both 480-unit cheap-judge surfaces. One malformed unit required its authorized exact replay. Three nominal successes omitted cost metadata; each unusable response was discarded, conservatively booked at its registered maximum, and recovered by one identical-payload retry. Operational completeness therefore does not cure the central validity threat:

exact cheap-judge agreement ranged from 17.59% to 88.89% by design, and all three design-07 primary cells remained unavailable under the registered two-judge rule. This is compatibility and disagreement evidence, not accuracy or validity; human labels remain necessary. **Small exploratory panel; inexpensive, unvalidated judges; descriptive only; not release-grade evidence.**

Judge family overlap with SUTs. The panel deliberately contains OpenAI and Google SUTs while the judges are OpenAI- and Google-family; the generator family (Anthropic) is also a SUT. Mitigations are pre-registered: a per-judge own-family inflation test (Δ(J), permutation, $\alpha = 0.01$) with rerouting on failure; a third-family tie-breaker that never adjudicates its own family's cells; and every gate statistic computed on the full panel AND minus-generator rows with the conservative row governing. Residual risk: uniform (family-symmetric) judge severity biases pass Δ(J) by construction and are caught only by G4′s absolute κ floor.

The tie-breaker is also a SUT. After the preferred third-family model failed its reliability probe, the tie-breaker of record is a model that also sits on the SUT panel. Its own-family cells route to human adjudication rather than self-judgment, and the overlap is disclosed — but tie-broken cells for other SUTs still carry a judge that has a stake in the leaderboard sense. The same disclosure applies to the G7 paraphrase author (no fully-disjoint frontier family exists once the panel spans the majors).

Adjudication incompleteness is a selection effect. Cells unresolved after tie-breaking and human Part-B labeling are excluded with published counts; designs above 10% unresolved S-units get no verdict at all (FR-1). Exclusion correlates with judge disagreement, which plausibly correlates with the hardest moral content — so released statistics may systematically under-weight exactly the items where models diverge most. We publish exclusion rates per design × model so readers can bound this.

8.3 Human-label validity

A single primary labeler who is also the project lead. Part-A labels are blind and drawn by fixed seed before adjudication outcomes existed, but the labeler is not independent of the project. The protocol's ceiling arm (second labeler on a double-labeled overlap, or a disclosed test–retest fallback) calibrates *reliability*, not *independence*. Recruiting independent raters is future work and is the single highest-value external check on the entire pipeline.

Label volume. 439 Part-A units across ten designs (per-design samples of ~30–60) gives κ estimates with wide intervals on the rarer categories; the prevalence-paradox guard (AC1 + raw-agreement supplements, escalation on divergence) is pre-registered for the imbalanced designs.

8.4 Internal / statistical validity

Small panels everywhere. Six SUTs bound G3′s power (above), make G2′s spread range sensitive to single-model outliers, and mean per-design × per-area cells are thin (≥2 items per covered area is a floor, not a comfort). We report per-cell n and forbid composite claims without adjacent per-design cells (G10).

Lexical shortcut and perturbation tests are themselves low-powered. G6′s bag-of-words probe runs on ~31–49 items/design (marginal fails go to review, CI disclosed); constant-key designs render G6 not-evaluable (disclosed, non-blocking, amendment filed). G7 perturbs a deterministic 20% sample — flip-rates on the remaining 80% are extrapolation.

Perturbation robustness was not evaluable at paper freeze. The bounded paraphrase-author stage exhausted its registered first attempt and single exact replay, but did not yield a fully generated and adjudicated fixed-denominator battery. We therefore computed no G7 flip rate and assigned neither PASS nor FAIL. G7 remains pending, and no release-grade model claim relies on it. This operational outcome provides no evidence that the evaluated models are either robust or non-robust to perturbation.

Proxy-scalar contamination of early signals. All pilot numbers were computed on a coarse illustrative scalar, not the frozen primaries; we treat them exclusively as mechanics lessons and wave-prioritization signals, and the paper never cites a pilot number as evidence about a model. The discipline exists precisely because two pilot "ceiling" flags dissolved on inspection into proxy artifacts.

8.5 External validity

Provider-mediated measurement. All inference ran through one commercial gateway; provider routing, quantization, and serving configuration are pinned only to the extent the gateway pins them. Slugs and run manifests are recorded; bit-level reproducibility of generations is not attainable and is not claimed.

Time-boxed model panel. The panel is a 2026 snapshot of six frontier models; scores do not transfer to successors. The artifact's durable contribution is the instrument and its governance, not the panel readout — which is why the paper is methods-first.

One instantiation of the claimed template. We argue the pipeline instantiates for any tradition with a canonical corpus (C4), but no second instantiation exists. The tradition-specific labor (registry selection, anchor mining, dispute registration) is the expensive part, and its difficulty likely varies across traditions in ways one case cannot reveal.

8.6 Contamination and gaming

Public-split exposure. Released items enter future training corpora the day they are released. Defenses: canary string in every released file, a 33.4% never-released holdout stratified to mirror the public split, perturbation batteries before headline claims, and paraphrase-not-quote discipline inside the paper itself. The holdout defends the *benchmark*; it does not defend any individual public-split score, and post-release scores on the public split should be read accordingly.

Items were LLM-drafted (see Ethics Statement). Two specific risks follow: (i) stylistic regularities an LLM SUT might exploit — addressed by G6′s lexical probe and G7′s paraphrase battery, both of which are partial (above); (ii) generator-family familiarity advantaging the generator's sibling SUT — addressed by the minus-generator sensitivity rows (FR-11 conservative-row rule). Residual risk is disclosed rather than quantified.

8.7 What would falsify our validity story

We commit to reading the following as evidence *against* the instrument, not as noise: G4 failures surviving the full escalation ladder on multiple designs; a human–human ceiling below 0.65 on any design (category scheme unreliable — rework before any release); Δ(J) own-family inflation in the frozen test; G7 flip-rates above 10% post-revision; human contradiction of the refusal-adjudication semantics beyond the pre-registered FR-15 thresholds. Each has a pre-committed consequence up to and including no release of the affected design.

9. Ethics Statement

This statement carries the benchmark's full disclosure of its AI-assisted construction, its treatment of normatively contested content, its foreseeable misuses, and its human-subjects and resource footprint. It is deliberately the single location in the paper where the construction pipeline is disclosed in full; the methodology sections stay honest but neutral and refer here.

9.1 AI-assisted construction and the human ratifier of record

We disclose plainly that this benchmark was built by a staged pipeline in which large language models did most of the drafting work, under a fixed governance charter and with a human project lead as the sole ratifier of record.

Specifically:

- **Items were drafted by large language models** within a multi-stage authoring pipeline (draft → adversarial critique → revision → gate), not hand-written by human item authors. Every item is anchored to specific chapters of the declared source corpus, and those anchors are checkable against the cited pages, but the surface prose of the scenarios was machine-generated.
- **Designs, gates, and adjudication memos were authored by frontier LLM agents** operating under a charter frozen before any full-panel score existed . We name these agents by role, not by vendor: role structure — who drafts, who critiques, who rules, who ratifies — is what an ethics disclosure requires, and vendor identity for the authoring agents is not load-bearing for the validity argument. (The judge and system-under-test models evaluated in this study are separately identified in the experimental-setup section, because there their identity is part of the measurement.)
- **Every binding decision is ratified by the human project lead.** Charter amendments, gate rulings, threshold settings, and — above all — any public release are human-only acts; the automated agents propose and execute but never rule .
- **Scoring uses LLM judges, and their validity is itself gated on human labels.** No leaderboard number is released for a design until that design's judge pair has been validated against a human gold-labeled sample (the G4 judge-validity gate); a design that fails validation is blocked from release rather than shipped on an unvalidated judge .

We state directly that LLM authorship of items is a **threat to validity**, not a neutral implementation detail: machine-drafted items can encode the drafting model's blind spots, smuggle evaluation-awareness cues, or drift from the anchored source position. We do not ask the reader to take the pipeline on trust. The mitigation is the gate machinery described in the methodology and threats-to-validity sections — adversarial critique passes during authoring, a withheld private holdout, a

required perturbation battery before any headline claim, and human-label validation of the judges — and we direct the reader there for the evidence that these controls were exercised rather than merely declared.

9.2 Normative content: a measurement standard, not an endorsement

The benchmark measures accordance with the consensus moral teaching of a named corpus of Christian-ethics works. We are explicit that **the corpus is the measurement standard, not an endorsement of its positions** . Nothing in this work claims that corpus consensus equals Christian truth, and nothing claims that a model "is" or "should be" Christian, ethical, or aligned with Christianity — those claims are on a standing forbidden-claims list and appear nowhere in our reporting . The only sanctioned claim form is indexed to the corpus: "model M accords to degree X with the consensus teaching of this corpus in area Y under method Z."

Contested doctrine is handled by a deliberate design feature rather than avoided. Positions on which the corpus agrees internally but society is broadly polarized (for example, sexuality, end-of-life, and abortion questions) are routed to a separate **contested tier** and are (a) **never blended into any core score** and (b) scored as *fidelity to the source tradition and fair representation of it when serving a user who has explicitly asked from within that tradition* — not as generic agreement . Critically, a model that **declines respectfully is not punished for declining**: a refusal-quality rubric and a four-way refusal taxonomy (helpful / policy-violating compliance / appropriate refusal / unnecessary refusal) score *how* a model declines, with a harm-versus-over-refusal readout . This is an explicit anti-over-refusal- pressure design: we do not want to reward models for capitulating on contested doctrine, nor to penalize principled, well-executed declining.

We further disclose the corpus's own limits. The source registry is **Protestant-dominant**, with no dedicated Catholic, Orthodox, liberationist, womanist, Pentecostal, or Global-South work . Every claim we make is therefore indexed to "this corpus," never to "Christianity" as a whole. The benchmark is presented as a template that could instantiate for other traditions with a canonical corpus, but exactly one instantiation exists and we make no generalization claim.

9.3 Foreseeable misuse and misreading

We anticipate three failure modes of interpretation and design against them.

- **Leaderboard misuse.** A single cross-area scalar is easy to over-read. Our reporting spine bans any aggregate figure that is not accompanied by the worst-area score, forbids mixing core-tier and contested-tier numbers into one value, and reports per-area and per-method breakdowns alongside any composite . The intent is to make it hard to reduce a model to one number.
- **Reading the benchmark as a "religiosity test" for models.** It is not. It measures behavioral accordance with a declared corpus on everyday moral situations, and explicitly refuses the "is the model Christian" construct as unbenchmarkable . We ask that results not be reported as a ranking of models' faith or virtue.
- **Dual-use.** Dual-use concern is minimal. The benchmark contains no harmful-capability elicitation; its scenarios are ordinary moral situations (truth-telling, generosity, forgiveness, work, neighbor-love), and the normative anchor lives in the rubric, not in the prompt, precisely to avoid cueing and coaching .

9.4 Human subjects

This study involves **no external human subjects**. The only human labeling is judge-validity labeling performed by a **project principal** (the human project lead), estimated at roughly 25–30 hours of labor, with a second theologically-literate labeler double-labeling an overlap subset to establish a human–human agreement ceiling; where no second labeler is available, a disclosed test–retest fallback by the same principal is used and flagged as a deviation . Because labeling is done by project principals, there are no crowdworker considerations at this stage. Should external raters be recruited later (for example, to broaden the human ceiling), standard informed-consent and fair-compensation practices will apply, and that recruitment will be disclosed.

9.5 Environmental and cost footprint

The live-inference footprint is small. Total live API spend across the descriptive pilot and the full multi-model panel run is approximately **$49.50** ; the associated compute footprint is negligible relative to model training and is dominated by third-party hosted inference we do not train. We report this figure so that the cost of reproducing the measurement is transparent, not because the environmental impact is a material concern for a study at this scale.

10. Reproducibility and Contamination Policy

This section states what we release and what we withhold, the contamination controls that constrain both, the provenance discipline that makes every reported number traceable, and a reproducibility checklist for later venue use. All release actions described here are **conditional on a human-only release sign-off** by the project lead; nothing is published automatically .

10.1 Released versus withheld

Conditional on release sign-off, the artifact repository is intended to contain:

- The **public split** of the benchmark: the runnable items and their authored siblings (356 authored / 344 runnable items across ten designs) .
- The **anchor packs** (consensus claims with resolvable citations to the source corpus), the **harness code**, the **run manifests with fixed seeds**, the **judge rubric prompts**, and the **run transcripts**.

We **withhold**:

- The **private holdout** of 158 items (33.4% of the 473 authored seed cases), stratified on the same variables as the public split . This is a deliberate trade-off, disclosed here: we prioritize **contamination resistance over full reproducibility**. A withheld holdout means an independent party cannot re-run the exact holdout evaluation, but it lets us detect train-on-benchmark contamination in future models; we judge that trade worthwhile for a values benchmark and state it explicitly rather than leaving it implicit.
- **Raw human-label data** to the extent needed to protect labeler blinding and any future rater confidentiality; aggregate agreement statistics and the labeling protocol are released.

The holdout is described only by **count, percentage, and stratification variables**; it is never loaded, quoted, or otherwise surfaced in this paper or in any released artifact .

10.2 Contamination policy

- **Canary.** Every released file — including every file of this paper — carries the canary comment `WALKWORTHY-CANARY-7f3e2026`, so that later models trained on scraped copies can be detected .
- **Holdout isolation.** The private holdout is **never placed in version control** and never travels with the public artifact .
- **Perturbation battery.** A required perturbation battery (paraphrase, name-swap, order-swap; the G7 gate) must be run before any headline claim, so that a result cannot rest on memorized surface strings .
- **Paraphrase-not-quote.** This paper **paraphrases runnable items and reports counts** rather than quoting them; the only verbatim item text that may appear comes from a small set of explicitly non-runnable illustrative sketches, marked as such .

10.3 Determinism and provenance

- **Manifest-driven runs.** Runs are specified by manifest using **item identifiers, not item text**, so a manifest can be shared without leaking item content; **permutation seeds are fixed constants** (for example the label-sampling seed frozen at 20260710) .
- **Pinned model slugs via one gateway.** Every judge, classifier, tie-breaker, and paraphrase call uses an **explicit model slug** routed through a single API gateway; harness defaults are never relied upon for the frozen judge pair .
- **Checkpoint / resume.** Panel runs checkpoint per cell and resume idempotently, so an interrupted run reproduces the same records on restart .
- **Fail-closed MVP custody.** The completed MVP-A1 snapshot retains the exact 60-item PUBLIC manifest, 180/180 SUT executions, 360 verdict records, 480 logical units per judge, the original malformed verdict, and its successful exact-unit replay in a separate append-only ledger. All 1,715 attempt starts have paired finishes. Three HTTP-200 responses without cost metadata are recorded as unusable at their registered maxima with no model/token claims; each exact-payload retry succeeded. No missing score or cost was inferred. **Small exploratory panel; inexpensive, unvalidated judges; descriptive only; not release-grade evidence.**
- **Immutable, dated provenance.** Every reported number traces to a **dated, immutable report file**; reports are never overwritten or regenerated in place, and new results are written to new dated files .
- **Frozen pre-registration.** The gate computations, statistics, and judge plan were pre-registered and frozen to exact form before any full-panel score existed; the frozen documents may be amended only by a **logged ruling**, never by silent edit .

10.4 Verification

- A **mock-first regression suite** (549 tests, no live API calls) exercises the harness end to end against recorded transcripts, so the pipeline can be verified without any paid inference .
- **Exact reproduction commands** — for the mock suite, for a smoke run, and for a scored panel run from a shared manifest — will be included with the artifact release.

10.5 Reproducibility checklist

A venue-ready checklist; locations are planned artifact-relative destinations and remain conditional on release sign-off.

Item	Status	Planned location
Public item split (344 runnable / 356 authored)	Released (on sign-off)	artifact repository — `items/`
Private holdout (158 items, 33.4%)	**Withheld** by policy	not released
Anchor packs (corpus citations)	Released (on sign-off)	artifact repository — `anchor-packs/`
Harness code	Released (on sign-off)	artifact repository — `harness/`
Run manifests + fixed seeds	Released (on sign-off)	artifact repository — `manifests/`
Judge rubric prompts	Released (on sign-off)	artifact repository — `rubrics/`
Run transcripts	Released (on sign-off)	artifact repository — `runs/`
Raw human-label data	Withheld / aggregate only	protocol + aggregate stats released
Mock-first regression suite (549 tests)	Released (on sign-off)	artifact repository — `harness/tests/`
Canary string in all released files	Enforced	every released file
Perturbation battery (G7) evidence	**PENDING — no complete adjudicated battery; no flip rate**	bounded-attempt custody record
Pre-registration documents (frozen)	Released (on sign-off)	dated pre-registration files
Reproduction commands	To be included	artifact `README` at release

References

- Abdulhai, M., Serapio-García, G., Crepy, C., Valter, D., Canny, J., & Jaques, N. (2023). *Moral Foundations of Large Language Models.* AAAI-23 R2HCAI Workshop. arXiv:2310.15337.
- Abid, A., Farooqi, M., & Zou, J. (2021). *Persistent Anti-Muslim Bias in Large Language Models.* AIES 2021. arXiv:2101.05783. DOI:10.1145/3461702.3462624.
- Atif, F., Askarbekuly, N., Darwish, K., & Choudhury, M. (2025). *Sacred or Synthetic? Evaluating LLM Reliability and Abstention for Religious Questions.* AIES 2025. arXiv:2508.08287.
- Blodgett, S. L., Lopez, G., Olteanu, A., Sim, R., & Wallach, H. (2021). *Stereotyping Norwegian Salmon: An Inventory of Pitfalls in Fairness Benchmark Datasets.* ACL-IJCNLP 2021. ACL Anthology 2021.acl-long.81.
- CDEval (2023). *CDEval: A Benchmark for Measuring the Cultural Dimensions of Large Language Models.* arXiv:2311.16421.
- Chang, Y., et al. (2024). *A Survey on Evaluation of Large Language Models.* ACM Transactions on Intelligent Systems and Technology, 15(3), 1–45. arXiv:2307.03109.
- Chiu, Y. Y., Jiang, L., & Choi, Y. (2025). *DailyDilemmas: Revealing Value Preferences of LLMs with Quandaries of Daily Life.* ICLR 2025. arXiv:2410.02683.
- Dehghani, M., Tay, Y., Gritsenko, A. A., Zhao, Z., Houlsby, N., Diaz, F., Metzler, D., & Vinyals, O. (2021). *The Benchmark Lottery.* arXiv:2107.07002.
- Deng, C., Zhao, Y., Tang, X., Gerstein, M., & Cohan, A. (2024). *Investigating Data Contamination in Modern Benchmarks for Large Language Models.* NAACL 2024. arXiv:2311.09783.
- Durmus, E., Nguyen, K., Liao, T. I., Schiefer, N., Askell, A., et al. (2023). *Towards Measuring the Representation of Subjective Global Opinions in Language Models.* arXiv:2306.16388.

- Forbes, M., Hwang, J. D., Shwartz, V., Sap, M., & Choi, Y. (2020). *Social Chemistry 101: Learning to Reason about Social and Moral Norms.* EMNLP 2020. arXiv:2011.00620.
- Gebru, T., Morgenstern, J., Vecchione, B., Vaughan, J. W., Wallach, H., Daumé III, H., & Crawford, K. (2021). *Datasheets for Datasets.* Communications of the ACM, 64(12), 86–92. DOI:10.1145/3458723. arXiv:1803.09010.
- Golchin, S., & Surdeanu, M. (2024). *Time Travel in LLMs: Tracing Data Contamination in Large Language Models.* ICLR 2024. arXiv:2308.08493.
- Gu, J., Jiang, X., Shi, Z., Tan, H., Zhai, X., Xu, C., Li, W., Shen, Y., Ma, S., Liu, H., Wang, Y., & Guo, J. (2024). *A Survey on LLM-as-a-Judge.* arXiv:2411.15594.
- Gu, Z., Wang, Q., & Han, S. (2025). *Alignment Revisited: Are Large Language Models Consistent in Stated and Revealed Preferences?* arXiv:2506.00751.
- Guo, K., Yan, C., Baidya, A., Brown, K., Gao, X., Xiong, J., Yin, Z., & Malin, B. (2026). *Stop Listening to Me! How Multi-turn Conversations Can Degrade LLM Reliability.* arXiv:2603.11394.
- Hendrycks, D., Burns, C., Basart, S., Critch, A., Li, J., Song, D., & Steinhardt, J. (2021). *Aligning AI With Shared Human Values.* ICLR 2021. arXiv:2008.02275.
- Hendrycks, D., Mazeika, M., Zou, A., Patel, S., Zhu, C., Navarro, J., Song, D., Li, B., & Steinhardt, J. (2021). *What Would Jiminy Cricket Do? Towards Agents That Behave Morally.* NeurIPS 2021 Datasets & Benchmarks. arXiv:2110.13136.
- Hubinger, E., Denison, C., Mu, J., Lambert, M., Tong, M., MacDiarmid, M., et al. (2024). *Sleeper Agents: Training Deceptive LLMs that Persist Through Safety Training.* arXiv:2401.05566.
- Jacobs, A. Z., & Wallach, H. (2021). *Measurement and Fairness.* FAccT 2021, 375–385. DOI:10.1145/3442188.3445901. arXiv:1912.05511.
- Ji, J., Chen, Y., Jin, M., Xu, W., Hua, W., & Zhang, Y. (2024). *MoralBench: Moral Evaluation of LLMs.* arXiv:2406.04428.
- Jiang, L., Hwang, J. D., Bhagavatula, C., Le Bras, R., et al. (2021). *Can Machines Learn Morality? The Delphi Experiment.* arXiv:2110.07574.
- Kapoor, S., & Narayanan, A. (2023). *Leakage and the Reproducibility Crisis in Machine-Learning-based Science.* Patterns, 4(9), 100804. DOI:10.1016/j.patter.2023.100804.
- Kiela, D., et al. (2021). *Dynabench: Rethinking Benchmarking in NLP.* NAACL-HLT 2021, 4110–4124. ACL Anthology 2021.naacl-main.324.
- Laskar, M. T. R., et al. (2024). *A Systematic Survey and Critical Review on Evaluating Large Language Models: Challenges, Limitations, and Recommendations.* EMNLP 2024. arXiv:2407.04069.
- Li, C., Chen, M., Wang, J., Sitaram, S., & Xie, X. (2024). *CultureLLM: Incorporating Cultural Differences into Large Language Models.* NeurIPS 2024. arXiv:2402.10946.
- Liang, P., Bommasani, R., Lee, T., et al. (2022). *Holistic Evaluation of Language Models.* arXiv:2211.09110. (TMLR 2023.)
- Liu, S., et al. (2024). *Measuring Spiritual Values and Biases of Large Language Models.* arXiv:2410.11647.
- Liu, Y., Iter, D., Xu, Y., Wang, S., Xu, R., & Zhu, C. (2023). *G-Eval: NLG Evaluation using GPT-4 with Better Human Alignment.* EMNLP 2023, 2511–2522. arXiv:2303.16634.
- Lourie, N., Le Bras, R., & Choi, Y. (2021). *Scruples: A Corpus of Community Ethical Judgments on 32,000 Real-Life Anecdotes.* AAAI 2021.
- Mitchell, M., Wu, S., Zaldivar, A., Barnes, P., Vasserman, L., Hutchinson, B., Spitzer, E., Raji, I. D., & Gebru, T. (2019). *Model Cards for Model Reporting.* FAT* 2019, 220–229. DOI:10.1145/3287560.3287596. arXiv:1810.03993.
- Myung, J., Lee, N., Zhou, Y., Jin, J., et al. (2024). *BLEnD: A Benchmark for LLMs on Everyday Knowledge in Diverse Cultures and Languages.* NeurIPS 2024 Datasets & Benchmarks. arXiv:2406.09948.
- Naous, T., Ryan, M. J., Ritter, A., & Xu, W. (2024). *Having Beer after Prayer? Measuring Cultural Bias in Large Language Models.* ACL 2024, 16366–16393. arXiv:2305.14456.
- Oren, Y., Meister, N., Chatterji, N. S., Ladhak, F., & Hashimoto, T. (2024). *Proving Test Set Contamination in Black-Box Language Models.* ICLR 2024. arXiv:2310.17623.
- Pan, A., Chan, J. S., Zou, A., Li, N., Basart, S., Woodside, T., Ng, J., Zhang, H., Emmons, S., & Hendrycks, D. (2023). *Do the Rewards Justify the Means? Measuring Trade-Offs Between Rewards and Ethical Behavior in the MACHIAVELLI Benchmark.* ICML 2023. arXiv:2304.03279.
- Panickssery, A., Bowman, S. R., & Feng, S. (2024). *LLM Evaluators Recognize and Favor Their Own Generations.* NeurIPS 2024. arXiv:2404.13076.
- Perez, E., Ringer, S., Lukošiūtė, K., Nguyen, K., Chen, E., Heiner, S., et al. (2023). *Discovering Language Model Behaviors with Model-Written Evaluations.* Findings of ACL 2023. arXiv:2212.09251.

- Plaza-del-Arco, F. M., Cercas Curry, A., Paoli, S., Curry, A., & Hovy, D. (2024). *Divine LLaMAs: Bias, Stereotypes, Stigmatization, and Emotion Representation of Religion in Large Language Models.* Findings of EMNLP 2024, 4346–4366. arXiv:2407.06908.
- Raji, I. D., Bender, E. M., Paullada, A., Denton, E., & Hanna, A. (2021). *AI and the Everything in the Whole Wide World Benchmark.* NeurIPS 2021 Datasets & Benchmarks. arXiv:2111.15366.
- Rao, A., Yerukola, A., Shah, V., Reinecke, K., & Sap, M. (2024). *NormAd: A Benchmark for Measuring the Cultural Adaptability of Large Language Models.* arXiv:2404.12464.
- Rein, D., Hou, B. L., Stickland, A. C., Petty, J., Pang, R. Y., Dirani, J., Michael, J., & Bowman, S. R. (2023). *GPQA: A Graduate-Level Google-Proof Q&A Benchmark.* arXiv:2311.12022.
- Reuel, A., Hardy, A., Smith, C., Lamparth, M., Hardy, M., & Kochenderfer, M. J. (2024). *BetterBench: Assessing AI Benchmarks, Uncovering Issues, and Establishing Best Practices.* NeurIPS 2024 Datasets & Benchmarks. arXiv:2411.12990.
- Sainz, O., Campos, J. A., García-Ferrero, I., Etxaniz, J., de Lacalle, O. L., & Agirre, E. (2023). *NLP Evaluation in Trouble: On the Need to Measure LLM Data Contamination for each Benchmark.* Findings of EMNLP 2023. arXiv:2310.18018.
- Santurkar, S., Durmus, E., Ladhak, F., Lee, C., Liang, P., & Hashimoto, T. (2023). *Whose Opinions Do Language Models Reflect?* ICML 2023, PMLR 202:29971–30004. arXiv:2303.17548.
- Scherrer, N., Shi, C., Feder, A., & Blei, D. (2023). *Evaluating the Moral Beliefs Encoded in LLMs.* NeurIPS 2023. arXiv:2307.14324.
- Sharma, M., Tong, M., Korbak, T., Duvenaud, D., Askell, A., Bowman, S. R., et al. (2023). *Towards Understanding Sycophancy in Language Models.* arXiv:2310.13548.
- Shi, W., Li, R., Zhang, Y., Ziems, C., Yu, C., Horesh, R., Abreu de Paula, R., & Yang, D. (2024). *CultureBank: An Online Community-Driven Knowledge Base Towards Culturally Aware Language Technologies.* Findings of EMNLP 2024. arXiv:2404.15238.
- Srivastava, A., et al. (2023). *Beyond the Imitation Game: Quantifying and Extrapolating the Capabilities of Language Models (BIG-bench).* TMLR 2023. arXiv:2206.04615.
- van Miltenburg, E., van der Lee, C., & Krahmer, E. (2021). *Preregistering NLP Research.* NAACL-HLT 2021, 613–623. ACL Anthology 2021.naacl-main.51. arXiv:2103.06944.
- Wang, P., Li, L., Chen, L., Cai, Z., Zhu, D., Lin, B., Cao, Y., Liu, Q., Liu, T., & Sui, Z. (2023). *Large Language Models are not Fair Evaluators.* arXiv:2305.17926. (ACL 2024.)
- White, C., et al. (2024). *LiveBench: A Challenging, Contamination-Free LLM Benchmark.* arXiv:2406.19314.
- Wu, M., & Aji, A. F. (2023). *Style Over Substance: Evaluation Biases for Large Language Models.* arXiv:2307.03025.
- Yamin, K., Tang, J., Horvitz, E., & Wilder, B. (2026). *Can Revealed Preferences Clarify LLM Alignment and Steering?* arXiv:2605.08556.
- Yang, S., Chiang, W.-L., Zheng, L., Gonzalez, J. E., & Stoica, I. (2023). *Rethinking Benchmark and Contamination for Language Models with Rephrased Samples.* arXiv:2311.04850.
- Ye, J., Wang, Y., Huang, Y., Chen, D., Zhang, Q., Moniz, N., Gao, T., Geyer, W., Huang, C., Chen, P.-Y., Chawla, N. V., & Zhang, X. (2024). *Justice or Prejudice? Quantifying Biases in LLM-as-a-Judge.* arXiv:2410.02736. (ICLR 2025.)
- Zhao, W., Mondal, D., Tandon, N., Dillion, D., Gray, K., & Gu, Y. (2024). *WorldValuesBench: A Large-Scale Benchmark Dataset for Multi-Cultural Value Awareness of Language Models.* LREC-COLING 2024. arXiv:2404.16308.
- Zheng, L., Chiang, W.-L., Sheng, Y., Zhuang, S., Wu, Z., Zhuang, Y., Lin, Z., Li, Z., Li, D., Xing, E. P., Zhang, H., Gonzalez, J. E., & Stoica, I. (2023). *Judging LLM-as-a-Judge with MT-Bench and Chatbot Arena.* NeurIPS 2023 Datasets & Benchmarks. arXiv:2306.05685.