

# 25 Useful Tips for Emacs (for beginners and advanced users)



## 1. Insert today's date into the buffer

---

`M-x shell-command or C-u M-!`

`date +%Y-%m-%d`

## 2. Quickly save snippets of text from a buffer to a file

---

`M-x shell-command-on-region or M-|`

`> cat >> tips`

Note by Sebastián Monía: One can also use the command `write-region`.

### 3. Links are not immediately clickable in Emacs in Text files

---

Change this with `global-goto-address-mode`

Then invoke `C-c RET` on the link.

### 4. Open multiple files in Direcd

---

- Mark the desired files
- `M-x direcd-do-find-marked-files`

### 5. Flush empty lines from a buffer

---

`M-x flush-lines RET ^$ RET`

### 6. Delete empty directories in Direcd

---

One can just use the find tool. Navigate to the directory you want to clear of empty folders.

`M-! find . -empty -type d -delete <RET>`

Hit `g` to refresh.

The echo area confirms if the command has run successfully.

### 7. Repeat complex (i.e. minibuffer commands)

---

`C-x Esc Esc`

### 8. Insert x number of lines of a single character

---

`C-u 70 *`

## 9. Change the encoding system for a file

---

`C-x C-m f`

## 10. Cycle org lists

---

Try the command `org-cycle-list-bullet` on a list and see it change:

1. `org-cycle-list-bullet`
2. `org-cycle-list-bullet`
3. `org-cycle-list-bullet`

## 11. Auto-expand without an external package

---

One can use `M-/ =dabbrev-expand`

## 12. Cycle org-agenda files

---

Invoke `org-agenda`, then use `C-'` to cycle between files.

## 13. Add a package manually

---

Add the path of the package:

```
(add-to-list 'load-path "~/.emacs.d/packages/session")
```

Then require it:

```
(require 'session)
```

**Note:** One can also use `package-install-file` which integrates the package with Emacs' package management. Also interesting and new:

If you are following master, you can use the related command `package-install-from-buffer` together with `Dired` to only install the files as a package that you have marked in the `Dired` buffer. See this [commit](#) (thanks to Philip Kaludercic on [mastadon](#).)

## 14. xah-make-backup

---

For easy manual backups of a given buffer:

[http://xahlee.info/emacs/emacs/elisp\\_make-backup.html](http://xahlee.info/emacs/emacs/elisp_make-backup.html)

## 15. Copy a link in Dired

---

`C-0 w` Provides an absolute path

`C-u w` Provides a relative path

## 16. Numbered lists in org

---

If you were to type this in Emacs:

1. item 1
2. item 2

And then go on to type text like this. It would interrupt the list and the next item would be numbered as 1) not 3). So, do this:

- 3) [`@3`] This will be item 3
- 4) and this will be item 4

## 17. Bind global keys interactively

---

`M-x global-set-key`

Bind whatever key you want. E.g. `C-c f`

Choose the command you want. E.g. `flush-lines`

Invoke: `C-x ESC ESC`

Yank that code into your Dot Emacs.

## 18. Preserve line breaks during org export

---

Customize this variable:

`org-export-preserve-breaks`

Or on a per file basis: `OPTIONS: \n:t`

## 19. Set mark at a place and return to it

---

`C-SPC`

`C-u C-SPC`

Note by Sebastián Monía: One could also use registers: `C-x r SPC`, save the position to a letter. Then `C-x r j` to jump to the position(s). More complex, but allows for storing multiple positions.

## 20. Delete text completely WITHOUT copying it to the kill ring

---

There are three methods:

- `M-x delete-region`
- `C-d`
- Backspace (on some keyboards the `DEL` key)

## 21. Get rid of peculiar `^M` characters in an Emacs file

---

One of the most straightforward ways is with just an Emacs command one-liner:

- Select the buffer (`C-x h`)
- Invoke `C-u M-| dos2unix`

(`dos2unix` would need to be installed.)

Note by Sebastián Monía: One can also change the encoding of the file between DOS and Unix, which may remove them. Otherwise, use `query-replace`. For input, type `C-q` followed by `C-m` to replace the literal `^M`.

## 22. Search the web

---

`M-s M-w`

## 23. Dired Listing Switches: change the way Dired sorts files and folders.

---

`C-u s`

Type `-alh` to sort by name

Type `-alt` to sort by date

Type `-lhs` to sort by size

## 24. Create new lines at end of a buffer

---

Set this variable:

```
(setq next-line-add-newlines t)
```

Then invoking `C-n` at a buffer's end will create new lines without `RET`.

## 25. How to RENAME a file while working on it in a buffer

---

Think out the box!

Simply use `C-x C-w` (`write-file`)

This is basically equivalent to `Save As` in Microsoft Word.

Advantage: You do not need to leave the buffer.

Then use `M-n` which will insert the current file name into the mini-buffer.

One can also just use `TAB` or `M-/` for name expansion.

The only "disadvantage" of this Method: The old file remains as a backup. But maybe that's a good thing!

You would need to delete it if you did not want it.

@cryptk@mastodon.social has also suggested the `rename-visited-file` function from Emacs 29.1.

That's all for today folks.

You can support me on PayPal:

<https://paypal.me/revrari>

[Return to Home](#)

### Comments

---

To comment, sign in with your GitHub account.

## 0 reactions



## 0 comments

Write

Preview

Aa

Sign in to comment

M↓

Sign in with GitHub