

英文版 Method

仅供客户在文章写作时参考，分析内容和方法请以结题报告为准，请客户自行承担文章查重等相关风险。

1. Experimental Procedure

1.1 Sample Quality Control

Please refer to QC report for methods of sample quality control.

1.2 Library Construction, Quality Control and Sequencing

A total amount of 0.2 µg DNA per sample was used as input material for the DNA library preparations. Briefly, genomic DNA sample was fragmented by sonication to a size of 350 bp. Then DNA fragments were endpolished, A-tailed, and ligated with the full-length adapter for Illumina sequencing, followed by further size selection and PCR amplification. After PCR products were purified by AMPure XP system (Beverly, USA). Subsequently, library quality was assessed on the Agilent 5400 system (Agilent, USA) and quantified by QPCR (1.5 nM).

The qualified libraries were pooled and sequenced on Illumina platforms with PE150 strategy, according to effective library concentration and data amount required.

2. Bioinformatics Analysis Pipeline

2.1 Data Quality Control

2.1.1 Raw data

The original fluorescence image files obtained from Illumina platform are transformed to short reads (Raw data) by base calling and these short reads are recorded in FASTQ (Cock et al., 2010) format, which contains sequence information and corresponding sequencing quality information.

2.1.2 Evaluation of data (Data quality control)

Sequence artifacts, including reads containing adapter contamination, low-quality nucleotides and unrecognizable nucleotide (N), undoubtedly set the barrier for the subsequent reliable bioinformatics analysis. Hence quality control is an essential step and applied to guarantee the meaningful downstream

analysis.

The steps of data processing were as follows:

- (1) Discard a paired reads if either one read contains adapter contamination (>10 nucleotides aligned to the adapter, allowing $\leq 10\%$ mismatches);
- (2) Discard a paired reads if more than 10% of bases are uncertain in either one read;
- (3) Discard a paired reads if the proportion of low quality (Phred quality <5) bases is over 50% in either one read.

3 References

2.2 Reads Mapping to Reference Sequence

Valid sequencing data was mapped to the reference genome by Burrows-Wheeler Aligner (BWA) (Li et al., 2009a) software to get the original mapping results stored in BAM format (parameter: mem -t 4 -k 32 -M). Then, the results were dislodged duplication by SAMtools (Li et al., 2009b) (parameter: rmdup) and Picard (<http://broadinstitute.github.io/picard/>).

2.3 Variant detection and annotation

2.3.1 SNP/InDel

The raw SNP/InDel sets are called by SAMtools with the parameters as '-C 50 - mpileup -m2 -F 0.002 -d 1000'. Then we filtered this sets using the following criteria:

- (1) The depth of the variate position >4;
- (2) The mapping quality >20.

2.3.2 CNV and SV

CNVs were detected by Control-FREEC(Barillot et al., 2012)to acquire potential deletion and duplication (parameter: window=100 step = 100).

SVs were detected by BreakDancer(Chen et al., 2009).

2.4 Annotation

ANNOVAR (Wang et al., 2010) was used for functional annotation of variants. The UCSC known genes were used for gene and region annotations.

3 References

Barillot E . Control-FREEC: a tool for assessing copy number and allelic content using next-generation sequencing data[J]. Bioinformatics, 2012, 28(3):423-425. doi: 10.1093/bioinformatics/btr670.

Chen K, Wallis JW, McLellan MD, et al. BreakDancer: an algorithm for high-resolution mapping of genomic structural variation. Nat Methods. 2009;6(9):677-681. doi:10.1038/nmeth.1363

Cock PJ, Fields CJ, Goto N, Heuer ML, Rice PM. The Sanger FASTQ file format for sequences with quality scores, and the Solexa/Illumina FASTQ variants. *Nucleic Acids Res.* 2010;38(6):1767-1771. doi:10.1093/nar/gkp1137

Li H, Durbin R. Fast and accurate short read alignment with Burrows-Wheeler transform. *Bioinformatics.* 2009a;25(14):1754-1760. doi:10.1093/bioinformatics/btp324

Li H, Handsaker B, Wysoker A, et al. The Sequence Alignment/Map format and SAMtools. *Bioinformatics.* 2009b;25(16):2078-2079. doi:10.1093/bioinformatics/btp352

Wang K, Li M, Hakonarson H. ANNOVAR: functional annotation of genetic variants from high-throughput sequencing data. *Nucleic Acids Res.* 2010;38(16):e164. doi:10.1093/nar/gkq603