

# Avalanche: An Event Dispatcher for SNO+

*(as in, a lot of sno(+), very fast)*

Andy Mastbaum\*

*The University of Pennsylvania*

January 12, 2012

## 1 Introduction

The “dispatcher” is the server software responsible for providing a stream of built events to various client software. Currently-planned client software includes the event viewer and detector monitoring tools. The dispatcher requires:

**High Throughput** The dispatcher must be able to keep up with the maximum data rate of 450 Mbps, simultaneously to all clients.

**Scalability** The dispatcher should support a large number of concurrent client connections without impact on performance.

**Compatibility** The dispatched data stream must be reasonably language-agnostic, since the language of the client software is unknown.

An obvious platform choice would be ROOT’s network I/O classes (`TPSocket`, etc.). However, the next-generation socket library ZeroMQ<sup>1</sup> provides a superior alternative. ZeroMQ is naturally asynchronous, natively supports fan-out, and implementations are typically faster than UNIX sockets. ZeroMQ’s fan-out allows clients to “subscribe” to a stream, optionally applying a filter (e.g. only events, no run headers). Bindings exist for all major languages.

## 2 Data Format

It has been decided that the “packed” events coming from the event builder will be in a ROOT format, with a structure developed by G. D. Orebi Gann and J. Kaspar. The packed format preserves the “raw” data structures from the detector front-end: for example, charge and time data is stored in 96-bit PMT bundles. This is in contrast the ‘full’ or ‘unpacked’ data structure used in RAT, where values are broken into separate, histogrammable fields.

The packed data is essentially a stream of `TObjects`, which may be event data, event-level headers, or run-level headers. For convenience of storage these are written to a `TTree`. Since `TTrees` are homogeneous lists, various data types must inherit from the same generic superclass to be stored in the tree. The data type must also be stored, so that objects can be properly re-cast when read back. The packed format `TTree` stores `RAT::DS::PackedRec` objects, which in turn contain a single `GenericRec` and an integer `RecordType`. All data types (events, headers) inherit from a class `GenericRec`, which is empty and exists only to support this polymorphism.

A full listing of packed format classes and their members is given in the appendix.

---

\*mastbaum@hep.upenn.edu

<sup>1</sup><http://www.zeromq.org>

## 3 Network Layer

The avalanche server broadcasts `PackedRec` objects, serialized using a ROOT `TBufferFile`. On the client side, software must create a `TBufferFile` using the packet data, read the `PackedRec` object out of it, and cast the `PackedRec`'s `Rec` object to the correct type based on the value of `RecordType`. C++ and Python libraries to perform this deserialization are included in with avalanche, and examples in both languages are given in the `examples/` directory.

## 4 Dispatched Data in RAT

Using the avalanche libraries, an input producer and output processor have been developed that allows RAT to interact with dispatched data. Simulated events may be dispatched on the network, simulating the real data flow chain, and RAT can read in dispatched events, which may be used for online processing or writing monitoring tools as RAT processors.

All new RAT-related source code is provided in the `rat/` directory, and `rat.diff` provides a diff generated against a recent SVN revision; to patch a working copy of RAT, run `$ patch -p0 rat.diff`.

### 4.1 Dispatching Simulated RAT Events

Avalanche includes a RAT output processor called `DispatchEvents` which broadcasts packed events. Clients may thus listen to a RAT-simulated data stream for testing and development.

To call the processor from a macro, use e.g.:

```
/rat/proc dispatch
/rat/procset address "tcp://localhost:5024"
```

where localhost is the server hostname and 5024 is the server port. To bind all interfaces, substitute `*` for localhost.

### 4.2 Reading Dispatched Events into RAT

Avalanche also includes a RAT input producer, `InDispatcher`, such that RAT may listen to a dispatcher stream and run a suite of processors on 'live' data.

To use this producer in a macro, use e.g.:

```
/rat/readdispatch/address tcp://localhost:5024
```

where localhost is the server hostname and 5024 is the server port. Note the lack of quotation marks.

## 5 Dispatching Detector Events

A C++ library with a very simple API is provided in the `lib/cpp` directory.

A server consists of a single `avalanche::server` object, constructed with a given socket address. The `avalanche::server` has one method, `sendObject`, which dispatches a ROOT `TObject`. For example, to send a histogram `TH1F* h1`:

```
avalanche::server* serv = new avalanche::server("tcp://localhost:5024");
serv->sendObject(h1);
```

Any number of clients may be subscribed to the stream on port 5024.

## 6 Writing Dispatcher Clients

Client software connects to a stream, receives and deserializes ROOT objects, and does something with these objects. Libraries for C++ and Python are provided in `lib/` that manage the first two steps.

## 6.1 C++

libavalanche provides a dispatcher client `avalanche::client`.

Consider the following example:

```
#include <iostream>
#include <TH1F.h>
#include <RAT/DS/PackedEvent.hh>
#include <avalanche.hpp>

int main(int argc, char* argv[]) {
    // create a client, listening for objects on port 5024
    avalanche::client client("tcp://localhost:5024");

    // you can listen to an unlimited number of stream, using addServer
    client.addServer("tcp://localhost:5025");

    // receive RAT::DS::PackedRec objects
    while (1) {
        RAT::DS::PackedRec* rec = (RAT::DS::PackedRec*) client.recvObject(RAT::DS::PackedRec::Class());
        if (rec)
            std::cout << "Received PackedRec of type " << rec->RecordType << std::endl;
        else
            std::cout << "Error deserializing message data" << std::endl;
        delete rec;
    }

    return 0;
}
```

First, we set up the client by giving it a server address to connect to. In this example, we also connect to one more server. You may connect to an unlimited number of streams; the packets received are interleaved, as if they arrived from one source. Next, we receive ROOT objects with `recvObject`. The class must be specified for the deserialization step. Now we are ready to operate on the data. In this example we just print the record type; a real client would at this point cast the member `Rec` object to the correct type, extract data, and perform some operations.

## 6.2 Python

The `avalanche` Python package in `lib/python` provides a dispatcher client `avalanche.Client`. To install this package on your system, run `$ python setup.py install`.

Consider the following example:

```
import avalanche
from rat import ROOT

if __name__ == '__main__':
    # create client listening to localhost port 5024
    cli = avalanche.Client('tcp://localhost:5024')

    # you can listen to an unlimited number of stream, using add_server
    cli.ad_server('tcp://localhost:5025');

    # receive RAT::DS::PackedRec objects
    while True:
```

```

rec = cli.recv_object(ROOT.RAT.DS.PackedRec.Class())

if rec:
    print 'Received PackedRec of type', rec.RecordType
else:
    print 'Error deserializing message data'

```

First, we set up the client by giving it a server address to connect to. In this example, we also connect to one more server. You may connect to an unlimited number of streams; the packets received are interleaved, as if they arrived from one source. Next, we receive ROOT objects with `recv_object`. The class must be specified for the deserialization step. Now we are ready to operate on the data. In this example we just print the record type; a real client would at this point cast the member `Rec` object to the correct type, extract data, and perform some operations.

Note that in Python, there is no need to cast the object returned by `recv_object`, as this is taken care of by PyROOT.

### 6.3 Other Languages

Many other languages are supported by ZeroMQ, and at least Ruby has supported ROOT bindings. Implementations will be similar to those given in C++ and Python.

A client must ‘subscribe’ to a ZeroMQ TCP ‘publish’ socket and deserialize ROOT `TObjects` using a `TBufferFile`. The former is achieved with the ZeroMQ API: set up a context and a subscriber socket, and connect that socket to one or more server addresses. The latter is simple in principle – create a `TBufferFile`, set the buffer to the packet contents, and read out the appropriate class. This may be complicated (as it is in Python) by the language’s handling of string termination; care must be taken to ensure that the buffer is not treated as a string and truncated at the first null byte. For guidance, see the C++ and Python client library source code in `lib`.

For examples of ZeroMQ in your language, see <https://github.com/imatix/zguide/tree/master/examples>.

## 7 Appendix: Packed Data Model

This is a complete listing of all packed format classes, taken from RAT's PackedEvent.hh.

### 7.1 class GenericRec : public TObject

(empty)

### 7.2 class PackedRec : public TObject

- UInt\_t RecordType
- GenericRec \*Rec

#### 7.2.1 Record Types

0. Empty
1. Detector event
2. RHDR
3. CAAC
4. CAST
5. TRIG
6. EPED

### 7.3 class PackedEvent : public GenericRec

- UInt\_t MTCInfo[kNheaders] (6 words for the event header from the MTC)
- UInt\_t RunID
- UInt\_t SubRunID
- UInt\_t NHits
- UInt\_t EVOrder
- ULong64\_t RunMask
- char PackVer
- char MCFlag
- char DataType
- char ClockStat10
- std::vector<PMTBundle> PMTBundles

### 7.4 class PMTBundle

- UInt\_t Word[3]

## 7.5 **class EPED : public GenericRec**

- UInt\_t GTDelayCoarse
- UInt\_t GTDelayFine
- UInt\_t QPedAmp
- UInt\_t QPedWidth
- UInt\_t PatternID
- UInt\_t CalType
- UInt\_t EventID (GTID of first events in this bank validity)
- UInt\_t RunID (doublecheck on the run)

## 7.6 **class TRIG : public GenericRec**

- UInt\_t TrigMask
- UShort\_t Threshold[10]
- UShort\_t TrigZeroOffset[10]
- UInt\_t PulserRate
- UInt\_t MTC\_CSR
- UInt\_t LockoutWidth
- UInt\_t PrescaleFreq
- UInt\_t EventID (GTID of first events in this banks validity)
- UInt\_t RunID (doublecheck on the run)

### 7.6.1 **Array Indices**

Arrays correspond to:

0. N100Lo
1. N100Med
2. N100Hi
3. N20
4. N20LB
5. ESUMLo
6. ESUMHi
7. OWL<sub>n</sub>
8. OWLELo
9. OWLEHi

### 7.7 class RHDR : public GenericRec

- UInt\_t Date
- UInt\_t Time
- char DAQVer
- UInt\_t CalibTrialID
- UInt\_t SrcMask
- UInt\_t RunMask
- UInt\_t CrateMask
- UInt\_t FirstEventID
- UInt\_t ValidEventID
- UInt\_t RunID (doublecheck on the run)

### 7.8 class CAST : public GenericRec

- UShort\_t SourceID
- UShort\_t SourceStat
- UShort\_t NRopes
- float ManipPos[3]
- float ManipDest[3]
- float SrcPosUncert1
- float SrcPosUncert2[3]
- float LBallOrient
- std::vector<int> RopeID
- std::vector<float> RopeLen
- std::vector<float> RopeTargLen
- std::vector<float> RopeVel
- std::vector<float> RopeTens
- std::vector<float> RopeErr

### 7.9 class CAAC : public GenericRec

- float AVPos[3]
- float AVRroll[3] (roll, pitch and yaw)
- float AVRopeLength[7]