

Diagnostic information - CAN

Fault entry in the specified control unit

INFORMATION

Internal function test completed.

Diagnostic conditions

The control unit initially tests internal function sequences during wake-up. If these are OK, all diagnosable outputs are then tested and any faults are stored.

Wake-up of the control unit by:

- ◆ Event-controlled CAN message
- ◆ Wake-up signal via wake-up line
- ◆ Key contact (terminal S)
- ◆ Ignition on

Possible fault causes

- ◆ Incorrect control unit coding
- ◆ The peripheral equipment connected to the specified control unit is faulty
- ◆ Control unit faulty (in most cases, faulty coding is the cause and not the control unit)

Fault effects

- ◆ The stated control unit sends only substitute values via the CAN
- ◆ Other control units detect these substitute values and set this fault code

Diagnostic information - CAN

Fault entry in the specified control unit

INFORMATION

Internal function test completed.

Diagnostic conditions

The control unit initially tests internal function sequences during wake-up. If these are OK, all diagnosable outputs are then tested and any faults are stored.

Wake-up of the control unit by:

- ◆ Event-controlled CAN message
- ◆ Wake-up signal via wake-up line
- ◆ Key contact (terminal S)
- ◆ Ignition on

Possible fault causes

- ◆ Incorrect control unit coding
- ◆ The peripheral equipment connected to the specified control unit is faulty
- ◆ Control unit faulty (in most cases, faulty coding is the cause and not the control unit)

Fault effects

- ◆ The stated control unit sends only substitute values via the CAN
- ◆ Other control units detect these substitute values and set this fault code

Diagnostic information - CAN

Fault entry in the specified control unit

INFORMATION

Internal function test completed.

Diagnostic conditions

The control unit initially tests internal function sequences during wake-up. If these are OK, all diagnosable outputs are then tested and any faults are stored.

Wake-up of the control unit by:

- ◆ Event-controlled CAN message
- ◆ Wake-up signal via wake-up line
- ◆ Key contact (terminal S)
- ◆ Ignition on

Possible fault causes

- ◆ Incorrect control unit coding
- ◆ The peripheral equipment connected to the specified control unit is faulty
- ◆ Control unit faulty (in most cases, faulty coding is the cause and not the control unit)

Fault effects

- ◆ The stated control unit sends only substitute values via the CAN
- ◆ Other control units detect these substitute values and set this fault code

Diagnostic information - CAN

Fault entry in the specified control unit

INFORMATION

Internal function test completed.

Diagnostic conditions

The control unit initially tests internal function sequences during wake-up. If these are OK, all diagnosable outputs are then tested and any faults are stored.

Wake-up of the control unit by:

- ◆ Event-controlled CAN message
- ◆ Wake-up signal via wake-up line
- ◆ Key contact (terminal S)
- ◆ Ignition on

Possible fault causes

- ◆ Incorrect control unit coding
- ◆ The peripheral equipment connected to the specified control unit is faulty
- ◆ Control unit faulty (in most cases, faulty coding is the cause and not the control unit)

Fault effects

- ◆ The stated control unit sends only substitute values via the CAN
- ◆ Other control units detect these substitute values and set this fault code

Diagnostic information - CAN

Fault entry in the specified control unit

INFORMATION

Internal function test completed.

Diagnostic conditions

The control unit initially tests internal function sequences during wake-up. If these are OK, all diagnosable outputs are then tested and any faults are stored.

Wake-up of the control unit by:

- ◆ Event-controlled CAN message
- ◆ Wake-up signal via wake-up line
- ◆ Key contact (terminal S)
- ◆ Ignition on

Possible fault causes

- ◆ Incorrect control unit coding
- ◆ The peripheral equipment connected to the specified control unit is faulty
- ◆ Control unit faulty (in most cases, faulty coding is the cause and not the control unit)

Fault effects

- ◆ The stated control unit sends only substitute values via the CAN
- ◆ Other control units detect these substitute values and set this fault code

Diagnostic information - CAN

Fault entry in the specified control unit

INFORMATION

Internal function test completed.

Diagnostic conditions

The control unit initially tests internal function sequences during wake-up. If these are OK, all diagnosable outputs are then tested and any faults are stored.

Wake-up of the control unit by:

- ◆ Event-controlled CAN message
- ◆ Wake-up signal via wake-up line
- ◆ Key contact (terminal S)
- ◆ Ignition on

Possible fault causes

- ◆ Incorrect control unit coding
- ◆ The peripheral equipment connected to the specified control unit is faulty
- ◆ Control unit faulty (in most cases, faulty coding is the cause and not the control unit)

Fault effects

- ◆ The stated control unit sends only substitute values via the CAN
- ◆ Other control units detect these substitute values and set this fault code

Diagnostic information - CAN

Fault entry in the specified control unit

INFORMATION

Internal function test completed.

Diagnostic conditions

The control unit initially tests internal function sequences during wake-up. If these are OK, all diagnosable outputs are then tested and any faults are stored.

Wake-up of the control unit by:

- ◆ Event-controlled CAN message
- ◆ Wake-up signal via wake-up line
- ◆ Key contact (terminal S)
- ◆ Ignition on

Possible fault causes

- ◆ Incorrect control unit coding
- ◆ The peripheral equipment connected to the specified control unit is faulty
- ◆ Control unit faulty (in most cases, faulty coding is the cause and not the control unit)

Fault effects

- ◆ The stated control unit sends only substitute values via the CAN
- ◆ Other control units detect these substitute values and set this fault code

Diagnostic information - CAN

Communication with control unit not possible

INFORMATION

Internal function test completed.

Diagnostic conditions

The PAS control unit initially tests internal function sequences during wake-up. If these are OK, all diagnosable outputs are then tested and any faults are stored.

Wake-up of the control unit by:

- ◆ Event-controlled CAN message
- ◆ Key contact (terminal S)
- ◆ Ignition ON

Possible fault causes

- ◆ No power supply to the control unit
- ◆ Incorrect control unit coding
- ◆ Short circuit or open circuit in CAN network
- ◆ Control unit faulty (in most cases, faulty coding is the cause and not the control unit)

Fault effects

- ◆ Communication is no longer possible via the CAN bus
- ◆ No other control units can communicate with the control unit

Diagnostic information - CAN

Communication with control unit not possible

INFORMATION

Internal function test completed.

Diagnostic conditions

The PAS control unit initially tests internal function sequences during wake-up. If these are OK, all diagnosable outputs are then tested and any faults are stored.

Wake-up of the control unit by:

- ◆ Event-controlled CAN message
- ◆ Key contact (terminal S)
- ◆ Ignition ON

Possible fault causes

- ◆ No power supply to the control unit
- ◆ Incorrect control unit coding
- ◆ Short circuit or open circuit in CAN network
- ◆ Control unit faulty (in most cases, faulty coding is the cause and not the control unit)

Fault effects

- ◆ Communication is no longer possible via the CAN bus
- ◆ No other control units can communicate with the control unit

U1714

Diagnostic information - CAN

Fault entry in the specified control unit

INFORMATION

Internal function test completed.

Diagnostic conditions

The control unit initially tests internal function sequences during wake-up. If these are OK, all diagnosable outputs are then tested and any faults are stored.

Wake-up of the control unit by:

- ◆ Event-controlled CAN message
- ◆ Wake-up signal via wake-up line
- ◆ Key contact (terminal S)
- ◆ Ignition on

Possible fault causes

- ◆ Incorrect control unit coding
- ◆ The peripheral equipment connected to the specified control unit is faulty
- ◆ Control unit faulty (in most cases, faulty coding is the cause and not the control unit)

Fault effects

- ◆ The stated control unit sends only substitute values via the CAN
- ◆ Other control units detect these substitute values and set this fault code

Diagnostic information - CAN

Communication with control unit not possible

INFORMATION

Internal function test completed.

Diagnostic conditions

The PAS control unit initially tests internal function sequences during wake-up. If these are OK, all diagnosable outputs are then tested and any faults are stored.

Wake-up of the control unit by:

- ◆ Event-controlled CAN message
- ◆ Key contact (terminal S)
- ◆ Ignition ON

Possible fault causes

- ◆ No power supply to the control unit
- ◆ Incorrect control unit coding
- ◆ Short circuit or open circuit in CAN network
- ◆ Control unit faulty (in most cases, faulty coding is the cause and not the control unit)

Fault effects

- ◆ Communication is no longer possible via the CAN bus
- ◆ No other control units can communicate with the control unit

Diagnosis information PDK control unit

Serial communication timeout: selector lever

Diagnostic conditions

The control unit must be active in order to test internal function sequences and diagnosable inputs/outputs.

In the event of a fault, check whether the fault is permanently >present<. To perform the check, erase the fault memory, meet the diagnostic conditions and read out the fault memory again.

- Ignition on

Possible fault causes

- ♦ Open circuit
- ♦ Short circuit to ground
- ♦ Short circuit to B+
- ♦ Loose contact or corrosion on connectors or lines
- ♦ Selector lever control unit faulty

Fault setting condition(s)

- Serial line timeout

Fault effects

- ♦ None

Diagnostic information - CAN

Communication with control unit not possible

INFORMATION

Internal function test completed.

Diagnostic conditions

The PAS control unit initially tests internal function sequences during wake-up. If these are OK, all diagnosable outputs are then tested and any faults are stored.

Wake-up of the control unit by:

- ◆ Event-controlled CAN message
- ◆ Key contact (terminal S)
- ◆ Ignition ON

Possible fault causes

- ◆ No power supply to the control unit
- ◆ Incorrect control unit coding
- ◆ Short circuit or open circuit in CAN network
- ◆ Control unit faulty (in most cases, faulty coding is the cause and not the control unit)

Fault effects

- ◆ Communication is no longer possible via the CAN bus
- ◆ No other control units can communicate with the control unit

Diagnostic information - CAN

Fault entry in the specified control unit

INFORMATION

Internal function test completed.

Diagnostic conditions

The control unit initially tests internal function sequences during wake-up. If these are OK, all diagnosable outputs are then tested and any faults are stored.

Wake-up of the control unit by:

- ◆ Event-controlled CAN message
- ◆ Wake-up signal via wake-up line
- ◆ Key contact (terminal S)
- ◆ Ignition on

Possible fault causes

- ◆ Incorrect control unit coding
- ◆ The peripheral equipment connected to the specified control unit is faulty
- ◆ Control unit faulty (in most cases, faulty coding is the cause and not the control unit)

Fault effects

- ◆ The stated control unit sends only substitute values via the CAN
- ◆ Other control units detect these substitute values and set this fault code

U1870

Diagnosis information PDK control unit

Serial communication signal error: selector lever

Diagnostic conditions

The control unit must be active in order to test internal function sequences and diagnosable inputs/outputs.

In the event of a fault, check whether the fault is permanently >present<. To perform the check, erase the fault memory, meet the diagnostic conditions and read out the fault memory again.

- Ignition on

Possible fault causes

- ♦ Selector lever control unit faulty

Fault setting condition(s)

- Serial line message counter not correct
- Serial line message checksum not correct

Fault effects

- ♦ None