

991 + 981 , MY 2012 =>

Diagnosis information - ParkAssist

107612.....	1
107614.....	2
107629.....	3
107631.....	4
107712.....	5
107714.....	6
107729.....	7
107731.....	8
107812.....	9
107814.....	10
107829.....	11
107831.....	12
107912.....	13
107914.....	14
107929.....	15
107931.....	16
107A14.....	17
107A16.....	18
107B13.....	19
10F614.....	20
10F629.....	21
10F631.....	22
10F712.....	23
10F714.....	24
10F729.....	25
10F731.....	26
10F812.....	27
10F814.....	28
10F829.....	29
10F831.....	30
10F912.....	31
10F914.....	32
10F929.....	33
10F931.....	34
10FA12.....	35
10FA14.....	36
10FA29.....	37
10FA31.....	38
10FB12.....	39

10FB14.....	40
10FB29.....	41
10FB31.....	42
10FC13.....	43
164000.....	44
60400.....	45
60500.....	46
A00087.....	47
C058.....	48
D01100.....	49
D01200.....	51
D01300.....	53
D40000.....	54
D40100.....	56

Diagnostic information - ParkAssist

ParkAssist ultrasound sensor

DANGER

Increased risk of accidents due to movement of the vehicle!

- ♦ Never step in front of or behind a vehicle unless it has been secured against rolling by the parking brake and transmission.
- ♦ The ParkAssist is subject to physical detection limits and does not free the driver from his/her responsibility to be careful.
- ♦ The system cannot detect short, thin and small obstacles and persons who are lying on the ground. It also cannot detect surfaces with unfavourable reflective characteristics, e.g. snow or glass.

Diagnostic conditions

- Internal function test on ParkAssist control unit
- Ignition on
- Reverse gear or transmission range R selected
- Vehicle speed briefly higher than 14 km/h (9 mph)

Fault setting condition(s)

INFORMATION

Fault entry due to ambient conditions: this fault can also occur if the sensors are heavily soiled, iced-up or have been painted. In addition, intense sound sources such as pneumatic hammers can cause interference.

- Signal lead Short circuit to B+/ground or open circuit in the line
- **Supply line**
- **Ground line**
- **ParkAssist ultrasound sensor** faulty

Fault effects

- ♦ System switches off
- ♦ Display in instrument cluster

Diagnostic information - ParkAssist

ParkAssist ultrasound sensor

DANGER

Increased risk of accidents due to movement of the vehicle!

- ♦ Never step in front of or behind a vehicle unless it has been secured against rolling by the parking brake and transmission.
- ♦ The ParkAssist is subject to physical detection limits and does not free the driver from his/her responsibility to be careful.
- ♦ The system cannot detect short, thin and small obstacles and persons who are lying on the ground. It also cannot detect surfaces with unfavourable reflective characteristics, e.g. snow or glass.

Diagnostic conditions

- Internal function test on ParkAssist control unit
- Ignition on
- Reverse gear or transmission range R selected
- Vehicle speed briefly higher than 14 km/h (9 mph)

Fault setting condition(s)

INFORMATION

Fault entry due to ambient conditions: this fault can also occur if the sensors are heavily soiled, iced-up or have been painted. In addition, intense sound sources such as pneumatic hammers can cause interference.

- Signal lead Short circuit to B+/ground or open circuit in the line
- **Supply line**
- **Ground line**
- **ParkAssist ultrasound sensor** faulty

Fault effects

- ♦ System switches off
- ♦ Display in instrument cluster

Diagnostic information - ParkAssist

ParkAssist ultrasound sensor

DANGER

Increased risk of accidents due to movement of the vehicle!

- ♦ Never step in front of or behind a vehicle unless it has been secured against rolling by the parking brake and transmission.
- ♦ The ParkAssist is subject to physical detection limits and does not free the driver from his/her responsibility to be careful.
- ♦ The system cannot detect short, thin and small obstacles and persons who are lying on the ground. It also cannot detect surfaces with unfavourable reflective characteristics, e.g. snow or glass.

Diagnostic conditions

- Internal function test on ParkAssist control unit
- Ignition on
- Reverse gear or transmission range R selected
- Vehicle speed briefly higher than 14 km/h (9 mph)

Fault setting condition(s)

INFORMATION

Fault entry due to ambient conditions: this fault can also occur if the sensors are heavily soiled, iced-up or have been painted. In addition, intense sound sources such as pneumatic hammers can cause interference.

- Signal lead Short circuit to B+/ground or open circuit in the line
- **Supply line**
- **Ground line**
- **ParkAssist ultrasound sensor** faulty

Fault effects

- ♦ System switches off
- ♦ Display in instrument cluster

Diagnostic information - ParkAssist

ParkAssist ultrasound sensor

DANGER

Increased risk of accidents due to movement of the vehicle!

- ♦ Never step in front of or behind a vehicle unless it has been secured against rolling by the parking brake and transmission.
- ♦ The ParkAssist is subject to physical detection limits and does not free the driver from his/her responsibility to be careful.
- ♦ The system cannot detect short, thin and small obstacles and persons who are lying on the ground. It also cannot detect surfaces with unfavourable reflective characteristics, e.g. snow or glass.

Diagnostic conditions

- Internal function test on ParkAssist control unit
- Ignition on
- Reverse gear or transmission range R selected
- Vehicle speed briefly higher than 14 km/h (9 mph)

Fault setting condition(s)

INFORMATION

Fault entry due to ambient conditions: this fault can also occur if the sensors are heavily soiled, iced-up or have been painted. In addition, intense sound sources such as pneumatic hammers can cause interference.

- Signal lead Short circuit to B+/ground or open circuit in the line
- **Supply line**
- **Ground line**
- **ParkAssist ultrasound sensor** faulty

Fault effects

- ♦ System switches off
- ♦ Display in instrument cluster

Diagnostic information - ParkAssist

ParkAssist ultrasound sensor

DANGER

Increased risk of accidents due to movement of the vehicle!

- ♦ Never step in front of or behind a vehicle unless it has been secured against rolling by the parking brake and transmission.
- ♦ The ParkAssist is subject to physical detection limits and does not free the driver from his/her responsibility to be careful.
- ♦ The system cannot detect short, thin and small obstacles and persons who are lying on the ground. It also cannot detect surfaces with unfavourable reflective characteristics, e.g. snow or glass.

Diagnostic conditions

- Internal function test on ParkAssist control unit
- Ignition on
- Reverse gear or transmission range R selected
- Vehicle speed briefly higher than 14 km/h (9 mph)

Fault setting condition(s)

INFORMATION

Fault entry due to ambient conditions: this fault can also occur if the sensors are heavily soiled, iced-up or have been painted. In addition, intense sound sources such as pneumatic hammers can cause interference.

- Signal lead Short circuit to B+/ground or open circuit in the line
- **Supply line**
- **Ground line**
- **ParkAssist ultrasound sensor** faulty

Fault effects

- ♦ System switches off
- ♦ Display in instrument cluster

Diagnostic information - ParkAssist

ParkAssist ultrasound sensor

DANGER

Increased risk of accidents due to movement of the vehicle!

- ♦ Never step in front of or behind a vehicle unless it has been secured against rolling by the parking brake and transmission.
- ♦ The ParkAssist is subject to physical detection limits and does not free the driver from his/her responsibility to be careful.
- ♦ The system cannot detect short, thin and small obstacles and persons who are lying on the ground. It also cannot detect surfaces with unfavourable reflective characteristics, e.g. snow or glass.

Diagnostic conditions

- Internal function test on ParkAssist control unit
- Ignition on
- Reverse gear or transmission range R selected
- Vehicle speed briefly higher than 14 km/h (9 mph)

Fault setting condition(s)

i INFORMATION

Fault entry due to ambient conditions: this fault can also occur if the sensors are heavily soiled, iced-up or have been painted. In addition, intense sound sources such as pneumatic hammers can cause interference.

- Signal lead Short circuit to B+/ground or open circuit in the line
- **Supply line**
- **Ground line**
- **ParkAssist ultrasound sensor** faulty

Fault effects

- ♦ System switches off
- ♦ Display in instrument cluster

Diagnostic information - ParkAssist

ParkAssist ultrasound sensor

DANGER

Increased risk of accidents due to movement of the vehicle!

- ♦ Never step in front of or behind a vehicle unless it has been secured against rolling by the parking brake and transmission.
- ♦ The ParkAssist is subject to physical detection limits and does not free the driver from his/her responsibility to be careful.
- ♦ The system cannot detect short, thin and small obstacles and persons who are lying on the ground. It also cannot detect surfaces with unfavourable reflective characteristics, e.g. snow or glass.

Diagnostic conditions

- Internal function test on ParkAssist control unit
- Ignition on
- Reverse gear or transmission range R selected
- Vehicle speed briefly higher than 14 km/h (9 mph)

Fault setting condition(s)

INFORMATION

Fault entry due to ambient conditions: this fault can also occur if the sensors are heavily soiled, iced-up or have been painted. In addition, intense sound sources such as pneumatic hammers can cause interference.

- Signal lead Short circuit to B+/ground or open circuit in the line
- **Supply line**
- **Ground line**
- **ParkAssist ultrasound sensor** faulty

Fault effects

- ♦ System switches off
- ♦ Display in instrument cluster

Diagnostic information - ParkAssist

ParkAssist ultrasound sensor

DANGER

Increased risk of accidents due to movement of the vehicle!

- ♦ Never step in front of or behind a vehicle unless it has been secured against rolling by the parking brake and transmission.
- ♦ The ParkAssist is subject to physical detection limits and does not free the driver from his/her responsibility to be careful.
- ♦ The system cannot detect short, thin and small obstacles and persons who are lying on the ground. It also cannot detect surfaces with unfavourable reflective characteristics, e.g. snow or glass.

Diagnostic conditions

- Internal function test on ParkAssist control unit
- Ignition on
- Reverse gear or transmission range R selected
- Vehicle speed briefly higher than 14 km/h (9 mph)

Fault setting condition(s)

INFORMATION

Fault entry due to ambient conditions: this fault can also occur if the sensors are heavily soiled, iced-up or have been painted. In addition, intense sound sources such as pneumatic hammers can cause interference.

- Signal lead Short circuit to B+/ground or open circuit in the line
- **Supply line**
- **Ground line**
- **ParkAssist ultrasound sensor** faulty

Fault effects

- ♦ System switches off
- ♦ Display in instrument cluster

Diagnostic information - ParkAssist

ParkAssist ultrasound sensor

DANGER

Increased risk of accidents due to movement of the vehicle!

- ♦ Never step in front of or behind a vehicle unless it has been secured against rolling by the parking brake and transmission.
- ♦ The ParkAssist is subject to physical detection limits and does not free the driver from his/her responsibility to be careful.
- ♦ The system cannot detect short, thin and small obstacles and persons who are lying on the ground. It also cannot detect surfaces with unfavourable reflective characteristics, e.g. snow or glass.

Diagnostic conditions

- Internal function test on ParkAssist control unit
- Ignition on
- Reverse gear or transmission range R selected
- Vehicle speed briefly higher than 14 km/h (9 mph)

Fault setting condition(s)

INFORMATION

Fault entry due to ambient conditions: this fault can also occur if the sensors are heavily soiled, iced-up or have been painted. In addition, intense sound sources such as pneumatic hammers can cause interference.

- Signal lead Short circuit to B+/ground or open circuit in the line
- **Supply line**
- **Ground line**
- **ParkAssist ultrasound sensor** faulty

Fault effects

- ♦ System switches off
- ♦ Display in instrument cluster

Diagnostic information - ParkAssist

ParkAssist ultrasound sensor

DANGER

Increased risk of accidents due to movement of the vehicle!

- ♦ Never step in front of or behind a vehicle unless it has been secured against rolling by the parking brake and transmission.
- ♦ The ParkAssist is subject to physical detection limits and does not free the driver from his/her responsibility to be careful.
- ♦ The system cannot detect short, thin and small obstacles and persons who are lying on the ground. It also cannot detect surfaces with unfavourable reflective characteristics, e.g. snow or glass.

Diagnostic conditions

- Internal function test on ParkAssist control unit
- Ignition on
- Reverse gear or transmission range R selected
- Vehicle speed briefly higher than 14 km/h (9 mph)

Fault setting condition(s)

INFORMATION

Fault entry due to ambient conditions: this fault can also occur if the sensors are heavily soiled, iced-up or have been painted. In addition, intense sound sources such as pneumatic hammers can cause interference.

- Signal lead Short circuit to B+/ground or open circuit in the line
- **Supply line**
- **Ground line**
- **ParkAssist ultrasound sensor** faulty

Fault effects

- ♦ System switches off
- ♦ Display in instrument cluster

Diagnostic information - ParkAssist

ParkAssist ultrasound sensor

DANGER

Increased risk of accidents due to movement of the vehicle!

- ♦ Never step in front of or behind a vehicle unless it has been secured against rolling by the parking brake and transmission.
- ♦ The ParkAssist is subject to physical detection limits and does not free the driver from his/her responsibility to be careful.
- ♦ The system cannot detect short, thin and small obstacles and persons who are lying on the ground. It also cannot detect surfaces with unfavourable reflective characteristics, e.g. snow or glass.

Diagnostic conditions

- Internal function test on ParkAssist control unit
- Ignition on
- Reverse gear or transmission range R selected
- Vehicle speed briefly higher than 14 km/h (9 mph)

Fault setting condition(s)

INFORMATION

Fault entry due to ambient conditions: this fault can also occur if the sensors are heavily soiled, iced-up or have been painted. In addition, intense sound sources such as pneumatic hammers can cause interference.

- Signal lead Short circuit to B+/ground or open circuit in the line
- **Supply line**
- **Ground line**
- **ParkAssist ultrasound sensor** faulty

Fault effects

- ♦ System switches off
- ♦ Display in instrument cluster

Diagnostic information - ParkAssist

ParkAssist ultrasound sensor

DANGER

Increased risk of accidents due to movement of the vehicle!

- ♦ Never step in front of or behind a vehicle unless it has been secured against rolling by the parking brake and transmission.
- ♦ The ParkAssist is subject to physical detection limits and does not free the driver from his/her responsibility to be careful.
- ♦ The system cannot detect short, thin and small obstacles and persons who are lying on the ground. It also cannot detect surfaces with unfavourable reflective characteristics, e.g. snow or glass.

Diagnostic conditions

- Internal function test on ParkAssist control unit
- Ignition on
- Reverse gear or transmission range R selected
- Vehicle speed briefly higher than 14 km/h (9 mph)

Fault setting condition(s)

INFORMATION

Fault entry due to ambient conditions: this fault can also occur if the sensors are heavily soiled, iced-up or have been painted. In addition, intense sound sources such as pneumatic hammers can cause interference.

- Signal lead Short circuit to B+/ground or open circuit in the line
- **Supply line**
- **Ground line**
- **ParkAssist ultrasound sensor** faulty

Fault effects

- ♦ System switches off
- ♦ Display in instrument cluster

Diagnostic information - ParkAssist

ParkAssist ultrasound sensor

DANGER

Increased risk of accidents due to movement of the vehicle!

- ♦ Never step in front of or behind a vehicle unless it has been secured against rolling by the parking brake and transmission.
- ♦ The ParkAssist is subject to physical detection limits and does not free the driver from his/her responsibility to be careful.
- ♦ The system cannot detect short, thin and small obstacles and persons who are lying on the ground. It also cannot detect surfaces with unfavourable reflective characteristics, e.g. snow or glass.

Diagnostic conditions

- Internal function test on ParkAssist control unit
- Ignition on
- Reverse gear or transmission range R selected
- Vehicle speed briefly higher than 14 km/h (9 mph)

Fault setting condition(s)

INFORMATION

Fault entry due to ambient conditions: this fault can also occur if the sensors are heavily soiled, iced-up or have been painted. In addition, intense sound sources such as pneumatic hammers can cause interference.

- Signal lead Short circuit to B+/ground or open circuit in the line
- **Supply line**
- **Ground line**
- **ParkAssist ultrasound sensor** faulty

Fault effects

- ♦ System switches off
- ♦ Display in instrument cluster

Diagnostic information - ParkAssist

ParkAssist ultrasound sensor

DANGER

Increased risk of accidents due to movement of the vehicle!

- ♦ Never step in front of or behind a vehicle unless it has been secured against rolling by the parking brake and transmission.
- ♦ The ParkAssist is subject to physical detection limits and does not free the driver from his/her responsibility to be careful.
- ♦ The system cannot detect short, thin and small obstacles and persons who are lying on the ground. It also cannot detect surfaces with unfavourable reflective characteristics, e.g. snow or glass.

Diagnostic conditions

- Internal function test on ParkAssist control unit
- Ignition on
- Reverse gear or transmission range R selected
- Vehicle speed briefly higher than 14 km/h (9 mph)

Fault setting condition(s)

INFORMATION

Fault entry due to ambient conditions: this fault can also occur if the sensors are heavily soiled, iced-up or have been painted. In addition, intense sound sources such as pneumatic hammers can cause interference.

- Signal lead Short circuit to B+/ground or open circuit in the line
- **Supply line**
- **Ground line**
- **ParkAssist ultrasound sensor** faulty

Fault effects

- ♦ System switches off
- ♦ Display in instrument cluster

Diagnostic information - ParkAssist

ParkAssist ultrasound sensor

DANGER

Increased risk of accidents due to movement of the vehicle!

- ♦ Never step in front of or behind a vehicle unless it has been secured against rolling by the parking brake and transmission.
- ♦ The ParkAssist is subject to physical detection limits and does not free the driver from his/her responsibility to be careful.
- ♦ The system cannot detect short, thin and small obstacles and persons who are lying on the ground. It also cannot detect surfaces with unfavourable reflective characteristics, e.g. snow or glass.

Diagnostic conditions

- Internal function test on ParkAssist control unit
- Ignition on
- Reverse gear or transmission range R selected
- Vehicle speed briefly higher than 14 km/h (9 mph)

Fault setting condition(s)

INFORMATION

Fault entry due to ambient conditions: this fault can also occur if the sensors are heavily soiled, iced-up or have been painted. In addition, intense sound sources such as pneumatic hammers can cause interference.

- Signal lead Short circuit to B+/ground or open circuit in the line
- **Supply line**
- **Ground line**
- **ParkAssist ultrasound sensor** faulty

Fault effects

- ♦ System switches off
- ♦ Display in instrument cluster

Diagnostic information - ParkAssist

ParkAssist ultrasound sensor

DANGER

Increased risk of accidents due to movement of the vehicle!

- ♦ Never step in front of or behind a vehicle unless it has been secured against rolling by the parking brake and transmission.
- ♦ The ParkAssist is subject to physical detection limits and does not free the driver from his/her responsibility to be careful.
- ♦ The system cannot detect short, thin and small obstacles and persons who are lying on the ground. It also cannot detect surfaces with unfavourable reflective characteristics, e.g. snow or glass.

Diagnostic conditions

- Internal function test on ParkAssist control unit
- Ignition on
- Reverse gear or transmission range R selected
- Vehicle speed briefly higher than 14 km/h (9 mph)

Fault setting condition(s)

INFORMATION

Fault entry due to ambient conditions: this fault can also occur if the sensors are heavily soiled, iced-up or have been painted. In addition, intense sound sources such as pneumatic hammers can cause interference.

- Signal lead Short circuit to B+/ground or open circuit in the line
- **Supply line**
- **Ground line**
- **ParkAssist ultrasound sensor** faulty

Fault effects

- ♦ System switches off
- ♦ Display in instrument cluster

Diagnostic information - ParkAssist

Supply voltage Sensors below limit

DANGER

Increased risk of accidents due to movement of the vehicle!

- ◆ Never step in front of or behind a vehicle unless it has been secured against rolling by the parking brake and transmission.
- ◆ The ParkAssist is subject to physical detection limits and does not free the driver from his/her responsibility to be careful.
- ◆ The system cannot detect short, thin and small obstacles and persons who are lying on the ground. It also cannot detect surfaces with unfavourable reflective characteristics, e.g. snow or glass.

INFORMATION

- The sensors are supplied with power only when the ignition is switched on and with the Shift lever or selector lever in position R.
- A voltage which is below the required supply voltage may be caused if the resistance of the loads (sensors) is too low

Diagnostic conditions

- Internal function test on ParkAssist control unit
- Ignition on
- Reverse gear or transmission range R selected
- Vehicle speed briefly higher than 14 km/h (9 mph)

Fault setting condition(s)

- Wiring connection between control unit and sensor faulty (open circuit, short circuit to ground or B+)
- Sensors faulty
- ParkAssist control unit faulty

Fault effects

- ◆ System switches off
- ◆ Display in instrument cluster

Diagnostic information - ParkAssist

Supply voltage Sensors below limit

DANGER

Increased risk of accidents due to movement of the vehicle!

- ◆ Never step in front of or behind a vehicle unless it has been secured against rolling by the parking brake and transmission.
- ◆ The ParkAssist is subject to physical detection limits and does not free the driver from his/her responsibility to be careful.
- ◆ The system cannot detect short, thin and small obstacles and persons who are lying on the ground. It also cannot detect surfaces with unfavourable reflective characteristics, e.g. snow or glass.

INFORMATION

- The sensors are supplied with power only when the ignition is switched on and with the Shift lever or selector lever in position R.
- A voltage which is below the required supply voltage may be caused if the resistance of the loads (sensors) is too low

Diagnostic conditions

- Internal function test on ParkAssist control unit
- Ignition on
- Reverse gear or transmission range R selected
- Vehicle speed briefly higher than 14 km/h (9 mph)

Fault setting condition(s)

- Wiring connection between control unit and sensor faulty (open circuit, short circuit to ground or B+)
- Sensors faulty
- ParkAssist control unit faulty

Fault effects

- ◆ System switches off
- ◆ Display in instrument cluster

Diagnostic information - ParkAssist

ParkAssist ultrasound sensor

DANGER

Increased risk of accidents due to movement of the vehicle!

- ♦ Never step in front of or behind a vehicle unless it has been secured against rolling by the parking brake and transmission.
- ♦ The ParkAssist is subject to physical detection limits and does not free the driver from his/her responsibility to be careful.
- ♦ The system cannot detect short, thin and small obstacles and persons who are lying on the ground. It also cannot detect surfaces with unfavourable reflective characteristics, e.g. snow or glass.

Diagnostic conditions

- Internal function test on ParkAssist control unit
- Ignition on
- Reverse gear or transmission range R selected
- Vehicle speed briefly higher than 14 km/h (9 mph)

Fault setting condition(s)

i INFORMATION

Fault entry due to ambient conditions: this fault can also occur if the sensors are heavily soiled, iced-up or have been painted. In addition, intense sound sources such as pneumatic hammers can cause interference.

- Signal lead Short circuit to B+/ground or open circuit in the line
- **Supply line**
- **Ground line**
- **ParkAssist ultrasound sensor** faulty

Fault effects

- ♦ System switches off
- ♦ Display in instrument cluster

Diagnostic information - ParkAssist

ParkAssist ultrasound sensor

DANGER

Increased risk of accidents due to movement of the vehicle!

- ♦ Never step in front of or behind a vehicle unless it has been secured against rolling by the parking brake and transmission.
- ♦ The ParkAssist is subject to physical detection limits and does not free the driver from his/her responsibility to be careful.
- ♦ The system cannot detect short, thin and small obstacles and persons who are lying on the ground. It also cannot detect surfaces with unfavourable reflective characteristics, e.g. snow or glass.

Diagnostic conditions

- Internal function test on ParkAssist control unit
- Ignition on
- Reverse gear or transmission range R selected
- Vehicle speed briefly higher than 14 km/h (9 mph)

Fault setting condition(s)

INFORMATION

Fault entry due to ambient conditions: this fault can also occur if the sensors are heavily soiled, iced-up or have been painted. In addition, intense sound sources such as pneumatic hammers can cause interference.

- Signal lead Short circuit to B+/ground or open circuit in the line
- **Supply line**
- **Ground line**
- **ParkAssist ultrasound sensor** faulty

Fault effects

- ♦ System switches off
- ♦ Display in instrument cluster

Diagnostic information - ParkAssist

ParkAssist ultrasound sensor

DANGER

Increased risk of accidents due to movement of the vehicle!

- ♦ Never step in front of or behind a vehicle unless it has been secured against rolling by the parking brake and transmission.
- ♦ The ParkAssist is subject to physical detection limits and does not free the driver from his/her responsibility to be careful.
- ♦ The system cannot detect short, thin and small obstacles and persons who are lying on the ground. It also cannot detect surfaces with unfavourable reflective characteristics, e.g. snow or glass.

Diagnostic conditions

- Internal function test on ParkAssist control unit
- Ignition on
- Reverse gear or transmission range R selected
- Vehicle speed briefly higher than 14 km/h (9 mph)

Fault setting condition(s)

INFORMATION

Fault entry due to ambient conditions: this fault can also occur if the sensors are heavily soiled, iced-up or have been painted. In addition, intense sound sources such as pneumatic hammers can cause interference.

- Signal lead Short circuit to B+/ground or open circuit in the line
- **Supply line**
- **Ground line**
- **ParkAssist ultrasound sensor** faulty

Fault effects

- ♦ System switches off
- ♦ Display in instrument cluster

Diagnostic information - ParkAssist

ParkAssist ultrasound sensor

DANGER

Increased risk of accidents due to movement of the vehicle!

- ♦ Never step in front of or behind a vehicle unless it has been secured against rolling by the parking brake and transmission.
- ♦ The ParkAssist is subject to physical detection limits and does not free the driver from his/her responsibility to be careful.
- ♦ The system cannot detect short, thin and small obstacles and persons who are lying on the ground. It also cannot detect surfaces with unfavourable reflective characteristics, e.g. snow or glass.

Diagnostic conditions

- Internal function test on ParkAssist control unit
- Ignition on
- Reverse gear or transmission range R selected
- Vehicle speed briefly higher than 14 km/h (9 mph)

Fault setting condition(s)

i INFORMATION

Fault entry due to ambient conditions: this fault can also occur if the sensors are heavily soiled, iced-up or have been painted. In addition, intense sound sources such as pneumatic hammers can cause interference.

- Signal lead Short circuit to B+/ground or open circuit in the line
- **Supply line**
- **Ground line**
- **ParkAssist ultrasound sensor** faulty

Fault effects

- ♦ System switches off
- ♦ Display in instrument cluster

Diagnostic information - ParkAssist

ParkAssist ultrasound sensor

DANGER

Increased risk of accidents due to movement of the vehicle!

- ♦ Never step in front of or behind a vehicle unless it has been secured against rolling by the parking brake and transmission.
- ♦ The ParkAssist is subject to physical detection limits and does not free the driver from his/her responsibility to be careful.
- ♦ The system cannot detect short, thin and small obstacles and persons who are lying on the ground. It also cannot detect surfaces with unfavourable reflective characteristics, e.g. snow or glass.

Diagnostic conditions

- Internal function test on ParkAssist control unit
- Ignition on
- Reverse gear or transmission range R selected
- Vehicle speed briefly higher than 14 km/h (9 mph)

Fault setting condition(s)

INFORMATION

Fault entry due to ambient conditions: this fault can also occur if the sensors are heavily soiled, iced-up or have been painted. In addition, intense sound sources such as pneumatic hammers can cause interference.

- Signal lead Short circuit to B+/ground or open circuit in the line
- **Supply line**
- **Ground line**
- **ParkAssist ultrasound sensor** faulty

Fault effects

- ♦ System switches off
- ♦ Display in instrument cluster

Diagnostic information - ParkAssist

ParkAssist ultrasound sensor

DANGER

Increased risk of accidents due to movement of the vehicle!

- ♦ Never step in front of or behind a vehicle unless it has been secured against rolling by the parking brake and transmission.
- ♦ The ParkAssist is subject to physical detection limits and does not free the driver from his/her responsibility to be careful.
- ♦ The system cannot detect short, thin and small obstacles and persons who are lying on the ground. It also cannot detect surfaces with unfavourable reflective characteristics, e.g. snow or glass.

Diagnostic conditions

- Internal function test on ParkAssist control unit
- Ignition on
- Reverse gear or transmission range R selected
- Vehicle speed briefly higher than 14 km/h (9 mph)

Fault setting condition(s)

i INFORMATION

Fault entry due to ambient conditions: this fault can also occur if the sensors are heavily soiled, iced-up or have been painted. In addition, intense sound sources such as pneumatic hammers can cause interference.

- Signal lead Short circuit to B+/ground or open circuit in the line
- **Supply line**
- **Ground line**
- **ParkAssist ultrasound sensor** faulty

Fault effects

- ♦ System switches off
- ♦ Display in instrument cluster

Diagnostic information - ParkAssist

ParkAssist ultrasound sensor

DANGER

Increased risk of accidents due to movement of the vehicle!

- ♦ Never step in front of or behind a vehicle unless it has been secured against rolling by the parking brake and transmission.
- ♦ The ParkAssist is subject to physical detection limits and does not free the driver from his/her responsibility to be careful.
- ♦ The system cannot detect short, thin and small obstacles and persons who are lying on the ground. It also cannot detect surfaces with unfavourable reflective characteristics, e.g. snow or glass.

Diagnostic conditions

- Internal function test on ParkAssist control unit
- Ignition on
- Reverse gear or transmission range R selected
- Vehicle speed briefly higher than 14 km/h (9 mph)

Fault setting condition(s)

INFORMATION

Fault entry due to ambient conditions: this fault can also occur if the sensors are heavily soiled, iced-up or have been painted. In addition, intense sound sources such as pneumatic hammers can cause interference.

- Signal lead Short circuit to B+/ground or open circuit in the line
- **Supply line**
- **Ground line**
- **ParkAssist ultrasound sensor** faulty

Fault effects

- ♦ System switches off
- ♦ Display in instrument cluster

Diagnostic information - ParkAssist

ParkAssist ultrasound sensor

DANGER

Increased risk of accidents due to movement of the vehicle!

- ♦ Never step in front of or behind a vehicle unless it has been secured against rolling by the parking brake and transmission.
- ♦ The ParkAssist is subject to physical detection limits and does not free the driver from his/her responsibility to be careful.
- ♦ The system cannot detect short, thin and small obstacles and persons who are lying on the ground. It also cannot detect surfaces with unfavourable reflective characteristics, e.g. snow or glass.

Diagnostic conditions

- Internal function test on ParkAssist control unit
- Ignition on
- Reverse gear or transmission range R selected
- Vehicle speed briefly higher than 14 km/h (9 mph)

Fault setting condition(s)

i INFORMATION

Fault entry due to ambient conditions: this fault can also occur if the sensors are heavily soiled, iced-up or have been painted. In addition, intense sound sources such as pneumatic hammers can cause interference.

- Signal lead Short circuit to B+/ground or open circuit in the line
- **Supply line**
- **Ground line**
- **ParkAssist ultrasound sensor** faulty

Fault effects

- ♦ System switches off
- ♦ Display in instrument cluster

Diagnostic information - ParkAssist

ParkAssist ultrasound sensor

DANGER

Increased risk of accidents due to movement of the vehicle!

- ♦ Never step in front of or behind a vehicle unless it has been secured against rolling by the parking brake and transmission.
- ♦ The ParkAssist is subject to physical detection limits and does not free the driver from his/her responsibility to be careful.
- ♦ The system cannot detect short, thin and small obstacles and persons who are lying on the ground. It also cannot detect surfaces with unfavourable reflective characteristics, e.g. snow or glass.

Diagnostic conditions

- Internal function test on ParkAssist control unit
- Ignition on
- Reverse gear or transmission range R selected
- Vehicle speed briefly higher than 14 km/h (9 mph)

Fault setting condition(s)

INFORMATION

Fault entry due to ambient conditions: this fault can also occur if the sensors are heavily soiled, iced-up or have been painted. In addition, intense sound sources such as pneumatic hammers can cause interference.

- Signal lead Short circuit to B+/ground or open circuit in the line
- **Supply line**
- **Ground line**
- **ParkAssist ultrasound sensor** faulty

Fault effects

- ♦ System switches off
- ♦ Display in instrument cluster

Diagnostic information - ParkAssist

ParkAssist ultrasound sensor

DANGER

Increased risk of accidents due to movement of the vehicle!

- ♦ Never step in front of or behind a vehicle unless it has been secured against rolling by the parking brake and transmission.
- ♦ The ParkAssist is subject to physical detection limits and does not free the driver from his/her responsibility to be careful.
- ♦ The system cannot detect short, thin and small obstacles and persons who are lying on the ground. It also cannot detect surfaces with unfavourable reflective characteristics, e.g. snow or glass.

Diagnostic conditions

- Internal function test on ParkAssist control unit
- Ignition on
- Reverse gear or transmission range R selected
- Vehicle speed briefly higher than 14 km/h (9 mph)

Fault setting condition(s)

INFORMATION

Fault entry due to ambient conditions: this fault can also occur if the sensors are heavily soiled, iced-up or have been painted. In addition, intense sound sources such as pneumatic hammers can cause interference.

- Signal lead Short circuit to B+/ground or open circuit in the line
- **Supply line**
- **Ground line**
- **ParkAssist ultrasound sensor** faulty

Fault effects

- ♦ System switches off
- ♦ Display in instrument cluster

Diagnostic information - ParkAssist

ParkAssist ultrasound sensor

DANGER

Increased risk of accidents due to movement of the vehicle!

- ♦ Never step in front of or behind a vehicle unless it has been secured against rolling by the parking brake and transmission.
- ♦ The ParkAssist is subject to physical detection limits and does not free the driver from his/her responsibility to be careful.
- ♦ The system cannot detect short, thin and small obstacles and persons who are lying on the ground. It also cannot detect surfaces with unfavourable reflective characteristics, e.g. snow or glass.

Diagnostic conditions

- Internal function test on ParkAssist control unit
- Ignition on
- Reverse gear or transmission range R selected
- Vehicle speed briefly higher than 14 km/h (9 mph)

Fault setting condition(s)

INFORMATION

Fault entry due to ambient conditions: this fault can also occur if the sensors are heavily soiled, iced-up or have been painted. In addition, intense sound sources such as pneumatic hammers can cause interference.

- Signal lead Short circuit to B+/ground or open circuit in the line
- **Supply line**
- **Ground line**
- **ParkAssist ultrasound sensor** faulty

Fault effects

- ♦ System switches off
- ♦ Display in instrument cluster

Diagnostic information - ParkAssist

ParkAssist ultrasound sensor

DANGER

Increased risk of accidents due to movement of the vehicle!

- ♦ Never step in front of or behind a vehicle unless it has been secured against rolling by the parking brake and transmission.
- ♦ The ParkAssist is subject to physical detection limits and does not free the driver from his/her responsibility to be careful.
- ♦ The system cannot detect short, thin and small obstacles and persons who are lying on the ground. It also cannot detect surfaces with unfavourable reflective characteristics, e.g. snow or glass.

Diagnostic conditions

- Internal function test on ParkAssist control unit
- Ignition on
- Reverse gear or transmission range R selected
- Vehicle speed briefly higher than 14 km/h (9 mph)

Fault setting condition(s)

INFORMATION

Fault entry due to ambient conditions: this fault can also occur if the sensors are heavily soiled, iced-up or have been painted. In addition, intense sound sources such as pneumatic hammers can cause interference.

- Signal lead Short circuit to B+/ground or open circuit in the line
- **Supply line**
- **Ground line**
- **ParkAssist ultrasound sensor** faulty

Fault effects

- ♦ System switches off
- ♦ Display in instrument cluster

Diagnostic information - ParkAssist

ParkAssist ultrasound sensor

DANGER

Increased risk of accidents due to movement of the vehicle!

- ♦ Never step in front of or behind a vehicle unless it has been secured against rolling by the parking brake and transmission.
- ♦ The ParkAssist is subject to physical detection limits and does not free the driver from his/her responsibility to be careful.
- ♦ The system cannot detect short, thin and small obstacles and persons who are lying on the ground. It also cannot detect surfaces with unfavourable reflective characteristics, e.g. snow or glass.

Diagnostic conditions

- Internal function test on ParkAssist control unit
- Ignition on
- Reverse gear or transmission range R selected
- Vehicle speed briefly higher than 14 km/h (9 mph)

Fault setting condition(s)

INFORMATION

Fault entry due to ambient conditions: this fault can also occur if the sensors are heavily soiled, iced-up or have been painted. In addition, intense sound sources such as pneumatic hammers can cause interference.

- Signal lead Short circuit to B+/ground or open circuit in the line
- **Supply line**
- **Ground line**
- **ParkAssist ultrasound sensor** faulty

Fault effects

- ♦ System switches off
- ♦ Display in instrument cluster

Diagnostic information - ParkAssist

ParkAssist ultrasound sensor

DANGER

Increased risk of accidents due to movement of the vehicle!

- ♦ Never step in front of or behind a vehicle unless it has been secured against rolling by the parking brake and transmission.
- ♦ The ParkAssist is subject to physical detection limits and does not free the driver from his/her responsibility to be careful.
- ♦ The system cannot detect short, thin and small obstacles and persons who are lying on the ground. It also cannot detect surfaces with unfavourable reflective characteristics, e.g. snow or glass.

Diagnostic conditions

- Internal function test on ParkAssist control unit
- Ignition on
- Reverse gear or transmission range R selected
- Vehicle speed briefly higher than 14 km/h (9 mph)

Fault setting condition(s)

INFORMATION

Fault entry due to ambient conditions: this fault can also occur if the sensors are heavily soiled, iced-up or have been painted. In addition, intense sound sources such as pneumatic hammers can cause interference.

- Signal lead Short circuit to B+/ground or open circuit in the line
- **Supply line**
- **Ground line**
- **ParkAssist ultrasound sensor** faulty

Fault effects

- ♦ System switches off
- ♦ Display in instrument cluster

Diagnostic information - ParkAssist

ParkAssist ultrasound sensor

DANGER

Increased risk of accidents due to movement of the vehicle!

- ♦ Never step in front of or behind a vehicle unless it has been secured against rolling by the parking brake and transmission.
- ♦ The ParkAssist is subject to physical detection limits and does not free the driver from his/her responsibility to be careful.
- ♦ The system cannot detect short, thin and small obstacles and persons who are lying on the ground. It also cannot detect surfaces with unfavourable reflective characteristics, e.g. snow or glass.

Diagnostic conditions

- Internal function test on ParkAssist control unit
- Ignition on
- Reverse gear or transmission range R selected
- Vehicle speed briefly higher than 14 km/h (9 mph)

Fault setting condition(s)

i INFORMATION

Fault entry due to ambient conditions: this fault can also occur if the sensors are heavily soiled, iced-up or have been painted. In addition, intense sound sources such as pneumatic hammers can cause interference.

- Signal lead Short circuit to B+/ground or open circuit in the line
- **Supply line**
- **Ground line**
- **ParkAssist ultrasound sensor** faulty

Fault effects

- ♦ System switches off
- ♦ Display in instrument cluster

Diagnostic information - ParkAssist

ParkAssist ultrasound sensor

DANGER

Increased risk of accidents due to movement of the vehicle!

- ♦ Never step in front of or behind a vehicle unless it has been secured against rolling by the parking brake and transmission.
- ♦ The ParkAssist is subject to physical detection limits and does not free the driver from his/her responsibility to be careful.
- ♦ The system cannot detect short, thin and small obstacles and persons who are lying on the ground. It also cannot detect surfaces with unfavourable reflective characteristics, e.g. snow or glass.

Diagnostic conditions

- Internal function test on ParkAssist control unit
- Ignition on
- Reverse gear or transmission range R selected
- Vehicle speed briefly higher than 14 km/h (9 mph)

Fault setting condition(s)

INFORMATION

Fault entry due to ambient conditions: this fault can also occur if the sensors are heavily soiled, iced-up or have been painted. In addition, intense sound sources such as pneumatic hammers can cause interference.

- Signal lead Short circuit to B+/ground or open circuit in the line
- **Supply line**
- **Ground line**
- **ParkAssist ultrasound sensor** faulty

Fault effects

- ♦ System switches off
- ♦ Display in instrument cluster

Diagnostic information - ParkAssist

ParkAssist ultrasound sensor

DANGER

Increased risk of accidents due to movement of the vehicle!

- ♦ Never step in front of or behind a vehicle unless it has been secured against rolling by the parking brake and transmission.
- ♦ The ParkAssist is subject to physical detection limits and does not free the driver from his/her responsibility to be careful.
- ♦ The system cannot detect short, thin and small obstacles and persons who are lying on the ground. It also cannot detect surfaces with unfavourable reflective characteristics, e.g. snow or glass.

Diagnostic conditions

- Internal function test on ParkAssist control unit
- Ignition on
- Reverse gear or transmission range R selected
- Vehicle speed briefly higher than 14 km/h (9 mph)

Fault setting condition(s)

INFORMATION

Fault entry due to ambient conditions: this fault can also occur if the sensors are heavily soiled, iced-up or have been painted. In addition, intense sound sources such as pneumatic hammers can cause interference.

- Signal lead Short circuit to B+/ground or open circuit in the line
- **Supply line**
- **Ground line**
- **ParkAssist ultrasound sensor** faulty

Fault effects

- ♦ System switches off
- ♦ Display in instrument cluster

Diagnostic information - ParkAssist

ParkAssist ultrasound sensor

DANGER

Increased risk of accidents due to movement of the vehicle!

- ♦ Never step in front of or behind a vehicle unless it has been secured against rolling by the parking brake and transmission.
- ♦ The ParkAssist is subject to physical detection limits and does not free the driver from his/her responsibility to be careful.
- ♦ The system cannot detect short, thin and small obstacles and persons who are lying on the ground. It also cannot detect surfaces with unfavourable reflective characteristics, e.g. snow or glass.

Diagnostic conditions

- Internal function test on ParkAssist control unit
- Ignition on
- Reverse gear or transmission range R selected
- Vehicle speed briefly higher than 14 km/h (9 mph)

Fault setting condition(s)

INFORMATION

Fault entry due to ambient conditions: this fault can also occur if the sensors are heavily soiled, iced-up or have been painted. In addition, intense sound sources such as pneumatic hammers can cause interference.

- Signal lead Short circuit to B+/ground or open circuit in the line
- **Supply line**
- **Ground line**
- **ParkAssist ultrasound sensor** faulty

Fault effects

- ♦ System switches off
- ♦ Display in instrument cluster

Diagnostic information - ParkAssist

ParkAssist ultrasound sensor

DANGER

Increased risk of accidents due to movement of the vehicle!

- ♦ Never step in front of or behind a vehicle unless it has been secured against rolling by the parking brake and transmission.
- ♦ The ParkAssist is subject to physical detection limits and does not free the driver from his/her responsibility to be careful.
- ♦ The system cannot detect short, thin and small obstacles and persons who are lying on the ground. It also cannot detect surfaces with unfavourable reflective characteristics, e.g. snow or glass.

Diagnostic conditions

- Internal function test on ParkAssist control unit
- Ignition on
- Reverse gear or transmission range R selected
- Vehicle speed briefly higher than 14 km/h (9 mph)

Fault setting condition(s)

INFORMATION

Fault entry due to ambient conditions: this fault can also occur if the sensors are heavily soiled, iced-up or have been painted. In addition, intense sound sources such as pneumatic hammers can cause interference.

- Signal lead Short circuit to B+/ground or open circuit in the line
- **Supply line**
- **Ground line**
- **ParkAssist ultrasound sensor** faulty

Fault effects

- ♦ System switches off
- ♦ Display in instrument cluster

Diagnostic information - ParkAssist

ParkAssist ultrasound sensor

DANGER

Increased risk of accidents due to movement of the vehicle!

- ♦ Never step in front of or behind a vehicle unless it has been secured against rolling by the parking brake and transmission.
- ♦ The ParkAssist is subject to physical detection limits and does not free the driver from his/her responsibility to be careful.
- ♦ The system cannot detect short, thin and small obstacles and persons who are lying on the ground. It also cannot detect surfaces with unfavourable reflective characteristics, e.g. snow or glass.

Diagnostic conditions

- Internal function test on ParkAssist control unit
- Ignition on
- Reverse gear or transmission range R selected
- Vehicle speed briefly higher than 14 km/h (9 mph)

Fault setting condition(s)

INFORMATION

Fault entry due to ambient conditions: this fault can also occur if the sensors are heavily soiled, iced-up or have been painted. In addition, intense sound sources such as pneumatic hammers can cause interference.

- Signal lead Short circuit to B+/ground or open circuit in the line
- **Supply line**
- **Ground line**
- **ParkAssist ultrasound sensor** faulty

Fault effects

- ♦ System switches off
- ♦ Display in instrument cluster