

Class 14: Pathway Analysis from RNA-Seq Results

Clarissa Savko (PID: A69028482)

Table of contents

Data Import	4
Data Tidying	4
DESeq setup and analysis	5
Save Results	6
Visualize	7
Annotation Data	9
Geneset enrichment/pathway analysis	11
Gene Ontology	16
Reactome	17

```
library(DESeq2)
```

```
Loading required package: S4Vectors
```

```
Loading required package: stats4
```

```
Loading required package: BiocGenerics
```

```
Attaching package: 'BiocGenerics'
```

The following objects are masked from 'package:stats':

IQR, mad, sd, var, xtabs

The following objects are masked from 'package:base':

anyDuplicated, aperm, append, as.data.frame, basename, cbind,
colnames, dirname, do.call, duplicated, eval, evalq, Filter, Find,
get, grep, grepl, intersect, is.unsorted, lapply, Map, mapply,
match, mget, order, paste, pmax, pmax.int, pmin, pmin.int,
Position, rank, rbind, Reduce, rownames, sapply, setdiff, sort,
table, tapply, union, unique, unsplit, which.max, which.min

Attaching package: 'S4Vectors'

The following object is masked from 'package:utils':

findMatches

The following objects are masked from 'package:base':

expand.grid, I, unname

Loading required package: IRanges

Attaching package: 'IRanges'

The following object is masked from 'package:grDevices':

windows

Loading required package: GenomicRanges

Loading required package: GenomeInfoDb

Warning: package 'GenomeInfoDb' was built under R version 4.3.2

Loading required package: SummarizedExperiment

Loading required package: MatrixGenerics

Loading required package: matrixStats

Warning: package 'matrixStats' was built under R version 4.3.2

Attaching package: 'MatrixGenerics'

The following objects are masked from 'package:matrixStats':

colAlls, colAnyNAs, colAnys, colAvgsPerRowSet, colCollapse,
colCounts, colCummaxs, colCummins, colCumprods, colCumsums,
colDiffs, colIQRDiffs, colIQRs, colLogSumExps, colMadDiffs,
colMads, colMaxs, colMeans2, colMedians, colMins, colOrderStats,
colProds, colQuantiles, colRanges, colRanks, colSdDiffs, colSds,
colSums2, colTabulates, colVarDiffs, colVars, colWeightedMads,
colWeightedMeans, colWeightedMedians, colWeightedSds,
colWeightedVars, rowAlls, rowAnyNAs, rowAnys, rowAvgsPerColSet,
rowCollapse, rowCounts, rowCummaxs, rowCummins, rowCumprods,
rowCumsums, rowDiffs, rowIQRDiffs, rowIQRs, rowLogSumExps,
rowMadDiffs, rowMads, rowMaxs, rowMeans2, rowMedians, rowMins,
rowOrderStats, rowProds, rowQuantiles, rowRanges, rowRanks,
rowSdDiffs, rowSds, rowSums2, rowTabulates, rowVarDiffs, rowVars,
rowWeightedMads, rowWeightedMeans, rowWeightedMedians,
rowWeightedSds, rowWeightedVars

Loading required package: Biobase

Welcome to Bioconductor

Vignettes contain introductory material; view with
'browseVignettes()'. To cite Bioconductor, see
'citation("Biobase")', and for packages 'citation("pkgname")'.

Attaching package: 'Biobase'

The following object is masked from 'package:MatrixGenerics':

rowMedians

The following objects are masked from 'package:matrixStats':

anyMissing, rowMedians

Data Import

```
metaFile <- "GSE37704_metadata.csv"
countFile <- "GSE37704_featurecounts.csv"

# Import metadata and take a peak
colData = read.csv(metaFile, row.names=1)
head(colData)
```

```
              condition
SRR493366 control_sirna
SRR493367 control_sirna
SRR493368 control_sirna
SRR493369      hoxa1_kd
SRR493370      hoxa1_kd
SRR493371      hoxa1_kd
```

Data Tidying

```
countData = read.csv(countFile, row.names=1)
head(countData)
```

```
              length SRR493366 SRR493367 SRR493368 SRR493369 SRR493370
ENSG00000186092    918         0         0         0         0         0
ENSG00000279928    718         0         0         0         0         0
ENSG00000279457   1982        23        28        29        29        28
ENSG00000278566    939         0         0         0         0         0
ENSG00000273547    939         0         0         0         0         0
ENSG00000187634   3214       124       123       205       207       212
              SRR493371
ENSG00000186092         0
ENSG00000279928         0
ENSG00000279457        46
ENSG00000278566         0
ENSG00000273547         0
ENSG00000187634       258
```

Q. Complete the code below to remove the troublesome first column from countData

```
countData <- as.matrix(countData[,-1])
head(countData)
```

	SRR493366	SRR493367	SRR493368	SRR493369	SRR493370	SRR493371
ENSG00000186092	0	0	0	0	0	0
ENSG00000279928	0	0	0	0	0	0
ENSG00000279457	23	28	29	29	28	46
ENSG00000278566	0	0	0	0	0	0
ENSG00000273547	0	0	0	0	0	0
ENSG00000187634	124	123	205	207	212	258

Q. Complete the code below to filter countData to exclude genes (i.e. rows) where we have 0 read count across all samples (i.e. columns).

How many genes do we have to start with?

```
nrow(countData)
```

```
[1] 19808
```

- 1) Find the rowSums() this will be zero for any genes with no count data
- 2) Find the zero sum genes
- 3) Remove them

```
to.rm.inds <- rowSums(countData) == 0
countData <- countData[!to.rm.inds,]
nrow(countData)
```

```
[1] 15975
```

DESeq setup and analysis

```
dds <- DESeqDataSetFromMatrix(countData = countData,
                              colData = colData,
                              design= ~condition)
```

Warning in DESeqDataSet(se, design = design, ignoreRank): some variables in design formula are characters, converting to factors

```
dds = DESeq(dds)
```

estimating size factors

estimating dispersions

gene-wise dispersion estimates

mean-dispersion relationship

final dispersion estimates

fitting model and testing

Save Results


Q. Call the `summary()` function on your results to get a sense of how many genes are up or down-regulated at the default 0.1 p-value cutoff.

```
res = results(dds)
summary(res)
```

```
out of 15975 with nonzero total read count
adjusted p-value < 0.1
LFC > 0 (up)      : 4349, 27%
LFC < 0 (down)    : 4396, 28%
outliers [1]      : 0, 0%
low counts [2]    : 1237, 7.7%
(mean count < 0)
[1] see 'cooksCutoff' argument of ?results
[2] see 'independentFiltering' argument of ?results
```

Visualize

```
plot( res$log2FoldChange, -log(res$padj) )
```




```
pc <- prcomp(t(countData), scale= T)
summary(pc)
```

Importance of components:

	PC1	PC2	PC3	PC4	PC5	PC6
Standard deviation	87.7211	73.3196	32.89604	31.15094	29.18417	7.373e-13
Proportion of Variance	0.4817	0.3365	0.06774	0.06074	0.05332	0.000e+00
Cumulative Proportion	0.4817	0.8182	0.88594	0.94668	1.00000	1.000e+00

```
plot(pc$x[,1], pc$x[,2], col=as.factor(colData$condition), pch=15)
```




Q. Improve this plot by completing the below code, which adds color and axis labels

```
# Make a color vector for all genes
mycols <- rep("gray", nrow(res) )

# Color red the genes with absolute fold change above 2
mycols[ abs(res$log2FoldChange) > 2 ] <- "red"

# Color blue those with adjusted p-value less than 0.01
# and absolute fold change more than 2
inds <- (res$padj < 0.01) & (abs(res$log2FoldChange) > 2 )
mycols[ inds ] <- "blue"

plot( res$log2FoldChange, -log(res$padj), col= mycols, xlab="Log2(FoldChange)", ylab="-Log
```

Annotation Data

Q. Use the `mapIDs()` function multiple times to add `SYMBOL`, `ENTREZID` and `GENENAME` annotation to our results by completing the code below.

```
library("AnnotationDbi")
```

Warning: package 'AnnotationDbi' was built under R version 4.3.2

```
library("org.Hs.eg.db")
```

```
columns(org.Hs.eg.db)
```

```
[1] "ACCNUM"      "ALIAS"       "ENSEMBL"     "ENSEMBLPROT" "ENSEMBLTRANS"
[6] "ENTREZID"    "ENZYME"      "EVIDENCE"     "EVIDENCEALL"  "GENENAME"
[11] "GENETYPE"    "GO"          "GOALL"        "IPI"          "MAP"
```

```
[16] "OMIM"          "ONTOLOGY"      "ONTOLOGYALL"  "PATH"         "PFAM"
[21] "PMID"          "PROSITE"       "REFSEQ"       "SYMBOL"       "UCSCKG"
[26] "UNIPROT"
```

```
res$symbol = mapIds(org.Hs.eg.db,
                     keys= row.names(res),
                     keytype="ENSEMBL",
                     column= "SYMBOL",
                     multiVals="first")
```

'select()' returned 1:many mapping between keys and columns

```
res$entrez = mapIds(org.Hs.eg.db,
                     keys=row.names(res),
                     keytype="ENSEMBL",
                     column="ENTREZID",
                     multiVals="first")
```

'select()' returned 1:many mapping between keys and columns

```
res$name = mapIds(org.Hs.eg.db,
                   keys=row.names(res),
                   keytype= "ENSEMBL",
                   column= "GENENAME",
                   multiVals="first")
```

'select()' returned 1:many mapping between keys and columns

```
head(res, 10)
```

log2 fold change (MLE): condition hoxa1 kd vs control sirna

Wald test p-value: condition hoxa1 kd vs control sirna

DataFrame with 10 rows and 9 columns

	baseMean	log2FoldChange	lfcSE	stat	pvalue
	<numeric>	<numeric>	<numeric>	<numeric>	<numeric>
ENSG00000279457	29.913579	0.1792571	0.3248216	0.551863	5.81042e-01
ENSG00000187634	183.229650	0.4264571	0.1402658	3.040350	2.36304e-03

ENSG00000188976	1651.188076	-0.6927205	0.0548465	-12.630158	1.43990e-36
ENSG00000187961	209.637938	0.7297556	0.1318599	5.534326	3.12428e-08
ENSG00000187583	47.255123	0.0405765	0.2718928	0.149237	8.81366e-01
ENSG00000187642	11.979750	0.5428105	0.5215598	1.040744	2.97994e-01
ENSG00000188290	108.922128	2.0570638	0.1969053	10.446970	1.51282e-25
ENSG00000187608	350.716868	0.2573837	0.1027266	2.505522	1.22271e-02
ENSG00000188157	9128.439422	0.3899088	0.0467163	8.346304	7.04321e-17
ENSG00000237330	0.158192	0.7859552	4.0804729	0.192614	8.47261e-01
	padj	symbol	entrez		name
	<numeric>	<character>	<character>		<character>
ENSG00000279457	6.86555e-01	NA	NA		NA
ENSG00000187634	5.15718e-03	SAMD11	148398	sterile alpha motif ..	
ENSG00000188976	1.76549e-35	NOC2L	26155	NOC2 like nucleolar ..	
ENSG00000187961	1.13413e-07	KLHL17	339451	kelch like family me..	
ENSG00000187583	9.19031e-01	PLEKHN1	84069	pleckstrin homology ..	
ENSG00000187642	4.03379e-01	PERM1	84808	PPARGC1 and ESRR ind..	
ENSG00000188290	1.30538e-24	HES4	57801	hes family bHLH tran..	
ENSG00000187608	2.37452e-02	ISG15	9636	ISG15 ubiquitin like..	
ENSG00000188157	4.21963e-16	AGRN	375790		agrin
ENSG00000237330	NA	RNF223	401934	ring finger protein ..	

Q. Finally for this section let's reorder these results by adjusted p-value and save them to a CSV file in your current project directory.

```
res = res[order(res$pvalue),]
write.csv(res, file = "deseq_results.csv")
```

Geneset enrichment/pathway analysis

```
library(gage)
library(gageData)
library(pathview)
```

The `gage()` function wants a “vector of importance” in our case here it will be fold-change values with associated entrez gene names.

```
foldchange <- res$log2FoldChange
names(foldchange) = res$entrez
```

```
data(kegg.sets.hs)
keggres = gage(foldchange, gsets= kegg.sets.hs)
head(keggres$less)
```

	p.geomean	stat.mean
hsa04110 Cell cycle	8.995727e-06	-4.378644
hsa03030 DNA replication	9.424076e-05	-3.951803
hsa05130 Pathogenic Escherichia coli infection	1.405864e-04	-3.765330
hsa03013 RNA transport	1.375901e-03	-3.028500
hsa03440 Homologous recombination	3.066756e-03	-2.852899
hsa04114 Oocyte meiosis	3.784520e-03	-2.698128

	p.val	q.val
hsa04110 Cell cycle	8.995727e-06	0.001889103
hsa03030 DNA replication	9.424076e-05	0.009841047
hsa05130 Pathogenic Escherichia coli infection	1.405864e-04	0.009841047
hsa03013 RNA transport	1.375901e-03	0.072234819
hsa03440 Homologous recombination	3.066756e-03	0.128803765
hsa04114 Oocyte meiosis	3.784520e-03	0.132458191

	set.size	exp1
hsa04110 Cell cycle	121	8.995727e-06
hsa03030 DNA replication	36	9.424076e-05
hsa05130 Pathogenic Escherichia coli infection	53	1.405864e-04
hsa03013 RNA transport	144	1.375901e-03
hsa03440 Homologous recombination	28	3.066756e-03
hsa04114 Oocyte meiosis	102	3.784520e-03

hsa04110 cell cycle


```
pathview(gene.data= foldchange, pathway.id = "hsa04110")
```

'select()' returned 1:1 mapping between keys and columns

Info: Working in directory C:/Users/clari/Desktop/BGGN213 Bioinformatics/R files BGGN213/Clari

Info: Writing image file hsa04110.pathview.png

Have a look at my figure (?@fig-cellcycle)



Q. Can you do the same procedure as above to plot the pathview figures for the top 5 down-regulated pathways?

```
pathview(gene.data= foldchange, pathway.id = "hsa03030")
```

'select()' returned 1:1 mapping between keys and columns

Info: Working in directory C:/Users/clari/Desktop/BGGN213 Bioinformatics/R files BGGN213/Clari

Info: Writing image file hsa03030.pathview.png

```
pathview(gene.data= foldchange, pathway.id = "hsa05130")
```

'select()' returned 1:1 mapping between keys and columns

Info: Working in directory C:/Users/clari/Desktop/BGGN213 Bioinformatics/R files BGGN213/Clari

Info: Writing image file hsa05130.pathview.png

```
pathview(gene.data= foldchange, pathway.id = "hsa03013")
```

'select()' returned 1:1 mapping between keys and columns

Info: Working in directory C:/Users/clari/Desktop/BGGN213 Bioinformatics/R files BGGN213/Clari


Info: Writing image file hsa03013.pathview.png


```
pathview(gene.data= foldchange, pathway.id = "hsa03440")
```

'select()' returned 1:1 mapping between keys and columns

Info: Working in directory C:/Users/clari/Desktop/BGGN213 Bioinformatics/R files BGGN213/Clari

Info: Writing image file hsa03440.pathview.png





G0:0007610	behavior	0.1968058	426	1.925222e-04
G0:0060562	epithelial tube morphogenesis	0.3566193	257	5.932837e-04
G0:0035295	tube development	0.3566193	391	5.953254e-04

\$less

		p.geomean	stat.mean	p.val
G0:0048285	organelle fission	1.536227e-15	-8.063910	1.536227e-15
G0:0000280	nuclear division	4.286961e-15	-7.939217	4.286961e-15
G0:0007067	mitosis	4.286961e-15	-7.939217	4.286961e-15
G0:0000087	M phase of mitotic cell cycle	1.169934e-14	-7.797496	1.169934e-14
G0:0007059	chromosome segregation	2.028624e-11	-6.878340	2.028624e-11
G0:0000236	mitotic prometaphase	1.729553e-10	-6.695966	1.729553e-10

		q.val	set.size	exp1
G0:0048285	organelle fission	5.843127e-12	376	1.536227e-15
G0:0000280	nuclear division	5.843127e-12	352	4.286961e-15
G0:0007067	mitosis	5.843127e-12	352	4.286961e-15
G0:0000087	M phase of mitotic cell cycle	1.195965e-11	362	1.169934e-14
G0:0007059	chromosome segregation	1.659009e-08	142	2.028624e-11
G0:0000236	mitotic prometaphase	1.178690e-07	84	1.729553e-10

\$stats

		stat.mean	exp1
G0:0007156	homophilic cell adhesion	3.824205	3.824205
G0:0002009	morphogenesis of an epithelium	3.653886	3.653886
G0:0048729	tissue morphogenesis	3.643242	3.643242
G0:0007610	behavior	3.565432	3.565432
G0:0060562	epithelial tube morphogenesis	3.261376	3.261376
G0:0035295	tube development	3.253665	3.253665

Reactome


We will use the online version of Reactome. It wants a list of your genes. We will write this out from R here:

```
sig_genes <- res[res$padj <= 0.05 & !is.na(res$padj), "symbol"]
print(paste("Total number of significant genes:", length(sig_genes)))
```


```
[1] "Total number of significant genes: 8147"
```

```
write.table(sig_genes, file="significant_genes.txt", row.names=FALSE, col.names=FALSE, quo
```

Have a look at my figure (?@fig-SMAD)



Have a look at my figure (?@fig-cellcycle)



Q: What pathway has the most significant “Entities p-value”? Do the most significant pathways listed match your previous KEGG results? What factors could cause differences between the two methods?

Mitotic cell cycle. This matches the most downregulated pathway in the KEGG results. They are using different databases as references so they will show different results.