

# MCP Server Implementation - Pseudocode Template

## Overview

This pseudocode template provides a complete, language-agnostic reference implementation for building a production-ready MCP (Model Context Protocol) server with OAuth 2.1 + PKCE authentication. The template expands on the pseudocode examples in the presentation and implementation documentation, providing comprehensive coverage of all server components.

**Purpose:** Serve as a blueprint for translating core MCP server logic into any programming language.

**Target Audience:** Developers and architects building ServiceNow MCP integrations or other enterprise MCP server implementations.

---

## Table of Contents

1. Configuration and Constants
  2. Data Structures
  3. Server Initialization
  4. OAuth 2.1 Endpoints
    - Dynamic Client Registration (DCR)
    - Authorization Endpoint
    - Token Endpoint
    - Token Revocation Endpoint
  5. JWT Token Management
  6. PKCE Validation
  7. Token Blacklist Management
  8. Rate Limiting
  9. Authentication Middleware
  10. MCP Protocol Handlers
  11. Metadata Endpoints
  12. Health Check Endpoint
  13. Audit Logging
-

## 1. Configuration and Constants

pseudocode

// Server Configuration

CONSTANT SERVER\_PORT = 3000

CONSTANT SERVER\_HOST = "0.0.0.0"

CONSTANT JWT\_ISSUER = "https://mcp-server.example.com"

// Token Lifetimes (in seconds)

CONSTANT AUTHORIZATION\_CODE\_LIFETIME = 300 // 5 minutes

CONSTANT ACCESS\_TOKEN\_LIFETIME = 3600 // 1 hour

CONSTANT REFRESH\_TOKEN\_LIFETIME = 2592000 // 30 days

// Security Configuration

CONSTANT JWT\_ALGORITHM = "HS256"

CONSTANT JWT\_SECRET = getEnvironmentVariable("JWT\_SECRET") // Load from secure environment

CONSTANT DCR\_REGISTRATION\_TOKEN = getEnvironmentVariable("DCR\_TOKEN") // Optional

// Rate Limiting Configuration

CONSTANT RATE\_LIMIT\_WINDOW\_MS = 900000 // 15 minutes

CONSTANT RATE\_LIMIT\_MAX\_REQUESTS = 100 // Max requests per window

CONSTANT OAUTH\_RATE\_LIMIT\_MAX = 10 // More restrictive for OAuth endpoints

// MCP Protocol Configuration

CONSTANT MCP\_PROTOCOL\_VERSION = "2025-06-18"

CONSTANT MCP\_SERVER\_NAME = "mcp-oauth21-server"

CONSTANT MCP\_SERVER\_VERSION = "3.3.0"

// PKCE Configuration

CONSTANT SUPPORTED\_PKCE\_METHODS = ["S256", "plain"]

CONSTANT RECOMMENDED\_PKCE\_METHOD = "S256"

---

## 2. Data Structures

pseudocode

```
// In-memory storage structures (replace with persistent storage in production)
```

```
GLOBAL registeredClients = Map()    // Map<client_id, ClientRecord>
```

```
GLOBAL authorizationCodes = Map()    // Map<code, AuthCodeRecord>
```

```
GLOBAL activeRefreshTokens = Set()   // Set<refresh_token_jti>
```

```
GLOBAL revokedTokens = Set()         // Set<token_jti> - Token blacklist
```

```
STRUCTURE ClientRecord:
```

```
    client_id: string
```

```
    client_secret: string
```

```
    client_name: string
```

```
    redirect_uris: array of string
```

```
    grant_types: array of string
```

```
    response_types: array of string
```

```
    use_pkce: boolean
```

```
    created_at: timestamp
```

```
END STRUCTURE
```

```
STRUCTURE AuthCodeRecord:
```

```
    code: string
```

```
    client_id: string
```

```
    redirect_uri: string
```

```
    scope: string
```

```
    code_challenge: string
```

```
    code_challenge_method: string
```

```
    user_id: string
```

```
    expires_at: timestamp
```

```
    used: boolean
```

```
END STRUCTURE
```

```
STRUCTURE JWTAccessTokenPayload:
```

```
    sub: string    // user_id
```

```
    client_id: string
```

```
    scope: string
```

```
    type: "access"
```

```
    iat: timestamp
```

```
    exp: timestamp
```

```
    iss: string
```

```
    jti: string    // Unique token identifier for revocation
```

```
END STRUCTURE
```

```
STRUCTURE JWTRefreshTokenPayload:
```

```
    sub: string    // user_id
```

```
    client_id: string
```

```
scope: string
type: "refresh"
rotation_count: integer
iat: timestamp
exp: timestamp
iss: string
jti: string      // Unique token identifier for revocation
END STRUCTURE
```

---

### 3. Server Initialization

pseudocode

```

FUNCTION initializeServer()
    LOG "Starting MCP OAuth 2.1 Server"
    LOG "Issuer: " + JWT_ISSUER
    LOG "Protocol Version: " + MCP_PROTOCOL_VERSION

    // Validate required configuration
    IF JWT_SECRET is empty THEN
        ERROR "JWT_SECRET environment variable is required"
        EXIT
    END IF

    // Initialize storage connections (if using persistent storage)
    initializeTokenBlacklist()

    // Register routes
    registerOAuthRoutes()
    registerMCPRoutes()
    registerMetadataRoutes()
    registerHealthCheckRoute()

    // Start HTTP server
    startHTTPServer(SERVER_HOST, SERVER_PORT)

    LOG "Server listening on " + SERVER_HOST + ":" + SERVER_PORT
END FUNCTION

```

```

FUNCTION initializeTokenBlacklist()
    // Initialize connection to token blacklist storage
    // This could be Redis, database, or in-memory for development
    LOG "Initializing token blacklist storage"

    // Example: Connect to storage backend
    // revokedTokens = connectToStorageBackend()
END FUNCTION

```

## 4. OAuth 2.1 Endpoints

### 4.1 Dynamic Client Registration (DCR)

pseudocode

ROUTE POST "/register"

FUNCTION handleDynamicClientRegistration(request, response)

LOG "=== DCR REQUEST ==="

// Optional: Validate DCR authorization token

IF DCR\_REGISTRATION\_TOKEN is configured THEN

authHeader = request.headers["authorization"]

IF NOT authHeader THEN

```
RETURN response(401, {  
  error: "invalid_token",  
  error_description: "Missing authorization header"  
})
```

END IF

IF NOT authHeader.startsWith("Bearer ") THEN

```
RETURN response(401, {  
  error: "invalid_token",  
  error_description: "Invalid authorization format"  
})
```

END IF

providedToken = authHeader.substring(7) // Remove "Bearer "

IF providedToken != DCR\_REGISTRATION\_TOKEN THEN

```
RETURN response(401, {  
  error: "invalid_token",  
  error_description: "Invalid registration token"  
})
```

END IF

LOG "âœ“ DCR token validated"

END IF

// Extract client registration details

client\_name = request.body.client\_name OR "Unnamed Client"

redirect\_uris = request.body.redirect\_uris OR []

grant\_types = request.body.grant\_types OR ["authorization\_code", "refresh\_token"]

use\_pkce = request.body.use\_pkce OR false

// Validate redirect URIs (required)

IF redirect\_uris.length = 0 THEN

```
RETURN response(400, {
```

```
        error: "invalid_redirect_uri",
        error_description: "At least one redirect_uri is required"
    })
END IF
```

```
// Generate unique client credentials
client_id = generateUUID()
client_secret = generateSecureToken(32)
```

```
// Create client record
clientRecord = ClientRecord {
    client_id: client_id,
    client_secret: client_secret,
    client_name: client_name,
    redirect_uris: redirect_uris,
    grant_types: grant_types,
    response_types: ["code"],
    use_pkce: use_pkce,
    created_at: currentTimestamp()
}
```

```
// Store client (persistent storage in production)
registeredClients.set(client_id, clientRecord)
```

```
LOG "âœ“ Client registered: " + client_id
LOG "Client name: " + client_name
LOG "PKCE enabled: " + use_pkce
```

```
// Return credentials (RFC 7591 format)
RETURN response(201, {
    client_id: client_id,
    client_secret: client_secret,
    client_name: client_name,
    redirect_uris: redirect_uris,
    grant_types: grant_types,
    response_types: ["code"],
    token_endpoint_auth_method: "client_secret_post"
})
```

```
END FUNCTION
END ROUTE
```

4.2 Authorization Endpoint

pseudocode



ROUTE GET "/oauth/authorize"

FUNCTION handleAuthorization(request, response)

LOG "=== AUTHORIZATION REQUEST ==="

// Extract OAuth 2.1 parameters

client\_id = request.query.client\_id

redirect\_uri = request.query.redirect\_uri

response\_type = request.query.response\_type

scope = request.query.scope OR "openid email profile"

state = request.query.state

code\_challenge = request.query.code\_challenge

code\_challenge\_method = request.query.code\_challenge\_method

// Validate response\_type

IF response\_type != "code" THEN

errorParams = "error=unsupported\_response\_type"

IF state THEN

errorParams = errorParams + "&state=" + state

END IF

RETURN redirect(redirect\_uri + "?" + errorParams)

END IF

// Validate required parameters

IF NOT client\_id OR NOT redirect\_uri THEN

RETURN response(400, {

error: "invalid\_request",

error\_description: "Missing required parameters: client\_id and redirect\_uri"

})

END IF

// PKCE validation (mandatory in OAuth 2.1)

IF NOT code\_challenge OR NOT code\_challenge\_method THEN

RETURN response(400, {

error: "invalid\_request",

error\_description: "PKCE required: code\_challenge and code\_challenge\_method must be provided"

})

END IF

// Validate PKCE method

IF code\_challenge\_method NOT IN SUPPORTED\_PKCE\_METHODS THEN

RETURN response(400, {

error: "invalid\_request",

error\_description: "code\_challenge\_method must be S256 or plain"

```
    })
END IF

// Validate client exists
client = registeredClients.get(client_id)
IF NOT client THEN
    RETURN response(400, {
        error: "invalid_client",
        error_description: "Client not found"
    })
END IF

LOG "âœ“ Client validated: " + client_id

// Validate redirect URI is registered
IF NOT client.redirect_uris.includes(redirect_uri) THEN
    RETURN response(400, {
        error: "invalid_request",
        error_description: "redirect_uri not registered for this client"
    })
END IF

LOG "âœ“ Redirect URI validated"
LOG "âœ“ PKCE parameters validated"
LOG "Method: " + code_challenge_method

// NOTE: In production, display user consent screen here
// For service-to-service integration, auto-approve
// ServiceNow handles user authentication, so simulate approved user
user_id = generateUUID() // Simulated authenticated user

LOG "âšŸ,   SIMULATED USER AUTHENTICATION - user_id: " + user_id
LOG "âšŸ,   In production, implement real user authentication here"

// Generate authorization code
authCode = generateSecureToken(32)

// Store authorization code with PKCE parameters
authCodeRecord = AuthCodeRecord {
    code: authCode,
    client_id: client_id,
    redirect_uri: redirect_uri,
    scope: scope,
    code_challenge: code_challenge,
```

```
    code_challenge_method: code_challenge_method,  
    user_id: user_id,  
    expires_at: currentTimestamp() + AUTHORIZATION_CODE_LIFETIME,  
    used: false  
}
```

```
authorizationCodes.set(authCode, authCodeRecord)
```

```
LOG "âœ“ Authorization code generated"
```

```
LOG "Code expires in " + AUTHORIZATION_CODE_LIFETIME + " seconds"
```

```
// Redirect back to client with authorization code
```

```
redirectParams = "code=" + authCode
```

```
IF state THEN
```

```
    redirectParams = redirectParams + "&state=" + state
```

```
END IF
```

```
redirectURL = redirect_uri + "?" + redirectParams
```

```
LOG "Redirecting to: " + redirectURL
```

```
RETURN redirect(redirectURL)
```

```
END FUNCTION
```

```
END ROUTE
```

## 4.3 Token Endpoint

pseudocode

```
ROUTE POST "/oauth/token"
```

```
  APPLY rateLimitMiddleware(OAUTH_RATE_LIMIT_MAX)
```

```
FUNCTION handleTokenExchange(request, response)
```

```
  LOG "=== TOKEN REQUEST ==="
```

```
  LOG "Grant type: " + request.body.grant_type
```

```
  grant_type = request.body.grant_type
```

```
  // Validate grant_type
```

```
  IF NOT grant_type THEN
```

```
    RETURN response(400, {  
      error: "invalid_request",  
      error_description: "grant_type is required"  
    })
```

```
  END IF
```

```
  // Route to appropriate grant handler
```

```
  IF grant_type = "authorization_code" THEN
```

```
    RETURN handleAuthorizationCodeGrant(request, response)
```

```
  ELSE IF grant_type = "refresh_token" THEN
```

```
    RETURN handleRefreshTokenGrant(request, response)
```

```
  ELSE
```

```
    RETURN response(400, {  
      error: "unsupported_grant_type",  
      error_description: "Supported grant types: authorization_code, refresh_token"  
    })
```

```
  END IF
```

```
END FUNCTION
```

```
// Authorization Code Grant Handler
```

```
FUNCTION handleAuthorizationCodeGrant(request, response)
```

```
  LOG "=== AUTHORIZATION CODE GRANT ==="
```

```
  // Extract parameters
```

```
  code = request.body.code
```

```
  redirect_uri = request.body.redirect_uri
```

```
  client_id = request.body.client_id
```

```
  client_secret = request.body.client_secret
```

```
  code_verifier = request.body.code_verifier
```

```
  // Validate required parameters
```

```
  IF NOT code OR NOT redirect_uri OR NOT client_id OR NOT client_secret THEN
```

```
    RETURN response(400, {
        error: "invalid_request",
        error_description: "Missing required parameters"
    })
END IF

// Validate client credentials
client = registeredClients.get(client_id)
IF NOT client OR client.client_secret != client_secret THEN
    RETURN response(401, {
        error: "invalid_client",
        error_description: "Invalid client credentials"
    })
END IF

LOG "âœ“ Client authenticated: " + client_id

// Retrieve authorization code
authCodeRecord = authorizationCodes.get(code)
IF NOT authCodeRecord THEN
    RETURN response(400, {
        error: "invalid_grant",
        error_description: "Authorization code not found"
    })
END IF

// Check if code has been used (prevent replay attacks)
IF authCodeRecord.used THEN
    RETURN response(400, {
        error: "invalid_grant",
        error_description: "Authorization code already used"
    })
END IF

// Check if code has expired
IF currentTimestamp() > authCodeRecord.expires_at THEN
    authorizationCodes.delete(code)
    RETURN response(400, {
        error: "invalid_grant",
        error_description: "Authorization code expired"
    })
END IF

// Validate client_id matches
```

```
IF authCodeRecord.client_id != client_id THEN
    RETURN response(400, {
        error: "invalid_grant",
        error_description: "Authorization code was issued to a different client"
    })
END IF
```

```
// Validate redirect_uri matches
IF authCodeRecord.redirect_uri != redirect_uri THEN
    RETURN response(400, {
        error: "invalid_grant",
        error_description: "redirect_uri does not match"
    })
END IF
```

```
LOG "âœ“ Authorization code validated"
```

```
// PKCE VALIDATION - code_verifier is MANDATORY
IF NOT code_verifier THEN
    RETURN response(400, {
        error: "invalid_request",
        error_description: "code_verifier is required (PKCE)"
    })
END IF
```

```
LOG "=== PKCE VALIDATION ==="
LOG "Method: " + authCodeRecord.code_challenge_method
LOG "Stored challenge: " + authCodeRecord.code_challenge
```

```
// Validate code_verifier against stored challenge
isValid = validatePKCE(
    code_verifier,
    authCodeRecord.code_challenge,
    authCodeRecord.code_challenge_method
)
```

```
IF NOT isValid THEN
    LOG "âœ— PKCE validation failed"
    RETURN response(400, {
        error: "invalid_grant",
        error_description: "Invalid code_verifier"
    })
END IF
```

```
LOG "âœ“ PKCE validation successful"
```

```
// Mark authorization code as used and delete
```

```
authCodeRecord.used = true
```

```
authorizationCodes.delete(code)
```

```
// Issue access token and refresh token
```

```
access_token = createAccessToken(
```

```
    authCodeRecord.user_id,
```

```
    client_id,
```

```
    authCodeRecord.scope
```

```
)
```

```
refresh_token = createRefreshToken(
```

```
    authCodeRecord.user_id,
```

```
    client_id,
```

```
    authCodeRecord.scope,
```

```
    0 // Initial rotation_count
```

```
)
```

```
LOG "âœ“ Tokens issued successfully"
```

```
// Return token response (RFC 6749 format)
```

```
RETURN response(200, {
```

```
    access_token: access_token,
```

```
    token_type: "Bearer",
```

```
    expires_in: ACCESS_TOKEN_LIFETIME,
```

```
    refresh_token: refresh_token,
```

```
    scope: authCodeRecord.scope
```

```
})
```

```
END FUNCTION
```

```
// Refresh Token Grant Handler
```

```
FUNCTION handleRefreshTokenGrant(request, response)
```

```
    LOG "=== REFRESH TOKEN GRANT ==="
```

```
// Extract parameters
```

```
refresh_token = request.body.refresh_token
```

```
client_id = request.body.client_id
```

```
client_secret = request.body.client_secret
```

```
scope = request.body.scope // Optional - can request reduced scope
```

```
// Validate required parameters
```

```
IF NOT refresh_token OR NOT client_id OR NOT client_secret THEN
```

```

    RETURN response(400, {
        error: "invalid_request",
        error_description: "Missing required parameters"
    })
END IF

// Validate client credentials
client = registeredClients.get(client_id)
IF NOT client OR client.client_secret != client_secret THEN
    RETURN response(401, {
        error: "invalid_client",
        error_description: "Invalid client credentials"
    })
END IF

LOG "âœ“ Client authenticated: " + client_id

// Validate refresh token
TRY
    decoded = verifyJWT(refresh_token, JWT_SECRET, {
        algorithms: [JWT_ALGORITHM],
        issuer: JWT_ISSUER
    })

    LOG "âœ“ Refresh token signature valid"
CATCH error
    LOG "âœ— Refresh token validation failed: " + error.message
    RETURN response(400, {
        error: "invalid_grant",
        error_description: "Invalid refresh token"
    })
END TRY

// Verify token type
IF decoded.type != "refresh" THEN
    RETURN response(400, {
        error: "invalid_grant",
        error_description: "Token is not a refresh token"
    })
END IF

// Check if token has been revoked
IF isTokenRevoked(decoded.jti) THEN
    LOG "âœ— Refresh token has been revoked"

```



```

    RETURN response(400, {
        error: "invalid_grant",
        error_description: "Refresh token has been revoked"
    })
END IF

// Validate client_id matches token
IF decoded.client_id != client_id THEN
    RETURN response(400, {
        error: "invalid_grant",
        error_description: "Refresh token was issued to a different client"
    })
END IF

LOG "â€œ Refresh token validated"

// Revoke old refresh token (token rotation)
addTokenToBlacklist(decoded.jti, decoded.exp)

LOG "â€œ Old refresh token revoked"

// Issue new tokens with incremented rotation count
new_access_token = createAccessToken(
    decoded.sub,
    client_id,
    scope OR decoded.scope
)

new_refresh_token = createRefreshToken(
    decoded.sub,
    client_id,
    scope OR decoded.scope,
    decoded.rotation_count + 1
)

LOG "â€œ New tokens issued (rotation count: " + (decoded.rotation_count + 1) + ")"

// Return token response
RETURN response(200, {
    access_token: new_access_token,
    token_type: "Bearer",
    expires_in: ACCESS_TOKEN_LIFETIME,
    refresh_token: new_refresh_token,
    scope: scope OR decoded.scope
})

```

})

END FUNCTION

END ROUTE

#### 4.4 Token Revocation Endpoint

pseudocode

```
ROUTE POST "/oauth/revoke"
```

```
FUNCTION handleTokenRevocation(request, response)
```

```
  LOG "=== TOKEN REVOCATION REQUEST ==="
```

```
  // Extract parameters
```

```
  token = request.body.token
```

```
  client_id = request.body.client_id
```

```
  client_secret = request.body.client_secret
```

```
  // RFC 7009: token parameter is required
```

```
  IF NOT token THEN
```

```
    RETURN response(400, {
```

```
      error: "invalid_request",
```

```
      error_description: "token is required"
```

```
    })
```

```
  END IF
```

```
  // Optional: Validate client credentials
```

```
  IF client_id AND client_secret THEN
```

```
    client = registeredClients.get(client_id)
```

```
    IF NOT client OR client.client_secret != client_secret THEN
```

```
      RETURN response(401, {
```

```
        error: "invalid_client",
```

```
        error_description: "Invalid client credentials"
```

```
      })
```

```
    END IF
```

```
    LOG "âœ“ Client authenticated"
```

```
  END IF
```

```
  // Decode token to get jti (token identifier)
```

```
  TRY
```

```
    decoded = decodeJWT(token) // Decode without verification
```

```
    IF decoded.jti THEN
```

```
      // Add token to blacklist
```

```
      addTokenToBlacklist(decoded.jti, decoded.exp)
```

```
      LOG "âœ“ Token revoked: " + decoded.jti
```

```
    END IF
```

```
  CATCH error
```

```
    // Token might be malformed, but still return 200 per RFC 7009
```

```
    LOG "âœ“ Could not decode token: " + error.message
```

```
  END TRY
```

```
// RFC 7009: Always return 200 OK (even if token not found)
RETURN response(200)
END FUNCTION
END ROUTE
```

---

## 5. JWT Token Management

pseudocode

```
FUNCTION createAccessToken(user_id, client_id, scope)
```

```
    LOG "Creating access token for user: " + user_id
```

```
    // Generate unique token identifier
```

```
    token_jti = generateUUID()
```

```
    // Create token payload
```

```
    payload = JWTAccessTokenPayload {
```

```
        sub: user_id,
```

```
        client_id: client_id,
```

```
        scope: scope,
```

```
        type: "access",
```

```
        iat: currentTimestamp(),
```

```
        exp: currentTimestamp() + ACCESS_TOKEN_LIFETIME,
```

```
        iss: JWT_ISSUER,
```

```
        jti: token_jti
```

```
    }
```

```
    // Sign token
```

```
    access_token = signJWT(payload, JWT_SECRET, JWT_ALGORITHM)
```

```
    RETURN access_token
```

```
END FUNCTION
```

```
FUNCTION createRefreshToken(user_id, client_id, scope, rotation_count)
```

```
    LOG "Creating refresh token for user: " + user_id
```

```
    // Generate unique token identifier
```

```
    token_jti = generateUUID()
```

```
    // Create token payload
```

```
    payload = JWTRefreshTokenPayload {
```

```
        sub: user_id,
```

```
        client_id: client_id,
```

```
        scope: scope,
```

```
        type: "refresh",
```

```
        rotation_count: rotation_count,
```

```
        iat: currentTimestamp(),
```

```
        exp: currentTimestamp() + REFRESH_TOKEN_LIFETIME,
```

```
        iss: JWT_ISSUER,
```

```
        jti: token_jti
```

```
    }
```

```

// Sign token
refresh_token = signJWT(payload, JWT_SECRET, JWT_ALGORITHM)

RETURN refresh_token
END FUNCTION

FUNCTION validateToken(token)
  TRY
    // Verify JWT signature and decode claims
    payload = verifyJWT(token, JWT_SECRET, {
      algorithms: [JWT_ALGORITHM],
      issuer: JWT_ISSUER
    })

    // Check if token has been revoked
    IF isTokenRevoked(payload.jti) THEN
      LOG "â€” Token has been revoked"
      RETURN null
    END IF

    // Token is valid
    LOG "â€” Token validated for client: " + payload.client_id
    RETURN payload

  CATCH error
    // Invalid signature, expired, or malformed
    LOG "â€” Token validation failed: " + error.message
    RETURN null
  END TRY
END FUNCTION

```

## 6. PKCE Validation

pseudocode

```

FUNCTION validatePKCE(code_verifier, code_challenge, method)
    // Validate using S256 method (RECOMMENDED)
    IF method = "S256" THEN
        // Hash the code_verifier using SHA-256
        computed_challenge = base64URLEncode(sha256(code_verifier))

        // Compare with stored challenge
        IF computed_challenge = code_challenge THEN
            RETURN true
        ELSE
            RETURN false
        END IF

    // Validate using plain method (ALLOWED but discouraged)
    ELSE IF method = "plain" THEN
        // Direct comparison (no hashing)
        IF code_verifier = code_challenge THEN
            RETURN true
        ELSE
            RETURN false
        END IF

    // Invalid method
    ELSE
        LOG "Invalid code_challenge_method: " + method
        RETURN false
    END IF
END FUNCTION

```

```

FUNCTION base64URLEncode(data)
    // Encode data in base64url format (RFC 4648)
    // This is URL-safe base64 encoding:
    // - Replace '+' with '-'
    // - Replace '/' with '_'
    // - Remove '=' padding

    base64 = base64Encode(data)
    base64url = base64.replace('+', '-').replace('/', '_').replace('=', '')

    RETURN base64url
END FUNCTION

```

## 7. Token Blacklist Management

pseudocode



```
FUNCTION addTokenToBlacklist(token_jti, expiration_timestamp)
```

```
    // Add token identifier to blacklist
```

```
    // Store with expiration time for automatic cleanup
```

```
    LOG "Adding token to blacklist: " + token_jti
```

```
    // Add to blacklist storage
```

```
    revokedTokens.add(token_jti)
```

```
    // Optional: Schedule automatic removal after expiration
```

```
    // This prevents blacklist from growing indefinitely
```

```
    scheduleTokenCleanup(token_jti, expiration_timestamp)
```

```
    LOG "âœ“ Token blacklisted until: " + expiration_timestamp
```

```
END FUNCTION
```

```
FUNCTION isTokenRevoked(token_jti)
```

```
    // Check if token identifier exists in blacklist
```

```
    RETURN revokedTokens.has(token_jti)
```

```
END FUNCTION
```

```
FUNCTION scheduleTokenCleanup(token_jti, expiration_timestamp)
```

```
    // Calculate delay until token expires
```

```
    current_time = currentTimestamp()
```

```
    delay = expiration_timestamp - current_time
```

```
    IF delay > 0 THEN
```

```
        // Schedule removal after expiration
```

```
        scheduleTask(delay, FUNCTION()
```

```
            revokedTokens.delete(token_jti)
```

```
            LOG "âœ“ Expired token removed from blacklist: " + token_jti
```

```
        END FUNCTION)
```

```
    ELSE
```

```
        // Already expired, remove immediately
```

```
        revokedTokens.delete(token_jti)
```

```
    END IF
```

```
END FUNCTION
```

```
FUNCTION cleanupExpiredTokens()
```

```
    // Periodic cleanup task for token blacklist
```

```
    // Run this on a schedule (e.g., every hour)
```

```
    LOG "Running blacklist cleanup"
```

```
current_time = currentTimestamp()
removed_count = 0

FOR EACH token_jti IN revokedTokens DO
    // Decode token to get expiration
    // In production, store expiration with blacklist entry
    // to avoid needing to decode

    TRY
        decoded = decodeJWT(getTokenByJTI(token_jti))

        IF decoded.exp < current_time THEN
            revokedTokens.delete(token_jti)
            removed_count = removed_count + 1
        END IF
    CATCH error
        // Token no longer valid, remove from blacklist
        revokedTokens.delete(token_jti)
        removed_count = removed_count + 1
    END TRY
END FOR

LOG "âœ“ Cleanup complete: " + removed_count + " expired tokens removed"
END FUNCTION
```

---

## 8. Rate Limiting

pseudocode

```

// Rate limit storage
GLOBAL rateLimitStore = Map() // Map<client_key, RateLimitRecord>

STRUCTURE RateLimitRecord:
    count: integer
    reset_time: timestamp
END STRUCTURE

FUNCTION rateLimitMiddleware(max_requests)
    RETURN FUNCTION(request, response, next)
        // Identify client (by IP address or client_id)
        client_key = getClientIdentifier(request)

        // Get current rate limit record
        record = rateLimitStore.get(client_key)
        current_time = currentTimestamp()

        IF NOT record OR current_time >= record.reset_time THEN
            // Start new window
            record = RateLimitRecord {
                count: 1,
                reset_time: current_time + RATE_LIMIT_WINDOW_MS
            }
            rateLimitStore.set(client_key, record)

            // Add rate limit headers to response
            response.setHeader("X-RateLimit-Limit", max_requests)
            response.setHeader("X-RateLimit-Remaining", max_requests - 1)
            response.setHeader("X-RateLimit-Reset", record.reset_time)

            RETURN next() // Allow request
        ELSE
            // Increment counter
            record.count = record.count + 1

            IF record.count > max_requests THEN
                // Rate limit exceeded
                LOG "âš ĩ,    Rate limit exceeded for: " + client_key

                response.setHeader("X-RateLimit-Limit", max_requests)
                response.setHeader("X-RateLimit-Remaining", 0)
                response.setHeader("X-RateLimit-Reset", record.reset_time)
                response.setHeader("Retry-After", record.reset_time - current_time)
            END IF
        END IF
    END FUNCTION
END FUNCTION

```

```

    RETURN response(429, {
        error: "too_many_requests",
        error_description: "Rate limit exceeded"
    })
ELSE
    // Update record and allow request
    rateLimitStore.set(client_key, record)

    response.setHeader("X-RateLimit-Limit", max_requests)
    response.setHeader("X-RateLimit-Remaining", max_requests - record.count)
    response.setHeader("X-RateLimit-Reset", record.reset_time)

    RETURN next() // Allow request
END IF
END IF
END FUNCTION
END FUNCTION

FUNCTION getClientIdentifier(request)
    // Identify client by client_id if available, otherwise IP address

    // Try to extract client_id from request
    IF request.body.client_id THEN
        RETURN "client:" + request.body.client_id
    ELSE IF request.query.client_id THEN
        RETURN "client:" + request.query.client_id
    ELSE
        // Fallback to IP address
        ip_address = request.headers["x-forwarded-for"] OR request.connection.remoteAddress
        RETURN "ip:" + ip_address
    END IF
END FUNCTION

```

## 9. Authentication Middleware

pseudocode

```
FUNCTION authenticationMiddleware(request, response, next)
```

```
  LOG "=== AUTHENTICATION CHECK ==="
```

```
  // Extract Authorization header
```

```
  authHeader = request.headers["authorization"]
```

```
  IF NOT authHeader THEN
```

```
    LOG "⚠️ — Missing Authorization header"
```

```
    RETURN response(401, {
```

```
      error: "Unauthorized",
```

```
      message: "Missing Authorization header"
```

```
    })
```

```
  END IF
```

```
  // Extract token from "Bearer <token>" format
```

```
  IF NOT authHeader.startsWith("Bearer ") THEN
```

```
    LOG "⚠️ — Invalid Authorization format"
```

```
    RETURN response(401, {
```

```
      error: "Unauthorized",
```

```
      message: "Invalid Authorization header format"
```

```
    })
```

```
  END IF
```

```
  token = authHeader.substring(7) // Remove "Bearer "
```

```
  // Validate token
```

```
  payload = validateToken(token)
```

```
  IF NOT payload THEN
```

```
    LOG "⚠️ — Token validation failed"
```

```
    RETURN response(401, {
```

```
      error: "Unauthorized",
```

```
      message: "Invalid or expired token"
```

```
    })
```

```
  END IF
```

```
  // Token is valid - attach user info to request
```

```
  request.user = {
```

```
    user_id: payload.sub,
```

```
    client_id: payload.client_id,
```

```
    scope: payload.scope
```

```
  }
```

```
LOG "âœ“ Authentication successful"
```

```
LOG "User: " + payload.sub
```

```
LOG "Client: " + payload.client_id
```

```
// Proceed to route handler
```

```
RETURN next()
```

```
END FUNCTION
```

---

## 10. MCP Protocol Handlers

### 10.1 Main MCP Endpoint

```
pseudocode
```

```
ROUTE POST "/mcp"
```

```
  APPLY authenticationMiddleware // Require authentication
```

```
  APPLY rateLimitMiddleware(RATE_LIMIT_MAX_REQUESTS)
```

```
FUNCTION handleMCPRequest(request, response)
```

```
  LOG "=== INCOMING MCP REQUEST ==="
```

```
  LOG "Method: " + request.body.method
```

```
  LOG "Request ID: " + request.body.id
```

```
  // Extract JSON-RPC parameters
```

```
  jsonrpc = request.body.jsonrpc
```

```
  method = request.body.method
```

```
  params = request.body.params
```

```
  request_id = request.body.id
```

```
  // Validate JSON-RPC version
```

```
  IF jsonrpc != "2.0" THEN
```

```
    RETURN response(400, {
```

```
      jsonrpc: "2.0",
```

```
      id: request_id,
```

```
      error: {
```

```
        code: -32600,
```

```
        message: "Invalid JSON-RPC version"
```

```
    }
```

```
  })
```

```
END IF
```

```
TRY
```

```
  // Handle notifications (no response needed)
```

```
  IF NOT request_id AND method.startsWith("notifications/") THEN
```

```
    LOG "â€œ Notification received: " + method
```

```
    RETURN response(200)
```

```
  END IF
```

```
  // Route to appropriate handler
```

```
  IF method = "initialize" THEN
```

```
    result = handleInitialize(params)
```

```
  ELSE IF method = "tools/list" THEN
```

```
    result = handleToolsList(params)
```

```
  ELSE IF method = "tools/call" THEN
```

```
    result = handleToolsCall(params)
```

```
  ELSE IF method = "resources/list" THEN
```

```
    result = handleResourcesList(params)
```

```

ELSE IF method = "resources/read" THEN
    result = handleResourcesRead(params)
ELSE IF method = "prompts/list" THEN
    result = handlePromptsList(params)
ELSE IF method = "prompts/get" THEN
    result = handlePromptsGet(params)
ELSE
    // Unknown method
    RETURN response(400, {
        jsonrpc: "2.0",
        id: request_id,
        error: {
            code: -32601,
            message: "Method not found: " + method
        }
    })
END IF

// Return success response
RETURN response(200, {
    jsonrpc: "2.0",
    id: request_id,
    result: result
})

CATCH error
    LOG "â€” MCP request error: " + error.message
    RETURN response(500, {
        jsonrpc: "2.0",
        id: request_id,
        error: {
            code: -32603,
            message: "Internal error: " + error.message
        }
    })
END TRY
END FUNCTION
END ROUTE

```

## 10.2 Initialize Handler

pseudocode



```
FUNCTION handleInitialize(params)
  LOG "=== INITIALIZE ==="
  LOG "Client protocol version: " + params.protocolVersion
  LOG "Client capabilities: " + params.capabilities

  // Return server capabilities and version info
  RETURN {
    protocolVersion: MCP_PROTOCOL_VERSION,
    capabilities: {
      tools: {
        listChanged: false
      },
      resources: {
        subscribe: false,
        listChanged: false
      },
      prompts: {
        listChanged: false
      },
      logging: {}
    },
    serverInfo: {
      name: MCP_SERVER_NAME,
      version: MCP_SERVER_VERSION
    }
  }
END FUNCTION
```

### 10.3 Tools Handlers

pseudocode

```
FUNCTION handleToolsList(params)
```

```
  LOG "=== TOOLS/LIST ==="
```

```
  // Define available tools
```

```
  // Replace with actual tool definitions for your use case
```

```
  tools = [
```

```
    {
```

```
      name: "get_weather",
```

```
      description: "Get current weather for a location",
```

```
      inputSchema: {
```

```
        type: "object",
```

```
        properties: {
```

```
          location: {
```

```
            type: "string",
```

```
            description: "City name or coordinates"
```

```
          }
```

```
        },
```

```
        required: ["location"]
```

```
      }
```

```
    },
```

```
    {
```

```
      name: "send_email",
```

```
      description: "Send an email message",
```

```
      inputSchema: {
```

```
        type: "object",
```

```
        properties: {
```

```
          to: {
```

```
            type: "string",
```

```
            description: "Recipient email address"
```

```
          },
```

```
          subject: {
```

```
            type: "string",
```

```
            description: "Email subject"
```

```
          },
```

```
          body: {
```

```
            type: "string",
```

```
            description: "Email body content"
```

```
          }
```

```
        },
```

```
        required: ["to", "subject", "body"]
```

```
      }
```

```
    }
```

```
  ]
```

```

    LOG "Returning " + tools.length + " tools"

    RETURN {
        tools: tools
    }
END FUNCTION

FUNCTION handleToolsCall(params)
    LOG "=== TOOLS/CALL ==="

    tool_name = params.name
    tool_args = params.arguments

    LOG "Executing tool: " + tool_name
    LOG "Arguments: " + tool_args

    // Route to appropriate tool implementation
    IF tool_name = "get_weather" THEN
        result = executeGetWeather(tool_args)
    ELSE IF tool_name = "send_email" THEN
        result = executeSendEmail(tool_args)
    ELSE
        THROW Error("Unknown tool: " + tool_name)
    END IF

    LOG "â€œ Tool execution complete"

    // Return result in MCP format
    RETURN {
        content: [
            {
                type: "text",
                text: result
            }
        ]
    }
END FUNCTION

// Example tool implementations
FUNCTION executeGetWeather(args)
    location = args.location

    // Call weather API or service

```

```

// This is a placeholder - replace with actual implementation
LOG "Fetching weather for: " + location

weather_data = callWeatherAPI(location)

RETURN "Weather in " + location + ": " + weather_data.description +
    ", Temperature: " + weather_data.temperature + "°C"
END FUNCTION

FUNCTION executeSendEmail(args)
    to = args.to
    subject = args.subject
    body = args.body

    // Call email service
    // This is a placeholder - replace with actual implementation
    LOG "Sending email to: " + to

    success = callEmailService(to, subject, body)

    IF success THEN
        RETURN "Email sent successfully to " + to
    ELSE
        THROW Error("Failed to send email")
    END IF
END FUNCTION

```

## 10.4 Resources Handlers (Optional)

pseudocode

```
FUNCTION handleResourcesList(params)
```

```
  LOG "=== RESOURCES/LIST ==="
```

```
  // Define available resources
```

```
  // Resources are read-only data sources
```

```
  resources = [
```

```
    {
```

```
      uri: "file:///config/settings.json",
```

```
      name: "Server Configuration",
```

```
      description: "Current server configuration settings",
```

```
      mimeType: "application/json"
```

```
    },
```

```
    {
```

```
      uri: "db://customers",
```

```
      name: "Customer Database",
```

```
      description: "Customer records",
```

```
      mimeType: "application/json"
```

```
    }
```

```
  ]
```

```
  LOG "Returning " + resources.length + " resources"
```

```
  RETURN {
```

```
    resources: resources
```

```
  }
```

```
END FUNCTION
```

```
FUNCTION handleResourcesRead(params)
```

```
  LOG "=== RESOURCES/READ ==="
```

```
  resource_uri = params.uri
```

```
  LOG "Reading resource: " + resource_uri
```

```
  // Route to appropriate resource handler
```

```
  IF resource_uri.startsWith("file:///") THEN
```

```
    content = readFileResource(resource_uri)
```

```
  ELSE IF resource_uri.startsWith("db:///") THEN
```

```
    content = readDatabaseResource(resource_uri)
```

```
  ELSE
```

```
    THROW Error("Unknown resource URI: " + resource_uri)
```

```
  END IF
```

```
LOG "âœ“ Resource read complete"
```

```
// Return resource content
```

```
RETURN {
```

```
  contents: [
```

```
    {
```

```
      uri: resource_uri,
```

```
      mimeType: "application/json",
```

```
      text: content
```

```
    }
```

```
  ]
```

```
}
```

```
END FUNCTION
```

## 10.5 Prompts Handlers (Optional)

pseudocode

```
FUNCTION handlePromptsList(params)
```

```
  LOG "=== PROMPTS/LIST ==="
```

```
  // Define available prompts
```

```
  // Prompts are templated workflows
```

```
  prompts = [
```

```
    {
```

```
      name: "code_review",
```

```
      description: "Review code for quality and security",
```

```
      arguments: [
```

```
        {
```

```
          name: "code",
```

```
          description: "Code to review",
```

```
          required: true
```

```
        },
```

```
        {
```

```
          name: "language",
```

```
          description: "Programming language",
```

```
          required: false
```

```
        }
```

```
      ]
```

```
    }
```

```
  ]
```

```
  LOG "Returning " + prompts.length + " prompts"
```

```
  RETURN {
```

```
    prompts: prompts
```

```
  }
```

```
END FUNCTION
```

```
FUNCTION handlePromptsGet(params)
```

```
  LOG "=== PROMPTS/GET ==="
```

```
  prompt_name = params.name
```

```
  prompt_args = params.arguments
```

```
  LOG "Getting prompt: " + prompt_name
```

```
  // Route to appropriate prompt template
```

```
  IF prompt_name = "code_review" THEN
```

```
    messages = generateCodeReviewPrompt(prompt_args)
```

```
  ELSE
```

```

        THROW Error("Unknown prompt: " + prompt_name)
    END IF

    LOG "âœ“ Prompt generated"

    RETURN {
        messages: messages
    }
END FUNCTION

FUNCTION generateCodeReviewPrompt(args)
    code = args.code
    language = args.language OR "unknown"

    // Generate prompt messages
    RETURN [
        {
            role: "user",
            content: {
                type: "text",
                text: "Please review the following " + language + " code for quality, security, and best practices:\n\n" + code
            }
        }
    ]
END FUNCTION

```

## 11. Metadata Endpoints

pseudocode



```

ROUTE GET "/.well-known/oauth-authorization-server"

FUNCTION handleAuthorizationServerMetadata(request, response)
    // RFC 8414 - Authorization Server Metadata
    LOG "=== AUTHORIZATION SERVER METADATA REQUEST ==="

    metadata = {
        issuer: JWT_ISSUER,
        authorization_endpoint: JWT_ISSUER + "/oauth/authorize",
        token_endpoint: JWT_ISSUER + "/oauth/token",
        revocation_endpoint: JWT_ISSUER + "/oauth/revoke",
        registration_endpoint: JWT_ISSUER + "/register",
        response_types_supported: ["code"],
        grant_types_supported: ["authorization_code", "refresh_token"],
        token_endpoint_auth_methods_supported: ["client_secret_post"],
        code_challenge_methods_supported: ["S256", "plain"],
        scopes_supported: ["openid", "email", "profile"],
        service_documentation: "https://github.com/your-org/mcp-server"
    }

    RETURN response(200, metadata)
END FUNCTION
END ROUTE

ROUTE GET "/.well-known/oauth-protected-resource"

FUNCTION handleProtectedResourceMetadata(request, response)
    // RFC 8414 - Protected Resource Metadata
    LOG "=== PROTECTED RESOURCE METADATA REQUEST ==="

    metadata = {
        resource: JWT_ISSUER,
        authorization_servers: [JWT_ISSUER],
        scopes_supported: ["openid", "email", "profile"],
        bearer_methods_supported: ["header"],
        resource_documentation: "https://github.com/your-org/mcp-server"
    }

    RETURN response(200, metadata)
END FUNCTION
END ROUTE

```

## 12. Health Check Endpoint

pseudocode

ROUTE GET "/health"

FUNCTION handleHealthCheck(request, response)

// Basic health check endpoint

// Does not require authentication

health\_status = {

status: "healthy",

timestamp: currentTimestamp(),

version: MCP\_SERVER\_VERSION,

uptime: getServerUptime()

}

RETURN response(200, health\_status)

END FUNCTION

END ROUTE

---

## 13. Audit Logging

pseudocode

STRUCTURE AuditLogEntry:

timestamp: timestamp

event\_type: string

client\_id: string

user\_id: string

method: string

status: string

ip\_address: string

details: object

END STRUCTURE

FUNCTION logAuditEvent(event\_type, client\_id, user\_id, method, status, ip\_address, details)

// Create audit log entry

entry = AuditLogEntry {

timestamp: currentTimestamp(),

event\_type: event\_type,

client\_id: client\_id OR "unknown",

user\_id: user\_id OR "unknown",

method: method,

status: status,

ip\_address: ip\_address,

details: details

}

// Write to audit log

// This could be written to file, database, or logging service

writeAuditLog(entry)

LOG "[AUDIT] " + event\_type + " | " + status + " | " + client\_id

END FUNCTION

// Example audit logging in endpoints

FUNCTION handleTokenExchangeWithAudit(request, response)

client\_id = request.body.client\_id

ip\_address = request.connection.remoteAddress

TRY

result = handleTokenExchange(request, response)

// Log successful token exchange

logAuditEvent(

"TOKEN\_EXCHANGE",

client\_id,

```
        null,
        "authorization_code",
        "SUCCESS",
        ip_address,
        { grant_type: request.body.grant_type }
    )

    RETURN result
CATCH error
    // Log failed token exchange
    logAuditEvent(
        "TOKEN_EXCHANGE",
        client_id,
        null,
        "authorization_code",
        "FAILURE",
        ip_address,
        { error: error.message, grant_type: request.body.grant_type }
    )

    THROW error
END TRY
END FUNCTION
```

---

## Implementation Notes

### Storage Considerations

This pseudocode uses in-memory data structures (`Map`, `Set`) for simplicity. In production:

1. **Client Registry** - Store registered clients in a persistent database
2. **Authorization Codes** - Use Redis or similar with automatic expiration
3. **Token Blacklist** - Use Redis with TTL for automatic cleanup
4. **Rate Limiting** - Use Redis for distributed rate limiting across servers

### Security Considerations

1. **JWT\_SECRET** - Must be cryptographically secure, minimum 256 bits
2. **HTTPS Required** - All endpoints must use TLS in production
3. **CORS** - Configure CORS headers appropriately for your deployment

4. **Input Validation** - Validate all user inputs before processing
5. **Error Messages** - Don't leak sensitive information in error responses

## Performance Optimization

1. **Token Validation** - Cache decoded tokens briefly to reduce CPU usage
2. **Client Lookup** - Index client registry by client\_id for fast lookups
3. **Rate Limiting** - Use efficient data structures (sliding window counters)
4. **Blacklist Cleanup** - Run periodic cleanup tasks during off-peak hours

## Testing Recommendations

1. **OAuth Flow** - Test complete authorization code flow with PKCE
  2. **Token Rotation** - Verify refresh token rotation prevents replay attacks
  3. **Rate Limiting** - Verify rate limits are enforced correctly
  4. **Token Revocation** - Test revocation immediately blocks access
  5. **MCP Protocol** - Test all MCP methods with valid and invalid inputs
- 

## Conclusion

This pseudocode template provides a complete reference implementation for building a production-ready MCP server with OAuth 2.1 + PKCE authentication. It demonstrates:

- Complete OAuth 2.1 authorization code flow with PKCE
- JWT token management with rotation and revocation
- Rate limiting and audit logging
- Full MCP protocol support (tools, resources, prompts)
- Security best practices and error handling

Translate this pseudocode into your chosen programming language and framework, adapting the data structures and storage mechanisms to your specific infrastructure requirements.