

Student

The screenshot shows the DBeaver 26.1.5 interface. The main window displays a SQL script for creating a database schema. The script includes the following SQL statements:

```
38 Section_identifier INT,
39 Grade CHAR(2),
40 PRIMARY KEY (Student_number, Section_identifier),
41 FOREIGN KEY (Student_number) REFERENCES STUDENT(Student_number),
42 FOREIGN KEY (Section_identifier) REFERENCES SECTION(Section_identifier)
43 );
44
45 CREATE TABLE PREREQUISITE (
46 Course_number VARCHAR(15),
47 Prerequisite_number VARCHAR(15),
48 PRIMARY KEY (Course_number, Prerequisite_number),
49 FOREIGN KEY (Course_number) REFERENCES COURSE(Course_number),
50 FOREIGN KEY (Prerequisite_number) REFERENCES COURSE(Course_number)
51 );
52
53 DESC STUDENT;
54 -- DESC COURSE;
55 -- DESC SECTION;
56 -- DESC GRADE_REPORT;
57 -- DESC PREREQUISITE;
```

The output pane on the right shows the result of the `DESC STUDENT` command, displaying the table structure for the `STUDENT` table:

AZ Field	AZ Type	AZ Null	AZ Key	AZ Default	AZ Extra
1 Student_number	int	NO	PRI	[NULL]	
2 Name	varchar(100)	NO		[NULL]	
3 Class	int	YES		[NULL]	
4 Major	varchar(50)	YES		[NULL]	

The bottom status bar indicates that the table has 4 columns and 4 rows fetched. The interface also shows a sidebar with connections and a file explorer.

Course

The screenshot shows the DBeaver 26.1.5 interface. The top menu bar includes File, Edit, Navigate, Search, SQL Editor, Database, Window, and Help. The main window is titled "DBeaver 26.1.5 - <wolfecj1> Script". The left sidebar shows a tree view of the database structure, including Connections, General, and Scripts. The central pane displays the SQL script for the "COURSE" table, which includes a PRIMARY KEY on "Course_number" and FOREIGN KEY constraints on "Student_number" and "Section_identifier". The script also includes a "DESC COURSE;" command. The right pane shows the output of the script, which is empty. The bottom pane shows the "columns 1 x Statistics 1" tab, displaying the table structure for "COURSE".

```
39      Grade          CHAR(2),
40      PRIMARY KEY (Student_number, Section_identifier),
41      FOREIGN KEY (Student_number) REFERENCES STUDENT(Student_number),
42      FOREIGN KEY (Section_identifier) REFERENCES SECTION(Section_identifier)
43  );
44
45  CREATE TABLE PREREQUISITE (
46      Course_number   VARCHAR(15),
47      Prerequisite_number VARCHAR(15),
48      PRIMARY KEY (Course_number, Prerequisite_number),
49      FOREIGN KEY (Course_number) REFERENCES COURSE(Course_number),
50      FOREIGN KEY (Prerequisite_number) REFERENCES COURSE(Course_number)
51  );
52
53  -- DESC STUDENT;
54  DESC COURSE;
55  -- DESC SECTION;
56  -- DESC GRADE_REPORT;
57  -- DESC PREREQUISITE;
```

AZ Field	AZ Type	AZ Null	AZ Key	AZ Default	AZ Extra
1 Course_number	varchar(15)	NO	PRI	[NULL]	
2 Course_name	varchar(100)	NO	UNI	[NULL]	
3 Credit_hours	int	NO		4	
4 Department	varchar(50)	NO		[NULL]	

Refresh Save Cancel Export data 200 4 4 row(s) fetched

General EDIT en Writable Smart Insert

Section

The screenshot shows the DBeaver 26.1.5 interface. The main window displays a SQL script for creating a table named `PREREQUISITE`. The script includes a `CREATE TABLE` statement with columns `Course_number` and `Prerequisite_number`, both of type `VARCHAR(15)`. It also includes foreign key constraints: `PRIMARY KEY (Course_number, Prerequisite_number)`, `FOREIGN KEY (Course_number) REFERENCES COURSE(Course_number)`, and `FOREIGN KEY (Prerequisite_number) REFERENCES COURSE(Course_number)`. Below the script, the `DESC COURSE` command is executed, showing the structure of the `COURSE` table.

SQL Script:

```
39 Grade CHAR(2),
40 PRIMARY KEY (Student_number, Section_identifier),
41 FOREIGN KEY (Student_number) REFERENCES STUDENT(Student_number),
42 FOREIGN KEY (Section_identifier) REFERENCES SECTION(Section_identifier)
43 );
44
45 CREATE TABLE PREREQUISITE (
46 Course_number VARCHAR(15),
47 Prerequisite_number VARCHAR(15),
48 PRIMARY KEY (Course_number, Prerequisite_number),
49 FOREIGN KEY (Course_number) REFERENCES COURSE(Course_number),
50 FOREIGN KEY (Prerequisite_number) REFERENCES COURSE(Course_number)
51 );
52
53 -- DESC STUDENT;
54 -- DESC COURSE;
55 DESC SECTION;
56 -- DESC GRADE_REPORT;
57 -- DESC PREREQUISITE;
```

Table Structure (DESC COURSE):

AZ Field	AZ Type	AZ Null	AZ Key	AZ Default	AZ Extra
1 Course_number	varchar(15)	NO	PRI	[NULL]	
2 Course_name	varchar(100)	NO	UNI	[NULL]	
3 Credit_hours	int	NO		4	
4 Department	varchar(50)	NO		[NULL]	

The interface also shows a sidebar with a tree view of the database structure, including connections, databases, users, and system information. The bottom status bar indicates that 4 row(s) were fetched.

Grade report

The screenshot shows the DBeaver 26.1.5 interface. The main window displays a SQL script for creating a table named `PREREQUISITE`. The script includes the following SQL code:

```
39      Grade CHAR(2),
40      PRIMARY KEY (Student_number, Section_identifier),
41      FOREIGN KEY (Student_number) REFERENCES STUDENT(Student_number),
42      FOREIGN KEY (Section_identifier) REFERENCES SECTION(Section_identifier)
43  );
44
45  CREATE TABLE PREREQUISITE (
46      Course_number VARCHAR(15),
47      Prerequisite_number VARCHAR(15),
48      PRIMARY KEY (Course_number, Prerequisite_number),
49      FOREIGN KEY (Course_number) REFERENCES COURSE(Course_number),
50      FOREIGN KEY (Prerequisite_number) REFERENCES COURSE(Course_number)
51  );
52
53  -- DESC STUDENT;
54  -- DESC COURSE;
55  -- DESC SECTION;
56  DESC GRADE_REPORT;
57  -- DESC PREREQUISITE;
```

The left sidebar shows the project structure for `wolfecj1`, including connections, databases, users, administrator, system info, bookmarks, dashboards, diagrams, and scripts. The bottom panel displays the table structure for `COURSE` in a grid view:

AZ Field	AZ Type	AZ Null	AZ Key	AZ Default	AZ Extra
1 Course_number	varchar(15)	NO	PRI	[NULL]	
2 Course_name	varchar(100)	NO	UNI	[NULL]	
3 Credit_hours	int	NO		4	
4 Department	varchar(50)	NO		[NULL]	

The bottom status bar indicates the current table is `COURSE`, with 4 rows fetched. The interface also shows a file explorer on the left and a script editor on the right.

Prereq

The screenshot shows the DBeaver 26.1.5 interface with a SQL script editor open. The script defines a table named PREREQUISITE with two columns: Course_number and Prerequisite_number. Both columns are of type VARCHAR(15). The Course_number column has a PRIMARY KEY constraint. The Prerequisite_number column has a FOREIGN KEY constraint that references the Course_number column. The script also includes comments for each table and column.

```
39      Grade          CHAR(2),
40      PRIMARY KEY (Student_number, Section_identifier),
41      FOREIGN KEY (Student_number) REFERENCES STUDENT(Student_number),
42      FOREIGN KEY (Section_identifier) REFERENCES SECTION(Section_identifier)
43  );
44
45  -- CREATE TABLE PREREQUISITE (
46  Course_number      VARCHAR(15),
47  Prerequisite_number VARCHAR(15),
48  PRIMARY KEY (Course_number, Prerequisite_number),
49  FOREIGN KEY (Course_number) REFERENCES COURSE(Course_number),
50  FOREIGN KEY (Prerequisite_number) REFERENCES COURSE(Course_number)
51  );
52
53  -- DESC STUDENT;
54  -- DESC COURSE;
55  -- DESC SECTION;
56  -- DESC GRADE_REPORT;
57  DESC PREREQUISITE;
```

The bottom panel shows the table structure for PREREQUISITE:

AZ Field	AZ Type	AZ Null	AZ Key	AZ Default	AZ Extra
Course_number	varchar(15)	NO	PRI	[NULL]	
Prerequisite_numl	varchar(15)	NO	PRI	[NULL]	

The status bar at the bottom indicates that 2 row(s) were fetched.