

Theoretical CompSci Cheat Sheet

Formal Language Fundamentals

Core Definitions

Concept	Formal Definition	Notes
Alphabet (Σ)	A finite, non-empty set of symbols.	Binary $\Sigma = \{0, 1\}$.
Word (w)	A finite sequence of letters from Σ .	Length $ w $ is the symbol count; $ ε = 0$.
Concatenation ($u \cdot w$)	Laying letters of w after u : $u_1 \dots u_n w_1 \dots w_m$.	Neutral element: $wε = εw = w$.
Kleene Star (Σ^*)	$\Sigma^* = \bigcup_{n=0}^{\infty} \Sigma^n = \Sigma^0 \cup \Sigma^1 \cup \Sigma^2 \cup \dots$	Set of all finite words over Σ , including $ε$.
Language (L)	Any subset $L \subseteq \Sigma^*$.	Closed under standard set operations $(\cup, \cap, \setminus, \overline{L})$.

Automata Formulations

Component	DFA $A=(\Sigma,Q,\delta,q_0,F)$	NFA $A=(\Sigma,Q,\Delta,I,F)$
States (Q)	Finite set of states	Finite set of states
Start State	Exactly one: $q_0 \in Q$	Set of initial states: $I \subseteq Q$
Accepting States (F)	Subset $F \subseteq Q$	Subset $F \subseteq Q$
Transition Function	$\delta : Q \times \Sigma \rightarrow Q$ (deterministic)	$\Delta : Q \times \Sigma \rightarrow \mathcal{P}(Q)$ (multi-path or dead ends)
Extended Transition	$\delta^*(\epsilon, q) = q$ $\delta^*(wa, q) = \delta(\delta^*(w, q), a)$	$\Delta^*(\epsilon, q) = \{q\}$ $\Delta^*(wa, q) = \bigcup_{p \in \Delta^*(w, q)} \Delta(p, a)$
Accepted Language	$L(A) = \{w \in \Sigma^* \mid \delta^*(w, q_0) \in F\}$	$L(A) = \{w \in \Sigma^* \mid (\bigcup_{i \in I} \Delta^*(w, i)) \cap F \neq \emptyset\}$

Inductive Proof Template: DFA Correctness

Use this template to prove an automaton A computes an intended invariant $P(w)$ (such as parity or remainder modulo k).

- **Claim:** Let $P : \Sigma^* \rightarrow Q$ denote the state assigned to the invariant property of word w . For all $n \in \mathbb{N}$ and all words $w \in \Sigma^*$ with $|w| = n$, $\delta^*(w, q_0) = P(w)$.
- **Base Case** ($n = 0$):
 - The only word of length 0 is $w = \epsilon$.
 - By the extended transition definition, $\delta^*(\epsilon, q_0) = q_0$.
 - Verify that $q_0 = P(\epsilon)$ holds by problem definition.
- **Inductive Hypothesis:**
 - Assume for some $n \geq 0$, $\delta^*(u, q_0) = P(u)$ holds for every word $u \in \Sigma^*$ with $|u| = n$.
- **Inductive Step:**
 - Consider a word $w \in \Sigma^*$ of length $n + 1$. Decompose w as $w = ua$ where $|u| = n$ and $a \in \Sigma$.
 - Expand using the inductive definition:
 $\delta^*(w, q_0) = \delta^*(ua, q_0) = \delta(\delta^*(u, q_0), a)$
 - Apply the Induction Hypothesis to substitute $\delta^*(u, q_0)$:
 $\delta(\delta^*(u, q_0), a) = \delta(P(u), a)$
 - Evaluate the machine's transition $\delta(P(u), a)$ and show it equals $P(ua) = P(w)$.
- **Conclusion:** By mathematical induction, the claim holds for all $n \geq 0$. Since $w \in L(A) \iff \delta^*(w, q_0) \in F \iff P(w) \in F, L(A) = L$.

Algorithms

Determinization: NFA to DFA (Subset Construction)

Converts an NFA $A = (\Sigma, Q, \Delta, I, F)$ into an equivalent DFA $A^D = (\Sigma, Q^D, \delta^D, q_0^D, F^D)$.

```
Algorithm Subset_Construction:
Input: NFA A = (Sigma, Q, Delta, I, F)
Output: DFA A^D = (Sigma, Q^D, delta^D, q_0^D, F^D)

q_0^D := I
Q^D := { q_0^D }
WorkList := [ q_0^D ]

While WorkList is not empty:
  Pop S from WorkList
  For each symbol a in Sigma:
    TargetSet := Union_{q in S} Delta(q, a)
    delta^D(S, a) := TargetSet
    If TargetSet not in Q^D:
      Add TargetSet to Q^D
      Push TargetSet to WorkList

F^D := { S in Q^D | S \cap F != empty_set }
```

DFA Minimization (Table-Filling / Hopcroft-Moore Variant)

Computes the minimal canonical DFA $A^{\min}$ by collapsing indistinguishable states ($L_p = L_q$).

1. **Step 1: Trim.** Eliminate unreachable states (run BFS/DFS from q_0) and dead states (states that cannot reach any $f \in F$).
2. **Step 2: Initialize Table.** Construct an upper-triangular table of all state pairs $\{p, q\}$ where $p \neq q$.
3. **Step 3: Base Mark** ($k = 0$). Mark any pair $\{p, q\}$ where one state is accepting and the other is non-accepting ($p \in F \oplus q \in F$). These are distinguished by ϵ .
4. **Step 4: Inductive Mark Propagation.**
 - For each unmarked pair $\{p, q\}$ and each symbol $a \in \Sigma$:
 - Find target states $p' = \delta(p, a)$ and $q' = \delta(q, a)$.
 - If $p' \neq q'$ and the pair $\{p', q'\}$ is already marked, mark $\{p, q\}$ with the next step index $k + 1$.
 - Repeat until a full pass over all unmarked pairs yields no new markings.
5. **Step 5: Partition & Construct Quotient Machine.**
 - Any pair $\{p, q\}$ left unmarked is indistinguishable ($p \sim q$).
 - Form equivalence classes $[q]$ from unmarked relations.
 - New DFA: $q_0^{\min} = [q_0]$, $F^{\min} = \{[q] \mid q \in F\}$, and $\delta^{\min}([q], a) = [\delta(q, a)]$.

Checking Equivalence of Two Languages: $L(A) \stackrel{?}{=} L(B)$

Plaintext

Algorithm Check_Language_Equivalence:
Input: Automata A and B (NFAs or DFAs)
1. If either is an NFA, convert to DFA via Subset Construction.
2. Minimize DFA_A to obtain canonical A_min.
3. Minimize DFA_B to obtain canonical B_min.
4. Compare A_min and B_min:

- Check graph isomorphism up to state renaming (match start states, transitions, accepting states).
- If isomorphic: L(A) = L(B).
- Otherwise: L(A) != L(B).

Regular Expressions Reference

A language is **regular** if and only if it is recognized by a DFA, an NFA, or matched by a Regular Expression.

Inductive Definition of REs over Σ

- **Base Cases:** $\emptyset$ (empty language), ϵ (empty string $\{\epsilon\}$), and a for each $a \in \Sigma \setminus \{\epsilon\}$.
- **Inductive Steps:** If r_1, r_2 are REs:
 - Union: $(r_1 + r_2)$ or $(r_1 | r_2)$
 - Concatenation: $(r_1 \cdot r_2)$ or simply $r_1 r_2$
 - Kleene Star: r_1^* (zero or more repetitions)
- **Precedence:** Star $(^*)$ > Concatenation $(\cdot)$ > Union $(+)$

Structural Translation: RE to NFA (Thompson's Construction)

Plaintext

```
Base Cases:
r = empty_set:  (start)          (accept)    [no transitions]
r = epsilon:    (start) --- epsilon --> ((accept))
r = a:          (start) ----- a -----> ((accept))

Inductive Constructions:
r = r1 + r2:     Split new start state via epsilon to Start(r1) and Start(r2).
                  Connect all Accept(r1) and Accept(r2) via epsilon to new single accept state.

r = r1 * r2:     Link Accept(r1) via epsilon transitions directly to Start(r2).
                  Start is Start(r1); accept states are Accept(r2).

r = (r1)*:       Add new start q0 and new accept qf.
                  Add epsilon transitions: q0 -> Start(r1), q0 -> qf (zero matches),
                  Accept(r1) -> Start(r1) (loop back), Accept(r1) -> qf.
```

Midterm 1 Synthesis: Comprehensive Example

Problem: Construct an automaton over $\Sigma = \{0,1\}$ for $L = \{w \mid w \text{ has an even number of 1s or contains } 01 \text{ as a factor}\}$.

- **Decomposition via Sub-languages:**
 - Let $L_1 = \{w \mid \text{count}_1(w) \equiv 0 \pmod{2}\}$.
 - Let $L_2 = \{w \mid w = x01y \text{ for } x,y \in \{0,1\}^*\} = \Sigma^*01\Sigma^*$.
 - Overall Language: $L = L_1 \cup L_2$.
- **Step-by-Step Execution Plan:**
 1. **NFA Construction:** Create an NFA with initial state branching via ϵ -transitions to the start of A_{L_1} (a 2-state parity cycle) and the start of A_{L_2} (a 3-state pattern matcher for 01).
 2. **Determinization:** Apply the Subset Construction table. Start at $S_0 = I$, expand transitions on 0 and 1 , and label states containing any original final states as accepting.
 3. **Minimization:** Fill the upper-triangular table to identify and collapse redundant states (e.g., once the factor 01 is detected and parity is satisfied).

asdf