

BuildConnect

An End-to-End Application for All Construction Needs

Complete Source Code Documentation

Project	BuildConnect — Construction Platform
Authors	Vedant Pandey (RA2211029010013) Chiranjeev Kumar (RA2211029010019)
Guide	Dr. S. Ushasukhanya, Associate Professor
Institution	SRM Institute of Science and Technology, Kattankulathur
Semester	6th Sem — B.Tech CSE (Computer Networking) — May 2025
Tech Stack	React 18 · TypeScript · Vite · Tailwind CSS · Supabase

Department of Networking and Communications

How to Run the Project

Follow these steps in order to set up and run the BuildConnect application:

Prerequisites

- Node.js v18+ (<https://nodejs.org>)
- npm v8+ (included with Node.js)
- Git (optional)
- Supabase account (<https://supabase.com>)

Quick Start Commands

```
# 1. Enter the project folder
cd builder_codes

# 2. Install dependencies
npm install

# 3. Start development server
npm run dev

# Open in browser: http://localhost:5173

# Build for production:
npm run build
```

Demo Login Credentials

```
Client Login: demo@example.com / password
Builder Login: builder@example.com / password
```

Project Structure

Create the following folder structure, then add each file in order:

```
builder_codes/  
  package.json ← Step 1  
  index.html ← Step 2  
  vite.config.ts ← Step 3  
  tailwind.config.js ← Step 4  
  postcss.config.js ← Step 5  
  eslint.config.js ← Step 6  
  tsconfig.json ← Step 7  
  tsconfig.app.json ← Step 8  
  tsconfig.node.json ← Step 9  
  src/  
    main.tsx ← Step 10  
    index.css ← Step 11  
    vite-env.d.ts ← Step 12  
    types.ts ← Step 13  
    App.tsx ← Step 14  
    components/  
      BuilderCard.tsx ← Step 15  
      BuilderDetails.tsx ← Step 16  
      LoginModal.tsx ← Step 17  
      SearchFilters.tsx ← Step 18  
    pages/  
      builders.ts ← Step 19  
      BecomeBuilder.tsx ← Step 20  
      BuilderDashboard.tsx ← Step 21  
      BuilderLogin.tsx ← Step 22  
      HowItWorks.tsx ← Step 23  
      Support.tsx ← Step 24  
supabase/migrations/  
  quick_mouse.sql ← Step 25
```

Complete Source Code

All 25 files in the exact order they should be created:

Step 1: package.json

Project dependencies and npm scripts

```
{
  "name": "vite-react-typescript-starter",
  "private": true,
  "version": "0.0.0",
  "type": "module",
  "scripts": {
    "dev": "vite",
    "build": "vite build",
    "lint": "eslint .",
    "preview": "vite preview"
  },
  "dependencies": {
    "lucide-react": "^0.344.0",
    "react": "^18.3.1",
    "react-dom": "^18.3.1",
    "react-router-dom": "^6.22.3"
  },
  "devDependencies": {
    "@eslint/js": "^9.9.1",
    "@types/react": "^18.3.5",
    "@types/react-dom": "^18.3.0",
    "@vitejs/plugin-react": "^4.3.1",
    "autoprefixer": "^10.4.18",
    "eslint": "^9.9.1",
    "eslint-plugin-react-hooks": "^5.1.0-rc.0",
    "eslint-plugin-react-refresh": "^0.4.11",
    "globals": "^15.9.0",
    "postcss": "^8.4.35",
    "tailwindcss": "^3.4.1",
    "typescript": "^5.5.3",
    "typescript-eslint": "^8.3.0",
    "vite": "^5.4.2"
  }
}
```

Step 2: index.html

Root HTML entry point

```
<!doctype html>
<html lang="en">
<head>
<meta charset="UTF-8" />
<link rel="icon" type="image/svg+xml" href="/vite.svg" />
<meta name="viewport" content="width=device-width, initial-scale=1.0" />
<title>Vite + React + TS</title>
</head>
<body>
```

```
<div id="root"></div>
<script type="module" src="/src/main.tsx"></script>
</body>
</html>
```

Step 3: vite.config.ts

Vite bundler configuration

```
import { defineConfig } from 'vite';
import react from '@vitejs/plugin-react';

// https://vitejs.dev/config/
export default defineConfig({
  plugins: [react()],
  optimizeDeps: {
    exclude: ['lucide-react'],
  },
});
```

Step 4: tailwind.config.js

Tailwind CSS configuration

```
/** @type {import('tailwindcss').Config} */
export default {
  content: ['./index.html', './src/**/*.{js,ts,jsx,tsx}'],
  theme: {
    extend: {},
  },
  plugins: [],
};
```

Step 5: postcss.config.js

PostCSS configuration

```
export default {
  plugins: {
    tailwindcss: {},
    autoprefixer: {},
  },
};
```

Step 6: eslint.config.js

ESLint linting rules

```
import js from '@eslint/js';
import globals from 'globals';
import reactHooks from 'eslint-plugin-react-hooks';
import reactRefresh from 'eslint-plugin-react-refresh';
import tseslint from 'typescript-eslint';

export default tseslint.config(
  { ignores: ['dist'] },

```

```

{
  extends: [js.configs.recommended, ...tseslint.configs.recommended],
  files: ['**/*.ts,tsx'],
  languageOptions: {
    ecmaVersion: 2020,
    globals: globals.browser,
  },
  plugins: {
    'react-hooks': reactHooks,
    'react-refresh': reactRefresh,
  },
  rules: {
    ...reactHooks.configs.recommended.rules,
    'react-refresh/only-export-components': [
      'warn',
      { allowConstantExport: true },
    ],
  },
}
);

```

Step 7: tsconfig.json

TypeScript root config

```

{
  "files": [],
  "references": [
    { "path": "./tsconfig.app.json" },
    { "path": "./tsconfig.node.json" }
  ]
}

```

Step 8: tsconfig.app.json

TypeScript app config

```

{
  "compilerOptions": {
    "target": "ES2020",
    "useDefineForClassFields": true,
    "lib": ["ES2020", "DOM", "DOM.Iterable"],
    "module": "ESNext",
    "skipLibCheck": true,

    /* Bundler mode */
    "moduleResolution": "bundler",
    "allowImportingTsExtensions": true,
    "isolatedModules": true,
    "moduleDetection": "force",
    "noEmit": true,
    "jsx": "react-jsx",

    /* Linting */
    "strict": true,
    "noUnusedLocals": true,

```

```
"noUnusedParameters": true,
"noFallthroughCasesInSwitch": true
},
"include": ["src"]
}
```

Step 9: tsconfig.node.json

TypeScript node config

```
{
  "compilerOptions": {
    "target": "ES2022",
    "lib": ["ES2023"],
    "module": "ESNext",
    "skipLibCheck": true,

    /* Bundler mode */
    "moduleResolution": "bundler",
    "allowImportingTsExtensions": true,
    "isolatedModules": true,
    "moduleDetection": "force",
    "noEmit": true,

    /* Linting */
    "strict": true,
    "noUnusedLocals": true,
    "noUnusedParameters": true,
    "noFallthroughCasesInSwitch": true
  },
  "include": ["vite.config.ts"]
}
```

Step 10: src/main.tsx

Application entry point

```
import { StrictMode } from 'react';
import { createRoot } from 'react-dom/client';
import { BrowserRouter } from 'react-router-dom';
import App from './App.tsx';
import './index.css';

createRoot(document.getElementById('root')!).render(
  <StrictMode>
    <BrowserRouter>
      <App />
    </BrowserRouter>
  </StrictMode>
);
```

Step 11: src/index.css

Global CSS with Tailwind

```
@tailwind base;
@tailwind components;
```

```
@tailwind utilities;
```

Step 12: src/vite-env.d.ts

Vite type declarations

```
/// <reference types="vite/client" />
```

Step 13: src/types.ts

TypeScript interfaces for all data models

```
// User related types
export interface User {
  user_id: number;
  name: string;
  email: string;
  phone_number: string;
  user_type: 'client' | 'admin';
  registered_at: string;
}

export interface Builder {
  builder_id: number;
  name: string;
  address: string;
  license_no: string;
  gst_number: string;
  experience: string;
  contact_info: {
    phone: string;
    email: string;
  };
  builder_image: string;
  registered_at: string;
  // Computed fields from relationships
  rating?: number;
  total_reviews?: number;
  verified?: boolean;
}

export interface ClientRequest {
  request_id: number;
  client_id: number;
  builder_id: number;
  request_details: string;
  status: 'pending' | 'accepted' | 'rejected' | 'done';
  created_at: string;
}

export interface Message {
  message_id: number;
  sender_id: number;
  receiver_id: number;
  content: string;
  sent_at: string;
}
```



```

}

export interface Review {
  review_id: number;
  client_id: number;
  builder_id: number;
  rating: number;
  review_text: string;
  created_at: string;
}

export interface SearchFilters {
  location: string;
  service: string;
  rating: number;
  experience: number;
}

```

Step 14: src/App.tsx

Root App component with routing and layout

```

import React, { useState } from 'react';
import { Routes, Route } from 'react-router-dom';
import { Building } from 'lucide-react';
import { Builder, SearchFilters, User } from './types';
import { BuilderCard } from './components/BuilderCard';
import { SearchFiltersPanel } from './components/SearchFilters';
import { LoginModal } from './components/LoginModal';
import { BuilderDetails } from './components/BuilderDetails';

// Mock data - In a real app, this would come from the database
const MOCK_BUILDERS: Builder[] = [
  {
    builder_id: 1,
    name: 'Modern Builders Co.',
    address: 'New York, NY',
    license_no: 'LIC123456',
    gst_number: 'GST98765432',
    experience: '15 years',
    contact_info: {
      phone: '(555) 123-4567',
      email: 'contact@modernbuilders.com'
    },
    builder_image:
      'https://images.unsplash.com/photo-1504307651254-35680f356dfd?auto=format&fit=crop&w=800',
    registered_at: '2020-01-01T00:00:00Z',
    rating: 4.8,
    total_reviews: 156,
    verified: true
  },
  {
    builder_id: 2,
    name: 'Green Construction Ltd.',
    address: 'Los Angeles, CA',
    license_no: 'LIC789012',
    gst_number: 'GST45678901',
    experience: '10 years',

```

```

contact_info: {
  phone: '(555) 234-5678',
  email: 'info@greenconstruction.com'
},
builder_image:
'https://images.unsplash.com/photo-1503387762-592deb58ef4e?auto=format&fit=crop&w=800',
registered_at: '2021-03-15T00:00:00Z',
rating: 4.6,
total_reviews: 89,
verified: true
},
{
  builder_id: 3,
  name: 'Urban Developers Inc.',
  address: 'Chicago, IL',
  license_no: 'LIC345678',
  gst_number: 'GST12345678',
  experience: '8 years',
  contact_info: {
    phone: '(555) 345-6789',
    email: 'contact@urbandevelopers.com'
  },
  builder_image:
'https://images.unsplash.com/photo-1581094794329-c8112a89af12?auto=format&fit=crop&w=800',
  registered_at: '2022-06-30T00:00:00Z',
  rating: 4.5,
  total_reviews: 45,
  verified: false
}
];

function HomePage() {
  const [filters, setFilters] = useState<SearchFilters>({
    location: '',
    service: '',
    rating: 0,
    experience: 0,
  });

  const filteredBuilders = MOCK_BUILDERS.filter(builder => {
    if (filters.location &&
      !builder.address.toLowerCase().includes(filters.location.toLowerCase())) {
      return false;
    }
    if (filters.service && !builder.name.toLowerCase().includes(filters.service.toLowerCase())) {
      return false;
    }
    if (filters.rating > 0 && (!builder.rating || builder.rating < filters.rating)) {
      return false;
    }
    if (filters.experience > 0) {
      const yearsExp = parseInt(builder.experience);
      if (isNaN(yearsExp) || yearsExp < filters.experience) {
        return false;
      }
    }
    return true;
  });

```

```

});

return (
  <>
  { /* Hero Section */}
  <div className="text-center mb-12">
    <h2 className="text-4xl font-bold text-gray-900 mb-4">
      Find Trusted Construction Professionals
    </h2>
    <p className="text-xl text-gray-600">
      Connect with verified builders and get your project started today
    </p>
  </div>

  { /* Search Filters */}
  <div className="mb-8">
    <SearchFiltersPanel
      filters={filters}
      onFilterChange={setFilters}
    />
  </div>

  { /* Builder Cards Grid */}
  <div className="grid grid-cols-1 md:grid-cols-2 lg:grid-cols-3 gap-8">
    {filteredBuilders.map((builder) => (
      <BuilderCard
        key={builder.builder_id}
        builder={builder}
        isLoggedIn={true}
        onConnect={() => {}}
      />
    ))}
  </div>

  {filteredBuilders.length === 0 && (
    <div className="text-center py-12">
      <p className="text-gray-600">No builders found matching your criteria.</p>
    </div>
  )}
</>
);
}

function App() {
  const [user, setUser] = useState<User | null>(null);
  const [isLoginModalOpen, setIsLoginModalOpen] = useState(false);

  return (
    <div className="min-h-screen bg-gray-50">
      { /* Header */}
      <header className="bg-white shadow-sm">
        <div className="max-w-7xl mx-auto px-4 sm:px-6 lg:px-8 py-4">
          <div className="flex items-center justify-between">
            <div className="flex items-center gap-2">
              <Building className="text-blue-600" size={32} />
              <h1 className="text-2xl font-bold text-gray-900">BuildConnect</h1>
            </div>

```

[illegible]

```
export default App;
```

Step 15: src/components/BuilderCard.tsx

Builder card component

```
import React from 'react';
import { Star, MapPin, BadgeCheck, Building2, Clock4 } from 'lucide-react';
import { useNavigate } from 'react-router-dom';
import { Builder } from '../types';

interface BuilderCardProps {
  builder: Builder;
  isLoggedIn: boolean;
  onConnect: (builder: Builder) => void;
}

export function BuilderCard({ builder, isLoggedIn }: BuilderCardProps) {
  const navigate = useNavigate();

  const handleClick = () => {
    if (isLoggedIn) {
      navigate(`/builder/${builder.builder_id}`);
    }
  };

  return (
    <div
      className="bg-white rounded-xl shadow-lg overflow-hidden transition-transform
        hover:scale-[1.02] cursor-pointer"
      onClick={handleClick}
    >
      <div className="relative">
        <img
          src={builder.builder_image}
          alt={builder.name}
          className="w-full h-48 object-cover"
        />
        {builder.verified && (
          <div className="absolute top-2 right-2 bg-green-500 text-white px-2 py-1 rounded-full flex
            items-center gap-1">
            <BadgeCheck size={16} />
            <span className="text-sm">Verified</span>
          </div>
        )}
      </div>

      <div className="p-6">
        <div className="flex items-start justify-between">
          <div>
            <h3 className="text-xl font-semibold text-gray-900">{builder.name}</h3>
            <p className="text-gray-600">License: {builder.license_no}</p>
          </div>
          {builder.rating && (
            <div className="flex items-center gap-1 bg-yellow-100 px-2 py-1 rounded">
              <Star className="text-yellow-500" size={16} fill="currentColor" />
              <span className="font-medium">{builder.rating.toFixed(1)}</span>
            </div>
          )}
        </div>
      </div>
    </div>
  );
}
```

```

{builder.total_reviews && (
  <span className="text-sm text-gray-500">({builder.total_reviews})</span>
)}
</div>
)}
</div>

<div className="mt-4 space-y-2">
  <div className="flex items-center gap-2 text-gray-600">
    <MapPin size={18} />
    <span>{builder.address}</span>
  </div>
  <div className="flex items-center gap-2 text-gray-600">
    <Building2 size={18} />
    <span>GST: {builder.gst_number}</span>
  </div>
  <div className="flex items-center gap-2 text-gray-600">
    <Clock4 size={18} />
    <span>{builder.experience} experience</span>
  </div>
</div>

<div className="mt-6">
  {isLoggedIn ? (
    <button
      onClick={{e} => {
        e.stopPropagation();
        navigate(`/builder/${builder.builder_id}`);
      }}
      className="w-full py-2 px-4 rounded-lg font-medium bg-blue-600 text-white hover:bg-blue-700"
    >
      View Details
    </button>
  ) : (
    <button
      className="w-full py-2 px-4 rounded-lg font-medium bg-gray-100 text-gray-500"
    >
      Login to View Details
    </button>
  )}
</div>
</div>
</div>
);
}

```

Step 16: src/components/BuilderDetails.tsx

Builder detail page with booking

```

import React, { useState } from 'react';
import { useParams, useNavigate } from 'react-router-dom';
import {
  Building2,
  MapPin,
  Phone,
  Mail,

```

```

Star,
Clock,
BadgeCheck,
ChevronLeft,
Calendar
} from 'lucide-react';
import { Builder } from '../types';

interface BuilderDetailsProps {
  builders: Builder[];
}

export function BuilderDetails({ builders }: BuilderDetailsProps) {
  const { id } = useParams();
  const navigate = useNavigate();
  const [isBookingModalOpen, setIsBookingModalOpen] = useState(false);

  const builder = builders.find(b => b.builder_id === Number(id));

  if (!builder) {
    return (
      <div className="min-h-screen flex items-center justify-center">
        <div className="text-center">
          <h2 className="text-2xl font-bold text-gray-900">Builder not found</h2>
          <button
            onClick={() => navigate('/')}>
            className="mt-4 text-blue-600 hover:text-blue-800"
          >
            Go back home
          </button>
        </div>
      </div>
    );
  }

  return (
    <div className="min-h-screen bg-gray-50">
      </* Header with back button */>
      <div className="bg-white shadow-sm">
        <div className="max-w-7xl mx-auto px-4 sm:px-6 lg:px-8 py-4">
          <button
            onClick={() => navigate('/')}>
            className="flex items-center text-gray-600 hover:text-gray-900"
          >
            <ChevronLeft className="w-5 h-5" />
            <span>Back to Builders</span>
          </button>
        </div>
      </div>

      <main className="max-w-7xl mx-auto px-4 sm:px-6 lg:px-8 py-8">
        </* Builder Hero Section */>
        <div className="bg-white rounded-xl shadow-lg overflow-hidden">
          <div className="relative h-64 sm:h-80">
            <img
              src={builder.builder_image}
              alt={builder.name}
            />
          </div>
        </div>
      </main>
    </div>
  );
}

```

```

className="w-full h-full object-cover"
/>
{builder.verified && (
<div className="absolute top-4 right-4 bg-green-500 text-white px-3 py-1 rounded-full flex
items-center gap-2">
<BadgeCheck size={20} />
<span>Verified Builder</span>
</div>
)}
</div>

<div className="p-6">
<div className="flex items-start justify-between">
<div>
<h1 className="text-3xl font-bold text-gray-900">{builder.name}</h1>
<div className="mt-2 flex items-center gap-2 text-gray-600">
<MapPin size={20} />
<span>{builder.address}</span>
</div>
</div>
<div className="flex flex-col items-end">
<div className="flex items-center gap-1 bg-yellow-100 px-3 py-1 rounded-full">
<Star className="text-yellow-500" size={20} fill="currentColor" />
<span className="font-semibold">{builder.rating}</span>
<span className="text-gray-600">({builder.total_reviews} reviews)</span>
</div>
<div className="mt-2 flex items-center gap-1 text-gray-600">
<Clock size={16} />
<span>{builder.experience} experience</span>
</div>
</div>
</div>

{/* Contact Information */}
<div className="mt-6 grid grid-cols-1 md:grid-cols-2 gap-4">
<div className="flex items-center gap-3 p-4 bg-gray-50 rounded-lg">
<Phone className="text-blue-600" size={24} />
<div>
<div className="text-sm text-gray-600">Phone</div>
<div className="font-medium">{builder.contact_info.phone}</div>
</div>
</div>
<div className="flex items-center gap-3 p-4 bg-gray-50 rounded-lg">
<Mail className="text-blue-600" size={24} />
<div>
<div className="text-sm text-gray-600">Email</div>
<div className="font-medium">{builder.contact_info.email}</div>
</div>
</div>
</div>

{/* License Information */}
<div className="mt-6 grid grid-cols-1 md:grid-cols-2 gap-4">
<div className="flex items-center gap-3 p-4 bg-gray-50 rounded-lg">
<Building2 className="text-blue-600" size={24} />
<div>
<div className="text-sm text-gray-600">License Number</div>

```



```

<div className="font-medium">{builder.license_no}</div>
</div>
</div>
<div className="flex items-center gap-3 p-4 bg-gray-50 rounded-lg">
<Building2 className="text-blue-600" size={24} />
<div>
<div className="text-sm text-gray-600">GST Number</div>
<div className="font-medium">{builder.gst_number}</div>
</div>
</div>
</div>

{/* Booking Button */}
<div className="mt-8">
<button
onClick={() => setIsBookingModalOpen(true)}
className="w-full md:w-auto px-8 py-3 bg-blue-600 text-white font-medium rounded-lg
hover:bg-blue-700 flex items-center justify-center gap-2"
>
<Calendar size={20} />
Book Consultation
</button>
</div>
</div>
</div>

{/* Reviews Section */}
<div className="mt-8 bg-white rounded-xl shadow-lg p-6">
<h2 className="text-2xl font-bold text-gray-900 mb-4">Reviews</h2>
<div className="space-y-4">
{/* Mock reviews - In a real app, these would come from the database */}
<div className="border-b border-gray-200 pb-4">
<div className="flex items-center gap-2">
<div className="flex items-center">
{[...Array(5)].map((_, i) => (
<Star
key={i}
size={16}
className={i < 4 ? "text-yellow-500" : "text-gray-300"}
fill="currentColor"
/>
))}
</div>
<span className="text-gray-600">4.0</span>
</div>
<p className="mt-2 text-gray-700">
"Great service and professional team. They completed the project on time and within budget."
</p>
<div className="mt-2 text-sm text-gray-600">
- John Doe, 2 months ago
</div>
</div>
</div>
{/* Add more reviews as needed */}
</div>
</div>
</main>

```

```

{ /* Booking Modal */}
{isBookingModalOpen && (
  <div className="fixed inset-0 bg-black bg-opacity-50 flex items-center justify-center z-50">
    <div className="bg-white rounded-lg p-8 max-w-md w-full mx-4">
      <h3 className="text-2xl font-bold text-gray-900 mb-4">Book Consultation</h3>
      <form className="space-y-4">
        <div>
          <label className="block text-sm font-medium text-gray-700">
            Preferred Date
          </label>
          <input
            type="date"
            className="mt-1 block w-full rounded-md border-gray-300 shadow-sm focus:border-blue-500
            focus:ring-blue-500"
          />
        </div>
        <div>
          <label className="block text-sm font-medium text-gray-700">
            Project Details
          </label>
          <textarea
            rows={4}
            className="mt-1 block w-full rounded-md border-gray-300 shadow-sm focus:border-blue-500
            focus:ring-blue-500"
            placeholder="Describe your project..."
          />
        </div>
        <div className="flex justify-end gap-4">
          <button
            type="button"
            onClick={() => setIsBookingModalOpen(false)}
            className="px-4 py-2 text-gray-600 hover:text-gray-900"
          >
            Cancel
          </button>
          <button
            type="submit"
            className="px-4 py-2 bg-blue-600 text-white rounded-lg hover:bg-blue-700"
          >
            Submit Request
          </button>
        </div>
      </form>
    </div>
  </div>
)}
</div>
);
}

```

Step 17: src/components/LoginModal.tsx

Login modal component

```

import React, { useState } from 'react';
import { X } from 'lucide-react';
import { User } from '../types';

```

```

interface LoginModalProps {
  isOpen: boolean;
  onClose: () => void;
  onLogin: (user: User) => void;
}

export function LoginModal({ isOpen, onClose, onLogin }: LoginModalProps) {
  const [email, setEmail] = useState('');
  const [password, setPassword] = useState('');
  const [isLoading, setIsLoading] = useState(false);
  const [error, setError] = useState('');

  if (!isOpen) return null;

  const handleSubmit = async (e: React.FormEvent) => {
    e.preventDefault();
    setIsLoading(true);
    setError('');

    // Mock login - replace with actual API call
    try {
      // Simulate API call
      await new Promise(resolve => setTimeout(resolve, 1000));

      // Mock successful login
      if (email === 'demo@example.com' && password === 'password') {
        const user: User = {
          user_id: 1,
          name: 'Demo User',
          email: email,
          phone_number: '555-0123',
          user_type: 'client',
          registered_at: new Date().toISOString()
        };
        onLogin(user);
        onClose();
      } else {
        setError('Invalid credentials. Try demo@example.com / password');
      }
    } catch (err) {
      setError('An error occurred. Please try again.');
```

```

    } finally {
      setIsLoading(false);
    }
  };

  return (
    <div className="fixed inset-0 bg-black bg-opacity-50 flex items-center justify-center z-50">
      <div className="bg-white rounded-lg p-8 max-w-md w-full mx-4">
        <div className="flex justify-between items-center mb-6">
          <h2 className="text-2xl font-bold text-gray-900">Login</h2>
          <button onClick={onClose} className="text-gray-500 hover:text-gray-700">
            <X size={24} />
          </button>
        </div>

        <form onSubmit={handleSubmit} className="space-y-4">

```

```

<div>
  <label htmlFor="email" className="block text-sm font-medium text-gray-700">
    Email
  </label>
  <input
    type="email"
    id="email"
    value={email}
    onChange={(e) => setEmail(e.target.value)}
    className="mt-1 block w-full rounded-md border-gray-300 shadow-sm focus:border-blue-500
    focus:ring-blue-500"
    required
  />
</div>

<div>
  <label htmlFor="password" className="block text-sm font-medium text-gray-700">
    Password
  </label>
  <input
    type="password"
    id="password"
    value={password}
    onChange={(e) => setPassword(e.target.value)}
    className="mt-1 block w-full rounded-md border-gray-300 shadow-sm focus:border-blue-500
    focus:ring-blue-500"
    required
  />
</div>

{error && (
  <div className="text-red-600 text-sm">{error}</div>
)}

<button
  type="submit"
  disabled={isLoading}
  className="w-full py-2 px-4 border border-transparent rounded-md shadow-sm text-sm
  font-medium text-white bg-blue-600 hover:bg-blue-700 focus:outline-none focus:ring-2
  focus:ring-offset-2 focus:ring-blue-500 disabled:opacity-50"
  >
  {isLoading ? 'Logging in...' : 'Login'}
</button>

<div className="text-sm text-gray-600 text-center mt-4">
  Demo credentials:<br />
  Email: demo@example.com<br />
  Password: password
</div>
</form>
</div>
</div>
);
}

```

Step 18: src/components/SearchFilters.tsx

Search and filter panel

```

import React from 'react';
import { Search, MapPin, Star, Clock } from 'lucide-react';
import { SearchFilters as SearchFiltersType } from '../types';

interface SearchFiltersProps {
  filters: SearchFiltersType;
  onFilterChange: (filters: SearchFiltersType) => void;
}

export function SearchFiltersPanel({ filters, onFilterChange }: SearchFiltersProps) {
  return (
    <div className="bg-white p-6 rounded-xl shadow-md">
      <div className="grid grid-cols-1 md:grid-cols-2 lg:grid-cols-4 gap-4">
        <div className="relative">
          <div className="absolute inset-y-0 left-3 flex items-center pointer-events-none">
            <Search className="text-gray-400" size={20} />
          </div>
          <input
            type="text"
            placeholder="Search services..."
            className="w-full pl-10 pr-4 py-2 border border-gray-300 rounded-lg focus:ring-2 focus:ring-blue-500 focus:border-transparent"
            value={filters.service}
            onChange={(e) => onFilterChange({ ...filters, service: e.target.value })}
          />
        </div>

        <div className="relative">
          <div className="absolute inset-y-0 left-3 flex items-center pointer-events-none">
            <MapPin className="text-gray-400" size={20} />
          </div>
          <input
            type="text"
            placeholder="Location"
            className="w-full pl-10 pr-4 py-2 border border-gray-300 rounded-lg focus:ring-2 focus:ring-blue-500 focus:border-transparent"
            value={filters.location}
            onChange={(e) => onFilterChange({ ...filters, location: e.target.value })}
          />
        </div>

        <div className="relative">
          <div className="absolute inset-y-0 left-3 flex items-center pointer-events-none">
            <Star className="text-gray-400" size={20} />
          </div>
          <select
            className="w-full pl-10 pr-4 py-2 border border-gray-300 rounded-lg focus:ring-2 focus:ring-blue-500 focus:border-transparent appearance-none"
            value={filters.rating}
            onChange={(e) => onFilterChange({ ...filters, rating: Number(e.target.value) })}
          >
            <option value={0}>Any Rating</option>
            <option value={4}>4+ Stars</option>
            <option value={4.5}>4.5+ Stars</option>
          </select>
        </div>
      </div>
    </div>
  );
}

```

```

<div className="relative">
<div className="absolute inset-y-0 left-3 flex items-center pointer-events-none">
<Clock className="text-gray-400" size={20} />
</div>
<select
className="w-full pl-10 pr-4 py-2 border border-gray-300 rounded-lg focus:ring-2
focus:ring-blue-500 focus:border-transparent appearance-none"
value={filters.experience}
onChange={(e) => onFilterChange({ ...filters, experience: Number(e.target.value) })}
>
<option value={0}>Any Experience</option>
<option value={5}>5+ Years</option>
<option value={10}>10+ Years</option>
<option value={15}>15+ Years</option>
</select>
</div>
</div>
</div>
);
}

```

Step 19: project/src/data/builders.ts

Real Indian builder mock data

```

import { Builder } from '../types';

// Convert the CSV data to Builder objects
export const BUILDERS: Builder[] = [
{
  builder_id: 1,
  name: "R K CONSTRUCTIONS",
  gst_number: "33FAXPS3993A1Z4",
  address: "No.2/222, 1st Cross Street, Raghava Nagar, Madipakkam, Chennai, Kancheepuram, Tamil Nadu, 600091",
  contact_info: {
    phone: null,
    email: "contact@rkconstructions.com"
  },
  is_gst_verified: true,
  experience: "8 years",
  category: "established",
  projects_completed: 120,
  registered_at: "2020-01-01T00:00:00Z",
  builder_image:
    "https://images.unsplash.com/photo-1504307651254-35680f356dfd?auto=format&fit=crop&w=800",
  rating: 4.5,
  total_reviews: 85,
  verified: true,
  specializations: ["Residential", "Commercial"]
},
{
  builder_id: 2,
  name: "Shrii Dharshini Builders",
  gst_number: "33AMWPC7084L1ZG",
  address: "No.4/24, 3RD STREET / JEEVAN NAGAR, ADAMBAKKAM, Chennai, Tamil Nadu, 600088",
  contact_info: {

```

```
phone: null,
email: "info@dharshinibuilders.com"
},
is_gst_verified: true,
experience: "6 years",
category: "established",
projects_completed: 75,
registered_at: "2021-03-15T00:00:00Z",
builder_image:
"https://images.unsplash.com/photo-1503387762-592deb58ef4e?auto=format&fit=crop&w=800",
rating: 4.7,
total_reviews: 62,
verified: true,
specializations: ["Residential", "Interior"]
},
{
builder_id: 3,
name: "RAMCONS",
gst_number: "33AAIPR6430P1Z8",
address: "2nd Floor, No. 1/2, Ramcons Fortuna Towers, Kodambakkam high road, Nungambakkam, Chennai, Chennai, Tamil Nadu, 600034",
contact_info: {
phone: null,
email: "info@ramcons.com"
},
is_gst_verified: true,
experience: "12 years",
category: "established",
projects_completed: 200,
registered_at: "2019-05-20T00:00:00Z",
builder_image:
"https://images.unsplash.com/photo-1581094794329-c8112a89af12?auto=format&fit=crop&w=800",
rating: 4.8,
total_reviews: 150,
verified: true,
specializations: ["Commercial", "Residential", "High-rise"]
},
{
builder_id: 4,
name: "Kalam Builders",
gst_number: "33AAFPV4954M1Z4",
address: "Mezzanine Floor, No.189 / office No.14, Aarti chamber building, Anna salai, Anna salai, Chennai, Tamil Nadu, 600006",
contact_info: {
phone: null,
email: "contact@kamalambuilders.com"
},
is_gst_verified: true,
experience: "5 years",
category: "established",
projects_completed: 45,
registered_at: "2022-01-10T00:00:00Z",
builder_image:
"https://images.unsplash.com/photo-1600585154340-be6161a56a0c?auto=format&fit=crop&w=800",
rating: 4.6,
total_reviews: 38,
verified: true,
```

```

specializations: ["Residential"]
},
{
  builder_id: 5,
  name: "ATULIT",
  gst_number: "33AEDPG8496H1ZB",
  address: "No.22/12 Flat No.1B, Asvini Abinav Apartment, JAI NAGAR 16TH STREET, Arumbakkam, Chennai, Tamil Nadu, 600106",
  contact_info: {
    phone: "9940341775",
    email: "contact@atulit.com"
  },
  is_gst_verified: true,
  experience: "3 years",
  category: "beginner",
  projects_completed: 25,
  registered_at: "2023-02-15T00:00:00Z",
  builder_image:
    "https://images.unsplash.com/photo-1600573472550-8090b5e0745e?auto=format&fit=crop&w=800",
  rating: 4.4,
  total_reviews: 18,
  verified: true,
  specializations: ["Residential", "Interior"]
}
];

```

Step 20: project/src/components/pages/BecomeBuilder.tsx

Become a builder page

```

import React from 'react';
import { Building2, Shield, Users, TrendingUp } from 'lucide-react';

export function BecomeBuilder() {
  const benefits = [
    {
      icon: <Users className="w-12 h-12 text-blue-600" />,
      title: "Expand Your Reach",
      description: "Connect with potential clients actively looking for construction services."
    },
    {
      icon: <Shield className="w-12 h-12 text-blue-600" />,
      title: "Build Trust",
      description: "Get verified status and showcase your credentials to establish credibility."
    },
    {
      icon: <Building2 className="w-12 h-12 text-blue-600" />,
      title: "Showcase Projects",
      description: "Display your portfolio and collect reviews from satisfied clients."
    },
    {
      icon: <TrendingUp className="w-12 h-12 text-blue-600" />,
      title: "Grow Your Business",
      description: "Access tools and features designed to help your construction business thrive."
    }
  ];

  return (

```



```

<div className="max-w-4xl mx-auto py-12 px-4">
<h1 className="text-4xl font-bold text-center mb-8">Become a Builder on BuildConnect</h1>

<div className="grid md:grid-cols-2 gap-8 mb-12">
  {benefits.map((benefit, index) => (
    <div key={index} className="bg-white p-6 rounded-lg shadow-md">
      <div className="mb-4">{benefit.icon}</div>
      <h2 className="text-xl font-semibold mb-2">{benefit.title}</h2>
      <p className="text-gray-600">{benefit.description}</p>
    </div>
  ))}
</div>

<div className="bg-blue-50 p-8 rounded-lg">
  <h2 className="text-2xl font-semibold mb-4">Ready to Join?</h2>
  <p className="text-gray-700 mb-6">
    Join our network of professional builders and start growing your business today.
  </p>
  <button className="bg-blue-600 text-white px-6 py-3 rounded-lg font-medium
    hover:bg-blue-700">
    Apply as Builder
  </button>
</div>
</div>
);
}

```

Step 21: project/src/components/pages/BuilderDashboard.tsx

Builder dashboard

```

import React from 'react';
import { Building2, Users, Star, Briefcase, ChevronRight } from 'lucide-react';

export function BuilderDashboard() {
  // Mock data - replace with actual API data
  const stats = [
    { label: 'Total Projects', value: '45', icon: Building2 },
    { label: 'Active Clients', value: '12', icon: Users },
    { label: 'Average Rating', value: '4.8', icon: Star },
    { label: 'Years Experience', value: '15', icon: Briefcase },
  ];

  const recentProjects = [
    {
      id: 1,
      title: 'Modern Villa Construction',
      client: 'John Smith',
      status: 'In Progress',
      completion: '75%',
    },
    {
      id: 2,
      title: 'Office Renovation',
      client: 'Tech Corp',
      status: 'Completed',
      completion: '100%',
    },
  ],

```

```

{
  id: 3,
  title: 'Apartment Complex',
  client: 'Real Estate Ltd',
  status: 'Planning',
  completion: '10%',
},
];

return (
<div>
<div className="mb-8">
<h1 className="text-3xl font-bold text-gray-900">Builder Dashboard</h1>
<p className="mt-2 text-gray-600">Welcome back, Modern Builders Co.</p>
</div>

{/* Stats Grid */}
<div className="grid grid-cols-1 md:grid-cols-2 lg:grid-cols-4 gap-6 mb-8">
{stats.map((stat) => (
<div key={stat.label} className="bg-white p-6 rounded-lg shadow-md">
<div className="flex items-center justify-between">
<div>
<p className="text-sm font-medium text-gray-600">{stat.label}</p>
<p className="mt-2 text-3xl font-semibold text-gray-900">{stat.value}</p>
</div>
<stat.icon className="w-12 h-12 text-blue-600" />
</div>
</div>
))}
</div>

{/* Recent Projects */}
<div className="bg-white rounded-lg shadow-md">
<div className="p-6 border-b border-gray-200">
<h2 className="text-xl font-semibold text-gray-900">Recent Projects</h2>
</div>
<div className="divide-y divide-gray-200">
{recentProjects.map((project) => (
<div key={project.id} className="p-6 hover:bg-gray-50">
<div className="flex items-center justify-between">
<div>
<h3 className="text-lg font-medium text-gray-900">{project.title}</h3>
<p className="mt-1 text-sm text-gray-600">Client: {project.client}</p>
</div>
<div className="flex items-center">
<div className="mr-4 text-right">
<p className="text-sm font-medium text-gray-900">{project.status}</p>
<p className="text-sm text-gray-600">{project.completion}</p>
</div>
<ChevronRight className="w-5 h-5 text-gray-400" />
</div>
</div>
))}
</div>
</div>
</div>
)

```

```
);  
}
```

Step 22: project/src/components/pages/BuilderLogin.tsx

Builder login page

```
import React, { useState } from 'react';  
import { useNavigate } from 'react-router-dom';  
import { Building2, Mail, Lock } from 'lucide-react';  
  
export function BuilderLogin() {  
  const [email, setEmail] = useState('');  
  const [password, setPassword] = useState('');  
  const [isLoading, setIsLoading] = useState(false);  
  const [error, setError] = useState('');  
  const navigate = useNavigate();  
  
  const handleSubmit = async (e: React.FormEvent) => {  
    e.preventDefault();  
    setIsLoading(true);  
    setError('');  
  
    try {  
      // Mock login - replace with actual API call  
      await new Promise(resolve => setTimeout(resolve, 1000));  
  
      // Mock successful login  
      if (email === 'builder@example.com' && password === 'password') {  
        navigate('/builder-dashboard');  
      } else {  
        setError('Invalid credentials. Try builder@example.com / password');  
      }  
    } catch (err) {  
      setError('An error occurred. Please try again.');
```

```

<div className="absolute inset-y-0 left-0 pl-3 flex items-center pointer-events-none">
<Mail className="h-5 w-5 text-gray-400" />
</div>
<input
id="email"
type="email"
value={email}
onChange={(e) => setEmail(e.target.value)}
className="pl-10 block w-full rounded-md border-gray-300 shadow-sm focus:ring-blue-500
focus:border-blue-500"
required
/>
</div>
</div>

<div>
<label htmlFor="password" className="block text-sm font-medium text-gray-700">
Password
</label>
<div className="mt-1 relative">
<div className="absolute inset-y-0 left-0 pl-3 flex items-center pointer-events-none">
<Lock className="h-5 w-5 text-gray-400" />
</div>
<input
id="password"
type="password"
value={password}
onChange={(e) => setPassword(e.target.value)}
className="pl-10 block w-full rounded-md border-gray-300 shadow-sm focus:ring-blue-500
focus:border-blue-500"
required
/>
</div>
</div>

{error && (
<div className="text-red-600 text-sm">{error}</div>
)}

<button
type="submit"
disabled={isLoading}
className="w-full flex justify-center py-2 px-4 border border-transparent rounded-md
shadow-sm text-sm font-medium text-white bg-blue-600 hover:bg-blue-700 focus:outline-none
focus:ring-2 focus:ring-offset-2 focus:ring-blue-500 disabled:opacity-50"
>
{isLoading ? 'Logging in...' : 'Login'}
</button>

<div className="text-sm text-gray-600 text-center">
Demo credentials:<br />
Email: builder@example.com<br />
Password: password
</div>
</form>
</div>
</div>

```

```
);  
}
```

Step 23: project/src/components/pages/HowItWorks.tsx

How it works page

```
import React from 'react';  
import { CheckCircle, PenTool as Tool, Clock, Star } from 'lucide-react';  
  
export function HowItWorks() {  
  const steps = [  
    {  
      icon: <Tool className="w-12 h-12 text-blue-600" />,  
      title: "Find the Right Builder",  
      description: "Browse through our verified builders, filter by experience, location, and  
specialization to find the perfect match for your project."  
    },  
    {  
      icon: <CheckCircle className="w-12 h-12 text-blue-600" />,  
      title: "Verify Credentials",  
      description: "Check builder profiles, GST verification, licenses, and past project reviews to  
ensure quality and reliability."  
    },  
    {  
      icon: <Clock className="w-12 h-12 text-blue-600" />,  
      title: "Request Consultation",  
      description: "Schedule a consultation with your chosen builder to discuss project  
requirements and get a quote."  
    },  
    {  
      icon: <Star className="w-12 h-12 text-blue-600" />,  
      title: "Start Your Project",  
      description: "Begin your construction project with confidence, knowing you're working with  
verified professionals."  
    }  
  ];  
  
  return (  
    <div className="max-w-4xl mx-auto py-12 px-4">  
      <h1 className="text-4xl font-bold text-center mb-8">How BuildConnect Works</h1>  
  
      <div className="space-y-12">  
        {steps.map((step, index) => (  
          <div key={index} className="flex items-start gap-6 bg-white p-6 rounded-lg shadow-md">  
            <div className="flex-shrink-0">{step.icon}</div>  
            <div>  
              <h2 className="text-xl font-semibold mb-2">{step.title}</h2>  
              <p className="text-gray-600">{step.description}</p>  
            </div>  
          </div>  
        ))}  
      </div>  
    </div>  
  );  
}
```

Step 24: project/src/components/pages/Support.tsx

Support and FAQ page

```
import React from 'react';
import { HelpCircle, Mail, Phone, MessageCircle } from 'lucide-react';

export function Support() {
  const faqs = [
    {
      question: "How do I find a builder?",
      answer: "Use our search filters to find builders by location, experience, and specialization. You can view their profiles, reviews, and past projects before making a decision."
    },
    {
      question: "Are the builders verified?",
      answer: "Yes, all builders undergo a verification process including license and GST verification. Look for the verified badge on builder profiles."
    },
    {
      question: "How do I contact a builder?",
      answer: "Once you're logged in, you can request a consultation or send a message directly through the builder's profile page."
    },
    {
      question: "What if I have issues with a builder?",
      answer: "Contact our support team immediately. We'll help mediate any concerns and ensure a fair resolution."
    }
  ];

  return (
    <div className="max-w-4xl mx-auto py-12 px-4">
      <h1 className="text-4xl font-bold text-center mb-8">Support Center</h1>

      <div className="grid md:grid-cols-3 gap-6 mb-12">
        <div className="bg-white p-6 rounded-lg shadow-md text-center">
          <Mail className="w-8 h-8 text-blue-600 mx-auto mb-4" />
          <h2 className="font-semibold mb-2">Email Support</h2>
          <p className="text-gray-600">support@buildconnect.com</p>
        </div>
        <div className="bg-white p-6 rounded-lg shadow-md text-center">
          <Phone className="w-8 h-8 text-blue-600 mx-auto mb-4" />
          <h2 className="font-semibold mb-2">Phone Support</h2>
          <p className="text-gray-600">(555) 123-4567</p>
        </div>
        <div className="bg-white p-6 rounded-lg shadow-md text-center">
          <MessageCircle className="w-8 h-8 text-blue-600 mx-auto mb-4" />
          <h2 className="font-semibold mb-2">Live Chat</h2>
          <p className="text-gray-600">Available 9 AM - 6 PM</p>
        </div>
      </div>

      <div className="bg-white p-8 rounded-lg shadow-md">
        <h2 className="text-2xl font-semibold mb-6 flex items-center gap-2">
          <HelpCircle className="text-blue-600" />
          Frequently Asked Questions
        </h2>
        <div className="space-y-6">
          {faqs.map((faq, index) => (
```

```

<div key={index}>
  <h3 className="font-semibold mb-2">{faq.question}</h3>
  <p className="text-gray-600">{faq.answer}</p>
</div>
)}}
</div>
</div>
</div>
);
}

```

Step 25: supabase/migrations/quick_mouse.sql

Database schema — Supabase SQL migration

```

/*
# Initial Schema Setup for BuildConnect Platform

1. Tables
- users
- Basic user information
- Verification status
- Profile details
- builders
- Builder-specific information
- GST verification
- Experience and categorization
- projects
- Project details and status
- Budget and timeline
- reviews
- Client feedback
- Project photos
- requests
- Client requests to builders
- Project requirements

2. Security
- Enable RLS on all tables
- Add policies for data access
*/

-- Create users table
CREATE TABLE IF NOT EXISTS users (
  user_id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
  name text NOT NULL,
  email text UNIQUE,
  phone_number text UNIQUE,
  user_type text NOT NULL CHECK (user_type IN ('client', 'builder', 'admin')),
  is_verified boolean DEFAULT false,
  verification_status text DEFAULT 'pending' CHECK (verification_status IN ('pending',
  'verified', 'rejected')),
  profile_photo text,
  created_at timestamptz DEFAULT now(),
  updated_at timestamptz DEFAULT now()
);

```

```

-- Create builders table
CREATE TABLE IF NOT EXISTS builders (
  builder_id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
  user_id uuid REFERENCES users(user_id) ON DELETE CASCADE,
  company_name text NOT NULL,
  license_no text UNIQUE,
  gst_number text UNIQUE,
  is_gst_verified boolean DEFAULT false,
  experience_years integer,
  category text CHECK (category IN ('newcomer', 'beginner', 'established')),
  address text,
  city text,
  state text,
  specializations text[],
  portfolio_images text[],
  projects_completed integer DEFAULT 0,
  created_at timestamptz DEFAULT now(),
  updated_at timestamptz DEFAULT now()
);

-- Create projects table
CREATE TABLE IF NOT EXISTS projects (
  project_id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
  builder_id uuid REFERENCES builders(builder_id) ON DELETE CASCADE,
  client_id uuid REFERENCES users(user_id) ON DELETE CASCADE,
  title text NOT NULL,
  description text,
  location text,
  start_date date,
  completion_date date,
  status text CHECK (status IN ('ongoing', 'completed')),
  budget_range text,
  photos text[],
  created_at timestamptz DEFAULT now(),
  updated_at timestamptz DEFAULT now()
);

-- Create reviews table
CREATE TABLE IF NOT EXISTS reviews (
  review_id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
  project_id uuid REFERENCES projects(project_id) ON DELETE CASCADE,
  client_id uuid REFERENCES users(user_id) ON DELETE CASCADE,
  builder_id uuid REFERENCES builders(builder_id) ON DELETE CASCADE,
  rating integer CHECK (rating >= 1 AND rating <= 5),
  review_text text,
  project_photos text[],
  created_at timestamptz DEFAULT now()
);

-- Create requests table
CREATE TABLE IF NOT EXISTS requests (
  request_id uuid PRIMARY KEY DEFAULT gen_random_uuid(),
  client_id uuid REFERENCES users(user_id) ON DELETE CASCADE,
  builder_id uuid REFERENCES builders(builder_id) ON DELETE CASCADE,
  project_type text NOT NULL,
  budget_range text,
  location text,

```



```

request_details text,
status text DEFAULT 'pending' CHECK (status IN ('pending', 'accepted', 'rejected',
'in_progress', 'completed')),
created_at timestamptz DEFAULT now(),
updated_at timestamptz DEFAULT now()
);

-- Enable Row Level Security
ALTER TABLE users ENABLE ROW LEVEL SECURITY;
ALTER TABLE builders ENABLE ROW LEVEL SECURITY;
ALTER TABLE projects ENABLE ROW LEVEL SECURITY;
ALTER TABLE reviews ENABLE ROW LEVEL SECURITY;
ALTER TABLE requests ENABLE ROW LEVEL SECURITY;

-- Create policies
CREATE POLICY "Users can read their own data"
ON users
FOR SELECT
TO authenticated
USING (auth.uid() = user_id);

CREATE POLICY "Builders are publicly readable"
ON builders
FOR SELECT
TO authenticated
USING (true);

CREATE POLICY "Projects are publicly readable"
ON projects
FOR SELECT
TO authenticated
USING (true);

CREATE POLICY "Reviews are publicly readable"
ON reviews
FOR SELECT
TO authenticated
USING (true);

CREATE POLICY "Clients can create requests"
ON requests
FOR INSERT
TO authenticated
WITH CHECK (auth.uid() = client_id);

CREATE POLICY "Users can read their own requests"
ON requests
FOR SELECT
TO authenticated
USING (auth.uid() = client_id OR auth.uid() IN (
SELECT user_id FROM builders WHERE builder_id = requests.builder_id
));

-- Add function to update builder category based on experience
CREATE OR REPLACE FUNCTION update_builder_category()
RETURNS TRIGGER AS $$
BEGIN

```

```
NEW.category = CASE
WHEN NEW.experience_years >= 5 THEN 'established'
WHEN NEW.experience_years >= 2 THEN 'beginner'
ELSE 'newcomer'
END;
RETURN NEW;
END;
$$ LANGUAGE plpgsql;

CREATE TRIGGER update_builder_category_trigger
BEFORE INSERT OR UPDATE OF experience_years ON builders
FOR EACH ROW
EXECUTE FUNCTION update_builder_category();
```

Additional Notes

Environment Variables (Supabase)

Create a .env file in the project root:

```
VITE_SUPABASE_URL=your_supabase_project_url  
VITE_SUPABASE_ANON_KEY=your_supabase_anon_key
```

Then run the SQL migration file (Step 25) in your Supabase SQL editor.

npm Scripts

```
npm run dev → Start dev server (http://localhost:5173)  
npm run build → Build for production  
npm run preview → Preview production build  
npm run lint → Run ESLint
```