

DOCUMENTATION

API Authentication

POST

SANDBOX
<https://devapi.mvola.mg/token>
PRODUCTION
<https://api.mvola.mg/token>

Overview

Authentication API to generate a token to be used by the other API. The request is secure, i.e. use [https](#) instead of [http](#), and requires having a **Consumer Key** and **Consumer Secret** after accessing the developer portal to be used in **64Base** encoding for basic access authentication

API Reference

The API is organized around **REST**

Use **Client Credentials** as grant type and

With **form-encoded** request body

Return **JSON-encoded** responses and HTTP response code

Request Headers

Authorization	Basic Base64(consumer-key:consumer-secret)
Content-Type	application/x-www-form-urlencoded
Cache-Control	no-cache

Body urlencoded

grant_type	client_credentials.
scope	EXT_INT_MVOLA_SCOPE

CURL Command

```
curl --location --request POST 'https://devapi.mvola.mg/token' \
--header 'Authorization: Basic Base64(consumer-key:consumer-secret)' \
--header 'Content-Type: application/x-www-form-urlencoded' \
--header 'Cache-Control: no-cache' \
--data-urlencode 'grant_type=client_credentials' \
--data-urlencode 'scope=EXT_INT_MVOLA_SCOPE'
```

HTTP Error

standard HTTP response code is used to indicate whether the request is a success or a failure.

200 - OK	Everything worked as expected.
400 - Bad Request	The request was unacceptable, often due to missing a required parameter.
401 - Unauthorized	No valid API key provided.
402 - Request Failed	The parameters were valid but the request failed.
403 - Forbidden	The API key doesn't have permissions to perform the request.
404 - Not Found	The requested resource doesn't exist.
409 - Conflict	The request conflicts with another request (perhaps due to using the same idempotent key).
429 - Too Many Requests	Too many requests hit the API too quickly. We recommend an exponential backoff of your requests.
500, 502, 503, 504 - Server Errors	Something went wrong on the server

Responses body

Success

Upon successful request FOUR (4) attributes will be return among which the **ACCESS_TOKEN** that will be used by the other API

```
{
  "access_token": "<ACCESS_TOKEN>",
  "scope": "EXT_INT_MVOLA_SCOPE",
  "token_type": "Bearer",
  "expires_in": 3600
}
```

Failed

If failed request then details of error will be returned

ErrorCategory	Error category
ErrorCode	Error Code
ErrorDescription	description on the error
ErrorDateTime	Date and time when the error occurred
ErrorParameters	Key/value which add more details on the nature of the error