

OPERATIONS AND REFERENCE

# Disaster Recovery Runbook

Severity levels

Publication edition | 2026-08-03

## Document Control

|                 |                                                                                             |
|-----------------|---------------------------------------------------------------------------------------------|
| <b>Purpose</b>  | Enterprise platform overview and buyer evaluation reference                                 |
| <b>Audience</b> | Business leaders, platform administrators, evaluators, partners, and technical stakeholders |
| <b>Scope</b>    | Capabilities, architecture, security, deployment, adoption, outcomes, and terminology       |
| <b>Source</b>   | ServicePro repository documentation; technical meaning preserved                            |

SEV1: Production unavailable or data corruption suspected.  
SEV2: Major feature unavailable.  
SEV3: Partial degradation.

## SEV1 recovery steps

- 1 Freeze deploys.
- 2 Preserve logs, audit events, and latest database snapshot.
- 3 Identify latest verified backup.
- 4 Restore backup to staging first.
- 5 Validate application boot and data integrity.
- 6 Promote restored database or re-point application.
- 7 Run post-restore checks.
- 8 Document root cause.

## Post-restore checks

```
npm run config:check
npm run migrations:check
npm test
Invoke-RestMethod https://your-domain/healthz
Invoke-RestMethod https://your-domain/readyz
```

## Data integrity check

```
POST /api/v1/integrity/run
GET /api/v1/integrity
```