

RELEASE DOCUMENTATION

ServicePro 8.0.0-alpha.1 — Deployment Readiness

Verified configuration

Publication edition | 2026-08-03

Document Control

Purpose	Enterprise platform overview and buyer evaluation reference
Audience	Business leaders, platform administrators, evaluators, partners, and technical stakeholders
Scope	Capabilities, architecture, security, deployment, adoption, outcomes, and terminology
Source	ServicePro repository documentation; technical meaning preserved

- `render.yaml` targets main, provisions a non-production free Render PostgreSQL instance, and executes the idempotent `npm run migrate` command before each API process starts because Render free services do not support pre-deploy commands.
- Both web services explicitly use Render's free instance type and may spin down after inactivity.
- The free PostgreSQL instance is limited to 1 GB, has no backups, and expires after 30 days. It must not hold production or irreplaceable data.
- Production secrets and allowed origins are environment inputs rather than repository defaults.
- Production Docker Compose fails closed when database, Redis, signing secrets, or CORS values are absent.
- Development Compose values are explicitly development-only.
- Cloudflare Pages/Workers static assets use the current `assets.directory = "/.out"` model.
- Application, package, and deployment versions agree on 8.0.0-alpha.1.

Non-production deployment checklist

- 1 For evaluation, provision the Blueprint's free PostgreSQL instance and record its 30-day expiration date. For production, replace it with managed PostgreSQL and Redis plans that include backup/retention policies.
- 2 Inject unique signing secrets, database credentials, Redis URL, canonical public API URL, and exact allowed origins.
- 3 Run the pre-deploy migration and retain its immutable log.
- 4 Verify `/healthz`, `/readyz`, login, dashboard, customer, work-order, invoice, and payment workflows.
- 5 Verify tenant isolation with two controlled tenants.
- 6 Perform and restore a deployment-environment backup.
- 7 Validate TLS, DNS, Cloudflare headers/caching rules, logging, alerting, and rollback.
- 8 Promote only the tested artifact digest; do not rebuild between environments.

Rollback gate

Before production promotion, record the previous artifact digest, database backup identifier, migration boundary, rollback owner, and maximum acceptable recovery time. A rollback is not considered ready until the restored application passes authenticated smoke testing.