

OPERATIONS AND REFERENCE

Backup and Recovery Guide

JSON mode backup

Publication edition | 2026-08-03

Document Control

Purpose	Enterprise platform overview and buyer evaluation reference
Audience	Business leaders, platform administrators, evaluators, partners, and technical stakeholders
Scope	Capabilities, architecture, security, deployment, adoption, outcomes, and terminology
Source	ServicePro repository documentation; technical meaning preserved

Table of Contents

[Document Control](#)

[Validate a JSON restore file](#)

[PostgreSQL backup](#)

[PostgreSQL restore](#)

[Retention](#)

[Recovery drill](#)

```
$env:DATA_FILE="./data/servicepro-runtime.json"
$env:BACKUP_DIR="./backups"
npm run backup:json
```

This creates:

```
backups/servicepro-json-<timestamp>.json
backups/servicepro-json-<timestamp>.json.manifest.json
```

Validate a JSON restore file

```
node scripts/validate-restore-file.js .\backups\servicepro-json-<timestamp>.json
```

PostgreSQL backup

Generate the command:

```
$env:DATABASE_URL="postgresql://servicepro:password@host:5432/servicepro"
npm run backup:postgres:command
```

Run the printed `pg_dump` command on a machine with PostgreSQL client tools installed.

PostgreSQL restore

Use the printed `pg_restore` command. Restore into a staging database first.

Retention

Recommended minimum:

```
Hourly backups retained for 48 hours
Daily backups retained for 30 days
Monthly backups retained for 12 months
```

Generate a local retention report:

```
node scripts/backup-retention-report.js
```

Recovery drill

At least once per month:

- 1 Restore latest backup into staging.
- 2 Run migrations.
- 3 Run `npm run config:check`.
- 4 Run `npm test`.
- 5 Smoke-test `/healthz` and `/readyz`.