INNER-JOIN:

1.NAME OF THE EMPLOYEE AND HIS LOCATION OF ALL THE EMPLOYEES.

```
 SELECT E.ENAME, D.LOC
 FROM EMP E
 JOIN DEPT D
 ON E.DEPTNO = D.DEPTNO;
```

2.WAQTD DNAME AND SALARY FOR ALL THE EMPLOYEE WORKING IN ACCOUNTING.

```
SELECT D.DNAME, E.SAL
FROM DEPT D
JOIN EMP E
ON D.DEPTNO = E.DEPTNO
WHERE DNAME = 'ACCOUNTING';
```

3.WAQTD DNAME AND ANNUAL SALARY FOR ALL EMPLOYEES WHOS SALARY IS MORE THAN 2340

```
SELECT D.DNAME,E.SAL*12
FROM DEPT D
JOIN EMP E
ON D.DEPTNO = E.DEPTNO
WHERE E.SAL > 2340;
```

4.WAQTD ENAME AND DNAME FOR EMPLOYEES HAVING CAHARACTER 'A' IN THEIR DNAME

```
SELECT E.ENAME, D.DNAME
FROM EMP E
JOIN DEPT D
ON E.DEPTNO = D.DEPTNO
WHERE DNAME LIKE '%A%';
```

5.WAQTD ENAME AND DNAME FOR ALL THE EMPLOYEES WORKING AS SALESMAN

```
 SELECT E.ENAME, D.DNAME
 FROM EMP E
 JOIN DEPT D
 ON E.DEPTNO = D.DEPTNO
WHERE E.JOB = 'SALESMAN';
```

6.WADTD DNAME AND JOB FOR ALL THE EMPLOYEES WHOS JOB AND DNAME STARTS WITH CHARACTER 'S

```
SELECT D.DNAME, E.JOB
FROM EMP E
JOIN DEPT D
ON E.DEPTNO = D.DEPTNO
WHERE E.JOB LIKE 'S%' AND D.DNAME LIKE 'S%';
```

7.WAQTD DNAME AND MGR NO FOR EMPLOYEES REPORTING TO 7839

```
 SELECT D.DNAME, E.MGR
 FROM DEPT D
 JOIN EMP E
 ON D.DEPTNO = E.DEPTNO
 WHERE MGR = 7839;
```

8.WAQTD DNAME AND HIREDATE FOR EMPLOYEES HIRED AFTER 83 INTO ACCOUNTING OR RESEARCH DEPT

```
 SELECT D.DNAME, E.HIREDATE
 FROM DEPT D
 JOIN EMP E
```

```
 ON D.DEPTNO = E.DEPTNO
 WHERE E.HIREDATE > '31-DEC-83' AND DNAME IN('ACCOUNTING','RESEARCH');
```

9.WAQTD ENAME AND DNAME OF THE EMPLOYEES WHO ARE GETTING COMM IN DEPT 10 OR 30

```
SELECT E.ENAME,D.DNAME
FROM EMP E
JOIN DEPT D
ON E.DEPTNO = D.DEPTNO
WHERE E.COMM IS NOT NULL AND E.DEPTNO IN (10,30);
```

10.WAQTD DNAME AND EMPNO FOR ALL THE EMPLOYEES WHO'S EMPNO ARE (7839,7902) AND ARE WORKING IN LOC NEW YORK.

```
 SELECT D.DNAME, E.EMPNO
 FROM DEPT D
 JOIN EMP E
 ON D.DEPTNO = E.DEPTNO
 WHERE E.EMPNO IN (7839,7902) AND D.LOC IN 'NEW YORK';
```

LEFT OUTER JOIN:

1.Write a SQL query to display, Employee name (ENAME), Employee salary (SAL),Department name (DNAME).

```
SELECT E.ENAME, E.SAL, D.DNAME
FROM EMP E
LEFT JOIN DEPT D
ON E.DEPTNO = D.DEPTNO;
```

2.Write a SQL query to display, All department names (DNAME),Employee names (ENAME) working in each department.

```
SELECT D.DNAME, E.ENAME
FROM DEPT D
LEFT JOIN EMP E
ON E.DEPTNO = D.DEPTNO;
```

3.Write a SQL query to display, Employee name (ENAME), Department number (DEPTNO), Department location (LOC).

```
SELECT E.ENAME, D.DEPTNO, D.LOC
FROM EMP E
LEFT JOIN DEPT D
ON E.DEPTNO = D.DEPTNO;
```

4.Write a SQL query to display, Employee name (ENAME), Employee job (JOB),Department name (DNAME),Department location (LOC).

```
SELECT E.ENAME,E.JOB,D.DNAME,D.LOC
FROM EMP E
LEFT JOIN DEPT D
ON E.DEPTNO = D.DEPTNO;
```

5.Write a SQL query to display, Department name (DNAME),Employee name (ENAME),Employee salary (SAL).

```
SELECT D.DNAME, E.ENAME, E.SAL
FROM DEPT D
LEFT JOIN EMP E
ON D.DEPTNO = E.DEPTNO;
```

General JOIN:

1.Display:
- Employee name (ENAME)
- Department name (DNAME)
Condition: Display all employees, including employees who don't have a matching department.

```
SELECT E.ENAME, D.DNAME
FROM EMP E
LEFT JOIN DEPT D
ON E.DEPTNO = D.DEPTNO;
```

2.Display:
- Department name (DNAME)
- Department location (LOC)
- Employee name (ENAME)
Condition: Display all departments, including departments that don't have any employees.

```
SELECT D.DNAME,D.LOC,E.ENAME
FROM EMP E
RIGHT JOIN DEPT D
ON E.DEPTNO = D.DEPTNO;
```

3.Display:
- Employee name (ENAME)
- Department name (DNAME)
- Department location (LOC)
Condition:

Display all employees AND all departments, including records that don't have matching values in the other table.

```
SELECT E.ENAME,D.DNAME,D.LOC
FROM EMP E
FULL JOIN DEPT D
ON E.DEPTNO = D.DEPTNO;
```

4.Display:
- Employee name (ENAME)
- Employee's manager name (MGR_NAME)
Condition:

Display each employee along with their manager's name. Both employee and manager details are available in the same EMP table.

```
SELECT E.ENAME,M.ENAME
FROM EMP E
JOIN EMP M
ON E.MGR = M.EMPNO;
```

5.Display:
- Employee name (ENAME)
- Department name (DNAME)
Condition:

Join both tables automatically.

```
SELECT E.ENAME,D.DNAME
FROM EMP E
NATURAL JOIN DEPT D;
```

6.Display:
- Employee name (ENAME)
- Department name (DNAME)

Condition: Generate all possible combinations of employees and departments, regardless of their department numbers.

```
SELECT *
FROM EMP E
CROSS JOIN DEPT D;
```