VotingBlock.java **Civilian.java** **AVLTree.java** **BinaryNode.java** **BinarySearchTree.java**

Stroudonia is using FingerPrint to try and determine the voting tendency of its populace. FingerPrint is Stroudonia's version of a social media platform where the user, in exchange for a free service of communication, willing allows the trade and exchange of information of said user based on their social media habits. It follows a grand tradition of individuals sacrificing their privacy for convenience.

The program will read a file that will contain an unknown amount of individuals. Each line of the account will include the person's name and a Fingerprint value recorded as a decimal value representing a numerical value of each person's ideology. Any value below zero means the individual's ideology is considered liberal to the prevalent ideology of Stroudonia. Any value above zero means the individual's ideology is considered conservative to the prevalent ideology of Stroudonia.

Place all individuals into an AVL tree. You may assume that there are no duplicates. Once the AVL is completed. Print out the list in level order, with each rating to the third decimal place. Print out the average Fingerprint value of all the individuals in the list to the fourth decimal place. Then print out the list of individuals who are marked as liberal and list of individuals marked as conservative, in ascending order. Finally, continually remove individuals from the AVL until The FingerPrint average is within the range given by the user, so 0.2 means a precission between -0.2 and 0.2, by removing the most extreme liberal/conservative from the list based on the average. This means if the list leans too conservative, remove the most extreme conservative from the list or if the list leans too liberal, remove the most extreme liberal from the list. Print the list of removed voters in the order they are removed and the resulting FingerPrint average.

The programmer needs to make a Civilian class that implements Comparable<Civilian> in order to use the AVL Tree. The user should make their own AVLTree class. The BinaryNode class and the BinarySearchTree class is provided, if the user would like to use it.

Sample Input:

```
civ1.txt
0.2
```

Sample Output :

```
AVL Tree:
Kyle Cuevas 2.128|
Emerson Porter -1.037|Tommy Stanton 4.039|
Dale Waters -3.184|Shelby Oconnell -0.036|null|null|
Fingerprint average:
```

0.3819
Liberal roll:
[Dale Waters -3.184, Emerson Porter -1.037, Shelby Oconnell -0.036]
Conservative roll:
[Kyle Cuevas 2.128, Tommy Stanton 4.039]
Removed roll:
[Tommy Stanton 4.039, Dale Waters -3.184, Kyle Cuevas 2.128, Emerson Porter -1.037]
Fingerprint average:
-0.0362