


SAT

NP-completeness, Cook and Levin through circuits, why SAT is hard, and how modern solvers answer it anyway: DPLL, CDCL, and babysat as the executable specification.

← CC 10 · Semantics as a Formula

DECIDABLE $\neq$ DOABLE

P, NP, and the asymmetry between finding and checking.




P: questions some method answers in time polynomial in the input size. Parsing, sorting, running mipster for k steps. Affordable.

NP: questions whose yes-answers come with a certificate checkable in polynomial time. A satisfying assignment. A colouring of the register graph. A schedule. Finding may take 2^n ; checking is a loop over the clauses.

$P \subseteq NP$, obviously. Whether $P = NP$ is the open question of the exact sciences. Most researchers bet no, and this class is built on that bet.

Polynomial or exponential: times ten, or plus one.



a polynomial is a line on log-log axes; the exponential is not

Times ten. Ten times the input costs a polynomial method a fixed factor: $\times 10$ if linear, like parsing; $\times 100$ if quadratic. That is what affordable means.

Plus one. One more variable doubles the 2^n assignments. One more value to colour multiplies the colourings by k . If adding one to the input multiplies the work, no hardware catches up.

P is the left test passing. NP-hard means nobody knows a method that escapes the right one.

SAT is NP-complete: every question in NP is a formula in disguise.

Take any polynomial-time checker — a machine that reads a question and a certificate and says yes or no in $p(n)$ steps. Its whole computation fits in $p(n)$ states of $p(n)$ bits. Write one variable per bit per step, and clauses saying each step follows from the last by the machine's rules — *next*, as a formula, $p(n)$ times.

The result is satisfiable exactly if some certificate makes the checker say yes. Finding the certificate is now solving SAT. So SAT is at least as hard as everything in NP: NP-hard, and in NP itself, so NP-complete.

YOU SAW THIS LAST WEEK

Cook's construction is rotor's unrolling. A machine's computation written down as a formula, one copy of the state per step. The proof technique of 1971 is the tool of week 10, and the class has already run it.

Karp, 1972: twenty-one more problems, by reduction to and from SAT. By now thousands. Crack one, crack all.

The exponential is a **worst case**. Real formulas have **structure**.

Random 3-SAT: below about 4.26 clauses per variable almost everything is satisfiable and easy; above, almost everything is unsatisfiable and easy; at the threshold, hard for every solver ever built. That phase transition is the closest thing to a picture of where the difficulty lives.

Formulas from chips, schedules and programs are not random. They have long implication chains, small backdoors, symmetries. Modern solvers handle millions of variables on them in seconds, and it is one of engineering's great quiet victories.

HARDNESS IS LOAD-BEARING

If SAT were easy, every certificate would be findable: every key, every signature, every password. Difficulty is the raw material of security and the reason abstraction and taste beat compute. The universe we live in trades that power for privacy and discovery.

The executable specification: try true, try false, **prune** when a clause is already lost.

```
uint64_t babysat(uint64_t depth) {  
    if (depth == number_of_sat_variables)  
        return SAT;  
    *(sat_assignment + depth) = TRUE;  
    if (instance_may_be_true(depth))  
        if (babysat(depth + 1) == SAT) return SAT;  
    *(sat_assignment + depth) = FALSE;  
    if (instance_may_be_true(depth))  
        if (babysat(depth + 1) == SAT) return SAT;  
    return UNSAT;  
}
```

Recursion over the variables in order. Set the next one true; if no clause is already false, recurse. Then false, the same. If both fail, backtrack. A clause may still be true if some literal is true or unassigned.

Four hundred lines of C* on top of selfie, so mipster runs it. It is what a SAT solver is: the search tree walked depth-first and pruned at dead branches.

```
$ make sat  
./babysat: examples/sat/rivest.cnf is satisfiable  
with -1 -2 3 4
```

Propagate what is forced. Decide only when nothing is.

Unit propagation. A clause with all but one literal false forces the last one. Set it, and repeat, because that may make other clauses unit. A human does this without thinking; babysat does not do it at all.


Pure literals. A variable occurring only positively can be set true harmlessly; dually for negative.

Decide, backtrack. Only when neither applies, pick a variable and try a value; on conflict, go back to the last decision and try the other. Depth-first search with the subtrees that propagation kills never entered.

WHAT IT FORGETS

DPLL backtracks to the most recent decision, whether or not that decision caused the conflict, and may run into the same conflict again elsewhere. It does not learn. That is the gap between 1962 and 1996.

A conflict is **information**. Write down why, and never fail that way again.



Decide $x1 = T$, then $x2 = T$; propagation forces $x3$ and $x4$, and $C6$ dies. The decisions responsible are $x1$ and $x2$: learn $\neg x1 \vee \neg x2$.

Backjump: the learned clause forces $x2 = F$. $C1$ dies, and this time only $x1$ is to blame. Learn $\neg x1$.

With $x1 = F$, decide $x2 = T$: $C5$ dies, learn $\neg x2$. Then $x2 = F$, $x3 = T$ satisfies everything. Four assignments instead of sixteen; the learned clauses are theorems.

ASSIGNMENT

struct-declaration.

- 1 Specify. Extend the grammar with struct declarations: a name, a braced list of fields with types, and the type `struct name *` for pointers to them.
- 2 Represent. The symbol table needs a new class of entry: a struct with its list of fields, each with a type and an offset. Fields are laid out in declaration order, eight bytes each.
- 3 Check. Declaring a variable of a struct pointer type, and the type checking of week 4 extended to the new types. No access yet; that is next week.
- 4 `./grader/self.py struct-declaration and self-compile.`

WHY STRUCTS LAST

They are the one extension that changes the symbol table's shape rather than adding an entry, and the one that selfie itself would most benefit from: its own symbol table entries are hand-laid-out words with getter procedures, because C* has no structs. Next week you will be able to write the table you have been reading all semester.

Listen, then read.

LISTEN

Bach · Musical Offering — Jordi Savall, Le Concert des Nations. Over two of the canons Bach wrote *Quaerendo invenietis*, seek and you shall find: the score gives the theme and the rule, and the player must find the assignment that makes it work. SAT, 1747.

READ

The Art of Computer Programming, Volume 4, Fascicle 6: Satisfiability — Knuth, 2015: three hundred pages on SAT solving, with solvers sat0 to sat13; babysat is deliberately more naive than sat0. And, more technical, Chaff: Engineering an Efficient SAT Solver — Moskewicz and others, 2001: the paper that made CDCL fast, with the two watched literals and VSIDS; what runs inside every solver since.