TROUBLESHOOTING GUIDE

Grip, movement, curling, flatness, washing, and surface compatibility

Product	YaoX indoor stair treads, Moroccan Beige, 15 pack
ASIN	B0FHKT432K
Grip system	Removable protective liner over non-permanent TPE friction-grip backing
Intended surfaces	Clean, dry, smooth, sealed, level indoor stair surfaces after a one-tread compatibility test

FIRST RESPONSE TO MOVEMENT OR CURLING

Stop using the affected step. Hold the handrail, remove the tread, and keep the stair out of normal use until the cause is corrected. Do not add tape, glue, staples, or nails to compensate for a grip or flatness problem.

1. Quick diagnostic table

SYMPTOM	LIKELY CAUSE	CORRECTIVE ACTION	USE AGAIN WHEN
Tread moves immediately after installation	Dust, moisture, wax, oil, polish, cleaner residue, unsuitable finish, or incomplete surface contact.	Remove the tread. Clean the stair according to the floor manufacturer's instructions. Rinse away residue and dry both surfaces completely. Reinstall one tread and test again.	Only when the tread remains flat and does not move during a careful handrail-assisted test.
Backing does not feel sticky	The TPE backing is a physical friction-grip surface, not permanent glue. It may not feel tacky like adhesive tape.	Do not apply glue. Confirm the protective liner is removed, the backing is clean and dry, and the stair surface is compatible.	Only after full contact is achieved and the movement test is passed.
Tread moves on sealed wood	Invisible wax, polish, oil, silicone, or cleaner residue may remain on the finish. Some highly textured or low-contact finishes may be incompatible.	Check the floor-care products used on the stair. Clean and dry one test area, then repeat the one-tread test. Do not use the product if movement continues.	Only after the tested tread remains stable on the actual finish.
Corner lifts after unpacking	Temporary shape memory from folded shipping or storage.	Remove the tread and place it on a clean, flat surface at room temperature until the complete tread lies flat. Do not use heat or an iron.	Only when all four corners remain completely flat.

1. Quick diagnostic table - continued

SYMPTOM	LIKELY CAUSE	CORRECTIVE ACTION	USE AGAIN WHEN
Corner lifts after installation	The tread was not fully flat before installation, debris is trapped underneath, the edge is unsupported, or the surface is incompatible.	Remove, inspect, clean, dry, flatten, and reinstall. Make sure the entire tread is on the horizontal step and does not cross the nosing.	Only when every corner remains flat during the movement test.
Tread will not lie flat	Persistent crease, damaged edge, layer deformation, or unsuitable storage.	Do not install. Lay flat at room temperature without heat. If the condition remains, discontinue use and contact the seller through the Amazon order page.	Only when the full tread lies flat without raised areas.
Grip seems reduced after washing	The backing or stair is still damp, or detergent or fabric-softener residue remains.	Rinse again with cold water and no fabric softener. Air dry flat in the shade until both sides are completely dry. Clean and dry the stair before reinstalling.	Only after complete drying and a successful one-tread test.
Top surface feels slippery	Moisture, spill residue, excessive debris, wear, or damage on the textile surface.	Remove the tread from use. Clean and dry it according to the care instructions. Replace it if the condition remains or the surface is damaged.	Only when clean, dry, undamaged, and stable.
Tread does not cover the full stair width	The nominal 30 in width is designed for the primary foot-contact area, not full-width coverage on every staircase.	Measure each stair and center the tread over the normal walking path. Keep the entire tread supported. Do not cut, overlap, or extend it over the edge.	Only when placement is consistent and the full tread is supported.
Backing leaves a visible mark	Possible moisture, contamination, transferred cleaner residue, heat exposure, or incompatibility with the stair finish.	Remove the tread and stop use on that finish. Follow the stair manufacturer's cleaning instructions. Do not use solvents on the tread or stair unless approved by the stair manufacturer.	Only after the finish is confirmed compatible and a low-visibility test is successful.

DO NOT FORCE A FIT

If the tread repeatedly moves, curls, or fails the one-tread test after cleaning and complete drying, the stair finish may be incompatible. Discontinue use on that staircase.

2. Movement and grip recovery procedure

1 **Stop use**

Block normal use of the affected step and remove the tread while holding the handrail.

2 **Inspect**

Check the stair, TPE backing, edges, and corners for dust, moisture, residue, damage, or deformation.

3 **Clean**

Clean the stair according to the stair manufacturer's instructions. Clean the TPE with cold water if needed. Remove all residue.

4 **Dry completely**

Air dry the tread flat in the shade. Confirm the stair and both sides of the tread are completely dry.

5 **Reinstall one tread**

Place the full tread on the horizontal step, smooth from the center outward, and press all corners.

6 **Test**

While holding the handrail, apply gentle pressure and check for movement. Stop if the tread shifts or any corner lifts.

3. When to discontinue use

- The tread moves during a careful post-installation test or during normal use.
- Any corner or edge remains raised after flattening and reinstallation.
- The tread cannot remain fully supported on the horizontal step.
- The backing is cracked, hardened, deformed, contaminated, or separating from the upper layers.
- The edge binding is loose, damaged, or frayed.
- The top surface remains slippery after cleaning and complete drying.
- The stair surface is wet, waxed, oily, rough, unsealed, uneven, carpeted, or otherwise incompatible.

REPLACEMENT Do not repair a damaged tread with household glue, tape, staples, or nails. Replace the affected tread or discontinue use of the set if a compatible and stable installation cannot be achieved.

4. Information to provide when requesting support

Contact the seller through the Contact Seller option on the Amazon order page. To help identify the condition, include the following information:

- Amazon order number and ASIN B0FHKT432K.
- Package label, production batch, or lot information if available.
- A photo of the full staircase and a close-up of the affected tread.
- The stair material and finish, including any wax, polish, oil, coating, or recent cleaning product used.
- Whether the issue occurred before or after washing.
- Whether the stair and TPE backing were completely dry at installation.
- A short video showing the tread position and any movement or corner lifting.

5. Pre-use checklist after troubleshooting

CHECK	PASS CONDITION
Stair surface	Clean, dry, smooth, sealed, level, and free of wax, oil, dust, and cleaner residue
TPE backing	Clean, dry, undamaged, and free of residue
Flatness	Full tread and all four corners lie completely flat
Placement	Entire tread rests on the horizontal step and does not cross the front edge
Movement test	No shifting or lifting during a careful handrail-assisted test

FINAL DECISION If any pass condition is not met, do not use the affected tread. Review the User Manual or contact the seller through the Amazon order page.

Document control: YaoX Troubleshooting Guide, ASIN B0FHKT432K, version 2.0. This guide supplements the User Manual and does not replace normal stair-safety practices or the use of a handrail.