

Table of Contents

Timeline Weather API

May 22, 2025

1. Introduction
2. Creating a weather API request
3. Request Examples
4. Weather API Response Structure
 - 4.1. Typical JSON response format
 - 4.2. Response Elements
 - 4.2.1. Response weather data elements
 - 4.2.2. Location and station elements
5. HTTP Response Code and Error Handling
6. Accessing the Timeline Weather API using the OpenAPI Description
7. Questions or need help?

Introduction

The Timeline Weather API is a versatile and powerful tool for retrieving weather data globally. You can request data over any time window including windows that span the past, present, and future. The API will take care of the combining historical observations, current 15-day forecasts, and statistical weather forecasts to create a single, consolidated dataset via a single API call. By leveraging advanced data sources, this API offers superior features like:

- GET Request Simplicity: All queries use straightforward HTTP GET requests.
- Timeline-Based Queries: Retrieve data for any date range, including past, present, and future.
- Location-Based Flexibility: Use addresses, latitude/longitude, or ZIP codes for pinpoint weather data.
- Comprehensive Coverage: Includes hourly, daily, and statistical weather details, as well as alerts and astronomical data.

- Customizable Output: Get data in JSON or CSV format.

Table of Contents

Dynamic Periods: Use dynamic keywords like last30days, today, or yesterday for queries.

1. Introduction
The Timeline API offers complete, global weather data coverage both geographically and chronologically. It always picks the best available data sources to answer any weather API query. These sources include:

2. Creating a weather API request

- 4. Weather API Response Structure
- Current weather conditions

- 4.1 Typical JSON response format
- Daily historical, forecast and statistical forecast data (depending on dates requested)

- 4.2 Response Elements
- Hourly historical observations and 15-day forecast

- 4.2.1. Response weather data elements
- Weather alerts

- 4.2.2. Location and station elements
- Astronomical observations including sunrise, sunset and moon phase.

Result data is provided in a common JSON format allowing you to ignore to complex underlying data sources and focus entirely on your weather data use case. You can also request the result in CSV text format if you prefer.

- 5. Using Data Sources and Forecast Handling
- 6. Accessing the Timeline Weather API using the OpenAPI Description

- 7. Questions or need help?

Latest features and recent changes

We continue to invest heavily in enhancing the Timeline Weather API and expanding its underlying data sources. Recent improvements include:

- **Radar-Based Precipitation Estimates**

You can now [include radar-derived precipitation data directly in your datasets](#), providing improved estimates of precipitation amount and intensity.

- **New Programmatic Dataset APIs**

[New APIs](#) have been added to enable programmatic submission, modification, and download of stored datasets, streamlining automated workflows.

- **Sub-Hourly Data Support**

The Timeline Weather API now supports [sub-hourly data with minute-level granularity](#), offering more precise short-term forecasts and observations.

For a full list of additions to the Timeline Weather API, please see the [changelog](#).

Timeline Weather API Query Builder

The [Weather Query Builder](#) page includes a full, interactive query builder so you can create queries and see the live results directly in your browser.

Table of Contents

Creating a weather API request

1. Introduction

2. Creating a weather API request

Base URL

3. Request Examples

4. Weather API Response Structure

`https://weather.visualcrossing.com/VisualCrossingWebServices/rest/servi`

4.1. Typical JSON response format

4.2. Response Elements

Endpoints

4.2.1. Response weather data elements

4.2.2. Location and station elements

The possible endpoints of the Timeline Weather API requests are as follows:

- `/timeline/[location]` – forecast queries.

- `/timeline/[location]/[date1]/[date2]` – queries for a specific date

range

6. Accessing the Timeline Weather API using the OpenAPI Description

7. Questions or need help?

Main Format of the URL

All requests to the Timeline Weather API use the following the form:

`https://weather.visualcrossing.com/VisualCrossingWebServices/rest/ser`

Request Parameters

Main Parameters (Path Parameters)

location (required) – is the address, partial address or latitude,longitude location for which to retrieve weather data. You can also use US ZIP Codes. If you would like to submit multiple locations in the same request, consider our [Multiple Location Timeline Weather API](#).

date1 (optional) – is the start date for which to retrieve weather data. If a **date2** value is also given, then it represents the first date for which to retrieve weather data. If no **date2** is specified then weather data for a single day is retrieved, and that date is specified in **date1**. All dates and times are in local time of the **location** specified. Dates should be in

the format yyyy-MM-dd. For example 2020-10-19 for October 19th, 2020 or 2017-02-03 for February 3rd, 2017.

Table of Contents

Instead of an exact date, you can specify a [dynamic date period](#). See below for more details. You may also supply the in “UNIX time”. In this case provide the number of seconds since 1st January 1970 UTC. For example 1612137600 for

Midnight on 1st February 2021.

4. Weather API Response Structure

You can also request the information for a specific time for a single date by including time into the date1 field using the format yyyy-MM-ddTHH:mm:ss. For example 2020-10-19T13:00:00.

4.2. Response Elements

4.2.1. Response weather data elements

The results are returned in the 'elements' field and are truncated to the hour requested (i.e. 2020-10-19T13:59:00 will return data at 2020-10-19T13:00:00).

5. HTTP Response Code and Error Handling

date2 (optional) – is the end date for which to retrieve weather data. This value may only be used when a **date1** value is given. When both **date1** and **date2** values are given, the query is inclusive of **date2** and the weather data request period will end on midnight of the **date2** value. All dates and times are in local time of the specified location and should be in the format yyyy-MM-dd.

When no **date1** or **date2** is specified, the request will retrieve the forecast at the requested **location** for the next 15 days.

Additional Parameters (QueryParameters)

The following are specified as HTTP query parameters (they may also be passed in a POST query).

key (required) – your API key. Sign up for a free account using our [Weather Data Services](#) page.

unitGroup (optional) – The system of units used for the output data. Supported values are `us`, `uk`, `metric`, and `base`. See [Unit groups and measurement units](#) for more information. Defaults to US system of units.

lang (optional) – Sets the language of the translatable parts of the output such as the conditions field. Available languages include: ar (Arabic), bg (Bulgarian), cs (Czech), da (Danish), de (German), el (Greek Modern), en (English), es (Spanish), fa (Farsi), fi (Finnish), fr (French), he (Hebrew), hu (Hungarian), it (Italian), ja (Japanese), ko (Korean), nl (Dutch), pl (Polish), pt (Portuguese), ru (Russian), sk (Slovakian), sr (Serbian), sv (Swedish), tr (Turkish), uk (Ukrainian), vi (Vietnamese) and zh (Chinese). In addition

passing request IDs in the raw descriptor IDs. See [How to create or modify language files](#) for more information on how to help add additional languages.

include (optional) – Specifies the sections you would like to include in the result data. This allows you to reduce query cost and latency. Specify this as a comma separated list. For example, `&include=obs,fcst` will include the historical observations and forecast data. The options are:

- **days** – daily data
- **hours** – hourly data
- **minutes** – minutely data (beta). See [Requesting sub-hourly data in the Timeline](#)
- **alerts** – weather alerts
- **current** – current conditions or conditions at requested time.
- **events** – [historical events such as a hail, tornadoes, wind damage and earthquakes](#) (not enabled by default)
- **obs** – historical observations from weather stations
- **remote** – historical observations from remote source such as satellite or radar
- **fcst** – forecast based on 16 day models.
- **stats** – historical statistical normals and daily statistical forecast
- **statsfcst** – use the full statistical forecast information for dates in the future beyond the current model forecast. Permits hourly statistical forecast.

elements (optional) – Specifies the specific weather elements you would like to include in the response as a comma separated list. For example, `&elements=tempmax,tempmin,temp` will request the only the tempmax, tempmin and temp response elements. For the full list of available elements, see the response below.

options (optional) – Specifies additional options on the requests to either indicate the type of data or format of the output. Supported values include:

- **nonnulls** – remove all null values from the JSON response
- **noheaders** – removes the header row from the CSV response

contentType (optional) – indicates the output format for the API. By default the output is formatted in JSON. You can also set `contentType=csv` to retrieve CSV formatted data. Note that CSV format does not support the full JSON output due to the format

Table of Contents

limitations. You must use the **include** parameter to indicate which section you would like to retrieve. CSV include parameters support are days, hours, alerts, events and current.

1. Introduction

2. Creating a weather API request

3. Request Examples

iconSet (optional) Response structure which icons IDs are populated. For more information see [Defining the icon set parameter in the Weather API](#).

4.1. Typical JSON response format

4.2. Response Elements

timezone (optional) – specifies the timezone of the input and result dates and times.

When not specified, all date times are considered local times. If you would like to

specify that all dates are entered as UTC dates and times, use `timezone=Z` parameter.

maxDistance (optional) The maximum distance in meters used to search for local weather stations (By default, 50 miles or approximately 80km (80,467m). This setting is combined with the `maxStations` parameter to find local weather stations.

5. HTTP Response Code and Error Handling

6. Accessing the Timeline Weather API using

the OpenAPI Description

maxStations (optional) The maximum number of weather stations used to calculate a weather record (default 3). Closer weather stations are weighted significantly more heavily than farther stations.

elevationDifference (optional) The maximum elevation difference in meters between the requested location and weather stations. Any weather station that is either lower or higher than more than this setting will be excluded. Default is turned off.

locationNames (optional) provides alternative name for the location requested. This is typically used by users who need to be able to join the API results back to a dataset. For example, you may pass a store database ID in this parameter so that you can populate the weather forecast for that store.

forecastBasisDate (optional, requires historical forecast license) – specifies the date when the weather forecast model was run. For example, if you specify `2021-06-01` , then the data from 2021-06-01 to 2021-06-15 will use the weather forecast produced on June 1st, 2021. For more information see [How to query weather forecasts from the past](#).

forecastBasisDay (optional, requires historical forecast license) – specifies the forecast day for the date1 parameter above. For example, if you specify the start date as

2021-06-05 and a forecastBasisDay value of 5 , then the value for 2021-06-06 will be the 5th day forecast (ie it will be based on the weather forecast produced five days earlier (2021-06-01). You can use this parameter to quickly find the forecast that was predicted for a particular day on multiple days (for example the 5, 3 and 1 day forecast).

1. Introduction
For more information see [How to query weather forecasts from the past](#).

2. Creating a weather API request

3. Request Examples

Degree days parameters (Query Parameters)

4. Weather API Response Structure

degreeDayTempFix – The temperature at which to start the degree day season if no season start and end dates are specified. For example, if the fix temperature is 32F (OC), then the cumulative degree days will reset to zero on the last 32F temperature of the winter. This defines the growing season for growing degree days.

4.1. Typical JSON response format

4.2. Response Elements

4.2.1. Response weather data elements

4.2.2. Location and station elements

degreeDayStartDate – Fixes the start of the degree day season based on fixed dates of the format yyyy-M-d (eg 1990-3-1 for 1st March). Default=not specified.

5. HTTP Response Code and Error Handling

degreeDayTempMaxThreshold – Defines the maximum temperature that is considered for the calculation. Any temperature above this temperature will be set to the maximum threshold temperature. Default value=not set.

7. Questions or need help?

degreeDayTempBase – The degree day base temperature. Default value is set to 10C/50F

degreeDayInverse – Calculate the inverse degree days so colder temperatures contribute more degree days. Used for heating degree days. Default=false.

degreeDayMethod (beta) – The method used for calculating the degree days. Values include average, sine, doublesine, triangle and doubletriangle. Default value is set to average.

Request Examples

Forecast Request Example

The following will retrieve the weather forecast for London, United Kingdom for the next 15 days, starting at midnight at the start of the current day (local time of the requested location).

<https://weather.visualcrossing.com/VisualCrossingWebServices/rest/services/forecast/zipcode/v2.json>

Table of Contents

Forecast Request Example using longitude and latitude

1. Introduction
2. Creating a weather API request
You may also pass the location as a "latitude,longitude" value. For example:

38.9697, -77.385

3. Request Examples
4. Weather API Response Structure

4.1. Typical JSON response format
<https://weather.visualcrossing.com/VisualCrossingWebServices/rest/services/forecast/zipcode/v2.json>

- 4.2. Response Elements

Date Range Request Example

- 4.2.1. Response weather data elements
- 4.2.2. Location and station elements

The following will retrieve the weather data for London, UK from October 1st, 2020 to December 31st, 2020 (inclusive).

5. HTTP Response Code and Error Handling

6. Accessing the Timeline Weather API using the OpenAPI Description
<https://weather.visualcrossing.com/VisualCrossingWebServices/rest/services/forecast/zipcode/v2.json>

7. Questions or need help?
Assuming the current date is November 1st, 2020, the result will include historical observations from October 1st to 31st, then 15 days of weather forecast and finally the remaining days will include the statistical forecast based on processing years of historical observations.

Date Range Request Example using UNIX Time (Epoch Time)

The following shows the same query using UNIX format of seconds since the 1970 UNIX time epoch. Note that these times are seconds in the UTC (GMT/Z) time zone.

<https://weather.visualcrossing.com/VisualCrossingWebServices/rest/services/forecast/zipcode/v2.json>

Specific Time Request Example

The following will retrieve the weather data for London, UK for the 15th December 2020 and will request the current conditions property be populated using the conditions at 13:00 local time (1pm local time).

[https://weather.visualcrossing.com/VisualCrossingWebServices/rest/services/timeline/usa/ny/ny-usa/2020-12-15/2020-12-15?unit=metric&include=moon&include=precipitation&include=sunrise&include=sunset&include=timezone&include=weather&include=wind&include=humidity&include=clouds&include=visibility&include=pressure&include=airquality&include=uv](https://weather.visualcrossing.com/VisualCrossingWebServices/rest/services/timeline/usa/ny/ny-usa/2020-12-15/2020-12-15?unit=metric&include=moon&include=precipitation&include=sunrise&include=sunset&include=timezone&include=weather&include=wind&include=humidity&include=clouds&include=visibility&include=pressure&include=airquality&include=uv&include=moon&include=precipitation&include=sunrise&include=sunset&include=timezone&include=weather&include=wind&include=humidity&include=clouds&include=visibility&include=pressure&include=airquality&include=uv)

Table of Contents

The above example will include the daily and hourly detail for the day of the current conditions (2020-12-15 in this case). This query cost will therefore be 24. If you only need the specific time data, and don't need the hourly detail, you can reduce the query cost by using the `include` parameter:

1. Introduction

2. Creating a weather API request

3. Request Example

4. Weather API Response Structure

<https://weather.visualcrossing.com/VisualCrossingWebServices/rest/services/timeline/usa/ny/ny-usa/2020-12-15/2020-12-15?unit=metric&include=moon&include=precipitation&include=sunrise&include=sunset&include=timezone&include=weather&include=wind&include=humidity&include=clouds&include=visibility&include=pressure&include=airquality&include=uv>

4.2. Response Elements

This query cost will be one.

4.2.1. Response weather data elements

4.2.2. Location and station elements

Dynamic period Request Example

5. HTTP Response Code and Error Handling

Rather than specify a date range, you can also specify a [dynamic period](#). A request

Accessing the Timeline Weather API using

based on a dynamic period will automatically adjust based on the period. In this

the OpenAPI Description

example, we will use the dynamic period value "last30days" to retrieve data for the most

recent 30 days.

7. Questions or need help?

<https://weather.visualcrossing.com/VisualCrossingWebServices/rest/services/timeline/usa/ny/ny-usa/2020-12-15/2020-12-15?unit=metric&include=moon&include=precipitation&include=sunrise&include=sunset&include=timezone&include=weather&include=wind&include=humidity&include=clouds&include=visibility&include=pressure&include=airquality&include=uv>

Other dynamic period values include "today", "yesterday", and "lastyear". For a complete list of options and additional example, please see the [dynamic period](#) article.

Using elements list and options parameter to request only daily with limited elements

By default both daily and hourly data is included in the response along with all the response weather data elements (see below). To reduce the size of the result JSON for lower query cost, reduced network transfer and faster client processing, the `options` and `elements` parameters may be used.

This example requests only the daily data:

<https://weather.visualcrossing.com/VisualCrossingWebServices/rest/services/degree/dayelements>

Table of Contents

This example requests the daily data with only temperature elements:

1. Introduction

2. Creating a weather API request

<https://weather.visualcrossing.com/VisualCrossingWebServices/rest/services/degree/dayelements>

3. Request Examples

Degree day elements list example

4. Weather API Response Structure

The following is a typical JSON response format for the requested location and date range (in this case the last 30 days).

4.2. Response Elements

4.2.1. Response weather data elements

<https://weather.visualcrossing.com/VisualCrossingWebServices/rest/services/degree/dayelements>

4.2.2. Location and station elements
unitGroup=us&key=YOUR_API_KEY&include=days&elements=datetime,tempmax,

For more information on our growing, cooling and heating degree day options, please see our [degree day page](#).

5. API Response Code and Error Handling

6. Accessing the Timeline Weather API using the OpenAPI Description

7. Questions or need help?

Industry elements

The Timeline API can be extended to include advanced agriculture, horticulture and energy elements. These include evapotranspiration, soil temperature & moisture, advanced solar radiation and higher altitude wind speeds and directions.

To include these advanced industry elements, please see our [Agriculture and Horticulture](#) and [Wind and Solar Energy](#) pages.

Weather API Response Structure

Typical JSON response format

All Timeline [Weather API requests](#) return response JSON in the same format. Here is an example for Reston, VA on 11/12/2020:

```
{  
  "latitude" : 38.9697,
```

Table of Contents

1. Introduction	"longitude" : -77.385,
2. Creating a weather API request	"resolvedAddress" : "Reston, VA, United States",
3. Request Examples	"address" : " Reston,VA",
4. Weather API Response Structure	"timezone" : "America/New_York",
4.1. Typical JSON response format	"tzoffset" : -5,
4.2. Response Elements	"description" : "Cooling down with a chance of rain on Friday.",
4.2.1. Response weather data elements	"days" : [{ //array of days of weather data objects
4.2.2. Location and station elements	"datetime" : "2020-11-12",
	"datetimeEpoch" : 1605157200,
	"temp" : 59.6,
	"feelslike" : 59.6,
	"stations" : {
	"hours" : [{ //array of hours of weather data objects
	"datetime" : "01:00:00",
	...
5. HTTP Response Code and Error Handling	},...]
6. Accessing the Timeline Weather API using the OpenAPI Description	"event" : "Flash Flood Watch",
7. Questions or need help?	"description" : "...",
	...
	}
	],
	"currentConditions" : {
	"datetime" : "2020-11-11T22:48:35",
	"datetimeEpoch" : 160515291500,
	"temp" : 67.9,
	...
	}
	}

The response starts with a set of properties describing the location and request including the specific location requested, the resolved address, the latitude and longitude, a text based time zone and a time zone offset in hours. Note that the time zone offset can change within a dataset (based on daylight savings). If this occurs, the a tzoffset property will be found in the day, hour or current conditions weather data object.

The days array is an array of weather data objects for each day requested.

Within each day may be an hours array for the hourly information. Statistical forecast days will not include an hourly array. Typically the hours array will be length 24 but day light savings may cause the array to be 23 or 25 hours long.

Table of Contents

1. Introduction
If the request includes the current date, the current conditions and any weather alerts available for the location will be included.

3. Request Examples

4. Weather API Response Structure

Response Elements

4.1. Typical JSON response format

Response weather data elements

4.2. Response Elements

cloudcover – how much of the sky is covered in cloud ranging from 0-100%

4.2.2. Location and station elements

conditions – textual representation of the weather conditions. See [Weather Data Conditions](#).

5. HTTP Response Code and Error Handling

description – longer text descriptions suitable for displaying in weather displays. The descriptions combine the main features of the weather for the day such as precipitation or amount of cloud cover. Daily descriptions are provided for historical and forecast days.

When the timeline request includes the model forecast period, a seven day outlook description is provided at the root response level.

datetime – ISO 8601 formatted date, time or datetime value indicating the date and time of the weather data in the local time zone of the requested location. See [Dates and Times in the Weather API](#) for more information.

datetimeEpoch – number of seconds since 1st January 1970 in UTC time

tzoffset – the time zone offset in hours. This will only occur in the data object if it is different from the global time zone offset.

dew – dew point temperature

feelslike – what the temperature feels like accounting for heat index or wind chill. Daily values are average values (mean) for the day.

feelslikemax (day only) – maximum feels like temperature at the location.

feelslikemin (day only) – minimum feels like temperature at the location.

hours – array of hourly weather data objects. This is a child of each of the daily weather object when hours are selected.

Table of Contents

humidity – relative humidity in %

1. Introduction

2. Creating a weather API request

icon – a fixed, machine readable summary that can be used to display an icon

3. Request Examples

moonphase – represents the fractional portion through the current moon lunation cycle

ranging from 0 (the new moon) to 0.5 (the full moon) and back to 1 (the next new moon).

See [How to include sunrise, sunset, moon phase, moonrise and moonset data into your API requests](#)

4. Weather API Response Structure

4.1. Typical JSON response format

4.2. Response Elements

4.2.1. Response weather data elements

normal – array of normal weather data values – Each weather data normal is an array of

three values representing, in order, the minimum value over the statistical period, the mean value, and the maximum value over the statistical period.

4.2.2. Location and station elements

5. HTTP Response Code and Error Handling

offsetseconds (hourly only) – time zone offset for this weather data object in seconds –

This value may change for a location based on daylight saving time observation.

6. Accessing the Timeline Weather API using

the OpenAPI Description

precip – the amount of liquid precipitation that fell or is predicted to fall in the period. This includes the liquid-equivalent amount of any frozen precipitation such as snow or ice.

precipremote – radar estimated precipitation amount. See [How to Include Weather Radar Data in Weather Datasets](#) for more information.

precipcover (days only) – the proportion of hours where there was non-zero precipitation

precipprob (forecast only) – the likelihood of measurable precipitation ranging from 0% to 100%

preciptype – an array indicating the type(s) of precipitation expected or that occurred. Possible values include rain, snow, freezingrain and ice.

reflectivity – (minutes only) estimates of the radar-based reflectivity values indicating precipitation intensity. See [How to Include Weather Radar Data in Weather Datasets](#) for more information.

pressure – the sea level atmospheric or barometric pressure in millibars (or hectopascals)

snow – the amount of snow that fell or is predicted to fall

Table of Contents

snowdepth – the depth of snow on the ground

1. Introduction

source – the type of weather data used for this weather object. – Values include historical observation ("obs"), forecast ("fcst"), historical forecast ("histfcst") or statistical forecast ("stats"). Request file types are used in the same day, "comb" is used. Today a combination of historical observations and forecast data.

2. Creating a weather API request

3. Request file types

of historical observations and forecast data.

4. Weather API Response Structure

4.1. Typical JSON response format

stations (historical only) – the weather stations used when collecting an historical observation record

4.2. Response Elements

4.2.1. Response weather data elements

sunrise (day only) – The formatted time of the sunrise (For example "2022-05-

23T05:50:40"). See [How to include sunrise, sunset, moon phase, moonrise and moonset data into your API requests](#)

4.2.2. Location and station elements

5. HTTP Response Code and Error Handling

sunriseEpoch – sunrise time specified as number of seconds since 1st January 1970 in UTC time

6. Accessing the Timeline Weather API using the OpenAPI Description

sunset – The formatted time of the sunset (For example "2022-05-23T20:22:29"). See [How to include sunrise, sunset, moon phase, moonrise and moonset data into your API requests](#)

sunsetEpoch – sunset time specified as number of seconds since 1st January 1970 in UTC time

moonrise (day only, optional) – The formatted time of the moonrise (For example "2022-05-23T02:38:10"). See [How to include sunrise, sunset, moon phase, moonrise and moonset data into your API requests](#)

moonriseEpoch (day only, optional) – moonrise time specified as number of seconds since 1st January 1970 in UTC time

moonset (day only, optional) – The formatted time of the moonset (For example "2022-05-23T13:40:07")

moonsetEpoch (day only, optional) – moonset time specified as number of seconds since 1st January 1970 in UTC time

temp – temperature at the location. Daily values are average values (mean) for the day.

tempmax (day only) – maximum temperature at the location.

Table of Contents

tempmin (day only) – minimum temperature at the location.

1. Introduction

uvindex – a value between 0 and 10 indicating the level of ultra violet (UV) exposure for that hour or day. 10 represents high level of exposure, and 0 represents no exposure. The UV index is based on amount of short wave solar radiation which in turn is a

2. Creating a weather API request

level the cloudiness, type of cloud, time of day, time of year and location altitude. Daily values represent the maximum value of the hourly values.

3. Request Examples

4. Weather API Response Structure

4.1. Typical JSON response format

4.2. Response Elements

uvindex2 (optional, 5 day forecast only) – an alternative UV index element that uses the algorithms and models used by the [US National Weather Service](#). In order to maintain backwards compatibility, this UV index element is deployed as a new, optional element

4.2.1. Response weather data elements

4.2.2. Location and station elements

'uvindex2' and may be requested using the elements parameter.

visibility – distance at which distant objects are visible

5. HTTP Response Code and Error Handling

winddir – direction from which the wind is blowing

6. Accessing the Timeline Weather API using the OpenAPI Description

windgust – instantaneous wind speed at a location – May be empty if it is not significantly higher than the wind speed. Daily values are the maximum hourly value for the day.

windspeed – the sustained wind speed measured as the average windspeed that occurs during the preceding one to two minutes. Daily values are the maximum hourly value for the day.

windspeedmax (day only, optional) – maximum wind speed over the day.

windspeedmean (day only , optional) – average (mean) wind speed over the day.

windspeedmin (day only , optional) – minimum wind speed over the day.

solarradiation – (W/m²) the solar radiation power at the instantaneous moment of the observation (or forecast prediction). See the [full solar radiation data documentation](#) and [Wind and Solar Energy](#) pages .

solarenergy – (MJ /m²) indicates the total energy from the sun that builds up over an hour or day. See the [full solar radiation data documentation](#) and [Wind and Solar Energy](#) pages .

severerisk (forecast only) – a value between 0 and 100 representing the risk of convective storms (e.g. thunderstorms, hail and tornadoes). Severe risk is a scaled measure that combines a variety of other fields such as the convective available potential energy (CAPE) and convective inhibition (CIN), predicted rain and wind. Typically, a severe risk value less than 30 indicates a low risk, between 30 and 70 a moderate risk and above 70 a high risk.

1. Introduction

2. Creating a weather API request

cape3 (forecast only) – convective available potential energy. This is a numbering indicating amount of energy available to produce thunderstorms. A higher values indicates a more unstable atmosphere capable of creating stronger storms. Values lower than 1000 J/kg indicate generally low instability, between 1000-2500 J/kg medium instability and 2500-4000 J/kg high instability. Values greater than 4000 J/kg indicating an extremely unstable atmosphere.

4. Weather API Response Structure

4.1. Typical JSON response format

4.2. Response Elements

4.2.1. Response weather data elements

4.2.2. Location and station elements

cin (forecast only) – convective inhibition. A number representing the level of atmospheric tendency to prevent instability and therefore prevent thunderstorms.

5. HTTP Response Code and Error Handling

degreedays (day only) – optional elements indicating the number of degree days for this date. See [Accessing the Timeline Weather API using the degree days API](#) for more information on degree days. To turn degree days and degree day accumulation, use the elements parameter. For example, elements=datetime,tempmax,tempmin,degreedays,acdegreedays.

6. The Open API Description

7. Questions or need help?

To convert existing Dark Sky API parameters to the Timeline Weather API, see [How to replace the Dark Sky API with the Timeline Weather API](#).

Location and station elements

The following are available in the JSON response type to provide information about the requested location:

queryCost – The record cost of this query. See [what is a record](#) for more information.

latitude,longitude – the latitude and longitude of the requested location. This is provided in decimal degrees.

resolvedAddress – if the requested location was made by address, the address that is found using our internal geocoding engine.

address – the requested location text from the request.

timezone – the timezone of the location. See [Date and Times in the Weather API](#) for more information.

tzoffset – the timezone offset from UTC time for the first record of the data. This may change throughout the dataset if there is a daylight savings change during the requested date range.

Table of Contents

1. Introduction
elevation (optional) – the elevation of the requested location. This is an optional element requested by including the elements parameter: (see [Adding and Removing Elements](#)).

2. Creating a weather API request

3. Request Examples

4. Weather API Response Structure

HTTP Response Code and Error Handling

4.1. Typical JSON response format

4.2. Response Elements

The API communicates error codes through the HTTP response code. In addition, the body of the response will normally include additional error information indicating the cause of the error.

4.2.1. Response weather data elements
4.2.2. Location and station elements

200 OK – a successfully processed request

5. HTTP Response Code and Error Handling

400 BAD_REQUEST – The TimeLine Weather API is using incorrect or an invalid parameter or

6. Accessing the TimeLine Weather API using the OpenAPI Description
combining the OpenAPI Description supplied

7. Questions or need help?

401 UNAUTHORIZED – There is a problem with the API key, account or subscription. May also be returned if a feature is requested for which the account does not have access to.

404 NOT_FOUND – The request cannot be matched to any valid API request endpoint structure.

429 TOO_MANY_REQUESTS – The account has exceeded their assigned limits. See [What is the cause of “Maximum concurrent jobs has been exceeded”, HTTP response 429](#)

500 INTERNAL_SERVER_ERROR – A general error has occurred processing the request.

For general information on debugging API queries, please see: [How to debug problems when running weather API queries in code](#)

Accessing the Timeline Weather API using the OpenAPI Description

The [OpenAPI Initiative](#) standardizes the description of APIs such as the Visual Crossing Weather API. If you are using a tool that supports the OpenAPI standard or Swagger, you can more easily use our API by importing the the specification document below.

- Table of Contents
1. Introduction

• <https://www.visualcrossing.com/weather/specs/visualcrossing-weather-api-openapi.json>

2. Creating a weather API request

• <https://www.visualcrossing.com/weather/specs/visualcrossing-weather-api-openapi.yaml>

3. HTTP Status Examples

4. Weather API Response Structure

• <https://www.visualcrossing.com/weather/specs/visualcrossing-weather-api-swagger.json>

4.1. Typical JSON response format

4.2. Response Elements

4.2.1. Response weather data elements

4.2.2. Location and station elements
- If you have a question or need help, please post on our [actively monitored forum](#) for the fastest replies. You can also contact us via our [support site](#)
5. HTTP Response Code and Error Handling

6. Accessing the Timeline Weather API using the OpenAPI Description

7. Questions or need help?
- Weather
Weather Data
Weather API
Excel Weather
- About
About Us
Support
Documentation
- Profile
Sign up
Account
Usage
- Contact Us
Support & General
Enquiries
Business or Sales
Enquiry
- © 2025 All right reserved [Visual Crossing Corporation](#)
- [Terms of use](#)
[Privacy policy](#)