

# Natural Language Models and Interfaces

BSc Artificial Intelligence

Lecturer: Wilker Aziz

Institute for Logic, Language, and Computation

2019, week 6, lecture b

# Text Classifiers

We have learnt two techniques to design feature-rich models

- ▶ naive Bayes classification
- ▶ logistic regression

# Text Classifiers

We have learnt two techniques to design feature-rich models

- ▶ naive Bayes classification
- ▶ logistic regression

They are both useful to condition on **high-dimensional data**

- ▶ NBC uses Bayes rule and a conditional independence assumption
- ▶ LR uses a linear model and the softmax function

# Pros and Cons

NBC

# Pros and Cons

NBC

- ▶ exact MLE solution
- ▶ strong independence assumption

LR

# Pros and Cons

## NBC

- ▶ exact MLE solution
- ▶ strong independence assumption

## LR

- ▶ flexible
- ▶ no closed-form MLE
- ▶ but gradient ascent converges to global optimum because the log-likelihood function is concave

# Applications

1. Text classifiers: predict a categorical target from high-dimensional input
2. Component in a generative model: parameterise a cpd that conditions on high-dimensional input

# Text Classification

Task	Description
Sentiment analysis	emotion towards a subject
Textual entailment	$x$ is a document and $y$ is a binary label given a two pieces of text, does one entail or contradict the other? $x$ is a pair of documents and $y$ is a binary label



# Text Classification

Task	Description
Sentiment analysis	emotion towards a subject
Textual entailment	$x$ is a document and $y$ is a binary label given a two pieces of text, does one entail or contradict the other? $x$ is a pair of documents and $y$ is a binary label

In both cases, there are extensions to multiple classes

- ▶ Stanford sentiment classification: 5 sentiment levels
- ▶ Stanford natural language inference: 3 logical entailment relations

# Feature functions

A feature function in NBC is a little different from a feature function in LR

- ▶ in NBC only the input  $x$  is available to the feature function
- ▶ in LR both  $x$  and  $y$  are available

Why?

# Feature functions

A feature function in NBC is a little different from a feature function in LR

- ▶ in NBC only the input  $x$  is available to the feature function
- ▶ in LR both  $x$  and  $y$  are available

Why?

- ▶ NBC:

$$P_{Y|X}(y|x) \stackrel{\text{def}}{=} P_{Y|F_1^n}(y|f_1^n = h(x))$$

# Feature functions

A feature function in NBC is a little different from a feature function in LR

- ▶ in NBC only the input  $x$  is available to the feature function
- ▶ in LR both  $x$  and  $y$  are available

Why?

- ▶ NBC:

$$P_{Y|X}(y|x) \stackrel{\text{def}}{=} P_{Y|F_1^n}(y|f_1^n = h(x)) \propto P_Y(y) \prod_{i=1}^n P_{F|Y}(f_i|y)$$

- ▶ LR:

$$P_{Y|X}(y|x) = \frac{\exp(w^\top f(y, x))}{\sum_{y' \in \mathcal{Y}} \exp(w^\top f(y', x))}$$

## Feature functions (cont.)

In NBC a feature is a random variable  
while in LR a feature is just input to a log-linear model

## Example: NBC for sentiment classification

Consider a sentence like

I did not like the acting, but the plot was decent

Example features are:

- ▶ unigrams: I, did, not, like, the, acting, but, the plot, was, decent

## Example: NBC for sentiment classification

Consider a sentence like

I did not like the acting, but the plot was decent

Example features are:

- ▶ unigrams: I, did, not, like, the, acting, but, the plot, was, decent
- ▶ we can apply certain filters: frequency based, stopwords

## Example: NBC for sentiment classification

Consider a sentence like

I did not like the acting, but the plot was decent

Example features are:

- ▶ unigrams: I, did, not, like, the, acting, but, the plot, was, decent
- ▶ we can apply certain filters: frequency based, stopwords
- ▶ we can distinguish some words (e.g. sentiment words): like, decent



## Example: NBC for sentiment classification

Consider a sentence like

I did not like the acting, but the plot was decent

Example features are:

- ▶ unigrams: I, did, not, like, the, acting, but, the plot, was, decent
- ▶ we can apply certain filters: frequency based, stopwords
- ▶ we can distinguish some words (e.g. sentiment words): like, decent
- ▶ we can use external resources (e.g. POS tagger)

## Example: NBC for sentiment classification

Consider a sentence like

I did not like the acting, but the plot was decent

Example features are:

- ▶ unigrams: I, did, not, like, the, acting, but, the plot, was, decent
- ▶ we can apply certain filters: frequency based, stopwords
- ▶ we can distinguish some words (e.g. sentiment words): like, decent
- ▶ we can use external resources (e.g. POS tagger)

We can pre-process the data to account for negation scope

I did not like-NEG the-NEG acting-NEG, but the plot was decent

## Example: LR for sentiment classification

Consider a sentence like

I did not like the acting, but the plot was decent

We can consider the same types of features and more

- ▶ we can pair them with the class: like<sub>+</sub>, like<sub>-</sub>

## Example: LR for sentiment classification

Consider a sentence like

I did not like the acting, but the plot was decent

We can consider the same types of features and more

- ▶ we can pair them with the class: like<sub>+</sub>, like<sub>-</sub>
- ▶ we can use overlapping features: not like, like acting, plot decent

## Example: LR for sentiment classification

Consider a sentence like

I did not like the acting, but the plot was decent

We can consider the same types of features and more

- ▶ we can pair them with the class: like<sub>+</sub>, like<sub>-</sub>
- ▶ we can use overlapping features: not like, like acting, plot decent
- ▶ with good regularisation, we can have far more features

# Evaluation

For binary classification

		<i>gold standard labels</i>		
		gold positive	gold negative	
<i>system output labels</i>	system positive	<b>true positive</b>	<b>false positive</b>	<b>precision</b> = $\frac{tp}{tp+fp}$
	system negative	<b>false negative</b>	<b>true negative</b>	
		<b>recall</b> = $\frac{tp}{tp+fn}$		<b>accuracy</b> = $\frac{tp+tn}{tp+fp+tn+fn}$

**Figure 4.4** Contingency table

- ▶ use a training/development/test split
- ▶ or, preferably, cross-validation

# Component in Generative Model

Recall that we modified the HMM by combining it with a bigram LM?

# Component in Generative Model

Recall that we modified the HMM by combining it with a bigram LM?

For that we modified emission probabilities to be

$$P_{X|X_{\text{prev}}C}(x|x', c)$$



# Component in Generative Model

Recall that we modified the HMM by combining it with a bigram LM?

For that we modified emission probabilities to be

$$P_{X|X_{\text{prev}}C}(x|x', c)$$

For the written assignment, we used **interpolation** to simplify conditioning on high-dimensional outcomes ( $X_{\text{prev}} = x', C = c$ )

# Interpolated CPD

This is a heuristic technique whereby we use a convex combination of simpler CPDs:

$$P_{X|X_{\text{prev}}C}(x|x', c) = \alpha \times P_{X|X_{\text{prev}}}(x|x') + (1 - \alpha) \times P_{X|C}(x|c)$$

# Interpolated CPD

This is a heuristic technique whereby we use a convex combination of simpler CPDs:

$$P_{X|X_{\text{prev}}C}(x|x', c) = \alpha \times P_{X|X_{\text{prev}}}(x|x') + (1 - \alpha) \times P_{X|C}(x|c)$$

- ▶ it requires  $0 < \alpha < 1$  for which no closed-form MLE is available
- ▶ we need to tune  $\alpha$  on held-out data
- ▶ and estimate the simpler cpds independently

# Naive Bayes CPD

We can use the Naive Bayes assumption to model CPDs!

$$P_{X|X_{\text{prev}}C}(x|x',c) =$$

# Naive Bayes CPD

We can use the Naive Bayes assumption to model CPDs!

$$P_{X|X_{\text{prev}}C}(x|x',c) = \frac{P_X(x)P_{X_{\text{prev}}C|x}(x',c|x)}{P_{X_{\text{prev}}C}(x',c)}$$

# Naive Bayes CPD

We can use the Naive Bayes assumption to model CPDs!

$$\begin{aligned} P_{X|X_{\text{prev}}C}(x|x',c) &= \frac{P_X(x)P_{X_{\text{prev}}C|x}(x',c|x)}{P_{X_{\text{prev}}C}(x',c)} \\ &\stackrel{\text{ind}}{=} \frac{P_X(x)P_{X_{\text{prev}}|x}(x'|x)P_{C|X}(c|x)}{P_{X_{\text{prev}}C}(x',c)} \end{aligned}$$

# Naive Bayes CPD

We can use the Naive Bayes assumption to model CPDs!

$$P_{X|X_{\text{prev}}C}(x|x', c) = \frac{P_X(x)P_{X_{\text{prev}}C|x}(x', c|x)}{P_{X_{\text{prev}}C}(x', c)}$$
$$\stackrel{\text{ind}}{=} \frac{P_X(x)P_{X_{\text{prev}}|x}(x'|x)P_{C|X}(c|x)}{P_{X_{\text{prev}}C}(x', c)}$$

Note the denominator needs to be inferred

$$P_{X_{\text{prev}}C}(x', c) = \sum_{y \in \mathcal{Y}} P_{X_{\text{prev}}CX}(x', c, x)$$

# Naive Bayes CPD

We can use the Naive Bayes assumption to model CPDs!

$$\begin{aligned} P_{X|X_{\text{prev}}C}(x|\textcolor{red}{x}', \textcolor{red}{c}) &= \frac{P_X(x) \textcolor{blue}{P}_{X_{\text{prev}}C|x}(\textcolor{blue}{x}', \textcolor{blue}{c}|x)}{P_{X_{\text{prev}}C}(x', c)} \\ &\stackrel{\text{ind}}{=} \frac{P_X(x) \textcolor{green}{P}_{X_{\text{prev}}|x}(\textcolor{green}{x}'|x) P_{C|X}(c|x)}{P_{X_{\text{prev}}C}(x', c)} \end{aligned}$$

Note the denominator needs to be inferred

$$\begin{aligned} P_{X_{\text{prev}}C}(x', c) &= \sum_{y \in \mathcal{Y}} P_{X_{\text{prev}}CX}(x', c, x) \\ &= \sum_{y \in \mathcal{Y}} P_X(x) P_{X_{\text{prev}}|X}(x'|x) P_{C|X}(c|x) \end{aligned}$$



# Naive Bayes CPD

We can use the Naive Bayes assumption to model CPDs!

$$P_{X|X_{\text{prev}}C}(x|x',c) = \frac{P_X(x)P_{X_{\text{prev}}C|x}(x',c|x)}{P_{X_{\text{prev}}C}(x',c)}$$
$$\stackrel{\text{ind}}{=} \frac{P_X(x)P_{X_{\text{prev}}|x}(x'|x)P_{C|X}(c|x)}{P_{X_{\text{prev}}C}(x',c)}$$

Note the denominator needs to be inferred

$$P_{X_{\text{prev}}C}(x',c) = \sum_{y \in \mathcal{Y}} P_{X_{\text{prev}}CX}(x',c,x)$$
$$= \sum_{y \in \mathcal{Y}} P_X(x)P_{X_{\text{prev}}|X}(x'|x)P_{C|X}(c|x)$$

Pro: MLE is exact (no need to tune heuristic coefficients)

Con: denominator must be computed  $O(|\mathcal{Y}|)$

# Logistic CPD

This is a direct application of LR, for example:

$$P_{X|X_{\text{prev}}C}(x|\mathbf{x}', \mathbf{c}; w) = \frac{\exp(w^\top f(x, x', c))}{\mathcal{Z}(x|w)}$$
$$\mathcal{Z}(x|w) = \sum_{y \in \mathcal{Y}} \exp(w^\top f(x, x', c))$$

# Logistic CPD

This is a direct application of LR, for example:

$$P_{X|X_{\text{prev}}C}(x|\mathbf{x}', \mathbf{c}; w) = \frac{\exp(w^\top f(x, x', c))}{\mathcal{Z}(x|w)}$$
$$\mathcal{Z}(x|w) = \sum_{y \in \mathcal{Y}} \exp(w^\top f(x, x', c))$$

Pro: flexible

Con: no closed-form MLE

# Logistic CPD

This is a direct application of LR, for example:

$$P_{X|X_{\text{prev}}C}(x|\mathbf{x}', \mathbf{c}; w) = \frac{\exp(w^\top f(x, x', c))}{\mathcal{Z}(x|w)}$$
$$\mathcal{Z}(x|w) = \sum_{y \in \mathcal{Y}} \exp(w^\top f(x, x', c))$$

Pro: flexible

Con: no closed-form MLE

- ▶ but we can start with some random  $w \in \mathbb{R}^D$  such that  $w_d \sim \mathcal{N}(0, 1)$

# Logistic CPD

This is a direct application of LR, for example:

$$P_{X|X_{\text{prev}}C}(x|\mathbf{x}', \mathbf{c}; w) = \frac{\exp(w^\top f(x, x', c))}{\mathcal{Z}(x|w)}$$
$$\mathcal{Z}(x|w) = \sum_{y \in \mathcal{Y}} \exp(w^\top f(x, x', c))$$

Pro: flexible

Con: no closed-form MLE

- ▶ but we can start with some random  $w \in \mathbb{R}^D$  such that  $w_d \sim \mathcal{N}(0, 1)$
- ▶ compute the log-likelihood function  $\mathcal{L}(w|\mathcal{D}) = \sum_{s=1}^N \log P(y^{(s)}|x^{(s)}; w)$  for some dataset  $\mathcal{D}$

# Logistic CPD

This is a direct application of LR, for example:

$$P_{X|X_{\text{prev}}C}(x|\mathbf{x}', \mathbf{c}; w) = \frac{\exp(w^\top f(x, x', c))}{\mathcal{Z}(x|w)}$$
$$\mathcal{Z}(x|w) = \sum_{y \in \mathcal{Y}} \exp(w^\top f(x, x', c))$$

Pro: flexible

Con: no closed-form MLE

- ▶ but we can start with some random  $w \in \mathbb{R}^D$  such that  $w_d \sim \mathcal{N}(0, 1)$
- ▶ compute the log-likelihood function  $\mathcal{L}(w|\mathcal{D}) = \sum_{s=1}^N \log P(y^{(s)}|x^{(s)}; w)$  for some dataset  $\mathcal{D}$
- ▶ and then  $w + \nabla_w \mathcal{L}(w|\mathcal{D})$  takes us closer to the optimum

# Logistic CPD

This is a direct application of LR, for example:

$$P_{X|X_{\text{prev}}C}(x|\mathbf{x}', \mathbf{c}; w) = \frac{\exp(w^\top f(x, x', c))}{\mathcal{Z}(x|w)}$$
$$\mathcal{Z}(x|w) = \sum_{y \in \mathcal{Y}} \exp(w^\top f(x, x', c))$$

Pro: flexible

Con: no closed-form MLE

- ▶ but we can start with some random  $w \in \mathbb{R}^D$  such that  $w_d \sim \mathcal{N}(0, 1)$
- ▶ compute the log-likelihood function  $\mathcal{L}(w|\mathcal{D}) = \sum_{s=1}^N \log P(y^{(s)}|x^{(s)}; w)$  for some dataset  $\mathcal{D}$
- ▶ and then  $w + \nabla_w \mathcal{L}(w|\mathcal{D})$  takes us closer to the optimum
- ▶ eventually the log-likelihood function stops improving and we have a global optimum

# This is it!

We reached the end of the course

- ▶ as far as exam material goes ;)



# This is it!

We reached the end of the course

- ▶ as far as exam material goes ;)

We can look into exercises (in preparation for final exam)  
and then you can go work on the final lab ;)

# References I