LING575 Summarization

2024.01

#D2
Process a docSet

Overview

- Process XML -> Retrieve corresponding articles from DocSets
- Process Articles: Segment paragraph into sentences, tokenize sentences
- Summarization System Plan Overview

extract.py

- Use XML.etree.ElementTree library to parse XML
- Extract topic ids and corresponding doc id from DocSetA
  - topic.docSetA.id
- Transform doc id into path
  - Case by case according to doc id format and year, but overall it is extracting dir_name, year and file_name, and generate the local path accordingly
  - e.g.
    - APW19990914.0234 -> /corpora/LDC/LDC02T31/apw/1999/19990914_APW_ENG
    - APW_ENG_20050609.0625 -> /corpora/LDC/LDC08T25/data/apw_eng/apw_eng_200506.xml

Demo Video - 1


ling575 [SSH: patas]
EXPLORER
LING575 [SSH: PATAS]
D2
test_output
devtest_paths
process.py
test_0119.py
LING-575-project
D1
D2
Documents
outputs
src
dev_output
dev_process.py
devtest_paths.sh
eval_process.py
evaltest_paths.sh
extract.py
proc_docset.sh
training_paths.sh
training_process.py
D2.md
devtest
eval
train
README.md
process.py 1
GuidedSumm11_test_topics.xml
LING-575-project > D2 > Documents > evaltest > GuidedSumm11_test_topics.xml
<?xml version="1.0" encoding="ISO-8859-1"?>
<!DOCTYPE TACtaskdata [
TAC 2011 Guided Summarization task data definition
Written 2011-06-01 by Karolina Owczarzak <karolina.owczarzak@nist.gov>
<!ELEMENT TACtaskdata (topic+) >
<!ELEMENT topic (title, docsetA, docsetB) >
<!ELEMENT title (#PCDATA) >
<!ELEMENT docsetA (doc+) >
<!ELEMENT docsetB (doc+) >
<!ELEMENT doc EMPTY >
<!ATTLIST TACtaskdata
year CDATA #REQUIRED
track (SUMMARIZATION) #REQUIRED
task (GUIDED) #REQUIRED
dataset (SAMPLE|TEST) #REQUIRED >
<!ATTLIST topic id ID #REQUIRED
category CDATA #REQUIRED >
<!ATTLIST docsetA id ID #REQUIRED >
PROBLEMS 1
OUTPUT
TERMINAL
PORTS
DEBUG CONSOLE
bash - src
(base) [jiayiy9@patas src]$ /nopt/dropbox/23-24/570/envs/570/bin/python ./extract.py $DEV_XML
OUTLINE
TIMELINE
SSH: patas
main*
Ln 1, Col 1
Tab Size: 4
UTF-8
LF
XML

process.py

- Use XML.etree.ElementTree library to parse XML
- If the file is not a standard XML (e.g. /corpora/LDC/LDC02T31/apw/1999/19990914_APW_ENG), then modify the file by adding <DOCSTREAM> tag
  - Find doc id by looking for DOCNO keyword
- If the file is standard XML, find the doc by looking for id keyword.
- Get headline and dateline from HEADLINE and DATELINE keyword.
- Get individual sentence by doc.TEXT.findall("P")
- Use nltk.word_tokenize to tokenize the sentences

Demo Video - 2


ling575 [SSH: patas]
EXPLORER
LING575 [SSH: PATAS]
D2
test_output
devtest_paths
process.py
test_0119.py
LING-575-project
D1
D2
Documents
outputs
src
devtest
dev_process.py
devtest_paths
devtest_paths.sh
eval_process.py
evaltest_paths
evaltest_paths.sh
extract.py
proc_docset.sh
training_paths
training_paths.sh
training_process.py
D2.md
README.md
process.py 1
D2 > process.py > process
import sys
import os
import xml.etree.ElementTree as ET
import nltk
def process(input_directory, output_directory, docID_docsetID_pairs):
files = os.listdir(input_directory)
# Iterate through each file
for file_name in files:
# Create the full path to the file
print(file_name)
#import pdb; pdb.set_trace()
if file_name.endswith('.xml'):
file_path = os.path.join(input_directory, file_name)
else:
continue
with open(file_path, 'r') as file:
xml_data = file.read()
# Parse the XML data
root = ET.fromstring(xml_data)
# Iterate over each DOC element
for doc in root.findall('DOC'):
docID = doc.get("id")
if docID not in docID_docsetID_pairs:
PROBLEMS 1
OUTPUT
TERMINAL
PORTS
DEBUG CONSOLE
python - src
(base) [jiayiy9@patas src]$ /nopt/dropbox/23-24/570/envs/570/bin/python ./dev_process.py $DEV_XML $EVAL_XML $TRAIN_XML $DEV_FILE_PATH dev_output
(base) [jiayiy9@patas src]$ rm -rf dev_output/
(base) [jiayiy9@patas src]$ /nopt/dropbox/23-24/570/envs/570/bin/python ./dev_process.py $DEV_XML $EVAL_XML $TRAIN_XML $DEV_FILE_PATH dev_output
OUTLINE
TIMELINE
SSH: patas
main*
Ln 23, Col 1
Spaces: 4
UTF-8
CRLF
Python
3.6.8 64-bit

Methods we are considering for summarization

- TF-IDF
  - Create a Document-Term Matrix using TF-IDF
  - Score the sentences using TF-IDF score for each term
- LLR
  - Create a Document-Term Matrix using LLR
  - Score the sentences using LLR score for each term
- LSI & LDA topic modelling
  - Latent Semantic Indexing (LSI) and Latent Dirichlet Allocation (LDA)
  - Used to extract topics from a collection of documents, and the topics can be used as feature
  - Can use key terms or phrases associated with dominant topics as content

Methods we are considering for summarization

Method	Pros	Cons
TF-IDF	- Simple and Intuitive - Efficient for Extractive Summarization	- Rely heavily on word overlap - Don't handle synonyms - Sparse representation - Sentence redundancy - Lack of Context Understanding
LLR	- More nuanced analysis for context - Handles Synonyms and Specific Contexts	- Data sensitivity - Not Suitable for Abstractive Summarization involving rephrasing and paraphrasing.
LSI/LDA topic modeling	- Semantic Understanding - Documents can be represented as a mixture of topics	- Require additional techniques to apply those extracted features - Dimensionality Reduction, potentially loss of information - Sensitivity to Hyperparameters