

Exam Code: 640-460

Exam Name: IIUC Implementing Cisco IOS Unified
Communications (IIUC)

Vendor: CISCO

Version: DEMO

Part: A

1: Which type of voice port will allow the gateway to terminate 23 or 30 circuits from the PSTN or a PBX?

- A.FXO
- B.FXS
- C.PRI T1/E1
- D.E&M
- E.BRI


Correct Answers: C

2: In which of the following scenarios would a Cisco switch supply PoE to an IP phone?

- A.In any cases as long as the switch and IP phone are Cisco products.
- B.If the Cisco switch supports prestandard PoE and the IP phone supports 802.3af.
- C.If the Cisco switch and IP phone both support a common PoE method.
- D.Only if both the switch and IP phone use 802.3af PoE.

Correct Answers: C

3: Refer to the exhibit. Which Cisco Unified Communications layer is the call processing layer?



- A.A
- B.B
- C.C
- D.D

Correct Answers: C

4: A customer wants to use a signaling protocol on the voice gateways that require registration with the Cisco Unified Communications Manager. What protocol should be recommended?

- A.SIP
- B.H.323
- C.SRTP
- D.MGCP

Correct Answers: D

5: What is the difference between voice VLAN and native VLAN?

- A.Voice VLAN uses tagged 802.1Q frames whereas native VLAN uses 802.1P frames.
- B.Voice VLAN uses untagged frames whereas native VLAN uses 802.1Q frames.
- C.Voice VLAN uses tagged 802.1Q frames whereas native VLAN uses untagged frames.
- D.Voice VLAN uses untagged frames only when no PCs are connected behind the phones whereas native VLAN always uses untagged frames.

Correct Answers: C

6: Which protocol is used to inform the IP phone of its voice VLAN ID?

- A.Cisco keepalives
- B.Cisco Discovery Protocol
- C.Cisco Spanning Tree Protocol
- D.Cisco VLAN Discovery Protocol

Correct Answers: B

7: Which value does an administrator assign to option 150 for DHCP to operate correctly in a Cisco Unified Communications Manager Express environment?

- A.IP address of the DNS server
- B.IP address of the TFTP server
- C.MAC address of the TFTP server
- D.MAC address of the DHCP server
- E.MAC address of the Cisco Unified Communications Manager Express router
- F.IP address of the PC on which the Cisco Unity Express module is installed

Correct Answers: B

8: Which two are considered endpoints in a Cisco Unified Communications solution? (Choose two.)

- A.gateway
- B.call agent
- C.IP telephone
- D.analog phone
- E.H.323 gatekeeper
- F.Cisco Unified Communications Manager

Correct Answers: A C

9: Which type of delay can lead to jitter in a voice network?

- A.propagation delay
- B.serialization delay
- C.CODEC delay
- D.queuing delay

Correct Answers: D

10: IP phone A places a call to IP phone B. How many RTP streams are required for the call to be successfully completed?

- A.1
- B.2
- C.4
- D.6

Correct Answers: B