

Vendor: IBM

Exam Code: 000-R24

Exam Name: IBM SurePOS 300 Series Models 34x and

E4x Tech Mastery

Version: DEMO

- 1. To minimize the effects of data loss during a power failure, what standard feature is included on all SurePOS 700 Series models?
- A. A special type of VRAM, called Windows RAM or WRAM
- B. An onboard standby power systems (SPSs)
- C. An internal UPS
- D. 128 KB of NVRAM

Answer: D

- 2. What is the first step a technical specialist should take before they begin removal or replacement procedures?
- A. Remove all attached devices and I/O connections from the system unit.
- B. Disconnect the power cord from the external power source.
- C. Switch off the power at the system unit and unplug the power cord.
- D. Make sure they are properly grounded.

Answer: C

- 3. When migrating a DOS application to the SurePOS 720, 740, or 780, which of the following statements is correct?
- A. The DOS LAN driver is the same as on the 4694, and it may be used on the SurePOS 720, 740, or 780.
- B. The four RS-232 ports on the SurePOS 740 and 780 are all legacy standard, and no special considerations must be taken for DOS RS-232 applications.
- C. DOS applications that use COM ports 3 and 4 on the SurePOS 740 or 780 must be capable of supporting a PCI-compliant plug-and-play device that uses the shared interrupt architecture.
- D. PC DOS versions 6.3 and later are formally supported on the SurePOS 720, 740, and 780 platforms.

Answer: C

- 4. Using the UPS available on the SurePOS 700 Series models 721, 741, and 781, backup power for typical POS configurations should last how long during operation (performing transactions)?
- A. Between five and ten minutes
- B. Between ten and twenty minutes
- C. Between twenty and thirty minutes
- D. Between thirty and forty minutes

Answer:A

- 5. Which of the following should be used to remove tape adhesive from the SurePOS 700 Series covers?
- A. Petroleum-based cleaner
- B. Distilled water
- C. Ammonia-based cleaner
- D. Isopropyl alcohol

Answer: D