

Exam Code: JN0-202

Exam Name: Juniper Networks Certified Internet
Associate.m(JNCIA)

Vendor: Juniper Networks

Version: DEMO

Part: A

1: Which command allows real-time monitoring of interface statistics on interface so-0/0/0?

- A.monitor interface so-0/0/0
- B.monitor traffic interface so-0/0/0
- C.monitor statistics so-0/0/0
- D.monitor so-0/0/0

Correct Answers: A

2: What are two reasons to apply an import policy in a BGP peer group? (Choose two.)

- A.to ignore some of the routes the BGP peer is advertising
- B.to add routes to outgoing OSPF advertisements
- C.to set a next-hop self policy towards IBGP peers
- D.to modify the properties of the routes

Correct Answers: A D

3: Which OSPF router will assume the role of the DR when the failure of the DR is detected?

- A.DRother
- B.ABR
- C.BDR
- D.ASBR

Correct Answers: C

4: Which BGP message is sent when an error is detected?

- A.Active
- B.Notification
- C.Update
- D.Keepalive

Correct Answers: B

5: Which command is used to view the IS-IS database?

- A.show OSI database
- B.show isis database
- C.show database
- D.show iso database

Correct Answers: B

6: Which CLI command is used to see the state of OSPF adjacencies?

- A.show ospf state
- B.show protocols ospf
- C.show ospf link-state
- D.show ospf neighbor

Correct Answers: D

7: For which two functions is the Routing Engine responsible? (Choose two.)

- A.packet forwarding
- B.queuing functions
- C.routing protocol control
- D.JUNOS software operation

Correct Answers: C D

8: Which type of routing protocol is RIP?

- A.link-vector
- B.link-state
- C.distance-vector
- D.hybrid

Correct Answers: C

9: In a T-Series, which board comprise the switch fabric?

- A.FPC
- B.PFE
- C.SIB
- D.RE

Correct Answers: C

10: Which command can be used to display information about packets that have been logged with the log firewall filter action?

- A.show log
- B.show log messages
- C.show firewall
- D.show firewall log

Correct Answers: D