

**Exam Code:** 9L0-610

**Exam Name:** Xsan Administration v1.1 Exam

**Vendor:** Apple

**Version:** DEMO

## Part: A

1: To view the WWPNS for an Apple Fibre Channel PCI-X card, use \_\_\_\_\_.

- A.Xsan Admin
- B.Fibre Channel Utility
- C.RAID Utility
- D.cvadmin

**Correct Answers: B**

2: Which application allows you to monitor the status of disks within Xserve RAID LUNs?

- A.Activity Monitor
- B.Disk Utility
- C.RAID Admin
- D.Xsan Admin

**Correct Answers: C**

3: Which statement is implied by the concept called "information lifecycle management"?

- A.All information should be backed up in a weekly cycle.
- B.Disk-to-disk backup should be used for archival information.
- C.Information should be regularly cycled between backup devices.
- D.Storage resources should be allocated according to importance of data.

**Correct Answers: D**

4: Xsan is a \_\_\_\_\_ file system.

- A.local
- B.cluster
- C.network
- D.distributed

**Correct Answers: B**

5: RAID Admin's LUN mapping and masking features allow you to \_\_\_\_\_.

- A.create folders that map data to a specified LUN or LUNs
- B.create LUNs that are available to only one client
- C.create LUNs that consist of a single dedicated drive
- D.add more disks to a LUN without taking the array offline

**Correct Answers: B**

6: Indicate the correct port settings when you configure an Emulex 355 switch for Xsan.

- A.Host machine ports set as "Initiator with Stealth" and storage device ports set as "Target with Stealth."
- B.Host machine ports set as "Target with Stealth" and storage device ports set as "Initiator with Stealth."
- C.Both host machine ports and storage device ports set as "Initiator with Stealth."
- D.Both host machine ports and storage device ports set as "Target with Stealth."

**Correct Answers: A**

7: When naming an Xsan volume, which TWO statements are true? (Choose TWO.)

- A. Any low-ASCII character can be used.
- B. Only letters and numbers can be used.
- C. Only lowercase letters and numbers can be used.
- D. Only uppercase letters and numbers can be used.
- E. Volume names can be up to 16 characters in length.
- F. Volume names can be up to 70 characters in length.
- G. Volume names can be up to 256 characters in length.

**Correct Answers: B F**

8: What is the recommended topology setting for the Apple Fibre Channel PCI-X card?

- A. Automatic
- B. Point-to-point
- C. Arbitrated loop
- D. Switched fabric

**Correct Answers: A**

9: Fibre Channel Arbitrated Loop addresses use only the \_\_\_\_\_ field of Fabric Address Space.

- A. Area
- B. Domain
- C. Loop
- D. Port

**Correct Answers: D**

10: Within a storage pool, Xsan stripes data over \_\_\_\_\_.

- A. LUNs
- B. volumes
- C. disks
- D. affinities

**Correct Answers: A**