

Exam Code: 0B0-410

Exam Name: BEA Certified Support Associate: WebLogic
Server 9/10

Vendor: BEA Systems

Version: DEMO

Part: A

1: What are the three different types of watches provided by the WebLogic 9.x Diagnostic Framework?

- A.MBean, Harvester, Log
- B.Harvester, Log, Instrumentation
- C.Alarm, Notification, Log
- D.Severity, Alarm, Harvester

Correct Answers: B

2: A single JMS server with a queue and a topic is configured for application-related JMS messages on a single WebLogic instance. JMS statistics showed that some of the queue messages are lost and not delivered to the application. Which one of the following would help in tracing each message in the system by tracking the message life cycle events?

- A.Enabling JMS debugging
- B.Enabling queue message logging
- C.Deleting the queue and reconfiguring the application to use topic
- D.Enabling topic message logging

Correct Answers: B

3: It was noticed that a high amount of pending messages backlogged in a JMS destination, to solve the problem the recommendation is to:

- A.Restart the JMS Server for the recovery of pending messages
- B.Tune the JMS Message thresholds for paging pending messages
- C.Purge the messages off the JMS destination from the admin console or with WLST
- D.Use thread dumps and JMS debug flags; establish flow to determine the root cause of the backlog

Correct Answers: D

4: In order to configure the Instrumentation, Harvester, and Watch and Notification components at the server level for the WebLogic Diagnostic Framework, what must you first create?

- A.Application Module.
- B.Diagnostic System Module
- C.Subsystem Diagnostic Module
- D.WebLogic Diagnostic Framework MBean

Correct Answers: B

5: When using WLDF to perform diagnostics tasks with WebLogic Server 9.x, which one of the following is true?

- A.WLDF configuration can only be done on the server-level
- B.WLDF configuration can only be done on the application-level
- C.WLDF configuration can be done both on the server-level and on the application-level
- D.WLDF configuration can only be done on the domain-level

Correct Answers: C

6: Which is NOT a legal value for logging severity threshold?

- A.DEBUG
- B.EMERGENCY
- C.INFO
- D.TRACE

Correct Answers: D

7: A notification is an action that is triggered when a watch rule evaluates to true. What are the four main types of diagnostic notifications used with watches in the WebLogic 9.x Diagnostic Framework?

- A.JMX, JMS, SMTP, SNMP
- B.JMX, RMI, HTTP, HTTPS
- C.HTTP, IIOP, T3, RMI
- D.JMS, JWS, HTTP, JPD

Correct Answers: A

8: RMI allows objects to invoke methods on remote objects using

- A.Interfaces and inner classes
- B.MBeans
- C.Stubs and skeletons
- D.Implementations and extensions

Correct Answers: C

9: While using FORM authentication for a web application, the HTML form can be generated by a JSP, Servlet or an HTML page. The form action must be submitted to

- A.j_security
- B.j_security_check
- C.j_check_security
- D.j_authenticate

Correct Answers: B

10: A developer is creating a servlet class. In the doPost method of a servlet, the method request.getParameter("id") is called. Which statement about the method call is true?

- A.It always throws a RuntimeException
- B.It works only if the user was authenticated
- C.It might return a null string
- D.It does NOT retrieve data that is sent by HTTP POST

Correct Answers: C

11: Which of these methods can be used to register an Object in the JNDI tree?

- A.register()
- B.bind()
- C.attach()

D.unbind()

Correct Answers: B

12: Which of the following about the Ant task wlsrserver is INCORRECT?

A.wlsrserver can be used to start, reboot or shut down server instances

B.wlsrserver can be used to connect to existing server instances

C.wlsrserver can be used to create a multiple server domain configuration

D.wlsrserver can be used to create a single server domain and to connect to the server

Correct Answers: C

13: Which of these methods retrieves an Object from the JNDI tree?

A.retrieve()

B.get()

C.lookup()

D.receive()

Correct Answers: C

14: When configuring the resource adaptor configuration files (ra.xml & weblogic-ra.xml), to use the default value for an optional element

A.You can omit creating the entire ra.xml and weblogic-ra.xml file

B.Specify a blank value for the elements for which you want to use the default values

C.You must specify the default value of the elements

D.None of the above

Correct Answers: B

15: Which of these statements is true about the Two-Phase Commit (2PC) protocol?

A.2PC protocol allows programs to control transactions within a single Resource Manager

B.Phase 1 asks the Resource Manager to commit the changes

C.It is implemented by XA protocol

D.None of the above

Correct Answers: C

16: Consider the following initialization parameter in web.xml

```
<context-param>
```

```
    <param-name>feedback</param-name>
```

```
    <param-value>feedback123@bea.com</param-value>
```

```
</context-param>
```

Which of the following code fragments is the correct way of retrieving this context parameter from within a Servlet?

A.ServletConfig cfg = getServletConfig();

String feedback = cfg.getInitParameter("feedback");

B.ServletContext ctx = getServletContext();

String feedback = ctx.getInitParameter("feedback123@bea.com");

C.ServletContext ctx = getServletContext();

```
String feedback = ctx.getInitParameter("feedback");  
D.JSPContext ctx = getJSPContext();  
String feedback = ctx.getInitParameter("feedback");
```

Correct Answers: C

17: When developing a custom security provider using WebLogic SSPI, one must also generate which of the following?

- A.Security Servlet
- B.Proxy Servlet
- C.Startup class
- D.MBeans

Correct Answers: D

18: Consider the following servlet code. When will this return an existing session? HttpSession session = request.getSession();

- A.In the client's first request
- B.The client request contains a valid session ID as a COOKIE or as a URL parameter
- C.The session has timed out due to no activity
- D.A Servlet has invalidated the session.

Correct Answers: B

19: A JAAS client application must contain which two of the following components? (Choose two)

- A.LoginModule interface implementation
- B.Remotehandler interface implementation
- C.PriviledgedAction interface implementation
- D.AuthorizationAction interface implementation

Correct Answers: A C

20: A JMS connection factory is a lightweight object used to create a connection to JMS destinations. Where is this connection factory stored?

- A.Database
- B.JNDI tree
- C.Flat file
- D.Connection pool

Correct Answers: B