

Theory-Based Interpretability in Deep Knowledge Tracing via Grounded Transformers

Concepcion Labra ¹ , Olga C. Santos ^{2,*} 

¹ Department of Artificial Intelligence, Computer Science School, UNED, 28040 Madrid, Spain; clabra@dia.uned.es

² PhyUM Research Center, Department of Artificial Intelligence, Computer Science School, UNED, 28040 Madrid, Spain; ocsantos@dia.uned.es

* Author to whom correspondence should be addressed.

Abstract

Knowledge Tracing, which estimates how students' knowledge evolves during interactions with educational content, is a cornerstone of Intelligent Tutoring Systems. While deep learning models achieve superior predictive performance in this task, they lack interpretability, a limitation that is particularly critical in educational contexts. We introduce *gTransformer*, a new type of grounded Transformer models bridging deep learning performance with intrinsic interpretability through *Representational Grounding*. It adds theory-based parameters to input interaction sequences and uses attention mechanisms to transform them into latent representations. These are projected into enriched parameters that incorporate historical learning context while preserving semantics. Validation demonstrates: (1) structural encoding around theoretical concepts (probing selectivity $\Delta R^2 > 0.5$); (2) semantic alignment; and (3) functional alignment with quantified confidence. Results show that *gTransformer* achieves predictive performance competitive with state-of-the-art architectures while offering intrinsically interpretable predictions. The trade-off is characterised by a significant AUC gain over traditional theory-based models (+19.9%), with a minimal cost (3.9%) relative to non-interpretable configurations. Critically, *gTransformer* enables context-aware personalisation by differentiating students based on longitudinal learning trajectories rather than immediate responses, capturing patterns that traditional Markovian models cannot represent. This offers a practical path toward AI-driven adaptive instruction that is both accurate and interpretable.

Keywords: deep knowledge tracing; theory-based interpretability; grounded transformers; bayesian knowledge tracing; educational data analysis; personalised learning

1. Introduction

1.1. Problem Statement and Motivation

Knowledge Tracing (KT) [?] is a foundational problem in Intelligent Tutoring Systems and Learning Analytics [?] aimed at estimating the evolution of student knowledge as they interact with a sequence of educational work items. Accurate mastery tracking enables data-driven personalisation, yet current approaches are caught in a dichotomy between interpretable but rigid probabilistic models and high-accuracy but opaque Deep Knowledge Tracing architectures [? ? ?]. While recent efforts have sought to bridge this gap, they generally do not aim for interpretability based on alignment with pedagogical principles [? ? ?]. Consequently, a critical research gap remains regarding

architectures that can maintain the capacity of deep learning while remaining grounded in educational theory. Specifically, there is a need for models that track student mastery through conceptual constructs, such as prior knowledge and learning rates, rather than opaque latent features, addressing the transparency and accountability concerns essential for trust in educational AI [?]. Knowledge Tracing (KT) [?] is a foundational problem in Intelligent Tutoring Systems and Learning Analytics [?]. Formally, it is conceptualized as a supervised sequence-modeling task aimed at estimating the longitudinal evolution of student knowledge based on their historical interaction traces. The input to the system consists of a temporal sequence $\mathcal{S} = \{(q_1, r_1), (q_2, r_2), \dots, (q_{T-1}, r_{T-1})\}$, where each tuple represents a question q_t and the student's binary response $r_t \in \{0, 1\}$, with $r_t = 1$ indicating a correct answer and $r_t = 0$ an incorrect one. The task objective is to predict the output $\hat{r}_t = P(r_t = 1 | q_t, \mathcal{S})$, signifying the probability of a correct response to the current question q_t given the observed history. By monitoring these longitudinal estimations, we can track the dynamic evolution of student knowledge, providing a data-driven foundation for personalized instruction and targeted pedagogical interventions. In an era where educational environments are becoming increasingly digital and personalized, the ability to accurately track and interpret student mastery is a critical requirement for effective, scalable and learner-centred education.

Historically, the development of KT has been characterized by a dichotomy between two distinct paradigms [?]. The first, which predominated in the field for years, is characterized by probabilistic models such as Bayesian Knowledge Tracing (BKT) [?] and Factor Analysis Models based on logistic regression, including Additive Factor Models [?], Performance Factor Analysis [?], and Knowledge Tracing Machines [?]. Factor Analysis Models are theoretically supported by the Item Response Theory (IRT) [?], which has played a large role in educational assessment and measurement. These traditional approaches are intrinsically interpretable: they model learning as a process governed by explicit parameters related to pedagogical, cognitive or psychometric principles. Because the model structure mirrors a theoretical understanding of human learning, educators can inspect these values to validate the model's reasoning and trust its outputs. However, this transparency comes at the cost of representational rigidity; the simplifying assumptions required by these models often limit their predictive power, causing them to struggle with the complex, non-linear and long-range dependencies inherent in real-world student behavior [?].

The second paradigm emerged with the advent of Deep Knowledge Tracing (DKT) [?], which leverages deep learning techniques ranging from initial Recurrent Neural Networks to more recent Transformer architectures [?]. The latter, based on encoder-decoder components and attention mechanisms, are especially relevant as they provide the foundation for current Large Language Models (LLMs). By treating student interaction histories as temporal sequences, Transformer models apply techniques similar to those that characterize LLMs. DKT models have achieved state-of-the-art predictive performance, significantly outperforming classical baselines due to a structural high capacity that allow them to extract latent features from vast amounts of data [?]. However, this substantial gain in predictive performance has come at the cost of model transparency, creating a significant interpretability gap. Deep learning models are notoriously opaque "black boxes", where the internal high-dimensional representations bear no direct correspondence to constructs that are interpretable in terms of human-understandable concepts or established domain knowledge. In a high-stakes domain such as education, where algorithmic decisions influence learning trajectories, grades and opportunities, this lack of transparency raises critical concerns regarding accountability and trust [?].

Extensive research has sought to bridge this gap, with [?] classifying modalities into *post-hoc* and *ante-hoc* categories. While *post-hoc* methods aim to extract explanations from black-box models after training, *ante-hoc* approaches seek to achieve intrinsic interpretability by design, ensuring the model's internal logic is transparent from the outset. Within this latter category, recent models have attempted to achieve intrinsic transparency by integrating attention mechanisms [?] or by incorporating side information such as IRT parameters [?]. These efforts aim to make the decision-making process visible, moving away from pure black-box architectures toward systems whose internal states can be inspected.

However, from the perspective of domain experts such as teachers and pedagogical designers, these solutions frequently fall short. Post-hoc explanations often rely on technical relevance scores or local approximations that remain disconnected from domain knowledge [?] while most current ante-hoc methods do not produce outputs that map directly to human-understandable concepts. As noted in various surveys [?], when deep learning models incorporate domain knowledge, the primary objective is typically the optimization of predictive performance, while interpretability is often overlooked or left as an unaddressed concern.

Consequently, there is a critical need for new approaches that move beyond technical transparency toward true pedagogical interpretability. For a KT system to be confidently adopted in high-stakes educational environments, its estimations must be grounded in trusted and empirically validated principles derived from relevant fields such as pedagogy, cognitive science, and psychometrics. Educators require models that align with their domain knowledge, tracking mastery not through opaque latent features but through concepts explicitly defined by established frameworks, including the prior knowledge, learning rates and knowledge components postulated by traditional approaches such as BKT and Factor Analysis Models.

1.2. Research Contributions

To address the challenge of achieving both high predictive accuracy and pedagogical transparency, this work provides the following key contributions:

- **Grounded Architecture:** We introduce gTransformer, a variant of attention-based Transformers that implements a novel *Representational Grounding* methodology. This approach explicitly anchors the model's latent representations to the concepts of an intrinsically interpretable reference model, bridging the gap between deep learning expressiveness and theoretical alignment.
- **Performance–Interpretability Trade-Off:** We demonstrate that grounded models achieve state-of-the-art predictive performance, providing a significant AUC gain over traditional theory-based models (+19.9%) while incurring a minimal cost (3.9%) relative to non-interpretable configurations.
- **Context-Aware Personalisation:** By leveraging attention mechanisms to encode longitudinal interaction histories into context-aware parameters, gTransformer overcomes the structural rigidity and Markovian limitations of traditional approaches, enabling the differentiation of students based on their unique learning trajectories.
- **Rigorous Validation Protocol:** We establish a triple validation methodology consisting of structural, semantic, and functional alignment to quantify the pedagogical integrity and reliability of the model's internal diagnostic representations.

1.3. Research Questions

Our research is guided by three primary research questions:

- RQ1: **Performance–Interpretability Trade-Off**

Are gTransformer models able to produce interpretable outputs while remaining competitive in terms of predictive performance? What is the trade-off between predictive performance and interpretability?

- **RQ2: Grounded Interpretability**

How can we check that the parameters used to get interpretable outputs are really grounded in theory-based estimations?

- **RQ3: Context-Aware PersonalisationStudent-Centered Personalization**

How can the historical learning context captured by a Transformer-based model enhance student-centred personalisation~~student-centered personalization~~, and how does this compare with capabilities of population-based models like BKT?

To address these questions, we implement a validation approach that quantifies the trade-off between predictive performance and interpretability (RQ1), assesses the pedagogical grounding of internal representations through a triple validation methodology (RQ2), and demonstrates practical applications for achieving context-aware personalisation (RQ3). The evaluation is designed to address each of these questions. First, to validate RQ1, we quantify the *accuracy-interpretability trade-off* across various benchmark datasets, demonstrating that interpretable predictions consistently surpass classical BKT (averaging +19.9% AUC improvement) with a low interpretability cost relative to black-box architectures (averaging -3.9% AUC). To validate *grounded interpretability* (RQ2), we employ a triple validation protocol consisting of: (1) *structural alignment* via diagnostic probing, confirming that Bayesian concepts are the dominant organizing principles in the latent space (with high selectivity $\Delta R^2 > 0.5$); (2) *semantic alignment*, which measures the monotonic consistency between grounded parameters and original theoretical priors to verify pedagogical integrity (Spearman $\rho_{LO} = 0.360$, $\rho_T = 0.544$); and (3) *functional alignment*, quantifying the confidence with which interpretable estimations can substitute for the supervised baseline. Finally, we demonstrate *student-centered personalization* (RQ3) through *context-aware diagnostics*. By clustering students into four distinct learning situations based on their longitudinal prior knowledge and learning rates, we illustrate how gTransformer captures high-granularity context that traditional models fundamentally overlook. Using case study visualizations of learning trajectories, we demonstrate that the model differentiates students even when their immediate response patterns are identical, establishing a robust foundation for individualized instruction that enables educators to move beyond simple outcome prediction toward a deeper understanding of how each student is learning over time. The remainder of this paper is structured as follows. ?? reviews related work and establishes the theoretical foundations; ?? describes the gTransformer architecture, detailing the neuro-symbolic grounding mechanism; ?? presents the experimental setup and validation protocol, followed by a discussion of the empirical results in ?. Finally, ?? provides the concluding remarks and future research directions.

2. Related Work

This section situates gTransformer within the broader landscape of KT research. We begin by tracing the historical evolution of KT models and the emergence of the interpretability-performance dichotomy. We then examine the theoretical foundations of Bayesian Knowledge Tracing (BKT) as our pedagogically grounded reference framework, followed by a review of the transition from recurrent to attention-based Deep Knowledge Tracing (DKT) architectures. Subsequently, we categorise existing efforts to bridge the interpretability gap through post-hoc and ante-hoc methodologies. Finally, we map our approach to Informed Machine Learning, establishing the connection with this paradigm. This section provides a review of research related to gTransformer. We first examine the theoretical foundations and limitations of BKT, which serves as our reference model

for pedagogical grounding. We then trace the evolution of DKT from Recurrent Neural Networks to recent attention-based architectures. Following this, we categorise existing efforts to bridge the interpretability gap in DKT, contrasting post-hoc and ante-hoc methodologies. Finally, our model is mapped to taxonomic dimensions of Informed Machine Learning, establishing the connection with this paradigm.

2.1. Interpretability–Performance Dichotomy

Historically, the development of KT has been characterized by a dichotomy between two distinct paradigms [?]. The first, which predominated in the field for years, is characterized by probabilistic models such as Bayesian Knowledge Tracing (BKT) [?] and Factor Analysis Models based on logistic regression, including Additive Factor Models [?], Performance Factor Analysis [?], and Knowledge Tracing Machines [?]. Factor Analysis Models are theoretically supported by the Item Response Theory (IRT) [?], which has played a large role in educational assessment and measurement. These traditional approaches are intrinsically interpretable: they model learning as a process governed by explicit parameters related to pedagogical, cognitive or psychometric principles. Because the model structure mirrors a theoretical understanding of human learning, educators can inspect these values to validate the model’s reasoning and trust its outputs. However, this transparency comes at the cost of representational rigidity; the simplifying assumptions required by these models often limit their predictive power, causing them to struggle with the complex, non-linear and long-range dependencies inherent in real-world student behavior [?].

The second paradigm emerged with the advent of Deep Knowledge Tracing (DKT) [?], which leverages deep learning techniques ranging from initial Recurrent Neural Networks to more recent Transformer architectures [?]. The latter, based on encoder-decoder components and attention mechanisms, are especially relevant as they provide the foundation for current Large Language Models (LLMs). By treating student interaction histories as temporal sequences, Transformer models apply techniques similar to those that characterize LLMs. DKT models have achieved state-of-the-art predictive performance, significantly outperforming classical baselines due to a structural high capacity that allow them to extract latent features from vast amounts of data [?]. However, this substantial gain in predictive performance has come at the cost of model transparency, creating a significant interpretability gap. Deep learning models are notoriously opaque “black boxes”, where the internal high-dimensional representations bear no direct correspondence to constructs that are interpretable in terms of human-understandable concepts or established domain knowledge. In a high-stakes domain such as education, where algorithmic decisions influence learning trajectories, grades and opportunities, this lack of transparency raises critical concerns regarding accountability and trust [?].

Extensive research has sought to bridge this gap, with [?] classifying modalities into *post-hoc* and *ante-hoc* categories. While *post-hoc* methods aim to extract explanations from black-box models after training, *ante-hoc* approaches seek to achieve intrinsic interpretability by design, ensuring the model’s internal logic is transparent from the outset. Within this latter category, recent models have attempted to achieve intrinsic transparency by integrating attention mechanisms [? ?] or by incorporating side information such as IRT parameters [? ? ?]. These efforts aim to make the decision-making process visible, moving away from pure black-box architectures toward systems whose internal states can be inspected.

However, from the perspective of domain experts such as teachers and pedagogical designers, these solutions frequently fall short. Post-hoc explanations often rely on technical relevance scores or local approximations that remain disconnected from domain

knowledge [?] while most current ante-hoc methods do not produce outputs that map directly to human-understandable concepts. As noted in various surveys [?], when deep learning models incorporate domain knowledge, the primary objective is typically the optimization of predictive performance, while interpretability is often overlooked or left as an unaddressed concern.

Consequently, there is a critical need for new approaches that move beyond technical transparency toward true pedagogical interpretability. For a KT system to be confidently adopted in high-stakes educational environments, its estimations must be grounded in trusted and empirically validated principles derived from relevant fields such as pedagogy, cognitive science, and psychometrics. Educators require models that align with their domain knowledge, tracking mastery not through opaque latent features but through concepts explicitly defined by established frameworks, including the prior knowledge, learning rates and knowledge components postulated by traditional approaches such as BKT and Factor Analysis Models.

2.2. Bayesian Knowledge Tracing

For this study, we selected BKT [?] as our reference theoretical framework. Student action sequences in Intelligent Tutoring Systems can be modeled as Hidden Markov Models, where the probability of a transition depends only on the previous state [?]. BKT models the learning process as a Hidden Markov process governed by four parameters that provide a causal narrative of student learning progress, which is intuitive to educators and aligned with cognitive science principles:

- **prior knowledge**~~Initial Mastery~~: The probability a student knows a concept prior to practice
- **learning rate**~~Learn Rate~~: The probability of transitioning from unlearned to learned states after a practice opportunity
- **guess**~~Guess~~: The probability of a correct response despite a lack of mastery
- **slip**~~Slip~~: The probability of an incorrect response despite mastery

These four parameters enable a recursive estimation of student mastery: the ~~prior knowledge~~*Initial Mastery* provides the starting probabilistic state, which is updated at each interaction using Bayes' theorem to incorporate the observed outcome (moderated by ~~guess~~ and ~~slip~~*Guess and Slip* probabilities) and shifted by the ~~learning rate~~*Learn Rate* to account for knowledge acquisition. This recursive cycle allows BKT to generate a transparent causal explanation of the student's learning progress that is directly interpretable by educators.

But standard BKT suffers from a significant limitation: it typically operates at a population level, estimating a single set of parameters for all students interacting with a given skill. While ~~Individualised~~*Individualized* BKT approaches exist, they are often computationally expensive and struggle with data sparsity [?]. The gTransformer approach offers a new way to address ~~individualisation~~*individualization* by leveraging the capabilities of Transformers to compress student interaction history into a context vector. This allows the model to infer parameter values at the student-level, transforming population-level BKT insights into high-granularity student diagnostics.

2.3. Deep Knowledge Tracing

The application of deep learning to KT was initiated by the DKT model [?], which framed student performance as a sequence ~~modelling~~*modeling* task. While pioneering, DKT was constrained by the inherent limitations of Recurrent Neural Networks (RNNs). These architectures are difficult to train [?] and their sequential nature precludes paral-

lization, a bottleneck that becomes critical at longer sequence lengths where memory constraints limit efficiency.

The introduction of attention-based architectures [?], such as Self-Attentive Knowledge Tracing (SAKT) [?] and Separated Self-Attentive Neural Knowledge Tracing (SAINT) [?], addressed these limitations by enabling parallel processing of interaction histories. This marked a significant shift toward the attention-based Transformer architectures that ~~characterise~~~~characterize~~ modern Large Language Models (LLMs). By replacing recurrent units with multi-head attention, these models capture long-range dependencies more effectively, allowing for a historical learning context-aware representation of a student's entire history. More recently, Attentive Knowledge Tracing (AKT) [?] further refined this approach by incorporating skill difficulty and attention mechanisms that weigh past interactions based on their temporal distance.

Beyond the prominent recurrent and attention-based paradigms, the research community has explored several other architectural directions to capture the multifaceted nature of student learning. Notable categories include Memory-Augmented models that utilize external storage to explicitly track concept mastery, Graph-Based approaches that model the topological relationships between skills, and specialized variations such as Text-Aware or Forgetting-Aware models that incorporate exercise semantics and temporal decay into the tracing process [?]. While these variants exploit diverse dimensions of domain knowledge to augment predictive performance, achieving intrinsic interpretability has generally not been ~~prioritised~~~~prioritized~~ as a primary objective.

2.4. Interpretability in Deep Knowledge Tracing

Interpretability in DKT remains an open challenge despite a variety of attempts, which can be categorised into two primary modalities: *post-hoc* and *ante-hoc*. Post-hoc methods attempt to explain trained black-box models by utilizing either model-specific techniques, such as Layer-Wise Relevance Propagation (LRP) [?], or model-agnostic approaches like Local Interpretable Model-agnostic Explanations (LIME) [?]. However, it has been argued that relying on post-hoc explanations for high-stakes decision-making is fundamentally flawed [?]. For teachers and domain experts, these methods offer limited utility as they produce explanations based on deep learning structures rather than pedagogically sound principles, necessitating significant technical expertise for meaningful interpretation.

The second category, *ante-hoc* methods, pursues intrinsic interpretability through two primary approaches. The first consists of traditional models that rely on transparent structures, such as BKT or Factor Analysis Models (e.g., Additive Factor Models [?], Performance Factor Analysis [?], and Knowledge Tracing Machines [?]). The second encompasses DKT variants that achieve interpretability by incorporating additional modules or ~~utilising~~~~utilizing~~ side information [?]. Among these, attention mechanisms have emerged as the most prominent architectural extensions. They have been integrated into a wide range of models, from the pioneering SAKT [?] to more recent architectures like AKT [?]. However, relying solely on attention weights presents similar practical obstacles to those of post-hoc methods for educational practitioners, as these mechanisms do not provide an explicit interpretation grounded in pedagogically sound principles.

In the integration of side information for ante-hoc interpretability, IRT [?] has served as the most prominent foundation. It estimates the probability of a correct response based on a student's latent ability and the item's difficulty. This theory has been coupled with DKT models such as Deep-IRT [?], which ~~utilises~~~~utilizes~~ dynamic key-value memory networks to capture learners' trajectories and uses inferred abilities and difficulties to predict performance. Similarly, TC-MIRT [?] embeds multidimensional IRT parameters to predict student states. Other relevant models include KIKT [?], which harnesses IRT

to simulate student performance; LANA [?], which adopts an IRT variant for ability clustering; and QIKT [?], which features question-centric representations integrated with an interpretable IRT layer. Beyond IRT, researchers have leveraged diverse principles, such as constructive learning [? ?], learning and forgetting curves [?], finite state automata (FSAs) [?], classical test theory (CTT) [?], and monotonicity constraints [?]. Furthermore, recent research has explored the use of surrogate explainable models and mixup-based loss functions to regularize deep learning predictors, providing a path toward balancing predictive performance with pedagogical transparency [?].

In contrast to the aforementioned models, whose diagnostic utility is often restricted by the specificity and scope of the single underlying theory serving as side information [?], gTransformer offers a more flexible framework. It can be grounded in any established theoretical reference, effectively decoupling the expressiveness of deep learning from the constraints of specific pedagogical models. The viability of this paradigm is further supported by recent developments in neural parameter generation, such as the BKTransformer architecture [?], which enhances the predictive performance of a BKT model utilising attention-based sequence modeling to estimate individualised, temporally-evolving BKT parameters.

2.5. Informed Machine Learning

The integration of domain knowledge into deep learning has been broadly explored through conceptual frameworks such as Theory-Guided Data Science (TGDS) [?], Physics-Informed Machine Learning (PIML) [?], and Informed Machine Learning (IML) [?].

TGDS emerged as a paradigm to address the limitations of purely data-driven “black-box” models, which may produce results inconsistent with established domain knowledge [?]. By explicitly requiring scientific consistency, TGDS integrates theoretical insights into the learning process to ensure that models remain scientifically plausible. This integration is typically achieved via theory-guided learning where domain-specific invariants serve as regularisationregularization terms, or through the design of neural architectures that respect the structural constraints of the problem [? ?]. A prominent implementation of this paradigm is Physics-Informed Neural Networks (PINNs) [? ?], which embed differential equations directly into the loss function, forcing the model to satisfy theoretical constraints while learning from empirical data.

A widely adopted technique to enforce this consistency involves incorporating domain-specific constraints into the loss function as follows [? ?]:

$$\mathcal{L} = \mathcal{L}_{TRN}(Y_{true}, Y_{pred}) + \gamma \mathcal{L}_{THEORY}(Y_{pred}), \quad (1)$$

where $\mathcal{L}_{TRN}$ measures the supervised error between true labels Y_{true} and predicted labels Y_{pred} , while $\mathcal{L}_{THEORY}$ penalisespenalizes violations of theoretical constraints, weighted by the hyperparameter γ .

[?] formalized these efforts into an IML taxonomy, which categorisescategorizes knowledge integration by its source, representation and the stage of the machine learning pipeline where it is incorporated. Knowledge can be represented as algebraic equations, logical rules or probabilistic priors, and integrated at various stages: within the training data, through the design of tailored architectures, or by influencing the model’s final output.

We operationalisedoperationalized these taxonomic dimensions in gTransformer by integrating theoretical priors from an interpretable BKT model into the inputs and employing a multi-objective loss function to anchor the model’s predictions to BKT parameters. However, while most IML approaches focus on using prior knowledge to maximise maximize predictive accuracy [?], gTransformer aims to achieve theory-based interpretability while offering competitive predictive performance, as detailed in ??.

3. The gTransformer Model

This section details the design and implementation of gTransformer, a hybrid architecture that bridges the gap between deep learning expressiveness and theoretical alignment by grounding the Transformer's latent representations in concepts established by a reference model. We begin by mapping its components to the taxonomic dimensions of IML, clarifying how theoretical priors and empirical data are processed using specialized inductive biases and multi-objective [optimisationoptimization](#). We then provide a comprehensive description of the model's architecture, detailing its functional layers: from embeddings enriched with prior knowledge to the core attention-based encoder-decoder engine. We explain the projection mechanism enabling the estimation of [individualisedindividualized](#), pedagogically meaningful parameters, which are fed into an output head implementing BKT logic to produce interpretable predictions. Finally, we detail the loss functions that anchor the model's predictions to BKT parameters.

3.1. Dimensions of Informed Machine Learning in gTransformer

Figure ?? illustrates the information flow through gTransformer, mapped to the taxonomic dimensions of IML as defined by ?].




Figure 1. Dimensions of IML in gTransformer.

Within the context of our architecture, the [operationalisationoperationalization](#) of these dimensions can be explained as follows:

- **Prior Knowledge:** The source of theoretical information comprises simulation results from a reference model, typically expressed as parameter values that represent foundational pedagogical constructs.

- **Training Data:** Empirical student interaction histories are augmented with prior knowledge to train the model.
- **Hypothesis Set:** An attention-based Transformer architecture is employed to provide the inductive biases necessary to lead the model toward desired states.
- **Learning Algorithm:** The model is [optimisedoptimized](#) via a multi-objective loss function formulated to balance the trade-off between predictive performance and pedagogical interpretability.
- **Final Hypothesis:** A set of learned weights that drive latent representations from which parameter values aligned with the reference model can be extracted.
- **Mastery Estimations:** The outputs generated through the grounded parameters serve as inputs to the reference model to produce interpretable mastery estimations.

3.2. Architecture

The gTransformer architecture, illustrated in Figure ??, implements a theory-guided deep learning framework that integrates BKT concepts throughout the processing pipeline. The architecture is [organisedorganized](#) into six functional layers, which are detailed in the following subsections. Specifically, we: (i) begin with input data comprising student interaction sequences along with prior knowledge from the Bayesian reference model (?); (ii) proceed to explain difficulty-aware embeddings that encode skill-specific variations (?); (iii) describe the attention-based encoder-decoder mechanism used to construct [contextualisedcontextualized](#) latent representations (?); (iv) explain how grounded parameters are obtained combining theoretical bases with contextual projections (?); (v) present the output heads intended to generate supervised predictions and interpretable predictions (?); and (vi) conclude with the multi-objective loss function that orchestrates the training process to achieve both predictive performance and theory-based interpretability (?).

3.2.1. Input Components

[The problem of KT can be formally conceptualised as a supervised sequence-modelling task aimed at estimating the longitudinal evolution of student knowledge based on their historical interaction traces. The input to the system consists of a temporal sequence of student interaction sequences enriched with population-level parameters from a pre-fit BKT reference model. Student interactions are represented as temporal sequences of tuples \$\(q_t, c_t, r_t\)\$, where \$q_t\$ denotes the question identifier, \$c_t\$ represents the associated knowledge component, concept or skill, and \$r_t \in \{0, 1\}\$ indicates the binary correctness of the student's response at timestep \$t\$.](#)

[These empirical interaction traces are augmented with theoretical priors extracted from the BKT reference model. For each knowledge component \$c\$, we obtain population-level estimates of the four BKT parameters introduced in ??: prior knowledge \$P\(L_0\)\$, learning rate \$P\(T\)\$, guess probability \$P\(G\)\$, and slip probability \$P\(S\)\$. Only \$P\(L_0\)\$ and \$P\(T\)\$ undergo the grounding process to calculate the interpretable predictions \$\hat{y}_{\text{ref}}\$. The data flow begins with the ingestion of student interaction sequences enriched with population-level parameters from a pre-fit BKT reference model. Student interactions are represented as temporal sequences of tuples \$\(q_t, c_t, r_t\)\$, where \$q_t\$ denotes the question identifier, \$c_t\$ represents the associated knowledge component, concept or skill, and \$r_t \in \{0, 1\}\$ indicates the binary correctness of the student's response at timestep \$t\$. These empirical interaction traces are augmented with theoretical priors extracted from the BKT reference model. For each knowledge component \$c\$, we obtain population-level estimates of the four BKT parameters introduced in ??: Initial Mastery \$P\(L_0\)\$, Learn Rate \$P\(T\)\$, Guess probability \$P\(G\)\$ and Slip probability \$P\(S\)\$. For the sake of simplicity, only \$P\(L_0\)\$ and \$P\(T\)\$ undergo the grounding](#)




Figure 2. Functional layers of the gTransformer architecture. GreyGray denotes standard Transformer elements, blue denotes gTransformer-specific elements.

process while we use directly the values estimated by BKT for the parameters $P(G)$ and $P(S)$ to calculate the interpretable predictions $\hat{y}_{\text{ref}}$.

In contrast the *guess* and *slip* parameters are set to fixed, population-level values estimated by the reference BKT model to prioritise the interpretability of knowledge acquisition over the modelling of performance errors. In established BKT literature, $P(L_0)$ and $P(T)$ are considered the primary parameters reflecting a student's latent state, whereas *guess* and *slip* are often viewed as performance parameters tied to the assessment item properties [?]. By fixing the latter, the model remains focused on the core pedagogical constructs whilst avoiding model degeneracy challenges [?] that arise when all four parameters vary simultaneously.

3.2.2. Embeddings

For question embeddings, we define:

$$x'_t = c_q + u_q \cdot d_c \quad (2)$$

where $c_q \in \mathbb{R}^d$ represents the invariant concept base embedding (encoding the semantic identity of the knowledge component), $u_q \in \mathbb{R}$ is a scalar difficulty parameter specific to question q , and $d_c \in \mathbb{R}^d$ is the concept-specific difficulty variation axis. This formulation allows multiple questions targeting the same concept to share a common semantic core (c_q) while differing in their position along a learned difficulty direction (d_c), with the magnitude of displacement controlled by the per-question difficulty scalar (u_q).

Similarly, for interaction history embeddings (encoding both the question and the student's response), we employ:

$$y'_t = e_{c,r} + u_q \cdot f_{c,r} \quad (3)$$

where $e_{c,r} \in \mathbb{R}^d$ is the interaction base embedding (jointly encoding the concept c and response outcome r), and $f_{c,r} \in \mathbb{R}^d$ is the interaction-specific difficulty variation axis.

These embeddings serve as the primary inputs to the Transformer's attention mechanism, providing multi-dimensional representations that enable attention-driven discovery of relevant ~~behavioural~~ behavioral patterns across the student's learning history.

3.2.3. Attention-Based Encoders-Decoders

The core processing engine of gTransformer is a stacked Transformer architecture composed of n encoder blocks and $2n$ decoder blocks. In our default configuration ($n = 4$), this results in 4 encoder layers and 8 decoder layers, providing a total of 12 sequential attention-driven processing stages. The architecture does not utilise explicit pooling layers (such as MaxPool or AvgPool) but rather relies on the attention mechanism to perform dynamic, context-aware aggregation of information across the temporal sequence. The encoder processes the student's longitudinal interaction history through n sequential self-attention layers, transforming the sequence of interaction embeddings $\{y'_1, y'_2, \dots, y'_{t-1}\}$ into a tensor of ~~contextualised~~ contextualized latent representations. Each encoder block applies multi-head self-attention ($h = 4$ or $h = 8$ depending on the dataset) with masking to prevent information leakage from future timesteps, followed by a position-wise feed-forward network (FFN) with a hidden dimension of $d_{\text{ff}} = 256$. Within each block, we apply residual connections followed by Layer Normalization and Dropout ($p = 0.1$) to ensure numerical stability and prevent over-fitting, following the established Transformer standards [?]. The core processing engine of gTransformer is a stacked Transformer architecture composed of n encoder blocks and $2n$ decoder blocks. The encoder processes the student's longitudinal interaction history through

n -sequential self-attention layers, transforming the sequence of interaction embeddings $\{y'_1, y'_2, \dots, y'_{t-1}\}$ into a tensor of contextualised latent representations $Y_{\text{enc}} \in \mathbb{R}^{(t-1) \times d}$. Each encoder block applies multi-head self-attention with masking to prevent information leakage from future timesteps, followed by feed-forward networks and residual connections with layer normalization, following the standard Transformer architecture [?].

The decoder architecture employs an alternating pattern of $2n$ sequential layers. Odd-numbered decoder layers (layers 1, 3, 5, ..., $2n-1$) perform self-attention over the current question embeddings x'_t using 4 or 8 heads, allowing the model to examine multiple aspects of the current task without incorporating response history. Even-numbered decoder layers (layers 2, 4, 6, ..., $2n$) perform cross-attention between the current question representation and the encoder's output, effectively acting as a knowledge retriever that selectively weights relevant evidence from the student's encoded learning trajectory. The decoder architecture employs an alternating pattern of $2n$ sequential layers. Odd-numbered decoder layers (layers 1, 3, 5, ..., $2n-1$) perform self-attention over the current question embeddings x'_t , allowing the model to examine multiple aspects of the current task without incorporating response history. Even-numbered decoder layers (layers 2, 4, 6, ..., $2n$) perform cross-attention between the current question representation and the encoder's output Y_{enc} , retrieving relevant knowledge from the student's encoded learning trajectory.

The final decoder layer produces an output tensor $d_{\text{out}} \in \mathbb{R}^{t \times d}$, which is concatenated with the question embedding to form the high-dimensional context vector:

$$z_t = [d_{\text{out},t}; x'_t] \in \mathbb{R}^z \quad (4)$$

where the dimensionality of z_t is the combined dimensionality of the decoder output and question embedding space. This context vector serves as a comprehensive encoding of the student's current cognitive state, synthesising synthesizing information from both the observed interaction history and the current task characteristics.

3.2.4. Grounded Parameters

To ensure pedagogical interpretability, gTransformer estimates BKT parameters through an additive composition mechanism operating in logit space. For each knowledge component c , we define theoretical base parameters $\ell_{L_0,c}$ and $\ell_{T,c}$, initialised initialized as the logit-transformed population-level BKT priors:

$$\ell_{L_0,c} = \text{logit}(P(L_0)_c), \quad \ell_{T,c} = \text{logit}(P(T)_c) \quad (5)$$

These bases are implemented as scalar embeddings with Gaussian initialisation initialization centred centered at the theoretical values.

Contextual adjustments are computed via dot products between the latent context vector z_t and learnable semantic axes. For each concept c , we define a knowledge axis $K_c \in \mathbb{R}^z$ and a learning velocity axis $V_c \in \mathbb{R}^z$. The contextual projections, representing the student-specific Knowledge (k_s) and Learning Velocity (v_s), are calculated as:

$$k_{s,t} = z_t \cdot K_c, \quad v_{s,t} = z_t \cdot V_c \quad (6)$$

These dot products project the high-dimensional latent state onto interpretable semantic dimensions, quantifying how much the student's observed behaviour deviates from the population average along the dimensions of prior knowledge and learning rate Initial Mastery and Learn Rate.

The final grounded parameters are obtained through additive composition in logit space, followed by sigmoid activation to ensure valid probability bounds:

$$p_{L_0,t} = \sigma(\ell_{L_0,c} + k_{s,t}), \quad p_{T,t} = \sigma(\ell_{T,c} + v_{s,t}) \quad (7)$$

This design ensures that the model's parameter estimates remain structurally anchored to BKT theory, with the base terms providing pedagogically sound [initialisationinitialization](#), while contextual projections enable [individualisedindividualized](#) adjustments driven by observed student [behaviourbehavior](#).

3.2.5. Output Heads

The gTransformer model generates predictions through various output heads, each serving a distinct functional role in the architecture's dual objectives of predictive accuracy and pedagogical interpretability:

- **Supervised Prediction Head (p_{sup}):** [A multi-layer perceptron \(MLP\) directly maps the high-dimensional context vector \$z_t\$ to a correctness prediction. The context vector \(\$z \in \mathbb{R}^{128}\$ \) is passed through a sequence of three linear layers with neuron sizes of 512, 256, and 1, respectively. Each hidden layer is followed by a ReLU activation function and a dropout layer \(\$p = 0.1\$ \).](#) This head is optimised purely for predictive accuracy via binary cross-entropy loss, leveraging the full expressive capacity of the Transformer's learned representations without theoretical constraints.
- **Interpretable Output Head (p_{ref}):** The grounded BKT parameters ($p_{L_0,t}, p_{T,t}$) are passed through an implementation of BKT logic, which performs a retrospective belief update walk over the student's interaction history. At each timestep, the BKT logic computes the probability of correctness $\hat{y}_{\text{ref},t}$ using the standard BKT update equations with the model's grounded parameters and the fixed population-level [guess and slipGuess and Slip](#) values. These predictions are intrinsically interpretable because they can be directly tracked to established pedagogical constructs, providing a transparent causal explanation that justifies each estimation through the theoretical lens of BKT. This head ensures that the grounded parameters retain their intended semantic meaning by requiring them to produce valid predictions subjected to the reference model's reasoning process.
- **Linear Probe Heads:** Two dedicated linear layers extract BKT parameter estimates directly from the context vector: $\hat{p}_{L_0,t} = \sigma(W_{L_0}z_t)$ and $\hat{p}_{T,t} = \sigma(W_Tz_t)$. Unlike the grounded parameter projections (which use concept-specific semantic axes), these probes are global linear extractors shared across all concepts. They serve to verify that the Transformer's internal representations explicitly encode the targeted pedagogical constructs in a linearly accessible manner.

3.2.6. Multi-Objective Loss

The training objective balances predictive performance with pedagogical grounding through a weighted combination of three loss terms:

$$\mathcal{L}_{\text{total}} = \lambda_{\text{sup}}\mathcal{L}_{\text{sup}} + \lambda_{\text{ref}}\mathcal{L}_{\text{ref}} + \lambda_{\text{probe}}\mathcal{L}_{\text{probe}} \quad (8)$$

The supervised loss $\mathcal{L}_{\text{sup}}$ measures the binary cross-entropy between the MLP's direct predictions $\hat{y}_t$ and the ground truth responses r_t , driving the model to [maximisemaximize](#) predictive accuracy:

$$\mathcal{L}_{\text{sup}} = -\frac{1}{N} \sum_{t=1}^N [r_t \log(\hat{y}_t) + (1 - r_t) \log(1 - \hat{y}_t)] \quad (9)$$

The reference loss $\mathcal{L}_{\text{ref}}$ applies the same binary cross-entropy metric to the BKT logic head's predictions $\hat{y}_{\text{ref},t}$, ensuring that the grounded parameters $(p_{L_0,t}, p_{T,t})$ produce pedagogically meaningful predictions when constrained to operate through BKT's causal inference mechanism:

$$\mathcal{L}_{\text{ref}} = -\frac{1}{N} \sum_{t=1}^N [r_t \log(\hat{y}_{\text{ref},t}) + (1 - r_t) \log(1 - \hat{y}_{\text{ref},t})] \quad (10)$$

The probing loss $\mathcal{L}_{\text{probe}}$ enforces global alignment between the Transformer's latent representations and BKT constructs by [minimising](#) the mean squared error between linear probe predictions and population-level BKT targets:

$$\mathcal{L}_{\text{probe}} = \sum_{k \in \{L_0, T\}} \text{MSE}(\hat{p}_{k,t}, P(k)_c) \quad (11)$$

This loss implements a grounding mechanism that constrains the context vector z_t to align its internal structure such that pedagogical parameters can be extracted via simple linear transformations. By constraining the latent space globally, rather than merely [regularising](#) output parameters locally, the probing loss enables that interpretability is structurally embedded throughout the model's representations.

The default configuration uses weight coefficients $\lambda_{\text{sup}} = 1.0$, $\lambda_{\text{ref}} = 0.5$, and $\lambda_{\text{probe}} = 1.0$, balancing supervised performance with theoretical grounding while [prioritising](#) global latent space alignment through active probing.

4. Experimental Setup

This section details the experimental setup employed to train and evaluate gTransformer relative to various baseline models. It includes a description of the validation methodology, training setup, datasets, and benchmark models selected for comparative evaluation.

4.1. Methodology

4.1.1. [Performance–Interpretability Trade-Off \(RQ1\)](#)

[To quantify the balance between predictive power and transparency, we assess gTransformer using four distinct prediction variants: \(1\) ablated supervised predictions \(\$p_{\text{sup1}}\$ \), representing the model's maximum capacity without grounding; \(2\) grounded supervised predictions \(\$p_{\text{sup2}}\$ \), from the standard supervised output; \(3\) interpretable predictions \(\$p_{\text{ref}}\$ \), derived exclusively from the BKT logic using grounded parameters; and \(4\) population-level BKT predictions \(\$p_{\text{bkt}}\$ \).](#)

[We establish three key metrics to quantify the trade-off:](#)

$$\mathcal{I}_{\text{drop}} = p_{\text{sup1}} - p_{\text{sup2}} \quad (12)$$

$$\mathcal{I}_{\text{cost}} = p_{\text{sup2}} - p_{\text{ref}} \quad (13)$$

$$\mathcal{I}_{\text{gain}} = p_{\text{ref}} - p_{\text{bkt}} \quad (14)$$

[where \$\mathcal{I}_{\text{drop}}\$ \(Interpretability Drop\) measures the impact of theoretical constraints on neural capacity, \$\mathcal{I}_{\text{cost}}\$ \(Interpretability Cost\) quantifies the accuracy reduction when switching to interpretable logic, and \$\mathcal{I}_{\text{gain}}\$ \(Interpretability Gain\) represents the advantage over traditional population-level models.](#)

4.1.2. Grounded Interpretability Validation (RQ2)

To verify that gTransformer's internal states are pedagogically valid, we implement a triple validation methodology based on the following hypotheses:

- **H2.1: Structural Alignment:** Latent representations in the gTransformer model are structurally organised around Bayesian concepts (*prior knowledge*~~*Initial Mastery*~~ $P(L_0)$ and *learning rate*~~*Learn-Rate*~~ $P(T)$) as the dominant organising principle. This is verified using *diagnostic probing* [? ?]. We measure *fidelity* as the quality of the parameter recovery via the coefficient of determination R^2 and Pearson correlation r . To distinguish genuine structural encoding from spurious correlations, *selectivity* is defined as:

$$\Delta R^2 = R^2_{\text{target}} - R^2_{\text{control}} \quad (15)$$

where R^2_{target} represents the probe performance on true BKT targets and R^2_{control} is the performance on a control task with randomly shuffled targets.

- **H2.2: Semantic Alignment:** Grounded parameters must retain their pedagogical semantics. We evaluate the monotonic consistency (Spearman correlation ρ) between the model's grounded parameters and the original theoretical priors to verify pedagogical integrity across datasets.
- **H2.3: Functional Alignment:** Quantifies the confidence with which interpretable, theory-constrained estimations (p_{ref}) can substitute for the black-box supervised baseline (p_{sup2}) without significant performance loss. To quantify this trustworthiness, we define a *composite confidence metric* calculated as a weighted sum of three relevant dimensions:

$$\text{Confidence} = w_1 \cdot C_{\text{calibrated}} + w_2 \cdot C_{\text{directional}} + w_3 \cdot C_{\text{percentile}} \quad (16)$$

where w_1, w_2, w_3 are relative weights. These dimensions include numerical proximity ($C_{\text{calibrated}}$), binary decision agreement ($C_{\text{directional}}$), and a dataset-wide rank of prediction disagreement ($C_{\text{percentile}}$).

4.1.3. Context-Aware Personalisation (RQ3)

To evaluate the model's ability to provide context-aware predictions, we implement an approach that clusters students along two dimensions corresponding to the predicted parameter values: *prior knowledge*~~*Initial Mastery*~~ (p_{L_0}) and *learning rate*~~*Learn-Rate*~~ (p_T). We select students with identical responses to the same sequence of questions but belonging to different clusters (i.e., demonstrating different longitudinal learning patterns). We then illustrate how gTransformer customises predictions based on these diverse learning contexts, whereas traditional BKT models, being fundamentally Markovian, produce identical predictions for the same response sequence regardless of the historical learning context. This approach highlights the non-Markovian patterns and context-aware personalisation that population-level baselines fundamentally cannot represent.

4.2. Training Setup

The gTransformer model was implemented in PyTorch using the pyKT library [?] for standardised data preprocessing, dataset splitting, and baseline model implementation. Training and evaluation followed a standard five-fold cross-validation protocol using an 80/20 train/test split. Predictive performance was measured using Area Under the Curve (AUC), applying the question-level, mean late-fusion protocol as recommended in [?]. Hyperparameter configurations for benchmark models were aligned with the optimised values reported in the official pyKT repository. The specific configurations used for gTransformer are detailed in ?? All experiments were conducted on a machine equipped with 40 CPU core and 8 NVIDIA Tesla V100-SXM2 GPUs with 32 GB HBM2 each.

Hyperparameter	Performance	Trade-off
<i>Ablation Configuration</i>		
Ablation mode	all	none
λ_{sup}	1.0	1.0
λ_{ref}	0	0.5
λ_{probe}	0	1.0
<i>Architecture Configuration</i>		
d_{model}	64	64
n_{blocks} (Encoder / Decoder)	4 / 8	4 / 8
Total attention layers	12	12
d_{ff}	256	256
Attention heads	4	AS2009: 8 others: 4
Output MLP dimensions	[128, 512, 256, 1]	[128, 512, 256, 1]
Activation function	ReLU	ReLU
Normalization	LayerNorm	LayerNorm
<i>Training Configuration</i>		
Learning rate	NIPS34: 3×10^{-4} others: 10^{-4}	10^{-4}
Batch size	64	64
Optimiser	adam	adam
Epochs	200	200
Dropout (p)	0.1	0.1
Weight initialization	Xavier /	
Orthogonal	Xavier /	
Orthogonal	Orthogonal	

Table 1. Hyperparameter configurations for Performance benchmark (??) and Trade-off evaluation (??).

4.3. Datasets

For our analysis, we utilised those datasets for which the *pyKT* library [?] provides standardised preprocessing mechanisms, thereby ensuring a rigorous and consistent treatment of student interactions. From this collection, we excluded those datasets that lack explicit mapping to Knowledge Components (*Statics2011* and *POJ*), as this information is essential for pedagogical interpretability, allowing mastery estimations to be anchored to defined educational concepts. The five datasets selected for this study are described below:

- **ASSISTments 2009 (AS2009):** Collected from the ASSISTments platform during the 2009-2010 school year, this dataset consists of math exercises and has served as the de facto standard benchmark for KT research for the past decade [?].
- **ASSISTments 2015 (AS2015):** A larger release from the same platform, for the 2015 school year, containing the highest number of students among the ASSISTments datasets. It focuses on a specific set of 100 knowledge concepts [?].
- **Algebra 2005 (AL2005):** Released as part of the KDD Cup 2010 EDM Challenge, it contains responses from 13-14 year old students solving Algebra problems [?].
- **Bridge to Algebra 2006 (BDG2006):** Also from the KDD Cup 2010 Challenge, this dataset focuses on the *Bridge to Algebra* tutoring system and includes a high number of total interactions [?].
- **NeurIPS 2020 Education Challenge (NIPS34):** A more recent dataset from the Eedi platform containing student answers to multiple-choice math questions, characterised by subject trees used for concept mapping [?].

The characteristics of the datasets are summarised in Table ??:

Dataset	Sequences (N_s)	Concepts (N_c)	Questions (N_q)	Interactions (N_i)
AS2009	4,217	123	26,688	346,860
AS2015	19,917	100	—	708,631
AL2005	574	112	210,710	809,694
BDG2006	1,146	493	207,856	3,679,199
NIPS34	4,918	57	948	1,382,727

Table 2. Characteristics of the benchmark datasets used to evaluate AUC. N_s , N_c , N_q and N_i denote the total number of sequences (students), knowledge components, questions and student-item interactions, respectively.

4.4. Baseline Models

For the comparative analysis, we selected six models that are among the most frequently mentioned baselines [?]: DKT [?], DKVMN [?], SAKT [?], SAINT [?], AKT [?] and ATKT [?]. These models represent a representative selection of the recurrent (DKT), memory-augmented (DKVMN), adversarial (ATKT), and attention-based (SAKT, SAINT, AKT) paradigms, providing a robust and diverse benchmark for evaluating our model.

5. Results and Discussion

5.1. Performance–Interpretability Trade-off (RQ1)

To evaluate the predictive performance of gTransformer, we utilise the Area Under the Curve (AUC) across the benchmark datasets described in ???. The experimental results are summarised in Table ???.

Model	AS2009	AS2015	AL2005	BDG2006	NIPS34
AKT	0.7825	0.7081	0.8306	0.8208	0.8033
ATKT	0.7715	0.7810	0.7995	0.7889	0.7665
DKT	0.7528	0.7031	0.8149	0.8015	0.7689
DKVMN	0.7440	0.7013	0.8054	0.7983	0.7673
SAKT	0.7263	0.6947	0.7880	0.7740	0.7517
SAINT	0.6921	0.6836	0.7775	0.7781	0.7873
midrule gTransformer	0.7831	0.7078	0.8240	0.8148	0.8006

Table 3. Comparison of predictive performance across various benchmark datasets. The table reports AUC values for gTransformer and baseline models evaluated at the question level, following a mean late-fusion protocol. Values in bold indicate the best-performing model for each dataset.

Compared to baseline models, gTransformer achieves highly competitive performance across all benchmarks. To ensure a fair comparison with these non-interpretable baselines, we evaluate gTransformer in an ablated configuration ($\lambda_{\text{ref}} = 0, \lambda_{\text{probe}} = 0$). This approach establishes the model’s maximum predictive capacity in the absence of theoretical constraints, allowing for a direct assessment against other deep learning architectures. On AS2009, gTransformer achieves an AUC of 0.7831, outperforming all other evaluated models. It ranks second on AL2005, BDG2006 and NIPS34 (surpassed only by AKT), and third on AS2015 (behind ATKT and AKT).

To evaluate the performance trade-off, we compare the results of the ablated configuration (p_{sup1}), the grounded supervised output (p_{sup2}), the interpretable predictions (p_{ref}) and the BKT baseline (p_{bkt}). Binary cross-entropy metrics (p_{bkt}) are omitted for AS2015 because this dataset lacks the question-level identifiers required for evaluation. ?? presents the results for these evaluations, quantifying the Interpretability Drop, Cost, and Gain as defined in ??.

Dataset	p_{sup1}	p_{sup2}	p_{ref}	p_{bkt}	$\mathcal{I}_{\text{drop}}$ (%)	$\mathcal{I}_{\text{cost}}$ (%)	$\mathcal{I}_{\text{gain}}$ (%)
AS2009	0.7831	0.7814	0.7436	0.6097	0.0017 (0.2%)	0.0378 (4.8%)	0.1339 (22.0%)
AS2015	0.7078	0.7070	0.6940	—	0.0008 (0.1%)	0.0130 (1.8%)	—
AL2005	0.8240	0.8237	0.7800	0.7215	0.0003 (0.0%)	0.0437 (5.3%)	0.0585 (8.1%)
BDG2006	0.8148	0.8107	0.7810	0.6756	0.0041 (0.5%)	0.0297 (3.6%)	0.1054 (15.6%)
NIPS34	0.8006	0.7987	0.7666	0.5729	0.0019 (0.2%)	0.0321 (4.0%)	0.1937 (33.8%)
Mean	0.7861	0.7843	0.7530	0.6449	0.0018 (0.2%)	0.0313 (3.9%)	0.1229 (19.9%)

Table 4. AUC–Interpretability trade-offs in gTransformer across datasets. The table shows AUC scores for the predictions of the ablated configuration (p_{sup1}), predictions of the grounded configuration (p_{sup2}), interpretable predictions (p_{ref}) and classical BKT predictions (p_{bkt}). The $\mathcal{I}_{\text{drop}}$ column shows the cost of grounding ($p_{\text{sup1}} - p_{\text{sup2}}$), $\mathcal{I}_{\text{cost}}$ shows the interpretability cost ($p_{\text{sup2}} - p_{\text{ref}}$), while $\mathcal{I}_{\text{gain}}$ shows the interpretability gain ($p_{\text{ref}} - p_{\text{bkt}}$).

The results reveal two insights regarding the accuracy–interpretability trade-off:

- **Low Cost of Interpretability.** This cost can be analysed through two distinct metrics. The Interpretability Drop ($\mathcal{I}_{\text{drop}}$) measures the impact of grounding constraints ($\mathcal{L}_{\text{ref}}$ and $\mathcal{L}_{\text{probe}}$) on the Transformer’s original representational capacity. The results in Table ?? show that this drop is negligible, with an average of only 0.0018 AUC points (0.2%), demonstrating that the model internalises pedagogical theory without sacrificing its expressive power. The Interpretability Cost ($\mathcal{I}_{\text{cost}}$) measures the performance impact of constraining final predictions to the causal logic of the reference model. The results show that the average cost across datasets is 0.0313 AUC points (3.9% reduction), which is highly acceptable given the substantial gains in interpretability.
- **General Interpretability Gain.** Comparing p_{ref} against p_{bkt} provides a measure of the *Interpretability Gain* ($\mathcal{I}_{\text{gain}}$). In all comparable datasets, interpretable gTransformer predictions consistently outperform classical BKT with an average improvement of 0.1229 AUC points (19.9%), showing a general advantage over population-level priors.

In summary, the cost of interpretability is consistently low and highly acceptable for practical educational applications. By accurately recovering student-specific learning parameters, gTransformer bridges the gap between black-box performance and theoretical rigor, offering a superior diagnostic alternative to traditional symbolic approaches without sacrificing performance.

5.2. Grounded Interpretability (RQ2)

For the remainder of this study, we employ AS2009 as our reference dataset. Given its status as a widely used benchmark and its rich interaction data, it provides an ideal testbed for validating structural and semantic alignment, especially considering the high predictive AUC gTransformer achieves on this data.

5.2.1. Structural Alignment via Diagnostic Probing (H2.1)

The H2.1 objective is to demonstrate that grounding constraints actively shape the model’s internal structure, rather than merely correlating with outputs. To verify whether gTransformer’s latent representations genuinely internalise pedagogical concepts, we analyze the quality of the parameter recovery from the final hidden states z_t .

??? present the diagnostic probing results via parity plots, comparing BKT theoretical priors (x-axis) with probe-extracted parameters (y-axis). Each point represents an aggregate of interactions, with its size proportional to the sample density. The high adherence to the diagonal confirms a high degree of linear recoverability, with the obtained values indicating strong structural encoding:

- **prior knowledge $P(L_0)$ Initial Mastery $P(L_0)$** : Achieves fidelity $R^2 = 0.549 \pm 0.064$ with Pearson $r = 0.743 \pm 0.041$, indicating strong linear recoverability. The selectivity $\Delta R^2 = 0.619 \pm 0.061$ exceeds the threshold of 0.5, demonstrating that this is a dominant organising principle in the latent space rather than an incidental pattern. The control task yields a negative $R^2 = -0.069$ (indicating performance worse than a mean-based baseline), confirming that probes cannot recover shuffled targets.
- **Learning Rate $P(T)$** : Shows strong structural encoding with fidelity $R^2 = 0.515 \pm 0.080$ and Pearson $r = 0.721 \pm 0.050$. The selectivity reaches $\Delta R^2 = 0.570 \pm 0.080$, demonstrating robust encoding of learning rate dynamics, with control $R^2 = -0.055$.

Interpretation: The high selectivity (> 0.5) for both parameters validates the H2.1 (Structural Alignment) hypothesis: BKT constructs are preserved through all Transformer layers and remain as primary organising concepts in final representations used for prediction.

5.2.2. Semantic Alignment (H2.2)

Hypothesis H2.2 examines whether grounded parameters retain their pedagogical semantics after processing, ensuring models do not repurpose theoretical constructs for black-box optimisation. Unlike H2.1, which probes latent representations, H2.2 validates monotonic relationship preservation in final projected parameters. We use Spearman's rank correlation (ρ) to measure alignment, as it captures monotonic consistency without assuming linearity ($\rho \geq 0.6$ strong, $0.4 \leq \rho < 0.6$ moderate).

??? present parity plots comparing BKT theoretical priors (x-axis) with grounded parameters (y-axis), where each bubble represents an aggregate of test interactions with size encoding sample density. The patterns reveal that:

- **prior knowledge (P_{L_0})Initial Mastery (P_{L_0})** shows weak alignment ($\rho = 0.360$) with substantial scatter, indicating strong student-specific individualisation. However, MAE = 0.168 validates that refinements remain within pedagogical bounds, indicating that the model neither abandons nor mechanically reproduces theoretical priors.
- **learning rate (P_T)** demonstrates moderate alignment ($\rho = 0.544$). A low MAE = 0.092 confirms the model preserves pedagogical understanding of practice effects while enabling context-aware refinement.

These findings support that grounded parameters maintain meaningful monotonic alignment with theory while capturing individual heterogeneity. The differential alignment reveals that learning ratesLearn Rate preserve more theoretical structure while prior knowledgeInitial Mastery estimates undergo stronger individualisation.

5.2.3. Functional Alignment (H2.3)

For the third hypothesis we compare two prediction paths: interpretable predictions $\hat{y}_{ref}$ generated by feeding enriched parameters (projected from context vectors z_t) through BKT logic, and supervised predictions $\hat{y}_{sup}$ obtained directly from an MLP applied to z_t . While $\hat{y}_{sup}$ uses the full representational capacity of the neural network for maximum predictive accuracy, $\hat{y}_{ref}$ constrains predictions through pedagogically interpretable BKT parameters, enabling causal explanations at the cost of some predictive power. We assess the *confidence* with which the interpretable reference path can functionally replace the supervised path.

In ??, we observe heterogeneous confidence patterns across AS2009 interactions. For the generation of this heatmap, balanced weight values ($w_1 = 0.4, w_2 = 0.3, w_3 = 0.3$) were used to assign equal importance to all criteria while slightly prioritising numerical calibration. Overall, 89.2% of student-skill pairs achieve medium or high confidence, while only 10.8% exhibit low confidence. This indicates that interpretable predictions




Figure 3. Structural Fidelity for *prior knowledge* $P(L_0)$ Initial Mastery $P(L_0)$. Plot showing demonstrating strong linear recoverability ($R^2 = 0.549$, $r = 0.743$, $\Delta R^2 = 0.619$) between BKT theoretical priors and probe-extracted parameters. Each bubble represents a binned aggregate of test interactions, with size encoding sample density. The high adherence to the diagonal and high selectivity ($\Delta R^2 > 0.5$) validate that this is a dominant organising principle in latent representations.




Figure 4. Structural Fidelity for *learning rate* $P(T)$. Plot demonstrating robust linear recoverability ($R^2 = 0.515$, $r = 0.721$, $\Delta R^2 = 0.570$) between BKT theoretical priors and probe-extracted parameters. The high adherence to the diagonal and high selectivity ($\Delta R^2 > 0.5$) confirm that learning rate dynamics are dominantly encoded in latent representations.




Figure 5. Semantic Alignment for *prior knowledge* $P(L_0)$ Initial Mastery $P(L_0)$. Plot showing weak monotonic relationship preservation (Spearman $\rho = 0.360$, MAE = 0.168) between BKT theoretical priors and grounded parameters after neural transformation. Each bubble represents an aggregate of test interactions, with size encoding sample density. The substantial scatter indicates strong student-specific individualisation, with the model prioritising context-aware adaptation over strict adherence to population priors.




Figure 6. Semantic Alignment for *learning rate* $P(T)$. Plot demonstrating moderate monotonic relationship preservation (Spearman $\rho = 0.544$, MAE = 0.092) between BKT theoretical priors and grounded parameters. The clustering around the diagonal across the full P_T range indicates the model preserves pedagogical understanding of practice effects through neural processing while enabling context-aware refinement.

provide actionable diagnostic value with quantified uncertainty, enabling educators to leverage theory-grounded explanations while recognising situations requiring additional validation.




Figure 7. Student Skill confidence heatmap. Green cells indicate high confidence (≥ 0.8) in the interpretable predictions. Yellow shows medium confidence and red indicates low confidence.

5.3. Context-Aware Personalisation (RQ3)

To validate RQ3, we show how gTransformer differentiates students based on their longitudinal learning context (i.e., their sequence of interactions) rather than just response patterns. This capability enables context-aware personalisation beyond what population-based models such as BKT can provide. Classical BKT is fundamentally Markovian: given the same response sequence, it produces identical predictions regardless of the student’s learning history. The gTransformer model, by contrast, uses its high capacity to capture temporal learning dynamics (the individualized parameters extracted from interaction history) to differentiate students even when their observable responses are identical. By synthesising this history into a latent context vector and projecting it onto student-specific parameters (p_{L_0} and p_T), the model identifies unique learning signatures that Markovian transitions fundamentally cannot represent. This allows gTransformer to differentiate students even when their immediate observable responses are identical. The gTransformer model, by contrast, leverages its attention mechanism to capture complex, non-linear dependencies across the entire interaction history.

In order to demonstrate this capability, we perform a cluster analysis on the AS2009 dataset based on the historical parameters p_{L_0} and p_T and then select representative students from each cluster to show how gTransformer can provide customized recommendations.

Students are categorised into four learning situations based on their historical learning parameters. ?? illustrates the distribution of students across the four quadrants:

- **Low prior knowledgeinitial mastery / Low learning ratelearning rate:** Observations for students in this quadrant suggest limited foundational mastery with slow skill acquisition.
- **Low prior knowledgeinitial mastery / High learning ratelearning rate:** Despite initial knowledge gaps, rapid progress indicates responsiveness to instruction.

- **High prior knowledgeinitial mastery / Low learning ratelearning-rate:** Strong foundational mastery but minimal progress may signal disengagement or instructional mismatch.
- **High prior knowledgeinitial mastery / High learning ratelearning-rate:** Consistent mastery and rapid skill development suggest readiness for advanced material.




Figure 8. Clustering of students into four learning situations based on their historical parameters (computed as averages across all previous interactions).

In order to demonstrate the gTransformer’s ability to capture historical learning context and overcome the Markovian limitations characteristic of traditional approaches, we show a comparative analysis of mastery trajectories for students with identical response sequences.

We select representative skills with meaningful sequence lengths (5–30 interactions) and identify students from at least two different learning quadrants who provide the same responses to the same questions in the same order. These trajectories are illustrated in the 4×3 mosaic shown in ??, where each subplot displays different predictions for students from different quadrants despite their identical performance within each skill. The dotted grey BKT lines overlap perfectly, reflecting the Markovian assumption: BKT produces identical probability estimates for all students who provide the same sequence of responses, regardless of their broader learning history. In contrast, the solid coloured gTransformer lines diverge based on the whole learning trajectory, demonstrating that the model attends to historical learning context, i.e., to the full trajectory of previous interactions across all skills, to differentiate students even when their current skill-specific responses are identical. This confirms that gTransformer captures non-Markovian personalisation patterns that classical models fundamentally cannot represent.

These findings validate our hypothesis for RQ3, showing how the historical learning context captured by a Transformer-based model can enhance student-centred personalisation.

5.4. Practical and Social Implications

By providing differentiated diagnostics based on longitudinal interaction histories, the model acknowledges that students are dynamic learners with unique contexts rather than static entities defined by fixed traits, thereby enabling more personalised instructional




Figure 9. Context-aware prediction mosaic showing non-Markovian personalisation. Each panel displays students with identical response sequences (same ground truth bars) but different learning profiles. BKT predictions (dotted grey) overlap due to Markovian constraints, while gTransformer predictions (solid coloured) diverge based on historical parameters (p_{L0} , p_T). Circles represent predictions of correctness, while crosses indicate predicted failures. This demonstrates that gTransformer differentiates students not by what they answered, but by how they learned along their whole learning trajectory.

interventions. For instance, high-momentum learners can be identified for accelerated pacing to maintain engagement, while students whose profiles indicate a need for foundational remediation can receive targeted scaffolding before significant learning gaps emerge.

In general, the balance between accuracy and interpretability provided by our gTransformer model is crucial for promoting transparency and trust. This allows educators to clearly understand the pedagogical rationale behind the model's estimations, even for students with similar response patterns. Thus, our approach offers a practical path toward building AI tools that are not only accurate but also student-centred and pedagogically justifiable.

6. Limitations and Future Research

The Representational Grounding methodology explored in this work is fundamentally domain-independent, which suggests that the resulting pedagogical insights and the accuracy–interpretability trade-off could be generalised to diverse educational contexts. Nonetheless, extending the empirical validation of gTransformer beyond the benchmark datasets utilised in this study to a wider range of domains and subjects represents a valuable research direction to further demonstrate its versatility.

In this initial study, the grounding process was restricted to the two primary knowledge parameters: *prior knowledge* $P(L_0)$ and *learning rate* $P(T)$. Future research could address the impact of incorporating student-specific *guess* and *slip* values to further refine the granularity of context-aware individualisation.

While gTransformer was validated using BKT as the primary reference model, the underlying Representational Grounding approach is inherently extensible. Within the educational domain, future research could investigate the integration of alternative theoretical frameworks, such as Additive Factor Models or Performance Factor Analysis, allowing for the use of diverse pedagogical parameters while leveraging the Transformer architecture's awareness of the historical learning context. Furthermore, the applicability of the gTransformer approach extends beyond Knowledge Tracing. The Representational Grounding framework can be adapted to any scientific field where established theoretical models coexist with high-volume empirical data. By anchoring latent representations to domain-specific concepts, this methodology offers a generalisable path toward bridging deep learning expressiveness with rigorous scientific grounding. Evaluating how different theoretical assumptions influence both the accuracy–interpretability trade-off and the context-awareness of domain-specific predictions across diverse disciplines remains an open and promising avenue for future research.

7. Conclusions

This work introduces gTransformer, a Transformer-based model that bridges the gap between deep learning performance and intrinsic interpretability through Representational Grounding. By anchoring latent representations to semantically meaningful constructs, we demonstrate that competitive predictive accuracy can coexist with theoretical alignment.

Our results validate the approach across three dimensions. First, quantifying the accuracy–interpretability trade-off, we showed that interpretable gTransformer predictions consistently surpass classical BKT with a low interpretability cost relative to black-box architectures (RQ1). Second, we confirmed that gTransformer internalises BKT constructs as its primary organising principle, achieving high structural selectivity and semantic alignment with theoretical priors (RQ2). Finally, we demonstrated that gTransformer enables context-aware personalisation by capturing longitudinal learning patterns that Markovian models inherently overlook, allowing for differ-

entiated diagnostics for students with similar response patterns but different interaction histories (RQ3).

Ultimately, gTransformer provides a practical approach for transforming opaque deep learning predictors into actionable interpretable tools. By grounding high-capacity models in established domain theory, this approach offers a path toward highly accurate, pedagogically justifiable, and context-aware personalisation.~~By grounding high-capacity models in established domain theory, this approach offers a path toward student-centred personalisation that is both highly accurate and pedagogically interpretable.~~

Author Contributions: Conceptualization, C. L.; methodology, C. L. and O. C. S.; software, C. L.; validation, C. L. and O. C. S.; formal analysis, C. L.; investigation, C. L.; resources, C. L. and O. C. S.; data curation, C. L.; writing—original draft preparation, C. L.; writing—review and editing, C. L. and O. C. S.; visualization, C. L.; supervision, O. C. S. All authors have read and agreed to the published version of the manuscript.

Funding: This research received no external funding.

Data Availability Statement: The datasets used in this paper can be downloaded through the links provided in <https://pykt-toolkit.readthedocs.io/en/latest/datasets.html>.

Conflicts of Interest: The authors declare no conflicts of interest.

References

- Corbett, A.T.; Anderson, J.R. Knowledge tracing: Modeling the acquisition of procedural knowledge. *User modeling and user-adapted interaction* **1994**, *4*, 253–278.
- Romero, C.; Ventura, S. Educational data mining and learning analytics: An updated survey. *Wiley Interdisciplinary Reviews: Data Mining and Knowledge Discovery* **2020**, *10*. Cited by: 759; All Open Access, Green Open Access, <https://doi.org/10.1002/widm.1355>.
- Abdelrahman, G.; Wang, Q.; Nunes, B. Knowledge tracing: A survey. *ACM Computing Surveys* **2023**, *55*, 1–37.
- Ines, Šarić-Grgić.; Ani, G.; Angelina, G. Twenty-Five Years of Bayesian knowledge tracing: a systematic review. *User Modeling and User-Adapted Interaction* **2024**, *34*, 1127 – 1173. Cited by: 16, <https://doi.org/10.1007/s11257-023-09389-4>.
- Vaswani, A.; Shazeer, N.; Parmar, N.; Uszkoreit, J.; Jones, L.; Gomez, A.N.; Kaiser, Ł.; Polosukhin, I. Attention is all you need. *Advances in neural information processing systems* **2017**, *30*.
- Bai, Y.; Zhao, J.; Wei, T.; Cai, Q.; He, L. A survey of explainable knowledge tracing. *Applied Intelligence* **2024**, *54*, 6483–6514.
- Rudin, C. Stop explaining black box machine learning models for high stakes decisions and use interpretable models instead. *Nature machine intelligence* **2019**, *1*, 206–215.
- Von Rueden, L.; Mayer, S.; Beckh, K.; Georgiev, B.; Giesselbach, S.; Heese, R.; Kirsch, B.; Pfrommer, J.; Pick, A.; Ramamurthy, R.; et al. Informed Machine Learning – A Taxonomy and Survey of Integrating Knowledge into Learning Systems. *IEEE Transactions on Knowledge and Data Engineering* **2021**, p. 1–1.
- Holmes, W.; Porayska-Pomsta, K.; Holstein, K.; Sutherland, E.; Baker, T.; Shum, S.B.; Santos, O.C.; Rodrigo, M.T.; Cukurova, M.; Bittencourt, I.I.; et al. Ethics of AI in Education: Towards a Community-Wide Framework. *International Journal of Artificial Intelligence in Education* **2022**, *32*, 504 – 526. Cited by: 636; All Open Access, Hybrid Gold Open Access, <https://doi.org/10.1007/s40593-021-00239-1>.
- Cen, H.; Koedinger, K.; Junker, B. Comparing two IRT models for conjunctive skills. In Proceedings of the International conference on intelligent tutoring systems. Springer, 2008, pp. 796–798.
- Pavlik, P.I.; Cen, H.; Koedinger, K.R. Performance factors analysis - A new alternative to knowledge tracing. *Frontiers in Artificial Intelligence and Applications* **2009**, *200*, 531 – 538. Cited by: 410, <https://doi.org/10.3233/978-1-60750-028-5-531>.
- Vie, J.J.; Kashima, H. Knowledge tracing machines: Factorization machines for knowledge tracing. In Proceedings of the Proceedings of the AAAI Conference on Artificial Intelligence, 2019, Vol. 33, pp. 750–757.
- Embretson, S.E.; Reise, S.P. *Item response theory for psychologists*; Psychology Press, 2013.
- Piech, C.; Bassen, J.; Huang, J.; Ganguli, S.; Sahami, M.; Guibas, L.J.; Sohl-Dickstein, J. Deep knowledge tracing. *Advances in neural information processing systems* **2015**, *28*.
- Pandey, S.; Karypis, G. A self-attentive model for knowledge tracing. In Proceedings of the Proceedings of the 12th International Conference on Educational Data Mining (EDM 2019). International Educational Data Mining Society, 2019, pp. 384–389. Cited by: 270.

- Ghosh, A.; Heffernan, N.; Lan, A.S. Context-aware attentive knowledge tracing. In Proceedings of the 26th ACM SIGKDD international conference on knowledge discovery & data mining, 2020, pp. 2330–2339.
- Yeung, C.K. Deep-IRT: Make deep learning based knowledge tracing explainable using item response theory. In Proceedings of the Proceedings of the 12th International Conference on Educational Data Mining (EDM 2019). International Educational Data Mining Society, 2019, pp. 683–686. Cited by: 86.
- Su, Y.; Cheng, Z.; Luo, P.; Wu, J.; Zhang, L.; Liu, Q.; Wang, S. Time-and-concept enhanced deep multidimensional item response theory for interpretable knowledge tracing. *Knowledge-Based Systems* **2021**, *218*, 106819.
- Chen, J.; Liu, Z.; Huang, S.; Liu, Q.; Luo, W. Improving interpretability of deep sequential knowledge tracing models with question-centric cognitive representations. In Proceedings of the Proceedings of the AAAI Conference on Artificial Intelligence, 2023, Vol. 37, pp. 14196–14204.
- Arnau-González, P.; Wu, Y.; Solera-Monforte, S.; Arnau, D.; Arevalillo-Herráez, M. Predicting User Actions in Algebra Intelligent Tutoring Systems with Markov Models. *Lecture Notes in Computer Science* **2025**, *15881 LNAI*, 195 – 202. Cited by: 0, https://doi.org/10.1007/978-3-031-98462-4_25.
- Yudelson, M.V.; Koedinger, K.R.; Gordon, G.J. Individualized bayesian knowledge tracing models. In Proceedings of the International conference on artificial intelligence in education. Springer, 2013, pp. 171–180.
- Pascanu, R.; Mikolov, T.; Bengio, Y. On the difficulty of training recurrent neural networks. In Proceedings of the Proceedings of the 30th International Conference on Machine Learning (ICML 2013). International Machine Learning Society (IMLS), 2013, pp. 2347–2355. Cited by: 1907.
- Choi, Y.; Lee, Y.; Cho, J.; Baek, J.; Kim, B.; Cha, Y.; Shin, D.; Bae, C.; Heo, J. Towards an appropriate query, key, and value computation for knowledge tracing. In Proceedings of the Proceedings of the seventh ACM conference on learning@ scale, 2020, pp. 341–344.
- Bach, S.; Binder, A.; Montavon, G.; Klauschen, F.; Müller, K.R.; Samek, W. On pixel-wise explanations for non-linear classifier decisions by layer-wise relevance propagation. *PloS one* **2015**, *10*, e0130140.
- Ribeiro, M.T.; Singh, S.; Guestrin, C. "Why should I trust you?" Explaining the predictions of any classifier. In Proceedings of the Proceedings of the 22nd ACM SIGKDD international conference on knowledge discovery and data mining, 2016, pp. 1135–1144.
- Gan, W.; Sun, Y.; Sun, Y. Knowledge interaction enhanced knowledge tracing for learner performance prediction. In Proceedings of the 2020 7th International conference on behavioural and social computing (BESC). IEEE, 2020, pp. 1–6.
- Zhou, Y.; Li, X.; Cao, Y.; Zhao, X.; Ye, Q.; Lv, J. LANA: Towards Personalized Deep Knowledge Tracing Through Distinguishable Interactive Sequences. In Proceedings of the Proceedings of the 14th International Conference on Educational Data Mining (EDM 2021). International Educational Data Mining Society, 2021, pp. 602–608. Cited by: 4.
- Liu, S.; Yu, J.; Li, Q.; Liang, R.; Zhang, Y.; Shen, X.; Sun, J. Ability boosted knowledge tracing. *Information Sciences* **2022**, *596*, 567–587.
- Sun, J.; Wei, M.; Feng, J.; Yu, F.; Li, Q.; Zou, R. Progressive knowledge tracing: Modeling learning process from abstract to concrete. *Expert Systems with Applications* **2024**, *238*, 122280.
- Zhang, L. Learning factors knowledge tracing model based on dynamic cognitive diagnosis. *Mathematical Problems in Engineering* **2021**, *2021*, 8777160.
- Zhu, J.; Yu, W.; Zheng, Z.; Huang, C.; Tang, Y.; Fung, G.P.C. Learning from interpretable analysis: Attention-based knowledge tracing. In Proceedings of the International conference on artificial intelligence in education. Springer, 2020, pp. 364–368.
- Lee, U.; Park, Y.; Kim, Y.; Choi, S.; Kim, H. Monacobert: Monotonic attention based convbert for knowledge tracing. In Proceedings of the International Conference on Intelligent Tutoring Systems. Springer, 2024, pp. 107–123.
- Zhang, M.; Zhu, X.; Zhang, C.; Qian, W.; Pan, F.; Zhao, H. Counterfactual Monotonic Knowledge Tracing for Assessing Students' Dynamic Mastery of Knowledge Concepts. In Proceedings of the Proceedings of the 32nd ACM international conference on information and knowledge management, 2023, pp. 3236–3246.
- Labra, C.; Santos, O.C. Exploring cognitive models to augment explainability in Deep Knowledge Tracing. In Proceedings of the Adjunct Proceedings of the 31st ACM Conference on User Modeling, Adaptation and Personalization (UMAP '23 Adjunct), 2023, pp. 220–223. <https://doi.org/10.1145/3563359.3597384>.
- Badrinath, A.; Pardos, Z. Optimizing Bayesian Knowledge Tracing with Neural Network Parameter Generation. *arXiv preprint arXiv:2501.00000* **2025**.
- Karpatne, A.; Atluri, G.; Faghmous, J.; Steinbach, M.; Banerjee, A.; Ganguly, A.; Shekhar, S.; Samatova, N.; Kumar, V. Theory-guided Data Science: A New Paradigm for Scientific Discovery from Data. *IEEE Transactions on Knowledge and Data Engineering* **2017**, *29*, 2318–2331.
- Karniadakis, G.E.; Kevrekidis, I.G.; Lu, L.; Perdikaris, P.; Wang, S.; Yang, L. Physics-informed machine learning. *Nature Reviews Physics* **2021**, *3*, 422–440.
- Jia, X.; Willard, J.; Karpatne, A.; Read, J.S.; Zwart, J.A.; Steinbach, M.; Kumar, V. Physics-guided machine learning for scientific discovery: An application in simulating lake temperature profiles. *ACM/IMS Transactions on Data Science* **2021**, *2*, 1–26.

- . Raissi, M.; Perdikaris, P.; Karniadakis, G.E. Physics-informed neural networks: A deep learning framework for solving forward and inverse problems involving nonlinear partial differential equations. *Journal of Computational Physics* **2019**, *378*, 686–707. 993
- . Willard, J.; Jia, X.; Xu, S.; Steinbach, M.; Kumar, V. Integrating scientific knowledge with machine learning for engineering and environmental systems. *ACM Computing Surveys* **2022**, *55*, 1–37. 994
- . Baker, R.S.d.; Corbett, A.T.; Aleven, V. More accurate student modeling through contextual estimation of slip and guess probabilities in bayesian knowledge tracing. In Proceedings of the International conference on intelligent tutoring systems. Springer, 2008, pp. 406–415. 995
- . Hewitt, J.; Liang, P. Designing and Interpreting Probes with Control Tasks. In Proceedings of the Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP); Inui, K.; Jiang, J.; Ng, V.; Wan, X., Eds., Hong Kong, China, 2019; pp. 2733–2743. 996
- . Belinkov, Y. Probing classifiers: Promises, shortcomings, and advances. *Computational Linguistics* **2022**, *48*, 207–219. 997
- . Liu, Z.; Liu, Q.; Chen, J.; Huang, S.; Tang, J.; Luo, W. pyKT: a python library to benchmark deep learning based knowledge tracing models. *Advances in Neural Information Processing Systems* **2022**, *35*, 18542–18555. 998
- . Feng, M.; Heffernan, N.; Koedinger, K. Addressing the assessment challenge with an online system that tutors as it assesses. *User modeling and user-adapted interaction* **2009**, *19*, 243–266. 999
- . Stamper, J.; Niculescu-Mizil, A.; Ritter, S.; Gordon, G.; Koedinger, K. Algebra I 2005-2006 and bridge to algebra 2006-2007. *Development data sets from KDD Cup* **2010**. 1000
- . Wang, Z.; Lamb, A.; Saveliev, E.; Cameron, P.; Zaykov, Y.; Hernández-Lobato, J.M.; Turner, R.E.; Baraniuk, R.G.; Barton, C.; Jones, S.P.; et al. Results and Insights from Diagnostic Questions: The NeurIPS 2020 Education Challenge. In Proceedings of the Proceedings of Machine Learning Research. ML Research Press, 2020, Vol. 133, pp. 191–205. Cited by: 16. 1001
- . Zhang, J.; Shi, X.; King, I.; Yeung, D.Y. Dynamic key-value memory networks for knowledge tracing. In Proceedings of the Proceedings of the 26th international conference on World Wide Web, 2017, pp. 765–774. 1002
- . Pandey, S.; Karypis, G. A self-attentive model for knowledge tracing. *arXiv preprint arXiv:1907.06837* **2019**. 1003
- . Guo, X.; Huang, Z.; Zhou, T.; Lang, L.; et al. Enhancing Knowledge Tracing via Adversarial Training. In Proceedings of the Proceedings of the 27th ACM SIGKDD Conference on Knowledge Discovery & Data Mining, 2021. 1004

Disclaimer/Publisher’s Note: The statements, opinions and data contained in all publications are solely those of the individual author(s) and contributor(s) and not of MDPI and/or the editor(s). MDPI and/or the editor(s) disclaim responsibility for any injury to people or property resulting from any ideas, methods, instructions or products referred to in the content. 1005