

Outline

- 1 Introduction
- 2 Analysis of the sample and hold
- 3 Fourier transform
- 4 Spectrum of a sampled signal
 - Aliasing
 - Sampling theorem
 - Hidden oscillations
- 5 Data extrapolation (reconstruction)
- 6 Block-diagram analysis of sampled-data systems
 - General Approach
 - Examples

Shannon-Nyquist sampling theorem

If all content above the half-sampling frequency is removed, no aliasing is introduced by sampling. Also the signal spectrum is not distorted, even though it is repeated endlessly, centered at $n2\pi/T_s$.

This critical frequency, π/T_s , is called the **Nyquist frequency**. Band-limited signals that have no components above the Nyquist frequency are represented unambiguously by their samples.

This is the **sampling theorem**: One can recover a signal from its samples if the sampling frequency ($\omega_s = 2\pi/T_s$) is at least twice the highest frequency (π/T) in the signal. This maximum frequency is also called the **bandwidth** B.

Shannon-Nyquist sampling theorem

The signal can be fully reconstructed if there are no overlaps in the frequency domain. If the sampling frequency is at least twice the bandwidth B , then the signal can be reconstructed without a problem (no overlap). (fig. a)
If the sampling frequency is too low then information will be lost (overlap). (fig. b)

Sampling frequency $f_s \geq 2B$

