Generation and cost report

Complete 70-segment register with generated filenames, selected edit filenames and retry outcomes.

70	82	77	5
planned segments	API requests	returned videos	failed requests

HK$2,897.13

Estimated total Seedance API cost
US$371.43 converted at the explicit reporting assumption of US$1 = HK$7.80.

Model - every request	Seedance 2.5 / dreamina-seedance-2-5-260628
Resolution / frame format	1080p / 1920 x 1080 / 16:9 / 24 fps. All 77 returned videos match.
Planned duration	16 scenes; 70 segments; 600 seconds (10:00). Per-request clips range from 4 to 19 seconds.
Request totals	60 segments used 1 request; 8 used 2; 2 used 3. All attempts requested 684 seconds in total.
Successful request duration	650 seconds, including discarded takes. Raw files can contain a few extra frames; final cut is exactly 600 seconds.
Usage / price basis	31,745,925 completion tokens x US$11.70 per million = US$371.4273225.

Final movie filename dog-20261015-1080p.mp4

`C:/Users/Admin 3/Downloads/codex-movie/movies/dog-20261015/exports/dog-20261015-1080p.mp4`

Cost scope: this new movie only, including discarded successful retakes. Previously created dog-20261014 assets/audio are reused; their historical production costs are not included. Local edits and assembly add no Seedance calls. No account invoice, tax or card FX charge has been verified.

FX context: HKMA describes a HK$7.75-7.85 per US dollar linked-rate band. The 7.80 used here is a reporting assumption, not a spot or settlement quote. HKMA reference.

Segment register | 01-18

S = returned video; F = failed request with no video file. History is chronological. Costs include all takes for the segment.

Files below are inside **chapters/<segment ID>/takes/** under the project folder. The selected file may be a local edit of a returned video.

#	Segment	Sec / try	API tries	Video files	History	Generated video filename(s)	Selected source / local-edit filename	Est. HK$
1	s01_c01	9	1	1	S	take_01.mp4	take_01.mp4	40.10
2	s01_c02	10	1	1	S	take_01.mp4	take_01.mp4	44.54
3	s01_c03	7	1	1	S	take_01.mp4	take_01.mp4	31.23
4	s01_c04	11	1	1	S	take_01.mp4	take_01.mp4	48.97
5	s01_c05	11	1	1	S	take_01.mp4	take_01.mp4	48.97
6	s02_c01	8	2	2	SS	take_01.mp4 take_02.mp4	take_02.mp4	71.33
7	s02_c02	7	1	1	S	take_01.mp4	take_01.mp4	31.23
8	s02_c03	10	1	1	S	take_01.mp4	take_01.mp4	44.54
9	s02_c04	5	3	1	FFS	take_03.mp4	take_03.mp4	22.36
10	s03_c01	11	2	2	SS	take_01.mp4 take_02.mp4	take_02.mp4	97.94
11	s03_c02	5	2	2	SS	take_01.mp4 take_02.mp4	take_02.mp4	44.72
12	s03_c03	6	1	1	S	take_01.mp4	take_01.mp4	26.80
13	s03_c04	6	1	1	S	take_01.mp4	take_01.mp4	26.80
14	s04_c01	7	1	1	S	take_01.mp4	take_01.mp4	31.23
15	s04_c02	7	1	1	S	take_01.mp4	take_01.mp4	31.23
16	s04_c03	6	2	2	SS	take_01.mp4 take_02.mp4	take_02.mp4	53.59
17	s04_c04	10	1	1	S	take_01.mp4	take_01.mp4	44.54
18	s04_c05	8	1	1	S	take_01.mp4	take_01.mp4	35.67

Project folder: C:/Users/Admin 3/Downloads/codex-movie/movies/dog-20261015/

Example: s02_c04 + take_03.mp4 resolves to chapters/s02_c04/takes/take_03.mp4. Failed requests have no invented filename. Totals use unrounded values; rounding the 70 rows independently creates a HK$0.04 difference.

Segment register | 19-36

S = returned video; F = failed request with no video file. History is chronological. Costs include all takes for the segment.

Files below are inside **chapters/<segment ID>/takes/** under the project folder. The selected file may be a local edit of a returned video.

#	Segment	Sec / try	API tries	Video files	History	Generated video filename(s)	Selected source / local-edit filename	Est. HK$
19	s04_c06	4	2	2	SS	take_01.mp4 take_02.mp4	take_02.mp4	35.85
20	s05_c01	8	1	1	S	take_01.mp4	take_01.mp4	35.67
21	s05_c02	9	1	1	S	take_01.mp4	take_01.mp4	40.10
22	s05_c03	8	1	1	S	take_01.mp4	take_01.mp4	35.67
23	s06_c01	10	1	1	S	take_01.mp4	take_01.mp4	44.54
24	s06_c02	5	2	2	SS	take_01.mp4 take_02.mp4	take_02.mp4	44.72
25	s06_c03	15	1	1	S	take_01.mp4	take_01_detailcrop03.mp4	66.71
26	s06_c04	13	1	1	S	take_01.mp4	take_01.mp4	57.84
27	s07_c01	7	1	1	S	take_01.mp4	take_01.mp4	31.23
28	s07_c02	6	3	1	FFS	take_03.mp4	take_03.mp4	26.80
29	s07_c03	5	1	1	S	take_01.mp4	take_01_roomtone01.mp4	22.36
30	s07_c04	4	1	1	S	take_01.mp4	take_01.mp4	17.93
31	s08_c01	6	1	1	S	take_01.mp4	take_01.mp4	26.80
32	s08_c02	5	1	1	S	take_01.mp4	take_01.mp4	22.36
33	s08_c03	7	1	1	S	take_01.mp4	take_01.mp4	31.23
34	s08_c04	6	1	1	S	take_01.mp4	take_01.mp4	26.80
35	s09_c01	9	1	1	S	take_01.mp4	take_01.mp4	40.10
36	s09_c02	7	1	1	S	take_01.mp4	take_01.mp4	31.23

Project folder: C:/Users/Admin 3/Downloads/codex-movie/movies/dog-20261015/

Example: s02_c04 + take_03.mp4 resolves to chapters/s02_c04/takes/take_03.mp4. Failed requests have no invented filename. Totals use unrounded values; rounding the 70 rows independently creates a HK$0.04 difference.

Segment register | 37-54

S = returned video; F = failed request with no video file. History is chronological. Costs include all takes for the segment.

Files below are inside **chapters/<segment ID>/takes/** under the project folder. The selected file may be a local edit of a returned video.

#	Segment	Sec / try	API tries	Video files	History	Generated video filename(s)	Selected source / local-edit filename	Est. HK$
37	s09_c03	7	1	1	S	take_01.mp4	take_01.mp4	31.23
38	s09_c04	19	1	1	S	take_01.mp4	take_01.mp4	84.45
39	s09_c05	7	1	1	S	take_01.mp4	take_01.mp4	31.23
40	s10_c01	12	1	1	S	take_01.mp4	take_01.mp4	53.41
41	s10_c02	10	1	1	S	take_01.mp4	take_01.mp4	44.54
42	s10_c03	12	1	1	S	take_01.mp4	take_01.mp4	53.41
43	s10_c04	12	1	1	S	take_01.mp4	take_01.mp4	53.41
44	s10_c05	8	1	1	S	take_01.mp4	take_01.mp4	35.67
45	s11_c01	12	1	1	S	take_01.mp4	take_01.mp4	53.41
46	s11_c02	8	1	1	S	take_01.mp4	take_01.mp4	35.67
47	s12_c01	6	1	1	S	take_01.mp4	take_01.mp4	26.80
48	s12_c02	14	1	1	S	take_01.mp4	take_01.mp4	62.28
49	s12_c03	5	1	1	S	take_01.mp4	take_01.mp4	22.36
50	s12_c04	10	1	1	S	take_01.mp4	take_01.mp4	44.54
51	s13_c01	6	1	1	S	take_01.mp4	take_01.mp4	26.80
52	s13_c02	6	1	1	S	take_01.mp4	take_01.mp4	26.80
53	s13_c03	6	1	1	S	take_01.mp4	take_01.mp4	26.80
54	s13_c04	4	1	1	S	take_01.mp4	take_01.mp4	17.93

Project folder: C:/Users/Admin 3/Downloads/codex-movie/movies/dog-20261015/

Example: s02_c04 + take_03.mp4 resolves to chapters/s02_c04/takes/take_03.mp4. Failed requests have no invented filename. Totals use unrounded values; rounding the 70 rows independently creates a HK$0.04 difference.

Segment register | 55-70

S = returned video; F = failed request with no video file. History is chronological. Costs include all takes for the segment.

Files below are inside **chapters/<segment ID>/takes/** under the project folder. The selected file may be a local edit of a returned video.

#	Segment	Sec / try	API tries	Video files	History	Generated video filename(s)	Selected source / local-edit filename	Est. HK$
55	s14_c01	7	1	1	S	take_01.mp4	take_01.mp4	31.23
56	s14_c02	10	1	1	S	take_01.mp4	take_01.mp4	44.54
57	s14_c03	4	1	1	S	take_01.mp4	take_01.mp4	17.93
58	s14_c04	14	1	1	S	take_01.mp4	take_01.mp4	62.28
59	s15_c01	5	1	1	S	take_01.mp4	take_01.mp4	22.36
60	s15_c02	12	1	1	S	take_01.mp4	take_01.mp4	53.41
61	s15_c03	11	1	1	S	take_01.mp4	take_01.mp4	48.97
62	s15_c04	10	1	1	S	take_01.mp4	take_01.mp4	44.54
63	s16_c01	11	1	1	S	take_01.mp4	take_01.mp4	48.97
64	s16_c02	8	1	1	S	take_01.mp4	take_01.mp4	35.67
65	s16_c03	10	1	1	S	take_01.mp4	take_01.mp4	44.54
66	s16_c04	9	1	1	S	take_01.mp4	take_01.mp4	40.10
67	s16_c05	17	1	1	S	take_01.mp4	take_01.mp4	75.58
68	s16_c06	12	2	1	FS	take_02.mp4	take_02.mp4	53.41
69	s16_c07	7	1	1	S	take_01.mp4	take_01.mp4	31.23
70	s16_c08	11	2	2	SS	take_01.mp4 take_02.mp4	take_02.mp4	97.94

Project folder: C:/Users/Admin 3/Downloads/codex-movie/movies/dog-20261015/

Example: s02_c04 + take_03.mp4 resolves to chapters/s02_c04/takes/take_03.mp4. Failed requests have no invented filename. Totals use unrounded values; rounding the 70 rows independently creates a HK$0.04 difference.

Retakes, failures and audit notes

Segment	History	Reason / resolution
s02_c01	SS	Rural-geography correction; both requests returned videos.
s02_c04	FFS	Two output-audio rejections. Third request returned silent picture; local training-room ambience supplied.
s03_c01	SS	Dialogue-performance retake; both requests returned videos.
s03_c02	SS	Dialogue-performance retake; both requests returned videos.
s04_c03	SS	Correct dog/table and floor-toast placement; both requests returned videos.
s04_c06	SS	Correct dog placement on the floor; both requests returned videos.
s06_c02	SS	Correct dog/mat placement beside Chan; both requests returned videos.
s07_c02	FFS	One output-audio rejection, then one output-video rejection. Third request returned silent picture; finalized original local audio supplied.
s16_c06	FS	Output-audio rejection. Second request returned silent picture; finalized original local audio supplied.
s16_c08	SS	First output put dogs on the bench. Second output corrected the ground-level ending.

API success vs. final selection. 67 segments returned a video on their first request; one first returned on request 2 and two on request 3. Seven returned videos were subsequently replaced for creative review. A returned video is not a guarantee of perfect continuity or dialogue.

Local selected edits. s06_c03 uses take_01_detailcrop03.mp4 (hand/eye reframing); s07_c03 uses take_01_roomtone01.mp4 (local audio edit). These are derivatives, not extra API generations. Picture-only selected takes are s02_c04/take_03.mp4, s07_c02/take_03.mp4 and s16_c06/take_02.mp4; local audio is attached during assembly.

Failure accounting. The five failed requests comprise four output-audio rejections and one output-video rejection. They have no returned video files and are recorded at estimated zero cost under the ledger pricing assumption. All 82 attempts are resolved; none have pending/unknown usage charges in the report. Actual billing remains unverified.

Sources and reproducibility. Read from project snapshot r32: project.json (plan and selected files), usage.json (82 attempts, measured tokens and cost estimates), exports/task-journal.json (take histories and real generated paths), exports/verification.json (600-second final technical profile), and exports/assembly-settings.json (movie inputs). All source movie records were read only.

Pricing reference recorded in the ledger: BytePlus model pricing, checked during production on 15 October 2026. The recorded rate is a list-price estimate; it is not an account invoice.