

FO duplex patch cord FC-PC - FC-PC

E9/125 G.652.D OS2




image similar

Description

Datwyler offers a broad range of terminated connectors for individual customer needs.
For all patch cords figure 0 cables with 4.8x3.2 mm are used.

General Properties

Cable construction	I-V(ZN)HH (4.8x3.2 mm)
Operating temperature	-10 °C - +60 °C

Optical Properties

Ferrule material	Zirconia
Grade, connector A (better than)	B2
Grade, connector B (better than)	B2
IL maximal, connector A	0.25 dB
IL maximal, connector B	0.25 dB
IL typical, connector A	0.12 dB
IL typical, connector B	0.12 dB
Lifetime	1000 connections with stable attenuation values
Reproducibility of the IL	maximal +/- 0.1dB
RL minimal, connector A	50 dB
RL minimal, connector B	50 dB
RL typical, connector A	55 dB
RL typical, connector B	55 dB
Standard connector A	IEC 61754-13
Standard connector B	IEC 61754-13

Mechanical properties

Bending (IEC 60794-1-21 E11, reversible fibre attenuation)	≤ 0,5 dB
Connector cable retention	100 N
Crush resistance (IEC 60794-1-21 E3, reversible fibre attenuation)	≤ 0,2 dB
Impact	IEC 60794-1-21 E4
Minimum bending radius	50 mm
Repeated bending	IEC 60794-1-21 E6
Tensile load (IEC 60794-1-21 E1 0,33% reversible fibre elongation)	200 N
Torsion (IEC 60794-1-21 E7, reversible fibre attenuation)	≤ 0,1 dB

Versions

Material number	Product	Outer sheath colour	Length (m)	Weight [kg]
425523	FO duplex patch cord FC-PC - FC-PC, E9/125 G.652.D OS2	yellow	0	0.2 kg
425511	FO duplex patch cord FC-PC - FC-PC, E9/125 G.652.D OS2	yellow	1	0.05 kg
425512	FO duplex patch cord FC-PC - FC-PC, E9/125 G.652.D OS2	yellow	2	0.1 kg
425513	FO duplex patch cord FC-PC - FC-PC, E9/125 G.652.D OS2	yellow	3	0.12 kg
425514	FO duplex patch cord FC-PC - FC-PC, E9/125 G.652.D OS2	yellow	4	0.16 kg
425515	FO duplex patch cord FC-PC - FC-PC, E9/125 G.652.D OS2	yellow	5	0.19 kg
425516	FO duplex patch cord FC-PC - FC-PC, E9/125 G.652.D OS2	yellow	6	0.22 kg
425517	FO duplex patch cord FC-PC - FC-PC, E9/125 G.652.D OS2	yellow	7	0.26 kg
425518	FO duplex patch cord FC-PC - FC-PC, E9/125 G.652.D OS2	yellow	8	0.29 kg
425519	FO duplex patch cord FC-PC - FC-PC, E9/125 G.652.D OS2	yellow	9	0.31 kg
425520	FO duplex patch cord FC-PC - FC-PC, E9/125 G.652.D OS2	yellow	10	0.36 kg