

FO duplex patch cord LCD - FC-PC

G50/125 OM3



image similar

Description

Datwyler offers a broad range of terminated connectors for individual customer needs. For all patch cords figure 0 cables with 4.8x3.2 mm are used.

General PropertiesCable constructionI-V(ZN)HH (4.8x3.2 mm)Operating temperature-10 °C - +60 °C

| Optical Properties | | | |
|----------------------------------|---|--|--|
| Ferrule material | Zirconia | | |
| Grade, connector A (better than) | Bm2m | | |
| Grade, connector B (better than) | Bm2m | | |
| IL maximal, connector A | 0.3 dB | | |
| IL maximal, connector B | 0.3 dB | | |
| IL typical, connector A | 0.15 dB | | |
| IL typical, connector B | 0.15 dB | | |
| Lifetime | 1000 connections with stable attenuation values | | |
| Reproducibility of the IL | maximal +/- 0.1dB | | |
| RL minimal, connector A | 30 dB | | |
| RL minimal, connector B | 30 dB | | |
| RL typical, connector A | 35 dB | | |
| RL typical, connector B | 35 dB | | |
| Standard connector A | IEC 61754-20 | | |
| Standard connector B | IEC 61754-13 | | |



| Mechanical properties | |
|--|-------------------|
| Bending (IEC 60794-1-21 E11, reversible fibre attenuation) | ≤ 0,5 dB |
| Connector cable retention | 100 N |
| Crush resistance (IEC 60794-1-21 E3, reversible fibre attenuation) | ≤ 0,2 dB |
| Impact | IEC 60794-1-21 E4 |
| Minimum bending radius | 50 mm |
| Repeated bending | IEC 60794-1-21 E6 |
| Tensile load (IEC 60794-1-21 E1 0,33% reversible fibre elongation) | 200 N |
| Torsion (IEC 60794-1-21 E7, reversible fibre attenuation) | ≤ 0,1 dB |

| Versions | | | | | | |
|-----------------|---|---------------------|------------|-------------|--|--|
| Material number | Product | Outer sheath colour | Length (m) | Weight [kg] | | |
| 423531 | FO duplex patch cord LCD - FC-PC, G50/125 OM3 | turquoise | 1 | 0.06 kg | | |
| 423532 | FO duplex patch cord LCD - FC-PC, G50/125 OM3 | turquoise | 2 | 0.1 kg | | |
| 423533 | FO duplex patch cord LCD - FC-PC, G50/125 OM3 | turquoise | 3 | 0.12 kg | | |
| 423534 | FO duplex patch cord LCD - FC-PC, G50/125 OM3 | turquoise | 4 | 0.16 kg | | |
| 423535 | FO duplex patch cord LCD - FC-PC, G50/125 OM3 | turquoise | 5 | 0.19 kg | | |
| 423536 | FO duplex patch cord LCD - FC-PC, G50/125 OM3 | turquoise | 6 | 0.22 kg | | |
| 423537 | FO duplex patch cord LCD - FC-PC, G50/125 OM3 | turquoise | 7 | 0.26 kg | | |
| 423538 | FO duplex patch cord LCD - FC-PC, G50/125 OM3 | turquoise | 8 | 0.29 kg | | |
| 423539 | FO duplex patch cord LCD - FC-PC, G50/125 OM3 | turquoise | 9 | 0.31 kg | | |
| 423540 | FO duplex patch cord LCD - FC-PC, G50/125 OM3 | turquoise | 10 | 0.36 kg | | |

Subject to technical modification As of 2020-12-03 12:49:37