



# Chapter 6: Artifact Rejection and Correction Part 1

Clara Rhee

# Overview


- *Artifacts* = Non-EEG signals
- Problematic in 3 ways
  - 1) May decrease the signal-to-noise ratio(SNR) of averaged ERP waveform, decreasing your ability to find significant differences between groups or conditions
  - 2) May be systematic rather than random
  - 3) Ocular artifacts (most common) change the sensory input
- Main classes of techniques for minimizing the effects of artifacts
  - 1) Artifact rejection
  - 2) Artifact correction

# The General Artifact Rejection Process

- Signal detection problem
  - Hit
  - Miss
  - False alarm
  - Correct rejection
- It is important to be clear about your goal when doing artifact rejection

# Choosing an Artifact Measure

- Be careful when choosing a system for artifact rejection
- Perform baseline correction prior to artifact rejection when using absolute voltage rejection approach
- Moving window peak-to-peak amplitude method



# Choosing an Rejection Threshold

- You must choose a threshold that does a good job of balancing misses and false alarms
- Remember that the goal is not to remove all artifacts but to maximize statistical power and avoid confounds
- Will this bias the results?
- Using visual inspection of the raw EEG
  - 1) Use prior experience or published values to select initial threshold
  - 2) Adjust threshold and try artifact rejection again
  - 3) Repeat until you are able to reject all the trials that clearly have artifacts without rejecting too many artifact-free trials
- Ask subjects to make some blinks and eye movements at the beginning of the session

# Visual Inspection

- Pro: Human visual system can be trained to do an excellent job of differentiating between real artifacts and normal EEG noise
- Con: Computer algorithm is fast, consistent, and bias-free
- Crucial that the person doing the rejection is blind to groups and conditions