

# Introductory Web Programming

# What this class is

This is an overview of JavaScript and how it interacts with the browser to make interactive websites

# What you'll learn

- A simple overview of JavaScript
- An explanation of the Document Object Model
- An overview of the event system in JavaScript
- Simple examples of writing code

# What you'll learn

- A simple overview of JavaScript
- An explanation of the Document Object Model
- An overview of the event system in JavaScript
- Simple examples of writing code

# What you'll learn

- A simple overview of JavaScript
- An explanation of the Document Object Model
- An overview of the event system in JavaScript
- Simple examples of writing code

# What you'll learn

- A simple overview of JavaScript
- An explanation of the Document Object Model
- An overview of the event system in JavaScript
- Simple examples of writing code

# What you won't learn

- The basics of HTML and CSS
- The full JavaScript programming language
- Libraries like jQuery or Angular or React

# What you won't learn


- The basics of HTML and CSS
- The full JavaScript programming language
- Libraries like jQuery or Angular or React



# What you won't learn

- The basics of HTML and CSS
- The full JavaScript programming language
- Libraries like jQuery or Angular or React



# Make an account



## neocities

Create your own free website.  
Unlimited creativity, zero ads.

Neocities is a social network of 117,000 web sites that are bringing back the lost individual creativity of the web. We offer free web hosting and tools that allow you to create your own web site. Join us!

-  **Powerful features to help you build**  
We've made it easy to build your web site and explore other sites. Neocities features an in-browser HTML editor, custom domain support, fast site performance, easy file uploading, RSS feeds, folder support, and so much more.
-  **Share your web creation with the world**  
It's your web site, your vision. Make it as normal or crazy as you want. You're the artist, you're in control.

### Sign up for free

Username  
 .neocities.org

Tags (your interests, site topics)

Password

Email

Confirm you are human  
☐ I'm not a robot

Create My Site

# HTML in a nutshell

```
<!doctype html>
<html>
  <body>
    <h1>This is a heading</h1>
    <p>
      This is a paragraph of text,
      where some of the text is <b>bold</b> and
      after this paragraph, there will be a numbered list
    </p>

    <ol>
      <li>lists are made of "list items"</li>
      <li>like these</li>
    </ol>
  </body>
</html>
```

# CSS in a nutshell

## Selectors and Properties

```
selector {  
    property: value;  
    property: value;  
    property: value;  
}
```

# CSS in a nutshell

## Selectors and Properties

```
selector {  
    property: value;  
    property: value;  
    property: value;  
}
```

# CSS in a nutshell

## Selectors and Properties

```
selector {  
    property: value;  
    property: value;  
    property: value;  
}
```

# What's a programming language?

Programming languages are languages for describing computation

JavaScript has a special relationship to the browser




# Learning programming

Learning programming requires specificity that's unnatural.  
It's always hard at first.

# The console

## Ctrl-Shift-K



# Syntax and Semantics

Every programming language has a *grammar* and it has to be followed exactly

# Numbers and Strings

## Numbers

10

20 + 30

0 \* 3 + 0.2

## Strings

"text"

'also text'

"this is an 'inner quote'"

# Variables

Variables are generalized pronouns: names that can refer to data

Type into the console

```
var thisIsAName = 10  
thisIsAName  
thisIsAName = 20  
thisIsAName
```

# Variables exercise

## Try for yourself

- Create a variable in the console
- Assign it a number
- Retrieve the data out of the variable

# Loading code into the browser

```
<head>  
  <script>  
    ...  
  </script>  
</head>
```

```
<head>  
  <script src="yourCode.js">  
  </script>  
</head>
```

# Sequencing code

To write multiple steps of code,  
separate them with by semicolons.

```
var thisIsAName = 10;  
thisIsAName;  
thisIsAName = 20;  
thisIsAName;
```



# Functions

Functions hold sequences of code that can be called again and again.

```
function funName (arg1) {  
    var arg2 = arg1;  
    return arg2;  
}
```

```
console.log(funName(10));
```

# Functions exercise

## Try for yourself

- ❶ open a new file, call it `funEx.js`
- ❷ In this file:
  - ▶ Create a function that
    - ★ takes three arguments
    - ★ multiplies all of them together
    - ★ uses `console.log` to write the value to the console
  - ▶ Call the function with three arguments
- ❸ Create an HTML file that looks like the following

## Example HTML

```
<html>
  <head>
    <script src="funEx.js"></script>
  </head>
</html>
```

# Objects

Objects are ways of holding data like dictionaries or contact lists: key/value pairs

## Type along

```
var obj = { property1: 10,  
            property2: 20}  
  
console.log(obj);  
console.log(obj.property1);  
console.log(obj.property2);
```

# The pineal gland of the browser

The Document Object Model (DOM) connects the webpage you can see with the JavaScript code

# The DOM

The DOM provides the *state of the webpage* as an *object* you can manipulate

# Creating elements

```
var newElement = document.createElement("h1");
var textInTheThing =
    document.createTextNode("There's some text in here.");
newElement.appendChild(textInTheThing);

document.body.appendChild(newElement);
```


Type the following into a file called LoadTest.html

```
<html>
  <head>
    <script>
      var newElement = document.createElement("h1");
      var textInTheThing =
        document.createTextNode("There's some text in here.");
      newElement.appendChild(textInTheThing);

      document.body.appendChild(newElement);
    </script>
  </head>
  <body>
  </body>
</html>
```

# Making sure it loads

You probably saw something like





# What went wrong?

## Loading order

The code needed to run after, not before, body existed

# A taste of events

```
<html>
  <head>
    <script>
      window.onload = function () {
        var newElement = document.createElement("h1");
        var textInTheThing =
          document.createTextNode("There's some text in here.");
        newElement.appendChild(textInTheThing);

        document.body.appendChild(newElement);
      }
    </script>
  </head>
  <body>
  </body>
</html>
```

# How to change elements

To change elements, you usually will change their CSS classes

## Adding and removing classes

```
var newElement = document.createElement("h1")
    .appendChild(document.createTextNode("Text here"));
document.body.appendChild(newElement);
newElement.classList.add("superbold");
```

# Finding elements

In order to modify already existing elements, we need to find them first

## Finding elements by id

```
var aHeading = document.getElementById("heading");  
aHeading.classList.add("superbold");
```

## Finding elements by class

```
var listItems = document.getElementsByClassName("listy");  
  
for(var i=0; i < listItems.length; i = i + 1){  
    listItems.item(i).classList.add("superbold");  
}
```

# JavaScript event model

Clicking, typing, moving the mouse, etc. create *events*



# Events are sensors

Events are the *senses* of your code

# Event handlers

```
window.onload = function () {  
    document.body  
        .addEventListener("mousemove", console.log);  
}
```

# Attaching events to buttons


```
<html>
  <head>
    <script>
      window.onload = function () {
        var button = document.getElementById("button");
        button.addEventListener("click", function () {
          console.log("the button was pressed");
        });
      }
    </script>
  </head>
  <body>
    <button id="button">Push me</button>
  </body>
</html>
```

# Retrieving data from forms

```
<html>
  <head>
    <script>
      window.onload = function () {
        var button = document.getElementById("button");
        button.addEventListener("click", function () {
          console.log("the button was pressed");
        });
      }
    </script>
  </head>
  <body>
    <input id="input" value="stuff"/>
    <button id="button">Press me</button>
  </body>
</html>
```

# Using the Mozilla Developer Network

`https://developer.mozilla.org/en-US/`



Questions?

Thank you for coming out!