

```

1 /**
2  * {@code Timer} interface provides methods for controlling a Pomodoro styled
3  * timer and displaying its state.
4  *
5  * It extends {@code TimerKernel}.
6  *
7  * @initially The timer is stopped, and the remaining time is set to work
8  *            session duration. The timer can be started, paused, stopped, and
9  *            reset. The remaining time is to be displayed as strings.
10 *
11 * @author Clarissa Le
12 */
13 public interface Timer extends TimerKernel {
14
15     /**
16      * Pauses the timer.
17      *
18      * @ensures isRunning = false
19      */
20     void pause();
21
22     /**
23      * Stops and resets the timern.
24      *
25      * @ensures remainingTime = sessionLength and isRunning = false
26      */
27     void stop();
28
29     /**
30      * Switches between work and break sessions.
31      *
32      * @ensures isWorkSession = !isWorkSession AND remainingTime is set to new
33      *            session's length
34      */
35     void switchSession();
36
37     /**
38      * Gets a string representing the current session type.
39      *
40      * @return work or rest session
41      */
42     String getSession();
43
44     /**
45      * Retrieves the remaining time.
46      *
47      * @return remaining time in minute, second format
48      */
49     String getFormattedTime();
50
51     /**
52      * Checks whether the timer is currently running.
53      *
54      * @return true if running, false otherwise
55      */
56     @Override
57     boolean isRunning();
58
59     /**
60      * Checks whether the current session is a work session.
61      *

```

```
62  * @return true if work session, false if break session
63  */
64  boolean isWorkSession();
65 }
66
```