Project HiveMind: A System Design for Decentralized Sparse Mixture-of-Experts Training with DiLoCo-Style Outer Optimization on 8 GB Consumer GPUs

Integration of Low-Communication Training Methods, Controlled Experimental Evaluations, and Lean 4 Bookkeeping Lemmas

Xavier Callens*
Project HiveMind Open-Source Contributors

October 23, 2026 — Version 3.5.0 (pre-registered research program; E5-toy and E5-het three-seed factorials; RDA as an outer-LR multiplier; E8 two-host internet pilot; Decoupled DiLoCo quorum syncer; 120 Lean 4 lemmas)

Abstract

Training and serving frontier Large Language Models (LLMs) are increasingly monopolized by hyperscale datacenters due to two fundamental systems bottlenecks: the **VRAM Wall** (a single 8 GB–12 GB consumer GPU cannot hold a 70B+ dense model or its FP32 AdamW optimizer states) and the **Bandwidth Wall** (standard synchronous All-Reduce Distributed Data Parallelism saturates 10–50 Mbps residential internet links instantly). Yet the global PC gaming and open-source developer community possesses millions of idle NVIDIA RTX 20/30/40-series, AMD ROCm, and Apple Metal GPUs alongside terabytes of NVMe flash storage.

We describe **Project HiveMind**, an open-source decentralized training and inference system, and report what has and has not yet been validated. The system combines **Branch-Train-Mix (BTM) sparse MoE upcycling**, **weight-tied looped recurrence**, and **DiLoCo-style outer optimization**, with an emphasis on fitting a strict 8 GB GPU memory budget. Workers stream open-weight backbones (`Qwen2.5`) into 4-bit NF4 and train QLoRA adapters; outer pseudo-gradients can be compressed with a DCT + 2-bit centroid scheme adapted from DeMo [23] and SparseLoCo [24]; the outer optimizer supports a CPU-resident flat-bucket state (after `prime-diloco` [12]) and the staleness gate of CGAD [19]; converged branches are upcycled into a sparse MoE with optional Iso-CTS [20] or TSV [22] attention merging and FoMoE-style partial expert replication [15].

Empirical and formal evaluation. We evaluate the system at three levels, separating verified properties from open multi-node questions: (i) Ten *unit-level implementation checks* (`H1`–`H10`, `artifacts/architecture_hypothesis_verification_report.json`) verify that each component satisfies its mathematical specification on controlled tensors, including non-trivial fixed-point halting ($\epsilon_{\text{fp}} = 0.65 \Rightarrow 3.05/4.0$ mean recurrent steps) and single-round vs. multi-step EF21 error-feedback conservation; an eleventh check (`H11`, `artifacts/decoupled_diloco_quorum_check.json`) covers a Decoupled DiLoCo syncer [5] with minimum quorum, adaptive grace window and token-weighted Radial-Directional Averaging, which restores the common outer-gradient norm that direct averaging shrinks by $1/\sqrt{M}$ (2.83× at $M = 8$). (ii) Four *controlled multi-regime experimental studies* (`E1`–`E4`, `artifacts/paper_v3_experiments_report.json`, Figures 1–4) measure held-out generalization across five synchronization regimes (showing that DeMo 2D-DCT + SparseLoCo 2-bit + EF21 achieves a **0.052%** held-out loss gap vs. uncompressed FP32 DiLoCo while cutting outer wire traffic by **12.49**× and **99.9**× vs. synchronous DDP, and that `MuLoCo` 5-step Newton-Schulz inner preconditioning slightly improves compressed held-out perplexity), outer convergence under severe straggler bursts ($\tau_w \geq 36$, where `PA-CGAD` reduces terminal MSE by **11.6**×

*Project HiveMind (`callensxavier@gmail.com`). Code and all artifacts referenced in this paper: https://github.com/xaviercallens/HiveMind. The project is non-commercial; contributors receive no payment.

relative to un-gated outer AdamW), fixed-point halting trade-offs across $\epsilon_{\text{fp}} \in [0.0, 1.10]$, and singular value spectra under `Iso-CTS` and `TSV` merging. (iii) A single-GPU proof of concept on an 8 GB NVIDIA RTX 2070 with `Qwen2.5-0.5B` trains four domain branches and upcycles them into a 4-expert top-2 MoE within **1,509.5 MB** peak VRAM, accompanied by **120** zero-`sorry` Lean 4 arithmetic and hypothesis-necessity lemmas (`lean4/HiveMindSpec.lean`). **Research program.** Because all experiments so far are single-host and single-seed, Section 9 turns the design into a testable thesis: the loss gap between a volunteer WAN swarm and a single-host run at matched tokens should decompose into the replica-count penalty of the DiLoCo scaling law plus a bounded "volunteer tax". It states eight research questions, the prediction each makes, the observation that would refute it, and five pre-registered experiments (E5–E9, three seeds, positive, negative and matched-random controls) that decide them. Section 10 details remaining multi-host WAN limitations.

Keywords: Decentralized AI · Pre-registered Experiments · Sparse Mixture-of-Experts (MoE) · DiLoCo & OpenDiLoCo · FoMoE · Looped Transformers · DeMo DCT & SparseLoCo · MuLoCo Newton-Schulz · Byzantine Fault Tolerance · Lean 4

Contents

1 Introduction: Breaking the VRAM and Bandwidth Walls **4**
1.1 Architecture Overview & Summary of Contributions 4

2 Lean 4 Bookkeeping Lemmas: Scope and Limits **5**

3 Pillar I: Zero-Copy 4-Bit NF4 & DiLoCo-QLoRA Foundation **6**
3.1 Zero-Copy Meta-Device Streaming & 4-Bit NormalFloat Quantization 6
3.2 DiLoCo Inner Loop & Baseline Top-k + `float8_e4m3fn` Deltas 7

4 Pillar II: Byzantine Fault Tolerance Without 2× Redundancy **8**
4.1 10% Deterministic Micro-Checkpoint Spot-Checks & Hardware Circuit-Breaker . . 8
4.2 Pre-Krum Sanitization, Multi-Krum 2σ Cosine Filter & ZK-OPoI v4 8

5 Pillar III & Phase 2 Swarm Fabric: Factored BTM Upcycling & Geo-Rings **8**

6 Missing MoE Architecture: 128-Expert 3-Tier Routing, FoMoE, Skip-Attention & Looped Recurrence **9**
6.1 3-Tier 128-Expert Hierarchical MoE Router (`ThreeTierHierarchicalMoERouter`) 9
6.2 Federated Partial Expert Replication (`FoMoE`) & Ghost-Expert `Skip-Token` 9
6.3 `Skip-Attention` Speculative Prefetch & Cache-Aware Routing (`CAR`) 10
6.4 Weight-Tied `LoopedExpertBackbone`, Fixed-Point Halting & Truncated BPTT . . 11
6.5 Subspace-Aware Attention & Expert Merging: `Iso-CTS` & `TSV` 11

7 OpenDiLoCo & Google DeepMind Outer-Loop Ecosystem **12**
7.1 `OpenDiLoCo` & `prime-diloco`: Contiguous 1D CPU Flat-Bucket Outer State (`0 B` GPU VRAM) 12
7.2 Decoupled DiLoCo: Minimum Quorum, Adaptive Grace Window & Radial-Directional Averaging 13
7.3 Streaming DiLoCo Fragments & Cosine-Gated Adam-Decay (`PA-CGAD`) 14
7.4 `DeMo` Chunked 2D DCT + `SparseLoCo` 2-Bit LUT + `PULSELoCo` + `EF21` 15
7.5 `AutoLoCo`, `HeLoCo` & Inner-Loop `MuLoCo` Newton-Schulz Preconditioning 15
7.6 Analytical Theorems, Proofs, Hypothesis-Necessity Counterexamples & 4-Definitions Contract 16

8 Empirical Verification, Controlled Experiments & Visualizations 17
8.1 Unit-Level Implementation Checks (`H1`–`H10`) . . . 17
8.2 Controlled Experimental Evaluations (`E1`–`E4`) & Visualizations . . . 18
8.2.1 Experiment E1: Held-Out Generalization & Wire Efficiency Across Five DiLoCo / MuLoCo Regimes . . . 18
8.2.2 Experiment E2: `PA-CGAD` Outer Convergence Under Severe Asynchronous Straggler Bursts . . . 19
8.2.3 Experiments E3 & E4: `LoopedMoE` Fixed-Point Halting Sweep, Subspace Spectra & Hardware Scaling . . . 19
8.3 Single-GPU Proof of Concept on an 8 GB NVIDIA GeForce RTX 2070 & FoMoE Scaling . . . 20

9 Research Program: Questions, Predictions and Pre-registered Experiments 21
9.1 Thesis and scaling-law prior . . . 21
9.2 Research questions and predictions . . . 22
9.3 Pre-registered experiments and controls . . . 22
9.4 Decision rules . . . 23
9.5 First pre-registered result: E5-toy (three seeds, all controls passed) . . . 24
9.6 Second pre-registered result: E5-het, a heterogeneity-controlled testbed . . . 25
9.7 First two-host measurement: E8-pilot over the public internet . . . 26
9.8 E10: a lattice codec for outer deltas, leveraged from the author's OptimalEnergyAI project . . . 27

10 Limitations, Threats to Validity, and Future Multi-Host Benchmarks 28
10.1 Epistemic Stratification & 6-Layer Security/Hardness Attestation . . . 29

1 Introduction: Breaking the VRAM and Bandwidth Walls

Modern frontier language models rely on massive parameter counts (70B to 1T+) trained over tightly coupled InfiniBand or NVLink fabrics (400–3,200 Gbps). Attempting to decentralize LLM training and inference across volunteer consumer gaming hardware—the modern equivalent of `SETI@home` [1] and `Folding@home`—confronts four structural barriers:

1. **The Consumer VRAM Wall:** The median gaming GPU on the Steam Hardware Survey (e.g., NVIDIA RTX 2070, RTX 3060, RTX 4060) provides **8 GB to 12 GB of GDDR6 VRAM**. On Windows 10/11 under the WDDM display driver model, approximately 1.0–1.5 GB is reserved by the operating system and desktop compositor, leaving a strict usable ceiling of $M_{\text{ceil}} \approx 6.5$ GB on an 8 GB card. A dense 7B model in FP16 with FP32 master weights and AdamW first/second moments requires > 56 GB of VRAM, causing immediate out-of-memory (OOM) failure.

2. **The Residential WAN Bandwidth & Straggler Wall:** Standard Distributed Data Parallel (DDP) training executes an All-Reduce over all gradients at every micro-step ($t = 1, 2, \dots$). Over residential fiber or cable connections (10–50 Mbps upload, 20–150 ms RTT), synchronizing gigabytes of gradients per second is physically impossible. Even under Distributed Low-Communication (`DiLoCo`) [2] training, asynchronous WAN stragglers inject stale pseudo-gradients that corrupt outer momentum and inflate outer Adam second moments [19].

3. **The Sparse MoE All-to-All & PCIe Thrashing Wall:** Scaling model capacity via Mixture-of-Experts (MoE) [41, 13, 11] traditionally requires either holding all E experts in GPU VRAM (violating the 8 GB ceiling when $E = 64$–128) or issuing synchronous token-level All-to-All RPCs and synchronous PCIe DMA loads that stall the GPU for 2–20 ms per layer.

4. **The Byzantine & Gamer Preemption Threat:** Volunteer consumer nodes include unstable GPU overclocks, bit-flips, Sybil botnets, and adversarial gradient poisoners. Classic BOINC mitigates this via 2× redundant workunit replication (wasting 50% of cluster FLOPs), while gamers demand < 1.5 s preemption latency whenever a game launches.

1.1 Architecture Overview & Summary of Contributions

Project HiveMind addresses these barriers with four design pillars (Sections 3–5), a next-generation **Hierarchical, Federated & Looped Sparse MoE architecture** (Section 6), and a unified **Google DeepMind DiLoCo + Prime Intellect OpenDiLoCo outer-loop stack** (Section 7):

- **Pillar 1 (Zero-Copy 4-Bit NF4 + MuLoCo-Preconditioned DiLoCo-QLoRA):** Meta-device skeleton initialization with streaming 4-bit NormalFloat (`NF4`) double quantization (`0 B` CPU heap duplication) paired with inner-loop **5-step quintic Newton-Schulz LoRA gradient orthogonalization** (Muon [34], as used inner-loop by MuLoCo [35, 36]) and **EF21 error-feedback wire compression** [37, 24, 23].

- **Pillar 2 (Byzantine Fault Tolerance Without 2× Replication):** Deterministic CUDA execution (`CUBLAS_WORKSPACE_CONFIG=:4096:8`) with SHA-256 micro-checkpoints every $s = 50$ steps enables 10% random segment replay within $\epsilon \leq 10^{-4}$ (20× fewer verification FLOPs than 2× BOINC), paired with **Multi-Krum 2σ cosine filtering** [40] and **ZK-OPoI v4 position-bound batch Merkle verification**.

- **Pillar 3 & Missing MoE Architecture (128-Expert 3-Tier Hierarchical MoE, `FoMoE`, `Skip-Attention` & `LoopedExpertBackbone`):** We extend Branch-Train-Mix (BTM)

[13] with (i) a **3-Tier** $4 \times 4 \times 8 = 128$**-Expert Hierarchical Router** (8.0× gating FLOP reduction), (ii) **Federated Partial Expert Replication (`FoMoE`)** [15] with **Ghost-Expert `Skip-Token`** local routing (3.46× WAN ring reduction, zero remote FFN RPCs), (iii) **`Skip-Attention` Speculative Prefetch + Cache-Aware Routing (`CAR`)** [16] (so far evaluated only in a synthetic unit check), (iv) **`Iso-CTS` & `TSV` Subspace Attention Merging** [20, 21, 22], and (v) a **Weight-Tied `LoopedExpertBackbone`** (`Prelude` → `RecurrentCore` $\times T \rightarrow$ `Coda`) [17, 18] with per-token fixed-point convergence exit and truncated BPTT.

- **Next-Generation OpenDiLoCo & Google DeepMind Outer-Loop Stack:** Building on Google DeepMind's `DiLoCo` [2], asynchronous Local-SGD [3], `Streaming DiLoCo` [4], `Scaling Laws for DiLoCo` [11], and `Decoupled DiLoCo` [5] with Prime Intellect's `OpenDiLoCo` / `prime-diloco` [12], we implement a **Contiguous 1D CPU Flat-Bucket Outer State** (`0 B` extra GPU VRAM), **Cosine-Gated Adam-Decay (`PA-CGAD`)** [19] with uniform staleness bias bound $\max_{\tau \geq 0} \tau\sigma(\tau) \leq \frac{1}{e\alpha}$, **`DeMo` + `SparseLoCo` + `PULSELoCo`-style 2-bit DCT wire compression** [23, 24, 25], **`AutoLoCo`** [33], **`HeLoCo`** [26], and a **Decoupled DiLoCo quorum syncer** (minimum quorum K, adaptive grace window $\xi_{\text{grace}} \leq \gamma\,\xi_{\text{slack}}$, token-weighted Radial-Directional Averaging; Section 7.2).
- **Pre-registered research program (Section 9):** a thesis, eight falsifiable predictions with refutation criteria, a scaling-law prior, five pre-registered experiments with controls, and decision rules that say what each outcome changes in the system and in this paper.
- **Honest scope statement:** each pillar is implemented and unit-tested, but the end-to-end system has not yet been evaluated across multiple machines or against a data-parallel baseline (Section 10).

2 Lean 4 Bookkeeping Lemmas: Scope and Limits

We maintain a Lean 4 [42] file of arithmetic and necessity lemmas that accompany the design (`lean4/HiveMindSpec.lean`, compiled with `leanprover/lean4:v4.33.0-rc2`). All **120** lemmas compile with no `sorry`, no `admit`, and no user axioms (`lake build`, `#print axioms`).

What these lemmas establish and what they do *not* establish. Every statement is over $\mathbb{N}$ or $\mathbb{Z}$; there is no real-valued functional analysis, no stochastic convergence theory, and no machine-checked refinement link between a Lean statement and the Python/CUDA runtime. Rather, the 120 lemmas serve as machine-checked arithmetic, hypothesis-necessity counterexamples, and non-vacuity invariants: e.g., that contiguous flat-bucket slice offsets partition the outer parameter buffer without overlap (Thm. 101), that staggered fragment streaming strictly reduces per-round peak serialization bytes (Thm. 102), that the piecewise PA-CGAD cutoff rule $\tau_{\text{eff}} \geq \tau_{\text{cut}}$ freezes the discrete second-moment accumulator v_{prev} strictly below the un-gated polluted value $v_{\text{prev}} + g_{\text{sq}}$ (Thm. 103), that a 4-tensor $[256, 16]$ 2-bit DCT package (820 B) clears both the 16× 16-bit and 32× FP32 compression gates (Thm. 105), that inward singular-value pulls $\delta > 0$ strictly contract the spectral spread $(s_{\max} - \delta) - (s_{\min} + \delta) < s_{\max} - s_{\min}$ (Thm. 106), that EF21 error-feedback residuals telescope across consecutive outer rounds (Thm. 107), and that dropping EF21 residual carry (Thm. 113), omitting the PA-CGAD staleness cutoff (Thm. 114), or violating the Multi-Krum $n \geq 2f + 3$ quorum bound (Thm. 115) strictly breaks each respective invariant, while `InhabitedRTX2070SwarmPackage` is provably non-empty (Thm. 116). Season 14 (Thms. 117–120) adds the Decoupled DiLoCo bookkeeping of Section 7.2: a grace window $\gamma\,\xi_{\text{slack}}$ with $\gamma < 1$ is strictly below any positive slack (Thm. 117), an exhausted compute budget yields a zero grace window (Thm. 118), the token-weighted learner weight is monotone in tokens and antitone in steps (Thm. 119), and the admitted set has size in $[K, M]$ while the degenerate $K = 0$ rule admits nobody (Thm. 120). Continuous-time optimization convergence, the real-valued calculus proof of $\sup_{\tau \geq 0} \tau e^{-\alpha\tau} = \frac{1}{e\alpha}$ (proved analytically in Theorem 7.3), and adaptive Byzantine resilience are *not* formalized in Lean 4.

Listing 1: Excerpt from `lean4/HiveMindSpec.lean` (Season 12: OpenDiLoCo Flat-Bucket, PA-CGAD Piecewise Cutoff, DeMo-SparseLoCo 2-Bit Gate, MuLoCo Spread Contraction, and EF21 Telescoping Sum).

```
namespace HiveMindSpec.Season12_OpenDiLoCoAndMissingMoEArchitectureHypotheses

theorem opendiloco_flat_bucket_partition_conserves_numel (n1 n2 n3 : Nat) :
    (n1 - 0) + ((n1 + n2) - n1) + ((n1 + n2 + n3) - (n1 + n2)) = n1 + n2 + n3 :=
      by
  omega

theorem pacgad_staleness_cutoff_preserves_second_moment
    (v_prev g_sq tau_eff tau_cut : Nat)
    (h_cutoff : tau_cut <= tau_eff) (h_gsq : 0 < g_sq) :
    (if tau_eff < tau_cut then v_prev + g_sq else v_prev) = v_prev /\
      v_prev < v_prev + g_sq := by
  have h_not_lt : Not (tau_eff < tau_cut) := Nat.not_lt.mpr h_cutoff
  simp [h_not_lt]; omega

theorem demo_sparseloco_2bit_package_exceeds_16x_compression :
    16 * (4 * (21 + 82 * 2 + 8 + 12)) <= 4 * 4096 * 2 /\
      32 * (4 * (21 + 82 * 2 + 8 + 12)) <= 4 * 4096 * 4 := by
  decide

theorem muloco_newton_schulz_condition_contraction
    (s_max s_min delta : Nat) (h_delta : 0 < delta)
    (h_order : s_min + delta <= s_max - delta) :
    (s_max - delta) - (s_min + delta) < s_max - s_min := by
  omega

theorem ef21_multistep_telescoping_sum_conservation
    (g1 g2 c1 r1 c2 r2 : Int)
    (h_step1 : c1 + r1 = g1) (h_step2 : c2 + r2 = g2 + r1) :
    (c1 + c2) + r2 = g1 + g2 := by
  omega
end HiveMindSpec.Season12_OpenDiLoCoAndMissingMoEArchitectureHypotheses
```

Independent kernel gate. Besides the project's own `lake build` audit, the file was gated on 23 October 2026 by a second, independently written verifier (`anse.formal.lean_runner` of the author's AutoevolveAI project), which compiles the file in place, requires one `#print axioms` line per declared theorem and whitelists only `propext`, `Classical.choice` and `Quot.sound`. Its first run reported 13 of the 120 theorems as unverified: they compiled but had no axioms line, so nothing had ever printed their footprint. The lines were added; the gate now reports **120/120** theorems, 0 `sorry`, 0 untrusted axioms (`artifacts/lean_independent_runner_check.json`; footprints: 57 on {`propext`, `Quot.sound`}, 30 add `Classical.choice`, 17 `propext` only, 16 none). The count of 120 was never wrong; the coverage of the axiom check was.

3 Pillar I: Zero-Copy 4-Bit NF4 & DiLoCo-QLoRA Foundation

3.1 Zero-Copy Meta-Device Streaming & 4-Bit NormalFloat Quantization

Standard model loaders instantiate a dense FP16/FP32 weight tree in system RAM before transferring tensors to the GPU, causing host pagefile exhaustion on 16 GB RAM gaming PCs. In Project HiveMind (`src/hivemind/core/quantization.py`), we initialize the causal Transformer architecture on PyTorch's zero-byte `meta` device (`init_empty_weights`) and stream each tensor slice directly from memory-mapped `safetensors` shards onto `cuda:0`, immediately quantizing

Table 1: Inventory of the 120 Lean 4 lemmas in `lean4/HiveMindSpec.lean`. Every lemma compiles with zero `sorry` and verifies discrete arithmetic, necessity counterexamples, and resource bounds over $\mathbb{N}/\mathbb{Z}$.

Season / Namespace	Theorem Range	Count	Core Mathematical Invariants Proved	Status
Pillars 1–4 & Phase 2	Thms. 1–14	14	NF4 4.125 b/w, 8 GB RTX 2070 ceiling, 10% Spot-Check (20× savings), Multi-Krum, Top-2 MoE, Async DMA 0 ms stall	compiles
Season 3 (Prefix Trie & 0-RTT)	Thms. 15–26	12	Prefix-Trie FLOP savings, RFC 9001 QUIC 0-RTT monotonic anti-replay, speculative rejection sampling invariance	compiles
Season 4 (DAO & Super-Ring)	Thms. 27–32	6	Quadratic voting cost, Steamworks anti-Sybil bound, Continental Super-Ring hop bound, SVD rank truncation, OPoI Merkle depth	compiles
Season 5 (Strategy & 64-MoE)	Thms. 33–40	8	TIES sign consensus, Interactive Bisection $\lceil \log_2 L \rceil$, 2-Level 64-Expert Router (4×), FP8 Paged KV-Cache, Fisher SVD budget	compiles
Season 6 (EF21 & 128-MoE)	Thms. 41–44, 57–69	17	3-Tier 128-Expert Router (8× FLOP savings), EF21 error-feedback contraction, energy split, UCB1 bandit optimality	compiles
Seasons 7–9 (Hardening & Safety)	Thms. 45–56, 70–77	20	Adaptive median norm clipping, staleness window rejection, thermal hysteresis deadband, WDDM TDR preemption, ZK-OPoI v4	compiles
Season 10 (Next-Gen DiLoCo)	Thms. 78–90	13	PA-CGAD cosine cutoff, FoMoE ring savings & Skip-Token, PULSELoCo half-ULP gate, Skip-Attention CAR, IsoLoCo, AutoLoCo, HeLoCo, `prime-diloco` 0 B VRAM, SparseLoCo 2-bit, LoopedMoE, MuLoCo	compiles
Season 11 (Looped FP & IsoSparse)	Thms. 91–100	10	Fixed-point recurrence contraction, early-exit FLOP savings, 3× terminal KV sharing, multi-wave FoMoE VRAM & payload bounds	compiles
Season 12 (OpenDiLoCo & H1–H10)	Thms. 101–112	12	Flat-bucket slice partition, fragment byte count, piecewise PA-CGAD cutoff, 16×/32× 2-bit DCT gate, MuLoCo spread contraction, EF21 telescoping sum, TBPTT memory, Skip-Token FLOPs	compiles
Season 13 (Necessity & Inhabitation)	Thms. 113–116	4	Disabled-EF21 mass loss counterexample, missing PA-CGAD cutoff variance inflation counterexample, violated Multi-Krum quorum counterexample, `Nonempty InhabitedRTX2070SwarmPackage` witness	compiles
Season 14 (Decoupled DiLoCo Quorum)	Thms. 117–120	4	Grace window $\gamma\,\xi_{\text{slack}}$ strictly below positive slack for $\gamma < 1$, exhausted slack ⇒ zero grace, token-weight monotonicity, quorum admitted-count bounds $K \le \lvert\mathcal{A}\rvert \le M$	compiles
Total Formal Specification	**Theorems 1–120**	**120**	Arithmetic over $\mathbb{N}/\mathbb{Z}$; standard Lean 4 axioms (`propext`, `Quot.sound`, `Classical.choice`)	120 / 120 compile

linear projections $W_0 \in \mathbb{R}^{d_{\text{out}} \times d_{\text{in}}}$ into 4-bit NormalFloat (`NF4`) [14] with block size $B = 64$:

$$\hat{W}_{\text{NF4}}(i) = \arg\min_{j \in \{0,\dots,15\}} \left| \frac{W_0(i)}{s_b} - q_j \right|, \qquad s_b = \max_{i \in \text{block } b} |W_0(i)|, \tag{1}$$

where $q_0, \dots, q_{15} \in [-1, 1]$ are the information-theoretically optimal quantiles of $\mathcal{N}(0, 1)$, packed two 4-bit indices per `uint8` byte. Block scales s_b are further compressed via 8-bit double quantization, yielding an effective footprint of 4.125 bits/parameter (**Theorem 1**). On `Qwen/Qwen2.5-0.5B`, the entire frozen backbone occupies just **175.96 MB** of VRAM with **0 bytes** of intermediate CPU heap duplication.

3.2 DiLoCo Inner Loop & Baseline Top-k + `float8_e4m3fn` Deltas

Each worker $k \in \{1, \dots, K\}$ assigned to domain branch $d \in \mathcal{D}$ freezes $\hat{W}_{\text{NF4}}$ and attaches trainable low-rank adapters $\theta_k = \{A_k, B_k\}$ of rank $r \in \{8, 16, 32, 64\}$ across all attention and SwiGLU projections ($\{W_q, W_k, W_v, W_o, W_{\text{gate}}, W_{\text{up}}, W_{\text{down}}\}$):

$$h = \text{Dequant}_{\text{FP16}}(\hat{W}_{\text{NF4}})x + \frac{\alpha}{r} B_k A_k x, \qquad A_k \in \mathbb{R}^{r \times d_{\text{in}}},\ B_k \in \mathbb{R}^{d_{\text{out}} \times r}. \tag{2}$$

Worker k executes H local inner steps on its Content-Addressed Hugging Face shard (`cid://sha256/...`) with **zero network communication** and computes its outer pseudo-gradient delta $\Delta_k^{(t)} = \theta^{(t-1)} - \theta_k^{(t,H)}$. In baseline mode (`compression_mode="topk_fp8"`), retaining Top-k ($\rho = 0.20$) entries quantized to `float8_e4m3fn` compresses a 16.78 MB rank-16 QLoRA delta into **5.04 MB** (3.33× wire reduction, or $> 1,666\times$ total bandwidth reduction at $H = 500$, **Theorem 3**). Section 7 details how Season 8 upgrades this wire layer with **DeMo 2D chunked DCT + 2-bit SparseLoCo + PULSELoCo** to achieve **39.96× package compression**.

4 Pillar II: Byzantine Fault Tolerance Without 2× Redundancy

4.1 10% Deterministic Micro-Checkpoint Spot-Checks & Hardware Circuit-Breaker

To verify untrusted consumer GPUs without running every workunit twice, we enforce deterministic CUDA execution (`CUBLAS_WORKSPACE_CONFIG=:4096:8`, `torch.use_deterministic_algorithms(True)`, and deterministic data-loader seeding derived from `prev_block_hash`). During its H inner steps, worker k records a cryptographic micro-checkpoint hash every s steps ($M = H/s = 10$ segments):

$$h_{k,m} = \text{SHA-256}\left(\theta_k^{(t,m\cdot s)}\right), \qquad m \in \{0, 1, \ldots, M\}. \tag{3}$$

The `DeterministicSpotCheckValidator` (`src/hivemind/boinc/validator.py`) selects a single random segment $m^* \sim \mathcal{U}\{0, \ldots, M-1\}$ and replays s steps from $\theta_k^{(t,m^*s)}$. The submission is accepted iff $\|\theta_{\text{validator}}^{(t,(m^*+1)s)} - \theta_k^{(t,(m^*+1)s)}\|_\infty \leq \epsilon = 10^{-4}$ (**Theorems 4–5**). Concurrently, the `GPUExecutionCircuitBreaker` (`src/hivemind/security/gpu_execution_circuit_breaker.py`) enforces thermal hysteresis deadbands (83°C throttle / 88°C abort), Windows WDDM TDR step-latency watchdogs (< 1.5 s), and NaN loss early abort (**Theorems 49–52**).

4.2 Pre-Krum Sanitization, Multi-Krum 2σ Cosine Filter & ZK-OPoI v4

Before outer aggregation, `FederatedLearningSecurityGuard` (`src/hivemind/security/federated_learning_hardening.py`) quarantines non-finite or free-rider zero-gradient submissions, applies Multi-Krum neighborhood selection ($k = n - f - 2 \geq f + 1$, **Theorem 6**) with a 2σ median pairwise cosine similarity gate, and clips surviving deltas via adaptive median-L_2 and coordinate-L_∞ neurotoxin bounds (**Theorem 45**). For decentralized inference, **ZK-OPoI v4** (`src/hivemind/swarm/swarm_fabric.py`) binds per-token activation commitments to their exact batch index, layer index, and token position inside a SHA-256 Merkle tree with interactive $\lceil \log_2 L \rceil$ bisection dispute resolution (**Theorems 35–36, 70–77**).

5 Pillar III & Phase 2 Swarm Fabric: Factored BTM Upcycling & Geo-Rings

When E domain branches converge, `upcycle_branches_to_sparse_moe()` (`src/hivemind/core/btm_upcycle.py`) converts them into a unified **Factored Sparse MoE** where all E SwiGLU experts at layer ℓ share the single frozen 4-bit NF4 base FFN $(\hat{W}_{\text{gate}}, \hat{W}_{\text{up}}, \hat{W}_{\text{down}})$ and keep only their lightweight FP16 LoRA adapters (A_e, B_e) in VRAM:

$$\begin{aligned} E_{\ell,e}(x) = \left(\hat{W}_{\text{down}} + \tfrac{\alpha}{r} B_{\text{down},e} A_{\text{down},e}\right) \Big[&\text{SiLU}\left(\hat{W}_{\text{gate}} x + \tfrac{\alpha}{r} B_{\text{gate},e} A_{\text{gate},e} x\right) \\ &\odot \left(\hat{W}_{\text{up}} x + \tfrac{\alpha}{r} B_{\text{up},e} A_{\text{up},e} x\right) \Big]. \end{aligned} \tag{4}$$

Across WAN nodes, the **Phase 2 Swarm Fabric** (`src/hivemind/swarm/swarm_fabric.py`) provides: (M1) Kademlia XOR < 20 ms Regional Geo-Rings with RFC 8489/8656 STUN/TURN NAT traversal and RFC 9001 QUIC 0-RTT anti-replay (**Theorems 11, 16–24**); (M2) 3-tier NVMe $\rightarrow$ Pinned Host RAM $\rightarrow$ CUDA double-buffered asynchronous DMA streaming (**Theorem 12**); (M3) Prefix-Trie deduplicated Eagle/Medusa token-tree speculation ($\gamma = 6$) with Triton `float8_e4m3fn` hidden-state compression (**Theorems 13, 15**); and (M4) an OpenAI-compatible `/v1/chat/completions` gateway.

6 Missing MoE Architecture: 128-Expert 3-Tier Routing, FoMoE, Skip-Attention & Looped Recurrence

Earlier revisions documented only flat 4-to-8 branch BTM upcycling. Scaling to 64–128 community experts across residential WAN links raises five further design problems. This section describes the components we implemented for them; none has yet been evaluated at the target scale (the largest MoE actually trained has 4 experts, Section 8.3). A caveat on the router: gating FLOPs are small compared with expert FFN FLOPs, and hierarchical gating restricts which expert combinations are reachable, so the saving below must eventually be weighed against routing quality.

6.1 3-Tier 128-Expert Hierarchical MoE Router (`ThreeTierHierarchicalMoERouter`)

In a flat $E = 128$ Sparse MoE, computing $\mathrm{Softmax}(W_g^\top x)$ requires $E = 128$ inner products of dimension d_{model} per token at every layer, and speculative prefetching over a token tree must evaluate all 128 expert columns. In `src/hivemind/core/btm_moe.py` (`HM-S6-02`), we partition the $E = 128$ experts into a 3-tier hierarchy of $S = 4$ super-clusters $\times M = 4$ macro-domains $\times U = 8$ micro-experts ($4 \times 4 \times 8 = 128$):

$$s^* = \arg\max_{s \in \{1..S\}} P_{\text{super}}(s \mid x), \qquad m^* = \arg\max_{m \in \{1..M\}} P_{\text{macro}}(m \mid x, s^*),$$
$$\mathcal{T}(x) = \text{Top-}k\Big(W_{\text{micro}}^{(s^*,m^*)} x\Big). \tag{5}$$

Per token, the router evaluates only $S + M + U = 4 + 4 + 8 = \mathbf{16}$ inner products of length d_{model} instead of 128—an exact **8.0× gating FLOP reduction** (an operation count; checked in H3 at toy scale). Furthermore, `predict_candidate_experts()` exposes the exact factored path probability $P(e \mid x) = P_{\text{super}}(s^*) P_{\text{macro}}(m^* \mid s^*) P_{\text{micro}}(e \mid s^*, m^*)$ ($\sum_e P(e \mid x) \le 1$) to drive token-tree lookahead DMA prefetching (`prefetch_token_tree_lookahead`).

6.2 Federated Partial Expert Replication (`FoMoE`) & Ghost-Expert `Skip-Token`

Following Sani *et al.* (`FoMoE`, `arXiv:2606.19025`) [15] and Google DeepMind's *Scaling Laws for DiLoCo* (`arXiv:2503.09799`) [11], requiring every consumer GPU to replicate and synchronize all $E = 128$ experts wastes both VRAM and outer-loop WAN bandwidth. In `FoMoEPartialReplicaPlanner` (`src/hivemind/swarm/diloco_nextgen.py`) and `UpcycledSparseMoEModel.set_local_expert_subset()` (`src/hivemind/core/btm_upcycle.py`, `HM-S8-06`), each of the M workers hosts only $M_{\text{loc}} = \frac{O_e}{M} E$ resident experts (where $O_e \in \{1, \dots, M\}$ is the replication overlap factor) while the remaining $E - M_{\text{loc}}$ experts act as **Ghost Experts**:

$$R(O_e) = \frac{2(O_e - 1)}{O_e}, \qquad V_{\text{comm}}(O_e) = \frac{2(M-1)}{M} B_{\text{dense}} + \left(R(O_e) + \gamma_{\text{shuf}} \left(1 - \frac{O_e}{M} \right) \right) M_{\text{loc}} B_{\text{expert}}. \tag{6}$$

During local inner-loop forward passes, any token slot routed by the global router to a non-resident Ghost Expert $e \notin \mathcal{E}_{\text{loc}}$ is dropped locally via **`Skip-Token`**:

$$y_{\text{FoMoE}}(x) = \sum_{e \in \mathcal{T}(x) \cap \mathcal{E}_{\text{loc}}} \tilde{g}_e(x)\, E_{\ell,e}(x), \qquad \text{RPC}_{\text{remote}}(x) = 0. \tag{7}$$

Evaluating this cost model (check H3) with $M = 16$ workers with overlap $O_e = 4$ (32 resident experts and 96 Ghost Experts per worker) predicts a 3.46× reduction in outer ring volume, with no synchronous remote FFN calls because ghost-routed tokens are skipped. This is a model prediction, not a network measurement; the effect of skipping on quality is studied in [15] but not yet in our setting.

σ-MoE routing and measured skip fraction. FoMoE's experts are selected by independent sigmoid gates (σ-MoE, following Csordás *et al.*) rather than a competitive softmax, and its cost model (their Eq. 2–3) uses the ideal scaling $\sigma_{\text{st}} = N_{\text{le}}/N_e$ while explicitly recommending the *measured* ghost-assignment frequency whenever routing is imbalanced. `FoMoEPartialReplicaPlanner` models only the ideal factor; `src/hivemind/core/fomoe_sigma_routing.py` adds `sigmoid_independent_topk_routing` (global router, ghost slots skipped *after* routing, realised ghost fraction returned per batch) and `skip_token_flops_per_token` (their Eq. 3 with either factor, and the N_{le}/N_e gate factor only when the router itself is partitioned). On the toy two-layer 128-expert configuration of `tests/test_fomoe_sigma_routing.py` (32 resident experts, top-2) the ideal factor and a measured 50% ghost fraction give 1,432 vs. 1,832 FLOPs per token, so the ideal factor under-estimates compute by 28% under that imbalance. Neither function has been run on a trained model.

6.3 `Skip-Attention` Speculative Prefetch & Cache-Aware Routing (`CAR`)

When serving all E experts locally via 3-tier NVMe → Pinned Host RAM → VRAM streaming, waiting until Layer $\ell + 1$'s self-attention finishes to evaluate Layer $\ell + 1$'s router exposes the PCIe DMA transfer latency. Inspired by the multi-tier expert caching and cache-aware routing of Paul Merolla's `fomoe` inference engine [16] and by expert prefetching in `learning-at-home/hivemind` [38], our `SkipAttentionSpeculativeRouter` (`src/hivemind/swarm/diloco_nextgen.py`, `HM-S8-07`) evaluates Layer $\ell + 1$'s RMSNorm and router projection $W_{g,\ell+1}$ directly on Layer ℓ's **post-FFN residual stream** $x_\ell^{\text{post-FFN}}$ *before* Layer $\ell + 1$'s self-attention begins:

$$\hat{\mathcal{T}}_{\ell+1}^{\text{spec}}(x) = \text{Top-}k\Big(W_{g,\ell+1}\, \text{RMSNorm}_{\ell+1}\Big(x_\ell^{\text{post-FFN}}\Big)\Big). \tag{8}$$

The predicted experts $\hat{\mathcal{T}}_{\ell+1}^{\text{spec}}$ are streamed asynchronously from Pinned Host RAM into the alternating lookahead CUDA double-buffer slot (`slot_A`/`slot_B`) in parallel with Layer $\ell + 1$'s self-attention compute. Once self-attention finishes and true post-attention router logits $z^{\text{true}} \in \mathbb{R}^E$ are available, any selected expert $e^* \notin \mathcal{C}_{\text{VRAM}}$ that missed the speculative prefetch is checked against the **Cache-Aware Routing (`CAR`)** threshold τ_{CAR}:

$$\text{If } \min_{e_c \in \mathcal{C}_{\text{VRAM}} \setminus \mathcal{T}} \left(z_{e^*}^{\text{true}} - z_{e_c}^{\text{true}}\right) \le \tau_{\text{CAR}}, \quad \text{substitute } e^* \leftarrow \arg\max_{e_c \in \mathcal{C}_{\text{VRAM}} \setminus \mathcal{T}} z_{e_c}^{\text{true}}. \tag{9}$$

In unit check H5 the speculative Top-2 prediction matched the true routing in 95.83% of cases. That figure is *not* a property of any trained model: the check uses random 32-dimensional states and sets the post-attention state to the post-FFN state plus Gaussian noise of scale 0.08, so the accuracy is determined by that noise level. Measuring speculative accuracy on real Qwen2.5 activations is future work.

6.4 Weight-Tied `LoopedExpertBackbone`, Fixed-Point Halting & Truncated BPTT

To multiply reasoning depth on 8 GB consumer GPUs without multiplying model weight VRAM, `LoopedExpertBackbone` (`src/hivemind/core/btm_upcycle.py`, `HM-S7-01/02`) wraps an upcycled Sparse MoE decoder stack into a three-stage recurrent architecture synthesized from *Towards Looped Models Done Right, Part I: Topology, Input Injection, Recurrent-State Design* (`arXiv:2610.23036`) [17] and *Part II: Rethinking at Fixed Points* (`arXiv:2610.06833`) [18]:

$$\begin{aligned} h^{(0)} &= \mathrm{Prelude}(x), \qquad y = \mathrm{Coda}\Big(h^{(T)}\Big), \\ h^{(t)} &= \mathrm{RecurrentCore}\Big(\mathcal{A}_t\Big(h^{(t-1)} + \mathbb{I}[t>1]h^{(0)}\Big)\Big) \quad (t = 1, \ldots, T), \end{aligned} \tag{10}$$

where $\mathcal{A}_t(u) = u + B_t^{\mathrm{step}} A_t^{\mathrm{step}} u$ is a lightweight per-step residual LoRA adapter initialized with $B_t^{\mathrm{step}} = 0$ (exact identity at initialization). `LoopedExpertBackbone` implements three systems optimizations (the associated Lean lemmas only count bytes):

1. **Zero Duplicate Core Weight VRAM:** The recurrent core layers are weight-tied across all T loop steps, saving $(T-1)B_{\mathrm{core}}$ bytes of weight storage (669,888 B saved at $T = 4$, multiplying effective depth from $4 \to 10$ layers with only 4,096 B of step adapters).

2. **Per-Token Fixed-Point Convergence Early Exit:** After each recurrent pass t, each active token position i evaluates its relative state drift $r_i^{(t)} = \|h_i^{(t)} - h_i^{(t-1)}\|_2 / \max(\|h_i^{(t-1)}\|_2, 10^{-6})$. Tokens satisfying $r_i^{(t)} \le \epsilon_{\mathrm{fp}}$ freeze their hidden state for subsequent passes while remaining visible as causal attention context.

3. **RNG-Restored Truncated Fixed-Point BPTT (`truncated_bptt_steps`):** When $k_{\mathrm{bptt}} < T$ and adaptive halting is active, forward passes discover the exact per-token halting trajectory without storing intermediate activation graphs, then replay only the trailing k_{bptt} recurrent passes under `torch.random.fork_rng` with restored CPU/CUDA RNG state and preserved MoE routing counters.

   In unit check H4 (`fixed_point_tol = 0.65` with $T = 4$ loop steps), tokens halt after a non-trivial mean of **3.05** recurrent passes (80% early-exit rate, mean residual 0.5215). In Experiment E3 (Section 8, Figure 3a), sweeping $\epsilon_{\mathrm{fp}} \in [0.0, 1.10]$ across a $T = 6$ looped MoE backbone maps the smooth trade-off between recurrent FLOP savings ($0\% \to 71.88\%$) and relative output logit drift ($0\% \to 58.61\%$).

6.5 Subspace-Aware Attention & Expert Merging: `Iso-CTS` & `TSV`

Standard BTM upcycling uniformly averages self-attention LoRA deltas ($\bar{\Delta}_{\mathrm{attn}} = \frac{1}{E}\sum_{e=1}^{E} \Delta_{\mathrm{attn},e}$), which suffers from singular-direction dominance collapse when heterogeneous domain branches are combined. Building on isotropic merging (Iso-C / Iso-CTS) by Marczak *et al.* [20], its use as a DiLoCo aggregator in IsoLoCo by Horoi *et al.* [21], and Task Singular Vectors by Gargiulo *et al.* [22], `upcycle_branches_to_sparse_moe()` supports two spectral subspace mergers (`HM-S8-03`, **Hypothesis H6**):

- **Reputation-Weighted `ISO-CTS` (`attention_merge_mode="iso_cts"`):** Elects sign consensus via reputation-weighted TIES, extracts the top $c = \lfloor \rho_c \min(d_{\mathrm{out}}, d_{\mathrm{in}}) \rfloor$ common singular vectors U_{common}, projects worker residuals onto the orthogonal complement $(I - U_{\mathrm{common}} U_{\mathrm{common}}^{\top})$, orthogonalizes the combined basis via SVD Procrustes projection, and flattens the singular value spectrum to its isotropic mean $\bar{\sigma} = \frac{1}{r}\sum_i \sigma_i$, which makes the merged singular-value condition number exactly 1 by construction (H6 confirms $2.5988 \to 1.0000$ on a toy merge; whether this helps downstream quality in our setting is untested).

- **Task Singular Vector Decorrelation (`attention_merge_mode="tsv"`):** Extracts the top $k_w = \lfloor d_{\min}/M \rfloor$ singular triplets $(U_m, \Sigma_m, V_m^\top)$ per branch and whitens inter-branch subspace interference via orthogonal Procrustes projection $U_{\text{orth}} = P_u Q_u^\top, V_{\text{orth}}^\top = P_v Q_v^\top$, achieving $\|U_{\text{orth}}^\top U_{\text{orth}} - I\|_F = \mathbf{6 \times 10^{-6}}$ (**Theorem 110**).

7 OpenDiLoCo & Google DeepMind Outer-Loop Ecosystem

To make outer-loop aggregation resilient to asynchronous WAN stragglers, residential upload limits, and 8 GB consumer GPU memory ceilings, Project HiveMind adapts ideas and, where licences allow, code from eight open-source repositories and recent papers from Google DeepMind, Prime Intellect, Mila, Covenant AI, Nous Research, and Cambridge / Flower Labs (Table 2). We credit these works for the underlying methods; HiveMind's contribution is their integration under an 8 GB memory budget.

Table 2: Open-Source GitHub Repositories & Foundational Papers Integrated into Project HiveMind's `OpenDiLoCo` + `Sparse MoE` Architecture (`src/hivemind/swarm/diloco_nextgen.py`).

Repository / Project	Primary Authors & Lab	Reference	Integrated HiveMind Module & Role
`google-deepmind/asyncdiloco`	Liu, Chhaparia, Douillard *et al.* (DeepMind)	[3, 4]	Reference for asynchronous outer updates; our fragment streaming (`synced_fragments`) follows Streaming DiLoCo
`Decoupled DiLoCo` (paper only; no public code)	Douillard, Rush, Donchev, Charles *et al.* (DeepMind & Google Research)	[5]	`DecoupledDiLoCoQuorumSyncer` (`decoupled_diloco.py`): minimum quorum K, adaptive grace window, token weights, RDA merge
`PrimeIntellect-ai/OpenDiLoCo`	Jaghouar, Ong, Hagemann (Prime Intellect)	[12]	Decentralized outer-step orchestration & Hivemind P2P fault-tolerant gradient averaging
`PrimeIntellect-ai/prime-diloco`	Prime Intellect Team	[12]	`CPUOffloadedFlatBucketOuterState`: contiguous 1D FP32 CPU master buffer (`0 B` extra GPU VRAM)
`one-covenant/SparseLoCo`	Sarfi, Belilovsky *et al.* (Mila / Covenant)	[24, 25]	`ComputeVisibleSparseLoCoCompressor` & `DCTSparse2BitTensorPayload` (2-bit 4-bin LUT + EF)
`bloc97/DeMo`	Peng, Quesnelle, Kingma (Nous Research)	[23]	`ChunkedOrthonormalDCTTransform`: 8×8 Type-II orthonormal DCT with deterministic `index_copy_`
`shoroi/isoloco`	Horoi, Thérien, Wolf, Belilovsky (Mila)	[21, 20]	`ReputationWeightedIsoCTSMerger` (`ISO-C/ISO-CTS`) & `TSVDecorrelatedMerger`
`pmerolla/fomoe`	Paul Merolla	[16]	Multi-tier expert cache & cache-aware routing; inspires `SkipAttentionSpeculativeRouter` (FoMoE partial replication follows [15])
`learning-at-home/hivemind`	Ryabinin, Diskin, Mazur *et al.*	[38, 39]	Kademlia DHT peer rings, background expert prefetching & decentralized MoE routing

7.1 `OpenDiLoCo` & `prime-diloco`: Contiguous 1D CPU Flat-Bucket Outer State (`0 B` GPU VRAM)

In naive PyTorch DiLoCo implementations, holding a copy of the outer master weights $\theta^{(t-1)}$ and outer Nesterov velocity buffer $v^{(t)}$ on `cuda:0` doubles the adapter/backbone memory footprint during every outer step. Adapting `PrimeIntellect-ai/prime-diloco` (`src/zeroband/diloco.py`) and `PrimeIntellect-ai/OpenDiLoCo` (`arXiv:2407.07852`) [12], `CPUOffloadedFlatBucketOuterState` (`src/hivemind/swarm/diloco_nextgen.py`) and `DiLoCoOuterOptimizer(use_cpu_flat_bucket=True)` (`src/hivemind/core/diloco_outer.py`, `HM-S8-02`) pack all parameter fragments into a single contiguous 1D FP32 host RAM allocation $\mathbf{w}_{\text{flat}} \in \mathbb{R}^N_{\text{CPU}}$ with deterministic slice offsets $\{[\text{lo}_k, \text{hi}_k)\}_{k=1}^F$:

$$\begin{aligned} \mathbf{v}_{\text{flat}}[\text{lo}_k : \text{hi}_k] &\leftarrow \mu \mathbf{v}_{\text{flat}}[\text{lo}_k : \text{hi}_k] + \bar{\Delta}_k^{(t)}, \\ \mathbf{w}_{\text{flat}}[\text{lo}_k : \text{hi}_k] &\leftarrow \mathbf{w}_{\text{flat}}[\text{lo}_k : \text{hi}_k] - \eta \left(\mu \mathbf{v}_{\text{flat}}[\text{lo}_k : \text{hi}_k] + \bar{\Delta}_k^{(t)} \right). \end{aligned} \tag{11}$$

By construction the outer state then uses no GPU memory; the cost moves to host RAM and to one host-to-device copy per outer step, which we have not yet timed. Check H1 confirms

the flat-bucket update matches the per-tensor Nesterov update to single-ULP FP32 precision ($\max \|\Delta\theta\|_\infty = 2.384 \times 10^{-7}$).

7.2 Decoupled DiLoCo: Minimum Quorum, Adaptive Grace Window & Radial-Directional Averaging

Google DeepMind's *Decoupled DiLoCo* (`arXiv:2604.21428`) [5] removes the lock-step outer all-reduce altogether: M independent learners report to a CPU-resident *syncer* that aggregates a fragment as soon as a minimum quorum of $K \leq M$ learners has arrived, optionally waits an adaptive grace window for late learners, weights each learner by its token throughput, and merges the per-learner outer gradients with Radial-Directional Averaging (RDA). This is the regime a volunteer swarm actually lives in (stragglers, churn, heterogeneous GPUs), and until this revision HiveMind cited the paper but implemented none of it. `DecoupledDiLoCoQuorumSyncer` (`src/hivemind/swarm/decoupled_diloco.py`, `SI-12`) implements the four mechanisms of Algorithm 2 of [5] as separately testable pieces:

1. **Minimum quorum.** The first K learners by arrival are always admitted; a round with fewer than K reports does not merge (**Theorem 120** fixes $K \leq |\mathcal{A}| \leq M$ and shows that the degenerate $K = 0$ rule admits nobody).

2. **Adaptive grace window.** With $\xi_{\text{slack}} = \tau\,\xi_{\text{step}} - (\xi_{\text{quorum}} + \xi_{\text{sync}})$ (their Eq. 3) tracked by exponential moving averages, learners arriving within $\xi_{\text{grace}} = \gamma \max(0, \xi_{\text{slack}})$ of the quorum instant are also admitted. **Theorems 117–118** check that $\gamma < 1$ keeps $\xi_{\text{grace}} < \xi_{\text{slack}}$ whenever the slack is positive and that an exhausted budget gives $\xi_{\text{grace}} = 0$.

3. **Token-weighted merging.** $w_m = c_m^{\text{tokens}} \cdot c_m^{\text{tokens}} / c_m^{\text{steps}}$ ("quantity × quality"; a learner with no inner step has weight 0; **Theorem 119**).

4. **Radial-Directional Averaging.** $\text{RDA}(\{(\Delta_m, w_m)\}) = \left(\sum_m \bar{w}_m \|\Delta_m\|\right) \phi\left(\sum_m \bar{w}_m \phi(\Delta_m)\right)$ with $\phi(x) = x/\|x\|$ and $\bar{w}_m = w_m / \sum_j w_j$, so that equal-norm, nearly orthogonal learner updates keep their norm R instead of shrinking to $R/\sqrt{M}$ under direct averaging; the outer learning rate therefore no longer needs retuning with M.

The syncer emits Δ_p and leaves the outer optimizer untouched: check `H11` chains it into the CPU flat-bucket Nesterov step above with `0 B` extra GPU memory. In `H11` (`artifacts/decoupled_diloco_quorum_check.json`; three arms, one positive and two negative controls) RDA returns norm R for $M \in \{2, 4, 8, 16\}$ orthogonal equal-norm deltas while the direct mean follows $R/\sqrt{M}$ exactly (RDA-to-direct ratio **2.8284** at $M = 8$); with $\tau = 2$, $\xi_{\text{step}} = 4.0\,\text{s}$, $\xi_{\text{quorum}} = 0.3\,\text{s}$, $\xi_{\text{sync}} = 1.0\,\text{s}$ and $\gamma = 0.5$ the controller opens a **3.35** s window on 6.7 s of slack, admits 6/8 learners, defers two stragglers carrying 10,000 of 40,000 tokens, and the stragglers' coordinates do not leak into Δ_p (leak = 0.0); a $K = M = 8$ quorum with seven reports correctly refuses to merge. These are bookkeeping checks on synthetic tensors: the goodput and quality results under chaos engineering are DeepMind's, not ours, and nothing here has yet run across machines.

What RDA does to the optimization problem is elementary and worth stating, because it turns the RQ2 prediction of Section 9 into a statement about one scalar.

Proposition 7.1 (RDA is direct averaging with an adaptive outer-learning-rate multiplier)**.** *Let $\Delta_1, \ldots, \Delta_M \in \mathbb{R}^d$ be non-zero and $\bar{w}_1, \ldots, \bar{w}_M \geq 0$ sum to one; write $u = \sum_m \bar{w}_m \Delta_m$ for the direct weighted average and suppose $u \neq 0$ and $\sum_m \bar{w}_m \phi(\Delta_m) \neq 0$. Then*

$$\text{RDA}(\{(\Delta_m, \bar{w}_m)\}) \;=\; r\,\|u\|\,\phi(u_\phi) \quad \textit{with} \quad r \;=\; \frac{\sum_m \bar{w}_m \|\Delta_m\|}{\|u\|} \;\geq\; 1, \tag{12}$$

where $u_\phi = \sum_m \bar{w}_m \phi(\Delta_m)$ *is the weighted mean* direction*; equality* $r = 1$ *holds iff all* Δ_m *with* $\bar{w}_m > 0$ *are positively collinear. If the* Δ_m *have a common norm* R*, then* $\phi(u_\phi) = \phi(u)$ *(RDA and direct averaging point the same way) and*

$$r \;=\; (\bar{w}^\top C\, \bar{w})^{-1/2}, \qquad C_{ij} = \cos \angle(\Delta_i, \Delta_j), \tag{13}$$

so for M *equally weighted orthogonal learners* $r = \sqrt{M}$*, and for equally weighted learners with mean pairwise cosine* $\bar{c}$*,* $r = \big(1/M + (1 - 1/M)\,\bar{c}\big)^{-1/2}$*.*

Proof. $\|\mathrm{RDA}\| = \sum_m \bar{w}_m \|\Delta_m\|$ by definition, and $\|u\| \le \sum_m \bar{w}_m \|\Delta_m\|$ is the triangle inequality, with equality iff the weighted terms are positively collinear. With a common norm R, $\phi(\Delta_m) = \Delta_m / R$, hence $u_\phi = u/R$ and the directions coincide; $\|u\|^2 = \sum_{i,j} \bar{w}_i \bar{w}_j \langle \Delta_i, \Delta_j \rangle = R^2\, \bar{w}^\top C \bar{w}$ gives the second formula, and $\bar{w} = \mathbf{1}/M$ with $C = I$ gives $\sqrt{M}$. □

Two consequences shape the experiments. First, in the common-norm case RDA changes nothing but the step length: a run with RDA at outer learning rate η takes, in each round t, exactly the step that direct averaging would take at $\eta \cdot r_t$. The RQ2 prediction is therefore not that RDA finds a better direction but that the sequence r_t absorbs the $\sqrt{M}$ shrinkage, so that one η serves every M. Second, r_t is a cheap, per-round observable ($\|\mathrm{RDA}\|/\|u\|$), and with the mean pairwise cosine it is reported for every cell of E5 (Section 9.6): a testbed on which $\bar{c} \approx 0.9$ has $r_t \approx 1.04$ and cannot separate the merges, which is precisely what E5-toy found. Theorem 120 and the H11 check verify the integer bookkeeping and the $\sqrt{M}$ instance; the proposition itself is elementary and is not among the Lean lemmas (the local Lean build has no real-valued norm).

7.3 Streaming DiLoCo Fragments & Cosine-Gated Adam-Decay (`PA-CGAD`)

Google DeepMind's `Streaming DiLoCo` (`arXiv:2501.18512`) [4] reduces peak WAN bandwidth by synchronizing only a subset of parameter fragments $\mathcal{S}_t \subset \{1, \dots, F\}$ per outer round (**Theorem 102**). However, under asynchronous WAN delays τ_w and staggered fragment ages a_f, standard outer Adam/Nesterov suffers from *stale variance pollution*: stale pseudo-gradients inflate the second-moment buffer v_f, shrinking future honest step sizes. Following V. Shah and J. Sun (`CGAD / PA-CGAD`, `arXiv:2605.09126`) [19], `CosineGatedAdamDecayOuterOptimizer` (`HM-S8-01`) defines the effective fragment staleness $\tau_{\mathrm{eff}}(f) = \max(0, \tau_w(f), a_f)$ and gates $\bar{\Delta}_f^{(t)}$ **before** updating (m_f, v_f):

$$\gamma(\tau) = \frac{1}{2}\left(1 + \cos\left(\frac{\pi\tau}{\tau_{\mathrm{cut}}}\right)\right) \mathbb{I}[\tau < \tau_{\mathrm{cut}}], \qquad \sigma(\tau) = \gamma(\tau) e^{-\alpha\tau}, \qquad \tilde{g}_f = \sigma(\tau_{\mathrm{eff}}(f))\, \bar{\Delta}_f^{(t)}. \tag{14}$$

When $\tau_{\mathrm{eff}}(f) \ge \tau_{\mathrm{cut}}$, $\sigma(\tau_{\mathrm{eff}}(f)) = 0$ and the fragment's moment buffers (m_f, v_f) are completely frozen (**Theorems 78, 103**). Furthermore, for all $\tau \ge 0$, the staleness bias satisfies the uniform upper bound:

$$\sup_{\tau \ge 0} \tau\sigma(\tau) \le \sup_{\tau \ge 0} \tau e^{-\alpha\tau} = \frac{1}{e\alpha}. \tag{15}$$

This bound is analytic and is due to [19]. Check H2 only confirms that our implementation of σ respects it ($\max_{\tau \in [0,64]} \tau\sigma(\tau) = 1.7417 \le 1.8394$ at $\alpha = 0.2$, $\tau_{\mathrm{cut}} = 32$) and that cut-off fragments leave (m_f, v_f) untouched; it says nothing about training dynamics under real delays. Two further DeepMind and Meta results bound what the outer loop can hide. *Eager updates* [9] overlap the outer all-reduce with a whole inner phase by applying each replica's fresh local outer gradient together with the one-round-stale average of the others ($\tilde{\Delta}_m = \frac{1}{M}(\Delta_m^{(t)} - \Delta_m^{(t-H)}) + \Delta^{(t-H)}$); on a 500M model this tolerates 2.4 s of communication latency at an evaluation-loss cost of $2.67 \to 2.69$, whereas the naïve delayed variant costs $2.67 \to 3.01$ unless its outer learning rate is cut 4×. Our E8 pilot (Section 9.7) found exactly the regime this addresses, round trip $\gg$ compute, and the eager rule is the first candidate for the deferred-learner path of `HM-S9-01`.

Generalized Primal Averaging [10] shows that single-worker DiLoCo is a choppy special case of a two-constant primal-averaging scheme (μ_x for the evaluated iterate, μ_y for the gradient point) that removes the inner/outer split and one hyper-parameter; it is the natural control for the outer-momentum-restart factor of E5.

7.4 `DeMo` Chunked 2D DCT + `SparseLoCo` 2-Bit LUT + `PULSELoCo` + `EF21`

To compress outer pseudo-gradients far beyond 8-bit `float8_e4m3fn`, `src/hivemind/core/compression.py` (`compression_mode="dct_sparse_2bit"`, `HM-S8-04/05`) unifies three complementary algorithms:

1. **Compute-visible gate after `PULSELoCo` (`arXiv:2602.03839`, introduced for distributed RL post-training) [25]:** Drops per-coordinate updates $|\Delta_i| < 2^{-8}|\theta_i|$ that would round to zero when added to a BF16/FP16 parameter (**Theorem 81**).

2. **`DeMo` Orthonormal 2D Chunked Type-II DCT (`bloc97/DeMo`, `arXiv:2411.19870`) [23]:** Reshapes each LoRA delta into 8×8 blocks and projects them via the orthonormal Type-II DCT basis $C \in \mathbb{R}^{8\times 8}$ ($CC^\top = I$, measured $\|CC^\top - I\|_F = 2.3 \times 10^{-7}$), concentrating spatial gradient energy into low-frequency coefficients.

3. **`SparseLoCo` 2-Bit Statistical Centroid LUT & Bit-Packing (`one-covenant/SparseLoCo`, `arXiv:2508.15706`) [24]:** Retains the top 2% DCT frequency coefficients, quantizes them into 4 empirical statistical centroids stored as a 4-entry FP16 lookup table (8 bytes), and packs four 2-bit codes per `uint8` byte (`_pack_2bit_codes`) with deterministic `index_copy_` reconstruction (eliminating `DeMo`'s non-deterministic CUDA `scatter_reduce_`).

In check H7 a package of four 256×16 LoRA deltas is encoded in 820 B. Measured against 16-bit storage (32,768 B) this is 39.96×; against FP32 (65,536 B) it is 79.92×. Because a single 2% Top-k projection on isotropic Gaussian noise has a high single-shot relative L_2 truncation error ($\|\hat{\Delta} - \Delta\|_2/\|\Delta\|_2 = 0.9313$ for 2-bit DCT and 0.8966 for PULSE+SparseLoCo), pairing aggressive 2-bit sparsification with **EF21 error-feedback residual accumulation** [37] is essential: `EF21DiLoCoErrorFeedbackBuffer` (**Theorems 57, 107**, **Hypothesis H10**) preserves exact multi-step telescoping sum conservation $\|(\sum_{t=1}^{3} c_t + r_3) - \sum_{t=1}^{3} g_t\|_2 = \mathbf{4 \times 10^{-8}}$, and Experiment E1 (Section 8, Figure 1) demonstrates that 2-bit DCT + EF21 matches uncompressed FP32 DiLoCo within **0.052%** held-out validation loss across 12 outer rounds.

7.5 `AutoLoCo`, `HeLoCo` & Inner-Loop `MuLoCo` Newton-Schulz Preconditioning

Finally, to stabilize heterogeneous worker cadences and large replica counts:

- **`AutoLoCo` (`arXiv:2609.36662`) [33] & `HeLoCo` (`arXiv:2606.00271`) [26]:** When `AdaptiveDiLoCoCadenceController` adapts inner step count H_t, `AutoLoCoIntervalCorrector` scales outer learning rate $\eta_{\text{outer}} \leftarrow \eta_0/\sqrt{S_t/S_{\text{ref}}}$ and outer momentum $\mu_{\text{outer}} \leftarrow \mu_0^{S_t/S_{\text{ref}}}$ (0.7000 → 0.4950 when $H : 32 \to 64$, **Theorem 84**), while `HeLoCoDirectionCorrector` projects out conflicting stale drift components whenever $\langle g_k, m_{\text{ref}} \rangle < 0$ (**Theorem 85**, **Hypothesis H8**).

- **Muon-style quintic Newton-Schulz LoRA preconditioning (Muon [34]; MuLoCo, `arXiv:2505.23725` [35]; replica-scaling analysis, `arXiv:2610.19064` [36]):** In `run_diloco_inner_loop(..., use_muon_lora_preconditioner=True)` (`src/hivemind/core/diloco_inner.py`, `HM-S8-09`), 2D LoRA gradients $G \in \mathbb{R}^{m\times n}$ are normalized ($X_0 = G/\|G\|_F$) and orthogonalized via $K = 5$ quintic Newton-Schulz iterations with the coefficients of Muon [34] ($a = 3.4445, b = -4.7750, c = 2.0315$):

$$X_{k+1} = aX_k + \left(bX_kX_k^\top + c\left(X_kX_k^\top\right)^2\right)X_k. \tag{16}$$

In check H9, 5 iterations reduce the condition number of a synthetic 32×16 rank-8 gradient from 125.0 to 1.65, and validator replay on CPU reproduces the worker bit-for-bit (difference 0.0). Cross-GPU bitwise reproducibility was not tested.

7.6 Analytical Theorems, Proofs, Hypothesis-Necessity Counterexamples & 4-Definitions Contract

To make the mathematical guarantees and their failure modes self-contained, we state the three core outer-loop invariants with explicit analytical proofs and paired *Hypothesis-Necessity Counterexamples* (`Season13`, Lean 4 Theorems 113–116), followed by the 4-Definitions Contract (Table 3).

Theorem 7.2 (Multi-Step EF21 Telescoping Conservation & Necessity of Residual Carry; Lean Thms. 107 & 113)**.** *Let $\{g_t\}_{t=1}^{T} \subset \mathbb{R}^d$ be a sequence of outer pseudo-gradients and $\mathcal{C} : \mathbb{R}^d \to \mathbb{R}^d$ be any deterministic compressor (including 2-bit `DeMo` DCT + `SparseLoCo` LUT). Under the error-feedback recurrence $u_t = g_t + r_{t-1}$, $c_t = \mathcal{C}(u_t)$, $r_t = u_t - c_t$ with $r_0 = 0$, the cumulative transmitted sum satisfies the exact telescoping identity:*

$$\sum_{t=1}^{T} c_t + r_T = \sum_{t=1}^{T} g_t. \tag{17}$$

Hypothesis-Necessity Counterexample (Thm. 113): *If error feedback is disabled ($r_t \equiv 0$, so $c_t = \mathcal{C}(g_t)$) and step 1 compression is strictly contractive on positive mass ($c_1 < g_1$ with $c_2 \le g_2$), then $c_1 + c_2 < g_1 + g_2$ with positive permanent deficit $g_1 - c_1 > 0$.*

Proof. At each round $t \in \{1, \dots, T\}$, substituting $u_t = g_t + r_{t-1}$ into $c_t + r_t = u_t$ yields $c_t = g_t + r_{t-1} - r_t$. Summing from $t = 1$ to T telescopes all intermediate residuals $r_1, \dots, r_{T-1}$:

$$\sum_{t=1}^{T} c_t = \sum_{t=1}^{T} g_t + r_0 - r_T = \sum_{t=1}^{T} g_t - r_T \implies \sum_{t=1}^{T} c_t + r_T = \sum_{t=1}^{T} g_t.$$

Conversely, when $r_1 = 0$, step 2 compresses g_2 alone ($c_2 \le g_2$), so $c_1 < g_1 \implies c_1 + c_2 < g_1 + g_2$ (machine-checked in `ef21_disabled_loses_untransmitted_residual`). This explains why single-round 2-bit DCT exhibits 0.9313 relative L_2 truncation error in `H7` yet achieves a 0.052% held-out loss gap across $R = 12$ rounds with EF21 in Experiment `E1`. □

Theorem 7.3 (PA-CGAD Staleness Bias Bound & Necessity of Cosine Cutoff; Lean Thms. 103 & 114)**.** *For any decay rate $\alpha > 0$ and cutoff horizon $\tau_{cut} > 0$, the PA-CGAD gate $\sigma(\tau) = \frac{1}{2}(1 + \cos(\pi\tau/\tau_{cut}))\,\mathbb{I}[\tau < \tau_{cut}]e^{-\alpha\tau}$ satisfies:*

$$\sup_{\tau \ge 0} \tau\sigma(\tau) \le \frac{1}{e\alpha}, \qquad \text{and} \qquad \forall \tau_{\text{eff}} \ge \tau_{cut}, \quad v_t = \beta_2 v_{t-1}. \tag{18}$$

Hypothesis-Necessity Counterexample (Thm. 114): *If the staleness cutoff is omitted ($\alpha_2 = 1$ at $\tau_{\text{eff}} \ge \tau_{cut}$), any non-zero stale gradient $\|g_{stale}\|_2^2 > 0$ with $1 - \beta_2 > 0$ strictly inflates the second moment: $v_{unfiltered} - v_{clean} = (1 - \beta_2)\|g_{stale}\|_2^2 > 0$.*

Proof. Since $0 \le \gamma(\tau) \le 1$ for all $\tau \ge 0$, we have $0 \le \tau\sigma(\tau) \le \phi(\tau) := \tau e^{-\alpha\tau}$. Differentiating $\phi(\tau)$ gives $\phi'(\tau) = (1 - \alpha\tau)e^{-\alpha\tau}$, which vanishes uniquely at $\tau^* = 1/\alpha$ with $\phi''(1/\alpha) = -\alpha e^{-1} < 0$. Hence $\sup_{\tau \ge 0} \tau\sigma(\tau) \le \phi(1/\alpha) = \frac{1}{e\alpha}$ (at $\alpha = 0.2$, $\frac{1}{0.2e} \approx 1.8394$, bounding the empirical maximum 1.7417). For $\tau_{\text{eff}} \ge \tau_{\text{cut}}$, $\mathbb{I}[\tau_{\text{eff}} < \tau_{\text{cut}}] = 0 \implies \tilde{g}_f = 0$, preserving v_t without stale variance inflation. When omitted ($\alpha_2 = 1$), $v_{\text{unfiltered}} = \beta_2 v_{t-1} + (1 - \beta_2) g_{\text{stale}}^2 > \beta_2 v_{t-1} = v_{\text{clean}}$ (machine-checked in `pacgad_missing_cutoff_inflates_stale_second_moment`, explaining the 11.6× MSE degradation in Experiment `E2`). □

Theorem 7.4 (Multi-Krum Honest Quorum & Violation Counterexample; Lean Thms. 4 & 115)**.** *In a swarm of n workers with at most f Byzantine adversaries, if $n \geq 2f + 3$, then the Multi-Krum neighborhood size $k = n - f - 2$ satisfies $k \geq f + 1$, so every k-nearest neighborhood contains at least one honest worker.* ***Hypothesis-Necessity Counterexample (Thm. 115):*** *If $n \leq 2f + 2$, then $k = n - f - 2 \leq f$, so f colluding Byzantine workers can fill the entire k-neighborhood (`multikrum_violated_quorum_loses_honest_majority`).*

Proof. Subtracting $f + 2$ from $n \geq 2f + 3$ yields $k = n - f - 2 \geq (2f + 3) - f - 2 = f + 1$. By the pigeonhole principle, since at most f workers are Byzantine, at least $k - f \geq 1$ selected neighbors are honest. Conversely, if $n \leq 2f + 2$, then $k = n - f - 2 \leq f$. □

Table 3: 4-Definitions Contract mapping each core subsystem across its Mathematical Operator (Def. A), Conservation/Lyapunov Invariant (Def. B), Discretization/Algorithm (Def. C), and Quantitative Verification Gate (Def. D).

Subsystem	Def. A: Operator	Def. B: Invariant	Def. C: Algorithm	Def. D: Quantitative Gate
2-Bit DCT + EF21	$\hat{\Delta}_t = \mathcal{C}_{2b}(g_t + r_{t-1})$	$\sum_{t=1}^{T} \hat{\Delta}_t + r_T = \sum_{t=1}^{T} g_t$	8 × 8 DCT-II + 4-bin LUT + `index_copy_`	39.96× wire savings; 0.052% loss gap (`E1`, Thms. 105, 107, 113)
PA-CGAD Outer	$\tilde{g}_f = \gamma(\tau_{\text{eff}})e^{-\alpha\tau_{\text{eff}}}\bar{\Delta}_f$	$\sup_{\tau \geq 0} \tau\sigma(\tau) \leq \frac{1}{e\alpha}$	Pre-AdamW staleness cutoff at $\tau_{\text{cut}} = 32$	1.7417 ≤ 1.8394; 11.6× lower straggler MSE (`E2`, Thms. 103, 114)
MuLoCo NS-5	$\Phi(X) = aX + (bXX^\top + c(XX^\top)^2)X$	$\sigma_i(\Phi^{(5)}(X_0)) \to 1$	5-step quintic Newton-Schulz on 2D LoRA grads	$\kappa : 125.0 \to 1.65$; replay diff = 0.0 (`H9`, `E1`, Thm. 106)
Looped MoE	$h^{(t)} = \text{Core}(\mathcal{A}_t(h^{(t-1)} + h^{(0)}))$	$r_i^{(t)} \leq \epsilon_{\text{fp}} \implies h_i^{(t+1)} = h_i^{(t)}$	Weight-tied core + RNG-restored TBPTT	669,888 B saved; $\bar{t} = 3.05/4.0$ at $\epsilon_{\text{fp}} = 0.65$ (`H4`, `E3`, Thm. 108)
Multi-Krum + Spot	$\mathcal{N}_k(i) = \text{KNN}_{n-f-2}(\Delta_i)$	$n \geq 2f + 3 \implies \lvert\mathcal{N}_k \cap \mathcal{H}\rvert \geq 1$	10% SHA-256 micro-segment replay + 2σ cosine	20× BOINC FLOP savings; 25/25 red-team vectors blocked (Thms. 4, 115)

8 Empirical Verification, Controlled Experiments & Visualizations

8.1 Unit-Level Implementation Checks (`H1`–`H10`)

Each check in `src/hivemind/swarm/architecture_hypothesis_verifier.py` (`pytest tests/test_architecture_hypotheses.py`) exercises one architectural subsystem in isolation on CPU with controlled tensors (hidden size 32–64, LoRA rank 4–16, up to 128 router outputs) and emits the cryptographically signed report `artifacts/architecture_hypothesis_verification_report.json` (`receipt_sha256: b427d910a2d3ba4c...`). Table 4 summarizes all 10 checks.

Check H11 (Decoupled DiLoCo quorum syncer). `scripts/verify_decoupled_diloco_quorum.py` writes `artifacts/decoupled_diloco_quorum_check.json` with one positive arm (RDA norm invariance vs. direct-average shrinkage for $M \in \{2, 4, 8, 16\}$) and two negative controls (late stragglers excluded by the grace window; a $K = M$ quorum with one missing learner refuses to merge). All three arms pass; the numbers are quoted in Section 7.2, and the provenance lock (`PROV-15`, `PROV-16`) ties the 2.8284 ratio and the 3.35 s window in the text to that artifact.

Table 4: Unit-level implementation checks (`artifacts/architecture_hypothesis_verification_report.json`, `receipt_sha256: b427d910a2d3ba4c...`). ‡H5's speculative Top-2 match rate is measured on synthetic Gaussian residual perturbations ($\sigma = 0.08$).

ID	Architectural Hypothesis	Measured Empirical Telemetry	Lean lemma	Check
H1	`OpenDiLoCo` / `prime-diloco` 1D CPU Flat-Bucket Outer State	`0 B` extra GPU VRAM; contiguous 5,120 B buffer; $\max \Delta\theta = 2.384 \times 10^{-7}$ vs. Nesterov	Thms. 86, 101	pass
H2	DeepMind `Streaming DiLoCo` + `PA-CGAD` Staleness Bias Bound	$\max_\tau \tau\sigma(\tau) = 1.7417 \le \frac{1}{e\alpha} = 1.8394$; $\sigma(\tau \ge 32) = 0$; v_{stale} unpolluted	Thms. 78, 102, 103	pass
H3	128-Expert 3-Tier Router + `FoMoE` Partial Replica & `Skip-Token`	16 vs. 128 dot products (**8.0**× **FLOP savings**); **3.4615**× WAN ring savings; 51/96 ghost skips	Thms. 42, 79, 80, 109	pass
H4	`LoopedExpertBackbone` Weight-Tied Core, Fixed-Point Exit & TBPTT	Depth 4 → 10 (2.5×); 669,888 B saved; $\epsilon_{\text{fp}} = 0.65 \Rightarrow$ **3.05**/**4.0** mean steps (80% early exit)	Thms. 88, 91, 92, 108	pass
H5‡	`Skip-Attention` Prefetch + `CAR` Fallback + 3-Tier Async DMA	95.83% speculative Top-2 match on synthetic states; DMA overlap simulated (0.0 ms exposed)	Thms. 12, 82, 111	pass
H6	`IsoLoCo` (`ISO-CTS`) Isotropic Spectrum & `TSV` Decorrelation	Condition number κ : 2.5988 → **1.0000**; TSV orthogonality error $\|U^\top U - I\|_F = 6 \times 10^{-6}$	Thms. 83, 97, 110	pass
H7	`DeMo` 2D Chunked DCT + `SparseLoCo` 2-Bit LUT + `PULSELoCo`	$\|CC^\top - I\|_F = 2.3 \times 10^{-7}$; 32,768 B → 820 B (**39.96**× vs. FP16); single-shot rel. L_2 = 0.9313	Thms. 81, 87, 105	pass
H8	`AutoLoCo` Interval Scaling & `HeLoCo` Half-Space Drift Projection	η_{outer} : 0.7000 → 0.4950 (H : 32 → 64); conflicting cos : −0.8083 → 0.0000 ($\langle g_{\text{corr}}, m\rangle = 0$)	Thms. 84, 85	pass
H9	`MuLoCo` 5-Step Quintic Newton-Schulz LoRA Preconditioning	Singular condition number κ : 125.0001 → **1.6495**; validator spot-check replay diff = **0.0**	Thms. 90, 106	pass
H10	`EF21-DiLoCo` Telescoping Sum Conservation & `FP8PagedKVCache`	3-round telescoping error = $\mathbf{4 \times 10^{-8}}$; KV page 16,384 B → 8,448 B (**1.9394**× compression)	Thms. 38, 57, 107	pass

8.2 Controlled Experimental Evaluations (`E1`–`E4`) & Visualizations

To move beyond isolated unit checks, `scripts/run_paper_experiments_and_figures.py` executes four controlled experimental studies (`E1`–`E4`) and records all curves and SHA-256 provenance digests in `artifacts/paper_v3_experiments_report.json` (`receipt_sha256: 8cba94a46af02f8a...`).

8.2.1 Experiment E1: Held-Out Generalization & Wire Efficiency Across Five DiLoCo / MuLoCo Regimes

We instantiate a 2-layer causal Qwen2-QLoRA model ($V = 256$, $d = 48$, $r = 8$, $\alpha = 16$) and generate a synthetic Zipfian-transition corpus partitioned into $K = 4$ disjoint non-IID worker training shards (64 sequences/worker, 256 total training sequences) and a strictly disjoint held-out validation split ($N_{\text{val}} = 128$ sequences). All five regimes start from identical initial weights (initial validation loss 3.71488, perplexity 41.0538) and execute $R = 12$ outer synchronization rounds of $H = 8$ local inner steps each (96 inner updates/worker). Table 5 and Figure 1 report the held-out trajectories and cumulative outer wire volumes:

- **2-Bit DCT + EF21 Wire Compression Gate (`PASS`):** `DiLoCo + DeMo 2D-DCT + SparseLoCo 2-Bit + EF21` achieves a final held-out loss of **3.70814** (PPL = 40.7779) vs. **3.70622** (PPL = 40.6996) for uncompressed FP32 DiLoCo—a relative validation loss gap of just **0.052%** (well within the pre-declared 2.0% gate), while reducing cumulative outer wire traffic from 384.0 KB to **30.75** KB (**12.49**× reduction vs. FP32 DiLoCo, and **99.9**× reduction vs. synchronous DDP's 3,072.0 KB).
- **Inner-Loop `MuLoCo` Newton-Schulz Preconditioning:** Adding 5-step quintic Newton-Schulz LoRA gradient orthogonalization inside the compressed 2-bit EF21 regime (`muloco_ns5_dct_2bit_ef21`) reaches a lower held-out loss (**3.70791**, PPL = 40.7687) than standard AdamW inner steps under the same 30.75 KB wire budget.

Table 5: Experiment E1 (`artifacts/paper_v3_experiments_report.json`): Held-out cross-entropy loss, validation perplexity ($N_{\text{val}} = 128$ disjoint sequences), and cumulative outer wire volume across $R = 12$ outer rounds ($K = 4$ workers, $H = 8$ inner steps).

Training & Synchronization Regime	Initial Val Loss	Final Val Loss	Final Val PPL	Outer Wire Traffic	Bandwidth Savings vs. DDP
1. Single Worker (No Outer Sync, $K = 1$)	3.71488	3.71072	40.8834	0.00 KB	—
2. Synchronous DDP (All-Reduce Every Step)	3.71488	**3.68822**	**39.9738**	3,072.00 KB	1.00×
3. Standard DiLoCo (FP32 Outer Nesterov, $H = 8$)	3.71488	3.70622	40.6996	384.00 KB	8.00×
4. DiLoCo + DeMo 2D-DCT + SparseLoCo 2-Bit + EF21	3.71488	3.70814	40.7779	**30.75** KB	**99.90**× (12.49× vs. DiLoCo)
5. MuLoCo (5-Step NS Inner) + 2-Bit DCT + EF21	3.71488	**3.70791**	**40.7687**	**30.75** KB	**99.90**× (0.045% gap vs. DiLoCo)




Figure 1: **Experiment E1 (`artifacts/paper_v3_experiments_report.json`): (a)** Held-out cross-entropy loss across $R = 12$ outer synchronization rounds ($N_{\text{val}} = 128$ disjoint sequences). **(b)** Pareto frontier of cumulative outer wire traffic (KB, log scale) vs. final held-out perplexity, showing 99.9× communication reduction over DDP with a 0.052% loss gap vs. uncompressed DiLoCo.

8.2.2 Experiment E2: `PA-CGAD` Outer Convergence Under Severe Asynchronous Straggler Bursts

Experiment E2 compares standard outer AdamW (un-gated second moment v_t) against `CosineGatedAdamDecayOuterOptimizer` (`PA-CGAD`, $\alpha = 0.2$, $\tau_{\text{cut}} = 32$) over 20 outer rounds subject to five severe straggler delay bursts ($\tau_w \in \{36, 42, 38, 45, 40\}$ at rounds $4, 7, 10, 13, 17$) carrying high-variance stale pseudo-gradients. As shown in Figure 2, un-gated outer AdamW suffers immediate second-moment inflation ($\|v_t\|_2$ spikes to 30.74) and diverges after round 7 to a terminal parameter MSE of **0.3976**, whereas `PA-CGAD` zeroes out fragments with $\tau_{\text{eff}} \geq \tau_{\text{cut}}$, keeps $\|v_t\|_2 \leq 0.453$, and converges to a terminal MSE of **0.0343** (**11.6× lower error**).

8.2.3 Experiments E3 & E4: `LoopedMoE` Fixed-Point Halting Sweep, Subspace Spectra & Hardware Scaling

Experiment E3 sweeps the fixed-point halting threshold $\epsilon_{\text{fp}} \in \{0.0, 0.25, 0.35, 0.45, 0.55, 0.70, 0.90, 1.10\}$ on a $T = 6$ weight-tied `LoopedExpertBackbone` (source depth 4 → effective depth 14). As shown in Figure 3a, mean effective recurrent steps decrease monotonically from 6.00 → 5.27 → 4.17 → 3.75 → 3.14 → 2.70 → 2.17 → 1.69, saving 12.2% → 71.9% of recurrent core FLOPs as relative logit drift increases smoothly from 0.0% → 14.0% → 18.8% → 58.6%. Experiment E4 (Figure 3b) compares the normalized singular values σ_i/σ_1 of 4 merged domain attention deltas: uniform averaging collapses after σ_1 ($\sigma_2/\sigma_1 = 0.0306$), `TSV` Procrustes orthogonalization preserves the top-4 task-specific directions ($\sigma_2/\sigma_1 = 0.8795, \sigma_4/\sigma_1 = 0.6467$), and `Iso-CTS` achieves an exact isotropic spectrum ($\sigma_i/\sigma_1 = 1.0000$, $\kappa = 1.0$).




Figure 2: **Experiment E2 (`artifacts/paper_v3_experiments_report.json`): (a)** Empirical verification of the PA-CGAD gate $\sigma(\tau) = \gamma(\tau)e^{-\alpha\tau}$ and uniform staleness bias bound $\max_{\tau\geq 0}\tau\sigma(\tau) = 1.7417 \leq \frac{1}{e\alpha} = 1.8394$. **(b)** Outer optimization trajectory under five stale straggler bursts ($\tau_w \geq 36$, red bands): PA-CGAD prevents second-moment variance pollution and achieves 11.6× lower parameter MSE than standard outer AdamW.




Figure 3: **Experiments E3 & E4 (`artifacts/paper_v3_experiments_report.json`): (a)** Per-token fixed-point halting sweep across $\epsilon_{\text{fp}} \in [0.0, 1.10]$ on a $T = 6$ `LoopedExpertBackbone`, showing mean effective recurrent steps $\bar{t}$ vs. relative output logit drift. **(b)** Top-12 normalized singular values (σ_i/σ_1) of merged domain attention matrices under Uniform Averaging, TSV Orthogonal Procrustes, and Iso-CTS Isotropic Flattening.

8.3 Single-GPU Proof of Concept on an 8 GB NVIDIA GeForce RTX 2070 & FoMoE Scaling

All workers in our hardware proof of concept were executed on a single PC equipped with an NVIDIA GeForce RTX 2070 (8 GB GDDR6, SM 7.5, Windows WDDM, PyTorch 2.6.0+cu124) using `Qwen/Qwen2.5-0.5B` (24 layers, $d = 896$). Four domain branches (Code, Mathematics, STEM, Multilingual-FR) were trained by three simulated workers on **8 rows each**, with one simulated Byzantine worker rejected by Multi-Krum, and upcycled into a **4-expert, top-2** Sparse MoE (96 expert FFN modules across 24 layers; 1.44 B total and 0.81 B active parameters). Table 6 and Figure 4a report the exact measured VRAM profile from `artifacts/poc_qwen25_rtx2070_report.json`, alongside the FoMoE partial expert replication communication scaling across overlap factors $O_e \in \{1, 2, 4, 8, 16\}$ (Figure 4b). Smoke-test single-prompt perplexity probes (`artifacts/hf_hack_miner_game_report.json`) decreased

from 8.54 → 2.90 (Code), 204.05 → 5.55 (biomedical), and 26.32 → 6.53 (arithmetic) within 1,192.7 MB peak VRAM.

Table 6: Single-GPU proof of concept on an RTX 2070 (`artifacts/poc_qwen25_rtx2070_report.json`). Losses are training losses on 8 rows per worker. VRAM values are process-wide.

Stage	Data	Training loss (first → last)	Spot-check
Branch `Code` (worker 1 of 3)	`sahil2801/CodeAlpaca-20k`, 8 rows	2.649 → 0.353	pass (max $\Delta = 0.0$)
Branch `Mathematics`	8 rows/worker	2.989 → 0.996	pass
Router training (4-expert top-2 MoE)	mixed	2.139 → 0.795	—

Measured VRAM: NF4 weights 175.96 MB; after base load 946.98 MB; after QLoRA 980.54 MB; MoE peak 1,509.5 MB (5.61 GB free).




Figure 4: **Hardware & WAN Scaling Profiles:** **(a)** Measured GPU memory waterfall on an 8 GB NVIDIA GeForce RTX 2070 (`artifacts/poc_qwen25_rtx2070_report.json` & `artifacts/hf_hack_miner_game_report.json`), remaining > 5.1 GB below the Windows WDDM usable ceiling. **(b)** Outer ring communication volume across FoMoE partial expert replication overlap factors $O_e \in \{1, 2, 4, 8, 16\}$ for $E = 128$ experts across $M = 16$ workers.

9 Research Program: Questions, Predictions and Pre-registered Experiments

Sections 3–8 describe a system and verify that its parts do what their specifications say. That is not yet science: no experiment so far has more than one seed, none has run across machines, and none was designed to be able to fail in a way that would change the design. This section states what the project claims, what would show it to be wrong, and which experiments decide it. The full specification, including acceptance rules and decision consequences, is `docs/RESEARCH_PROGRAM.md`; the engineering side (task breakdown, Definition of Done, gates) is `docs/ENGINEERING_COORDINATION_BRIEF.md`.

9.1 Thesis and scaling-law prior

Thesis. Volunteer consumer GPUs behind residential links can train a sparse MoE whose held-out loss at matched tokens lies within a *predictable* distance of a single-host DiLoCo run with the same replica count: the gap equals (a) the replica-count penalty described by the DiLoCo scaling law of Charles *et al.* [11] plus (b) a *volunteer tax* from churn, staleness and Byzantine filtering, and the mechanisms of Sections 6–7 keep (b) no larger than the penalty of simply having

$M(1-\text{churn})$ reliable workers. If (b) is not bounded that way, the design is wrong and this paper will say so.

Prior. Before any WAN run we fit the functional form of [11] (loss as a function of model size, tokens, replica count M and inner steps H) to HiveMind's own single-host runs at $M \in \{1, 2, 4, 8, 16\}$ with at least three seeds. We reuse the form, not the published coefficients, which were fitted on other models and data. The fitted curve is the replica-count penalty; the volunteer tax is the residual of the WAN run against it. If the form does not fit the single-host runs ($R^2 < 0.9$) we report that and fall back to the fewer-workers baseline alone.

9.2 Research questions and predictions

Table 7: Predictions ledger. Each prediction names the observation that refutes it; status is recorded in `artifacts/predictions_ledger.json` once E5 starts and a refuted prediction is reported as refuted, not removed.

RQ	Question	Prediction	Refuted if	Exp.
RQ1	Volunteer tax: WAN swarm vs. single host at matched tokens	With $K < M$ quorum, grace window and RDA, WAN loss $\leq$ single-host loss with $M(1-\text{churn})$ workers	WAN loss exceeds that baseline by more than the 95 % seed interval	E8
RQ2	Does RDA remove outer-LR retuning with M?	Under direct averaging the best η_{outer} grows with M ($\approx \sqrt{M}$ if learner deltas are near-orthogonal); under RDA it is the same grid point for $M \in \{4, 8, 16\}$	Best RDA η_{outer} moves by ≥ 1 grid step, or deltas are not near-orthogonal (prediction then inapplicable)	E5, E5-het
RQ2′	Is RDA only an outer-LR multiplier in practice (Prop. 7.1)?	$\log(\eta^\star_{\text{direct}}/\eta^\star_{\text{RDA}})$ lies within one grid step of $\log \bar{r}$, the mean per-round $\|\text{RDA}\|/\|u\|$	Deviation exceeds one grid step at some M	E5-het (P9)
RQ3	Is the adaptive grace window better than matched-random admission? [27]	At equal loss, adaptive grace reaches it in less wall-clock time than random admission with the same budget	Matched random ties or wins (controller is then deleted)	E5
RQ4	Does PA-CGAD still help under a quorum?	Its gain over un-gated AdamW is large without quorum (E2 reproduced) and shrinks with $K < M$; it never hurts	CGAD hurts under quorum, or its gain does not shrink	E5
RQ5	Is Skip-Token quality loss governed by the measured ghost fraction?	At fixed ideal factor N_{le}/N_e, perplexity degrades monotonically with the measured ghost fraction	No monotone relation, or the ideal factor predicts as well	E7
RQ6	Does a whitening inner optimizer flatten loss vs. M? [36, 35]	Slope of held-out loss vs. $\log M$ is smaller with Muon–Newton-Schulz inner than with AdamW at matched compute	Slopes equal within CI, or Muon worse at $M = 4$	E6
RQ7	Does a learned depth prior make terminal-KV sharing safe? [18]	Accuracy drop from full cache to terminal-KV sharing is smaller with the learned prior than with fixed depth	Drops equal within CI	E7b
RQ8	Does Multi-Krum $+ 2\sigma$ stop ALIE-style attacks under non-IID shards?	It does not for $f/n \geq 0.2$; deterministic spot-check replay is what catches them	The filter alone blocks ALIE at $f/n = 0.3$	E9

9.3 Pre-registered experiments and controls

Every experiment follows one protocol: at least three seeds per cell with a 95 % t-interval, an effect claimed only if the interval excludes zero; a *positive control* in which a known effect must reproduce (otherwise the run is invalid); a *negative control* in which the mechanism is switched off or the signal destroyed (if it still shows the effect, the measurement is an artefact); for every *policy* a *matched-random control* with the same budget, following the methodological point of [27] that forecast-free schedulers must beat matched random before any gain is attributed to the policy; and pre-registration of metric, cells, seeds and acceptance rule in

`artifacts/experiments/E`n`_prereg.json`, hashed into the result artifact. Numbers enter this paper only through the provenance lock of Section 8.

- **E5 (outer-loop factorial under simulated churn; decides RQ2–RQ4).** Merge $\in$ {direct, RDA} $\times$ quorum $\in \{K{=}M,\ K{=}\lceil M/2 \rceil\}$ $\times$ grace $\in$ {off, adaptive, matched-random} $\times$ gate $\in$ {AdamW, PA-CGAD} $\times$ $M \in \{4, 8, 16\}$, with $\eta_{\text{outer}} \in \{0.3, 0.5, 0.7, 0.9, 1.1\}$ per cell and an optional outer-momentum-restart factor [30]. Arrival times are replayed from the empirical RTT and drop-out distribution recorded by `wan_fault_benchmark.py`, identically across cells. Reported alongside: the mean pairwise cosine of learner deltas, on which the RQ2 prediction is conditional. Positive control: the E2 divergence reproduces in the {no quorum, AdamW} cell; negative control: identical learner deltas give RDA $\equiv$ direct and $\gamma = 0$ gives pure quorum.
- **E6 (replica scaling vs. inner optimizer; RQ6).** $M \in \{2, 4, 8, 16\}$ $\times$ inner $\in$ {AdamW, Muon-NS5} $\times$ $H \in \{32, 128\}$ at matched tokens; metric: least-squares slope of held-out loss vs. $\log_2 M$ with CI. Negative control: a shuffled-label run must show no inner-optimizer effect.
- **E7 (ghost-fraction sweep; RQ5) and E7b (depth prior; RQ7).** E7 holds the ideal factor at 0.25 (128 experts, 32 resident, top-2) and varies routing imbalance through the router temperature so that the measured ghost fraction spans roughly 0.5–0.9; metric: Spearman ρ between measured fraction and held-out perplexity. E7b trains the $T = 6$ looped backbone with fixed depth vs. the entropy-regularised, budget-penalised categorical depth prior of [18] and evaluates both with full cache and terminal-KV sharing.
- **E8 (multi-host residential WAN; RQ1).** Three machines, then eight; real tokens from the 8-domain mixture; $K = \lceil M/2 \rceil$, adaptive grace, RDA, PA-CGAD, FoMoE $O_e = 4$ at eight nodes; data leases after [32] so that no sample is trained twice under churn; baselines on the same hardware with M and $M(1 - \text{churn})$ single-host workers. Negative control: the same learners over localhost must match single-host within CI, otherwise the gap is not the network. A non-blocking/blocking mix split after [28, 29] is an additional cell once E5 shows which parameter blocks are sensitive.
- **E9 (adaptive Byzantine; RQ8).** Sign-flip (positive control, must be blocked), scaled, ALIE and label-flip attacks at $f/n \in \{0.1, 0.2, 0.3\}$ on non-IID shards against the Multi-Krum $+2\sigma$ filter alone, the 10 % spot-check replay alone, and both; negative control: an honest run through the same filter must lose under 1 % of updates.

9.4 Decision rules

Each outcome changes something concrete. If RQ2 is refuted, RDA stays optional and the campaign adopts an explicit $\sqrt{M}$ outer-LR rule, and Section 7.2 claims only norm bookkeeping. If RQ3 is refuted, the EMA grace controller is deleted in favour of a fixed admission budget. If PA-CGAD hurts under quorum, it is off by default whenever $K < M$ and E2 is reported as a no-quorum result. If RQ5 is supported, the measured ghost fraction becomes a logged, gated metric and the FoMoE cost model is quoted with it. If RQ6 is refuted, AdamW remains the default inner optimizer and the MuLoCo claim is limited to conditioning. If RQ8 is supported, the spot-check replay rate, not the filter, becomes the security parameter and Section 4 is rewritten around it. If RQ1 is refuted, the swarm is not scaled further until E5 identifies the failing mechanism, and the thesis is reported as not supported. The theoretical account of why outer momentum and its restarts matter [31, 30] is used to interpret E5, not to replace it.

9.5 First pre-registered result: E5-toy (three seeds, all controls passed)

E5 was run at toy scale exactly as pre-registered (`artifacts/experiments/E5_toy_prereg.json`, hashed into the report `artifacts/experiments/E5_toy_report.json`): the E1 synthetic LoRA model, $M \in \{4, 8\}$, merge $\in$ {direct, RDA}, admission $\in$ {all, quorum + adaptive grace, quorum + matched-random grace}, gate $\in$ {ungated, PA-CGAD}, five outer learning rates, three seeds; 360 training runs in 524 s on one CPU, with a parametric arrival model replayed identically across cells. The positive control (a 40-round stale burst raises the final loss in every seed) and both negative controls (RDA equals direct averaging on identical learners; $\gamma = 0$ admits exactly the first K) passed. The pre-registered acceptance rules then gave:

- **P2 (RDA vs. outer-LR retuning): inapplicable.** The mean pairwise cosine between learner deltas is **0.909**, far above the pre-registered applicability bound of 0.3: on this toy, workers see nearly the same gradient direction, so RDA and direct averaging coincide and the best outer learning rate is the top of the grid (1.1) for every M and both merges (Figure 5). The prediction cannot be tested here; it needs the non-IID 8-domain setting.
- **P3 (adaptive grace vs. matched random): inconclusive.** The paired loss difference at matched wall budget, random minus adaptive, is -0.0004 ± 0.0022 (24 pairs; the interval includes zero). Adaptive grace admitted 0.72 (M=4) and 0.80 (M=8) of the tokens at roughly half the wall-clock of waiting for everyone (55.6 $\rightarrow$ 28.8 and 59.5 $\rightarrow$ 25.0 simulated units), but matched-random admission did the same.
- **P4 (PA-CGAD under quorum): refuted at this scale.** The gate changed the final loss by -0.00063 ± 0.00029 (negative is a harm; 12 paired runs; the interval excludes zero) when stale deltas were present, and by exactly 0 without stale deltas (negative control). With learner deltas this aligned, a one-round-stale delta is still almost the right direction, so down-weighting it discards signal.

The main lesson is methodological: every cell of the factorial lies within 0.011 of every other while the seed interval is ± 0.024, so the toy model cannot discriminate between the mechanisms it was meant to rank. The experiment did what pre-registration is for: it stopped a weak testbed from producing a result. E5 at the `Qwen2.5-0.5B` 8-domain scale (`HM-S9-01`) is therefore the first G1 deliverable, and its delta cosine must be reported before any RDA or gate claim is made.




Figure 5: E5-toy, admission "all", ungated: held-out loss after 12 outer rounds vs. outer learning rate for direct averaging and RDA at $M = 4$ (left) and $M = 8$ (right); three seeds, 95 % t-intervals. The two merges coincide because the learner deltas are nearly collinear (mean pairwise cosine 0.909), which is exactly the condition under which RDA reduces to direct averaging.

9.6 Second pre-registered result: E5-het, a heterogeneity-controlled testbed

E5-toy failed to discriminate because every learner saw the same teacher. E5-het adds one knob: learner m is labelled by its own teacher whose LoRA factors are $B_{\text{shared}} + \rho\, B_m$, and the held-out set mixes all teachers equally; $\rho = 0$ reproduces E5-toy bit for bit (one of the negative controls: the $\rho = 0$ cell equals the E5-toy artifact to 10^{-9}). The ρ grid was chosen from a calibration of round-0 delta cosines only, before pre-registration (`artifacts/experiments/E5_het_prereg.json`, with its two amendments recorded: a reference-LR fix after an analysis crash that had printed no result, and the LR-grid extension below). The outer-LR grid is geometric with ratio $\sqrt{2}$ so that the $\sqrt{2}$ shift predicted between $M = 4$ and $M = 8$ is one grid step; 2,652 runs in 22 minutes on eight CPU cores (`artifacts/experiments/E5_het_report.json`, Figure 6).

Manipulation check. The mean pairwise delta cosine falls monotonically, $0.909 \to 0.627 \to 0.283 \to \mathbf{0.079}$ for $\rho \in \{0, 1, 2, 4\}$, and the measured per-round multiplier $\bar{r} = \|\text{RDA}\|/\|u\|$ rises to 1.80 ($M = 4$) and **2.25** ($M = 8$) at $\rho = 4$. Proposition 7.1 predicts $r = (1/M + (1 - 1/M)\bar{c})^{-1/2} =$ 1.80 and 2.27 from the cosines alone, within 1 % of the measurements: the common-norm formula describes these deltas. P2 and P9 are therefore applicable at $\rho = 4$.

Grid censoring and its pre-registered repair. On the original grid (0.15–2.4) every best outer LR, direct or RDA, sat at the top: the held-out loss falls monotonically with the outer LR in every cell, i.e. the toy was trained far below its optimal step. P2 and P9 were reported as censored, and the grid was extended upward by five more $\sqrt{2}$ steps (to 13.6) for the $\rho = 4$ merge cells only, as a second pre-registered amendment written before the extra 60 runs. The extension finds the optimum where the runs begin to diverge: direct averaging is best at $\eta = 6.79$ for both M (loss 3.62 ± 0.45 at $M = 4$, 3.78 ± 0.05 at $M = 8$; 9.6 diverges), RDA at $\eta = 4.8$ for both M (3.61 ± 0.08 and 3.74 ± 0.15; 6.79 already diverges at $M = 8$).

- **P2 (direct best LR grows with M, RDA's does not): refuted by the rule.** RDA's best LR is indeed the same grid point at both M, but so is direct averaging's: the best step is set by the divergence edge, which did not move between $M = 4$ and $M = 8$, not by the $\sqrt{M}$ shrinkage. The refutation is not statistically sharp, because the intervals of the candidate cells overlap (the $M = 4$ direct cells at 4.8 and 6.79 have intervals ± 0.06 and ± 0.45); the acceptance rule should have required the arg-min to be separated from its neighbours by its interval, and the 0.5B rule (`HM-S9-14`) now does.

- **P9 (RDA is an LR multiplier): refuted at $M = 8$, supported at $M = 4$.** The direct/RDA best-LR ratio is $\sqrt{2}$ at both M, against $\bar{r} = 1.80$ ($M = 4$: within one grid step, $|\Delta \log| = 0.24 < 0.35$) and 2.25 ($M = 8$: $0.46 > 0.35$). Near the divergence edge the multiplier identity (exact for the merged vector) no longer maps onto a shift of the stable region, which depends on the whole trajectory.

- **P3 (adaptive grace vs matched random): inconclusive**, $+0.0027 \pm 0.0123$ (24 pairs), as at $\rho = 0$; adaptive grace admits more tokens (0.80 vs 0.57 at $M = 8$) at the same wall-clock, but at these outer LRs the loss does not see it.

- **P4 (PA-CGAD under quorum): refuted at every ρ**; at $\rho = 4$ the gate changes the loss by -0.0025 ± 0.0023 (harm, interval excludes zero), and by exactly 0 without stale deltas. P3 and P4 were evaluated on the original grid, i.e. at outer LRs well below the optimum found by the extension; they stand as pre-registered but their power is low.

Two lessons carry forward. First, a toy that trains far below its optimal step cannot rank merge rules; the extension, not the factorial, produced the only cells with a real effect (3.96 → 3.61). Second, the multiplier formula of Proposition 7.1 is confirmed on the merged vectors to 1 %, so RDA's practical question at scale is only whether the stable LR region shifts by $\bar{r}$; E5 at 0.5B must sweep the LR up to divergence for both merges.




Figure 6: E5-het. Left: manipulation check, mean pairwise delta cosine and measured $\|\text{RDA}\|/\|u\|$ against ρ for $M = 4$ (solid) and $M = 8$ (dashed); the dotted line is the P2 applicability bound. Centre and right: held-out loss after 12 rounds against the outer learning rate (log axis, extended grid) for direct averaging and RDA at $\rho = 4$; the losses fall until the runs diverge, and RDA's curve is the direct curve shifted left by about one $\sqrt{2}$ step.

9.7 First two-host measurement: E8-pilot over the public internet

E8 was scaled down to the smallest real instance of its question: one learner on this workstation and one on a Google Cloud TPU VM in `us-west4-a` (CPU-only PyTorch, reached through an SSH reverse tunnel; ICMP round trip 151 ms, HTTP round trip through the tunnel ≈320 ms), a syncer on the workstation running `DecoupledDiLoCoQuorumSyncer`, the E1 toy model, 12 outer rounds, three seeds per cell, and a single-host baseline with identical seeds, shards and hyper-parameters (`scripts/run_experiment_E8_pilot.py`, `artifacts/experiments/E8_pilot_report.json`). Three cells were run.

- **Protocol validation ($K = 2$, 400 inner steps).** Waiting for both learners reproduces the single-host baseline: the paired final-loss difference is -0.00000 ± 0.00000 ($n = 3$), i.e. the shipping of shards and parameters, the remote inner loop and the RDA merge are numerically exact across machines. Round latency was p50 4.1 s and p95 14.2 s for about 2.7 s of local compute per round: the first real WAN numbers in this paper.
- **$K = 1$ with adaptive grace, 400 inner steps: the pilot protocol fails, instructively.** The 24-core VM finishes its inner loop before the contended workstation, wins every quorum (remote admitted fraction 1.00), and the workstation's delta always misses the round. Because the pilot learner loop is round-synchronous, that work is discarded rather than carried to the next merge with its token weight as in Algorithm 1 of [5]; the run trains on half the data and ends $+0.97 \pm 0.92$ nats worse than the baseline (round p50 1.0 s). This is a defect of our learner loop, not a measurement of Decoupled DiLoCo, and it fixes the first requirement of `HM-S9-01`: learners must keep training across rounds and be merged late with token weights.
- **$K = 1$, 8 inner steps (round trip $\gg$ compute).** The grace window, sized from compute-step durations, is shorter than one round trip, so the remote learner contributes only through one-round-late deferral (admitted in 0.67 of rounds); the loss difference to the baseline is $+0.0002 \pm 0.0005$ (round p50 0.37 s). The controller's slack formula needs the transport time as an explicit term before it is used over real links.

RQ1 remains open: a two-host toy with a round-synchronous learner loop is not the volunteer-tax measurement, but it has already produced a protocol fix, an exactness check across machines, and the first latency distribution for the roadmap's WAN tasks.

9.8 E10: a lattice codec for outer deltas, leveraged from the author's OptimalEnergyAI project

HiveMind ships outer deltas through scalar codecs (the 2-bit `SparseLoCo` LUT, `DeMo` DCT blocks). Lattice vector quantisation is the classical way to do better at the same rate: the normalised second moment of E_8 is $929/12960 \approx 0.0717$ against $1/12 \approx 0.0833$ for $\mathbb{Z}^8$, a 0.654 dB distortion gain on a Gaussian source [6]. The author's OptimalEnergyAI project [7] maintains reference nearest-point decoders for $\mathbb{Z}^n$, D_n and $E_8 = D_8 \cup (D_8 + \frac{1}{2})$ that were checked against exhaustive search (0 mismatches in $3 \cdot 10^6$ queries per lattice) together with a *measured* rate (the achievable rate of a coset-then-coordinates entropy coder). They were ported, with the same tie rules, to `hivemind.compress.lattice_quantizer`, with a two-sided brute-force check (lattice membership *and* distance) as a negative control, a 1-bit sign arm after signSGD [8], and EF21 error feedback (Theorem 107). E10 was pre-registered (`artifacts/experiments/E10_lattice_prereg.json`) on the E5-het $\rho = 4$, $M = 8$ testbed at the best direct outer LR of the E5-het artifact (6.79 after the grid extension): arms none, sign, $\mathbb{Z}^8$ and E_8 at target rates of 1 and 2 bits per coordinate (scales calibrated once on a round-0 delta), each with and without error feedback, three seeds, 36 runs in 46 s (`artifacts/experiments/E10_lattice_report.json`, Figure 7). A first execution at the pre-extension LR of 2.4 is kept as a sensitivity run (`E10_lattice_first_execution_lr2.4.json`).

- **Controls.** The 1-bit sign codec without error feedback raises the final loss in every seed, by +0.09 to +0.17 nats (positive control); E_8 at 6.9 bits per coordinate reproduces the unquantised loss to $2 \cdot 10^{-5}$ (negative control); both decoders pass the two-sided brute-force check (1000 queries each, 0 mismatches, 0 non-lattice outputs). The matched-rate control passed at the 1-bit target and failed at the 2-bit target (3.10 vs. 3.36 measured bits), so the 2-bit comparisons are reported as invalid. The realised rates also drift above their targets (1.71 and 1.76 bits at the "1-bit" target) because the deltas grow over rounds at this outer LR while the scale was fixed from round 0: the codec needs per-round scale adaptation before any rate is quoted for it.

- **P10a (distortion at matched rate): supported.** At the matched 1.7-bit rate the relative quantisation error of E_8 is $\mathbf{0.79} \pm 0.02$ times that of $\mathbb{Z}^8$ (paired over seeds; 0.81 ± 0.03 in the sensitivity run; the Gaussian-source value is 0.86). The lattice gain survives on real LoRA deltas.

- **P10b (loss at matched rate): inconclusive.** With error feedback E_8 ends -0.003 ± 0.019 nats relative to $\mathbb{Z}^8$; without it $+0.07 \pm 0.26$ (one E_8 seed landed 0.2 nats lower, the others 0.04–0.06 higher: at an outer LR on the divergence edge the quantisation noise acts as a perturbation of a barely stable trajectory). In the sensitivity run at LR 2.4 the same comparison was $+0.00002 \pm 0.00005$ with error feedback: once the residual is carried, both codecs reproduce the unquantised loss and there is nothing left for the lattice to win on this testbed.

- **P10c (error feedback recovers the unquantised loss at 1 bit): supported**, -0.012 ± 0.077 nats (interval includes zero; $+0.0001 \pm 0.0001$ in the sensitivity run, where the rule's letter called it refuted at a 10^{-4} residual). Error feedback cuts the 1-bit penalty of the sign codec from +0.14 to +0.11 and that of E_8 from +0.07 to −0.01.

What transfers and what does not: the distortion ratio is a property of the codec and the delta statistics and is expected to hold at scale; the loss effects are at the 10^{-4} level on a toy that barely moves in twelve rounds and say nothing about the 0.5B campaign (`HM-S10-01` compares E_8 with the `SparseLoCo` LUT there, with per-fragment measured rates).




Figure 7: E10 on the E5-het $\rho = 4$, $M = 8$ testbed, three seeds. Left: final held-out loss by codec (grey unquantised, red 1-bit sign, orange $\mathbb{Z}^8$, blue E_8; "+EF" = error feedback). Right: relative quantisation error against the measured rate for $\mathbb{Z}^8$ and E_8; the 2-bit points are not rate-matched (see text).

10 Limitations, Threats to Validity, and Future Multi-Host Benchmarks

What this paper establishes vs. what remains open.

1. **Single-host process simulation vs. multi-host WAN deployment.** While Experiments E1–E4 validate held-out generalization across synchronization regimes, PA-CGAD straggler resilience, fixed-point halting trade-offs, and subspace spectra in controlled PyTorch runs, all workers to date have executed on a single physical host. Real residential WAN packet loss, NAT hole-punching failure rates, and cross-vendor GPU floating-point drift remain to be measured over a live multi-node deployment.

2. **Single seed in E1–E4.** Every experiment in Section 8 uses one seed (2026) and therefore demonstrates that the mechanisms behave as specified without estimating an effect size. E5-toy (Section 9.5), E5-het (Section 9.6) and the E8 pilot (Section 9.7) are the first three-seed, controlled measurements; the IID toy's main finding is that it is too easy to rank the mechanisms.

3. **Full-scale standard benchmark suites.** While Experiment E1 evaluates held-out cross-entropy and perplexity on a 128-sequence disjoint validation split, full zero-shot/few-shot evaluations on standard LLM benchmarks (full GSM8K test split, HumanEval pass@1, PubMedQA) for 0.5B–7B upcycled MoE checkpoints are still required.

4. **128-expert training scale.** The largest MoE trained end-to-end on the RTX 2070 has 4 experts (96 FFN modules). The 3-tier 128-expert hierarchical router, FoMoE partial replication, and Skip-Attention prefetching have been verified at the module/planner level (`H3`, `H5`, `E4`) but not yet trained across 128 domain branches.

5. **Adaptive Byzantine adversaries.** Our Multi-Krum + 2σ cosine filter has been verified against sign-flipped/scaled poisoners; subtle inner-product manipulation (ALIE) and coordinated Sybil coalitions under non-IID drift warrant dedicated red-team evaluation.

6. **Scope of Lean 4 formalization.** The 120 Lean 4 lemmas in `lean4/HiveMindSpec.lean` verify discrete arithmetic, hypothesis-necessity counterexamples, non-vacuity inhabitation, and byte-budget invariants over $\mathbb{N}/\mathbb{Z}$ (Section 2); they do not formalize real-valued stochastic convergence or C++/CUDA kernel equivalence.

7. **No peer review has taken place.** `paper/autoevolve_peer_review_pipeline.py` is a deterministic script (Lean build, JSON-to-LaTeX number lock, LaTeX lint). Versions 2.9–3.1 of this preprint and its `PEER_REVIEW_REPORT.json` labelled that script a "Claude Opus 5.5 / Gemini 5-round peer review" with referee scores of 9.4–9.5/10; no language model and no human referee ever evaluated the manuscript, and those scores were constants in the script. The labels and scores are removed in v3.2.0 and the report now states `is_peer_review: false`. Several entries of `docs/ACKNOWLEDGMENTS_AND_CITATIONS.md` and `CITATION.cff` also carried invented titles, authors or arXiv identifiers; they were re-verified against arXiv on 23 October 2026 and corrected or removed, and every entry of this paper's bibliography was checked individually.

10.1 Epistemic Stratification & 6-Layer Security/Hardness Attestation

To prevent conflating machine-checked discrete arithmetic with empirical single-host measurements or unvalidated multi-host WAN scaling, Table 8 stratifies all claims into three explicit verification tiers. Concurrently, the repository is audited by the 6-Layer `HiveMindHardnessEngine` (`results/hivemind_hardness_report.json`), verifying: (L1) zero AST stubs across all modules; (L2) zero security findings across 147 scanned repository files (`risk_score = 0`); (L3) 25/25 simulated Byzantine, Sybil, NaN-injection, and WDDM TDR attack vectors blocked; (L4) 120/120 Lean 4 theorems compiled with 0 `sorry` and 0 custom axioms; (L5) exact rational bridge verification (`NF4` 128/33, `DiLoCo` wire 5000/3, `Prefix-Trie` 19/25, `3-Tier MoE` 1/8); and (L6) SHA-256 execution attestation.

Table 8: Epistemic stratification matrix separating machine-checked discrete lemmas, single-host empirical measurements, and open multi-host WAN validation targets.

Verification Category	Artifact / Proof Source	What Is Rigorously Established	Explicit Boundary / Not Claimed
Category I: Lean 4 Kernel Lemmas	`lean4/HiveMindSpec.lean` (120 lemmas, 0 `sorry`)	Discrete $\mathbb{N}/\mathbb{Z}$ byte budgets, flat-bucket partitions, EF21 telescoping sums, necessity counterexamples (Thms. 113–115), and `Nonempty` witness (Thm. 116).	Does not prove real-valued stochastic convergence or Python/CUDA kernel refinement.
Category II: Controlled Empirical & Single-GPU PoC	`H1`–`H10`, `E1`–`E4`, RTX 2070 PoC (`artifacts/*.json`)	0.052% held-out loss gap at 12.49× wire savings (`E1`); 11.6× lower straggler MSE under PA-CGAD (`E2`); 1,509.5 MB peak VRAM on 8 GB RTX 2070; 25/25 red-team vectors blocked.	Executed on a single physical host with synthetic WAN delays and controlled corpus shards.
Category III: Open Multi-Host WAN Targets	Future multi-node testbed (Section 10)	Analytical communication models for FoMoE (3.46×) and Kademlia Geo-Ring topologies.	Live multi-host residential WAN throughput, NAT punch success rates, and 128-branch full GSM8K/HumanEval accuracy remain open.

Reproducibility. Every number and figure in this paper is generated deterministically from committed scripts and JSON artifacts:

- `PYTHONPATH=src python -m hivemind.swarm.architecture_hypothesis_verifier` → `artifacts/architecture_hypothesis_verification_report.json` (H1–H10, `pytest tests/test_architecture_hypotheses.py`).
- `PYTHONPATH=src python scripts/run_paper_experiments_and_figures.py` → `artifacts/paper_v3_experiments_report.json` (E1–E4) and `paper/figures/fig1..fig4.{pdf,png}`.
- `PYTHONPATH=src python scripts/verify_decoupled_diloco_quorum.py` → `artifacts/decoupled_diloco_quorum_check.json` (H11, `pytest tests/test_decoupled_diloco_quorum.py tests/test_fomoe_sigma_routing.py`).
- `PYTHONPATH=src python paper/autoevolve_peer_review_pipeline.py` → `paper/PEER_REVIEW_REPORT.json` (scripted static audit: Lean inventory, JSON-to-LaTeX provenance lock, LaTeX lint; it calls no language model and is not a peer review).

- `cd lean4 && lake build` → compiles all 120 theorems in `lean4/HiveMindSpec.lean` with zero `sorry`.
- The PDF, the LaTeX source, the Lean specification and every JSON artifact quoted above are deposited on Zenodo under DOI 10.5281/zenodo.23601925 (`scripts/publish_hivemind_paper_zenodo.py`, receipt `paper/ZENODO_DEPOSIT_RECEIPT.json` with per-file MD5 verification).

References

[1] D. P. Anderson, "BOINC: A System for Public-Resource Computing and Storage," in *Proc. IEEE/ACM Int. Workshop on Grid Computing*, 2004, pp. 4–10.

[2] A. Douillard, Q. Feng, A. A. Rusu, R. Chhaparia, Y. Donchev, A. Kuncoro, M. Ranzato, A. Szlam, and J. Shen, "DiLoCo: Distributed Low-Communication Training of Language Models," *arXiv:2311.08105*, 2023.

[3] B. Liu, R. Chhaparia, A. Douillard, S. Kale, A. A. Rusu, J. Shen, A. Szlam, and M. Ranzato, "Asynchronous Local-SGD Training for Language Modeling," *arXiv:2401.09135*, 2024. Code: https://github.com/google-deepmind/asyncdiloco.

[4] A. Douillard, Y. Donchev, J. K. Rush, S. Kale, Z. Charles, G. Teston, Z. Garrett, J. Shen, R. McIlroy, D. Lacey, A. Ramé, A. Szlam, M. Ranzato, and P. R. Barham, "Streaming DiLoCo with Overlapping Communication: Towards a Distributed Free Lunch," in *Second Conference on Language Modeling (COLM)*, 2025, *arXiv:2501.18512*.

[5] Decoupled DiLoCo Team (Google DeepMind & Google Research; A. Douillard, K. Rush, Y. Donchev, Z. Charles, A. Dubey, B. Woodworth, *et al.*), "Decoupled DiLoCo for Resilient Distributed Pre-training," *arXiv:2604.21428*, 2026.

[6] J. H. Conway and N. J. A. Sloane, "Fast Quantizing and Decoding Algorithms for Lattice Quantizers and Codes," *IEEE Trans. Inf. Theory*, 28(2):227–232, 1982.

[7] X. Callens, "The Triangular Lattice and Universal Optimality: human proofs, Lean 4 verification, numerical validation in Python and Rust, and physics from fluids to plasmas," Zenodo, 2026, doi:10.5281/zenodo.23295142; companion code *OptimalEnergyAI* (`oai_ml.core.quantise`, `oai_ml.core.rate`).

[8] J. Bernstein, Y.-X. Wang, K. Azizzadenesheli, and A. Anandkumar, "signSGD: Compressed Optimisation for Non-Convex Problems," in *ICML*, 2018, *arXiv:1802.04434*.

[9] S. Kale, A. Douillard, and Y. Donchev, "Eager Updates for Overlapped Communication and Computation in DiLoCo," *arXiv:2502.12996*, 2025.

[10] A. Defazio, K. Mishchenko, P. Raman, H.-J. M. Shi, and L. Xiao, "Smoothing DiLoCo with Primal Averaging for Faster Training of LLMs," *arXiv:2512.17131*, 2025.

[11] Z. Charles, G. Teston, L. Dery, K. Rush, N. Fallen, Z. Garrett, A. Szlam, and A. Douillard, "Communication-Efficient Language Model Training Scales Reliably and Robustly: Scaling Laws for DiLoCo," *arXiv:2503.09799*, 2025.

[12] S. Jaghouar, J. M. Ong, and J. Hagemann, "OpenDiLoCo: An Open-Source Framework for Globally Distributed Low-Communication Training," *arXiv:2407.07852*, 2024. Code: https://github.com/PrimeIntellect-ai/OpenDiLoCo, https://github.com/PrimeIntellect-ai/prime-diloco.

[13] S. Sukhbaatar *et al.*, "Branch-Train-MiX: Mixing Expert LLMs into a Mixture-of-Experts LLM," *arXiv:2403.07816*, 2024.

[14] T. Dettmers, A. Pagnoni, A. Holtzman, and L. Zettlemoyer, "QLoRA: Efficient Finetuning of Quantized LLMs," in *NeurIPS*, 2023.

[15] L. Sani, Z. Cao, M. Kurmanji, A. Iacob, A. Jovanović, Y. Gao, W. Zhao, and N. D. Lane, "FoMoE: Breaking the Full-Replica Barrier with a Federation of MoEs," *arXiv:2606.19025*, 2026.

[16] P. Merolla, "fomoe: Fast Opportunistic Mixture-Of-Experts," software repository, https://github.com/pmerolla/fomoe.

[17] Huang *et al.*, "Towards Looped Models Done Right. Part I: Topology, Input Injection, Recurrent-State Design," *arXiv:2610.23036*, 2026.

[18] Huang, Shi, Chen *et al.*, "Towards Looped Models Done Right, Part II: Rethinking at Fixed Points," *arXiv:2610.06833*, 2026.

[19] V. Shah and J. Sun, "Cosine-Gated Adam-Decay: Drop-In Staleness-Aware Outer Optimization for Decoupled DiLoCo," *arXiv:2605.09126*, 2026.

[20] D. Marczak, S. Magistri, S. Cygert, B. Twardowski, A. D. Bagdanov, and J. van de Weijer, "No Task Left Behind: Isotropic Model Merging with Common and Task-Specific Subspaces," in *ICML*, 2025, *arXiv:2502.04959*.

[21] S. Horoi, B. Thérien, G. Wolf, and E. Belilovsky, "Can Model Merging Improve Aggregation in DiLoCo?," *arXiv:2607.03011*, 2026.

[22] A. A. Gargiulo *et al.*, "Task Singular Vectors: Reducing Task Interference in Model Merging," in *CVPR*, 2025, *arXiv:2412.00081*.

[23] B. Peng, J. Quesnelle, and D. P. Kingma, "DeMo: Decoupled Momentum Optimization," *arXiv:2411.19870*, 2024. Code: https://github.com/bloc97/DeMo.

[24] A. Sarfi, B. Thérien, J. Lidin, and E. Belilovsky, "Communication Efficient LLM Pre-training with SparseLoCo," *arXiv:2508.15706*, 2025. Code: https://github.com/one-covenant/SparseLoCo.

[25] E. Miahi and E. Belilovsky, "Understanding and Exploiting Weight Update Sparsity for Communication-Efficient Distributed RL," *arXiv:2602.03839*, 2026.

[26] Asif *et al.*, "HeLoCo: Efficient Asynchronous Low-Communication Training under Data and Device Heterogeneity," *arXiv:2606.00271*, 2026.

[27] M. Twelftree, D. Lemphers, A. He, and Y. Yang, "Not Every Sync Is Safe: Calibrated DiLoCo Scheduling for Shared AI Infrastructure," *arXiv:2607.02544*, 2026.

[28] C. H. Koneputugodage, T. Ajanthan, S. Ramasinghe, H. M. Dolatabadi, S. Siriwardhana, G. Avraham, V. Shevchenko, K. Pajak, J. Snewin, and A. Long, "Factored Gossip DiLoCo: Reducing Blocking Communication in DiLoCo," *arXiv:2606.22768*, 2026.

[29] P. Cagnasso, E. Belilovsky, and E. Oyallon, "Unifying Local Communications and Local Updates for LLM Pretraining," *arXiv:2606.11081*, 2026.

[30] K. Topollai, A. Ma, T. Dimlioglu, S. J. Tay, and A. Choromanska, "Outer-Momentum Restarting in High-Dimensional Two-Phase Optimization," *arXiv:2605.28585*, 2026.

[31] A. Agarwala, "High dimensional theory of two-phase optimizers," *arXiv:2603.26954*, 2026.

[32] Z. Palanciyan, T. van Osch, D. van der Wal, O. Kotevska, and T. Kok, "Cross-Facility LLM Pre-training on HPC: Elastic Aggregation, Data Leasing, and Queue-Aware Placement," *arXiv:2610.03457*, 2026.

[33] He *et al.*, "AutoLoCo: Communication Efficient Distributed LLM Training via Adaptive Synchronization," *arXiv:2609.36662*, 2026.

[34] K. Jordan *et al.*, "Muon: An Optimizer for Hidden Layers in Neural Networks," technical blog post, 2024.

[35] B. Thérien, X. Huang, A. Defazio, I. Rish, and E. Belilovsky, "MuLoCo: Muon is a Practical Inner Optimizer for DiLoCo," *arXiv:2505.23725*, 2025.

[36] E. Belilovsky, S. Horoi, E. Oyallon, and B. Thérien, "How Inner Optimizers Shape Replica Scaling," *arXiv:2610.19064*, 2026.

[37] P. Richtárik, I. Sokolov, and I. Fatkhullin, "EF21: A New, Simpler, Theoretically Better, and Practically Faster Error Feedback," in *NeurIPS*, 2021, *arXiv:2106.05203*.

[38] M. Ryabinin and A. Gusev, "Towards Crowdsourced Training of Large Neural Networks using Decentralized Mixture-of-Experts," in *NeurIPS*, 2020, *arXiv:2002.04013*. Code: https://github.com/learning-at-home/hivemind.

[39] A. Borzunov *et al.*, "Petals: Collaborative Inference and Fine-Tuning of Large Models," in *Proc. ACL System Demonstrations*, 2023.

[40] P. Blanchard, E. M. El Mhamdi, R. Guerraoui, and J. Stainer, "Machine Learning with Adversaries: Byzantine Tolerant Gradient Descent," in *NeurIPS*, 2017.

[41] W. Fedus, B. Zoph, and N. Shazeer, "Switch Transformers: Scaling to Trillion Parameter Models with Simple and Efficient Sparsity," *JMLR*, vol. 23, no. 120, pp. 1–39, 2022.

[42] L. de Moura and S. Ullrich, "The Lean 4 Theorem Prover and Programming Language," in *Proc. CADE-28*, 2021, pp. 625–635.