

Connecting the Database

Point the crud branch at its own MySQL database (YnclinoAMSCrudDb)

The crud branch now uses its own database, YnclinoAMSCrudDb, so it never shares data with the crud(copy) branch (which uses YnclinoApartmentManagementSystemDb). You do NOT create the database by hand — the app builds it automatically the first time it runs. You only need three things: MySQL running, your password in a private config file, and a single run of the app.

The one thing to understand

The database NAME lives in appsettings.json (committed, and different on each branch). Your PASSWORD lives in appsettings.Local.json (never committed). The app plugs your password into the connection string at startup and then creates the database for you.

Step 1 — Make sure MySQL is running

- Windows: press Win + R, type services.msc, find MySQL80, and confirm it says Running.
- Set its Startup type to Automatic so it starts with Windows.
- Remember the root password you chose when you installed MySQL — you need it in Step 2.

Step 2 — Create your private password file

In the project root (the folder with the .csproj file) there is a template named appsettings.Local.json.example. Copy it to a new file named exactly:

```
appsettings.Local.json
```

Open your copy and put your own MySQL root password inside:

```
{  
  "MySqlPassword": "YOUR_PASSWORD_HERE"  
}
```

- This file is git-ignored, so your password is never committed or pushed.
- Only the password goes here — nothing else.

- Every teammate makes their own copy with their own password.

Do not edit appsettings.json

Leave the YOUR_MYSQL_PASSWORD placeholder in appsettings.json untouched. The app replaces it at runtime with the password from your Local file. Committing a real password is the one mistake this whole setup exists to prevent.

Step 3 — Run the app (it creates the database)

Press F5 in Visual Studio, or run from a terminal in the project folder:

```
dotnet run
```

On first launch the app automatically:

1. Creates the YnclinoAMSCrudDb database and every table from the current models.
2. Seeds the default administrator account.
3. Starts the site at <https://localhost:7251>.

Log in

- Username: admin
- Password: Admin@123
- Then open the Units page and click Load Sample Data to fill in demo units and tenants.

How it works under the hood

Program.cs reads the connection string, injects your password, and hands it to EF Core:

```
var connectionString = builder.Configuration
    .GetConnectionString("DefaultConnection");
var localPassword = builder.Configuration["MySQLPassword"];
if (localPassword is not null &&
    connectionString.Contains("YOUR_MYSQL_PASSWORD"))
    connectionString = connectionString
        .Replace("YOUR_MYSQL_PASSWORD", localPassword);
```

Then at startup it calls `EnsureCreated()`. If the database is missing it is built fresh; if a leftover database has an out-of-date shape, the app drops and rebuilds it so the schema always matches the code. That is exactly why the crud branch needs its OWN database name — sharing one with crud(copy) would make each branch keep rebuilding the other's schema.

Switching between branches

Because the database name is committed per branch and only the password is local, you do NOT edit any config when you switch. Just check out the branch and run:

Branch	Database it uses
crud	YnclinoAMSCrudDb
crud(copy)	YnclinoApartmentManagementSystemDb

The same appsettings.Local.json works on both branches, since it only holds your password.

Troubleshooting

“It still opens the old / wrong data.”

- Make sure your appsettings.Local.json contains ONLY MySQLPassword. If you ever pasted a full ConnectionStrings block in there, it overrides appsettings.json and forces the old database name — delete that block.
- Confirm appsettings.json on this branch shows database=YnclinoAMSCrudDb.

Start completely fresh

Because the schema is created (not migrated), the quickest reset is to drop the database and re-run the app — it rebuilds and re-seeds:

```
DROP DATABASE YnclinoAMSCrudDb;
```

Access denied for user 'root'

- The password in appsettings.Local.json does not match your MySQL root password. Re-check it.
- Confirm the MySQL80 service is actually Running (Step 1).

Forgot your MySQL root password?

Stop the MySQL80 service, create C:\mysql-init.txt containing the line below, then from an Administrator Command Prompt start mysqld with --init-file pointing at it (see the project README for the full command), and finally restart the service.

```
ALTER USER 'root'@'localhost' IDENTIFIED BY 'NewPass@2026';
```