



25
Dec



RASPBERRY PI, RASPIAN

Install BCM2835 Library in Raspberry Pi

POSTED ON [DECEMBER 25, 2018](#) BY [MAX](#)

BCM2835 by AirSpayce is one of the widely used Raspberry Pi IO access library.

Steps to install as below;

1. Insert each line of following code into terminal or download script from link at bottom of page.

This site uses cookies to offer you a better browsing experience. By browsing this website, you agree to our use of cookies.

SUBSCRIBE

ACCEPT

```
./configure;
make;
sudo make install
```

*The version of library can be changed according to release.

BCM2835 Pin Map:

```
RPI_GPIO_P1_03      = 0,   RPI_GPIO_P1_05      = 1,
RPI_GPIO_P1_07      = 4,   RPI_GPIO_P1_08      = 14,
RPI_GPIO_P1_10      = 15,  RPI_GPIO_P1_11      = 17,
RPI_GPIO_P1_12      = 18,  RPI_GPIO_P1_13      = 21,
RPI_GPIO_P1_15      = 22,  RPI_GPIO_P1_16      = 23,
RPI_GPIO_P1_18      = 24,  RPI_GPIO_P1_19      = 10,
RPI_GPIO_P1_21      = 9,   RPI_GPIO_P1_22      = 25,
RPI_GPIO_P1_23      = 11,  RPI_GPIO_P1_24      = 8,
RPI_GPIO_P1_26      = 7,

/* RPi Version 2 /
RPI_V2_GPIO_P1_03    = 2,   RPI_V2_GPIO_P1_05    = 3,
RPI_V2_GPIO_P1_07    = 4,   RPI_V2_GPIO_P1_08    = 14,
RPI_V2_GPIO_P1_10    = 15,  RPI_V2_GPIO_P1_11    = 17,
RPI_V2_GPIO_P1_12    = 18,  RPI_V2_GPIO_P1_13    = 27,
RPI_V2_GPIO_P1_15    = 22,  RPI_V2_GPIO_P1_16    = 23,
RPI_V2_GPIO_P1_18    = 24,  RPI_V2_GPIO_P1_19    = 10,
RPI_V2_GPIO_P1_21    = 9,   RPI_V2_GPIO_P1_22    = 25,
RPI_V2_GPIO_P1_23    = 11,  RPI_V2_GPIO_P1_24    = 8,
RPI_V2_GPIO_P1_26    = 7,   RPI_V2_GPIO_P1_29    = 5,
RPI_V2_GPIO_P1_31    = 6,   RPI_V2_GPIO_P1_32    = 12,
RPI_V2_GPIO_P1_33    = 13,  RPI_V2_GPIO_P1_35    = 19,
RPI_V2_GPIO_P1_36    = 16,  RPI_V2_GPIO_P1_37    = 26,
RPI_V2_GPIO_P1_38    = 20,  RPI_V2_GPIO_P1_40    = 21,
/ RPi Version 2, new plug P5 /
RPI_V2_GPIO_P5_03     = 28,  RPI_V2_GPIO_P5_04     = 29,
RPI_V2_GPIO_P5_05     = 30,  RPI_V2_GPIO_P5_06     = 31,
/ RPi B+ J8 header, also RPi 2 40 pin GPIO header */
RPI_BPLUS_GPIO_J8_03  = 2,   RPI_BPLUS_GPIO_J8_05  = 3,
RPI_BPLUS_GPIO_J8_07  = 4,   RPI_BPLUS_GPIO_J8_08  = 14,
RPI_BPLUS_GPIO_J8_10  = 15,  RPI_BPLUS_GPIO_J8_11  = 17,
RPI_BPLUS_GPIO_J8_12  = 18,  RPI_BPLUS_GPIO_J8_13  = 27,
```

This site uses cookies to offer you a better browsing experience. By browsing this website, you agree to our use of cookies.

SUBSCRIBE

ACCEPT

RPI_BPLUS_GPIO_J8_33	= 13,	RPI_BPLUS_GPIO_J8_35	= 19,
RPI_BPLUS_GPIO_J8_36	= 16,	RPI_BPLUS_GPIO_J8_37	= 26,
RPI_BPLUS_GPIO_J8_38	= 20,	RPI_BPLUS_GPIO_J8_40	= 21

Reference:

Author Website

<https://www.airspayce.com/mikem/bcm2835/>

Raspberry Pi Script

<https://gist.github.com/techworked/f2f4ec804eb3ae5acfa2bf68769bd715>

Discover more from TechWorked

Subscribe to get the latest posts sent to your email.

SUBSCRIBE

This entry was posted in [Raspberry Pi](#), [Raspian](#) and tagged [bcm2835](#), [raspberrypi](#), [Raspberry Pi](#), [raspian](#).

[< Solve Network Computers Not Showing in Windows 10](#)

[Fixed IP for Raspberry Pi >](#)

Leave a Reply

Comment

This site uses cookies to offer you a better browsing experience. By browsing this website, you agree to our use of cookies.

SUBSCRIBE

ACCEPT