

## MC 24/48 Lighting Control Consoles



## MC 24/48 Lighting Control Consoles

## MC 24/48 Lighting Control Consoles

## MC 24/48 Lighting Control Consoles

- ## MC 24/48 Lighting Control Consoles



## MC 24/48 Lighting Control Consoles

## MC 24/48 Lighting Control Consoles

## MC 24/48 Lighting Control Consoles

## PRODUCT DATA



### CONSOLE CAPACITY

- 24 two scene or 48 single scene individual channel sliders
- 384 control channels for conventional dimmers
- 512 control channels for intelligent fixtures
- 24 submaster sliders
- 8 pages of submasters (24 each)
- 600 cue capacity
- 2,000 macros
- 1024 max dimmers

### DISPLAY SCREENS

- Stage, preview, device, cue sheet, track sheet, playback, patch, setup

### CONTROLS

- 2 pair of manual cross faders
- Master fader
- Go button
- Blackout button
- Hold/back buttons
- Rate buttons
- Bump buttons
- 7 encoder wheels for intelligent device personality traits
- Trackball for pan and tilt

### KEYPAD

- Cue numbering from .1 to 999.9
- Split up/down fade times
- Link to cue or macro
- Selective cue recording
- Modified rate recording
- Multi-part cues
- Proportional range editing of levels
- Programmable up/dwell/down times

### SUBMASTERS

- Independent submasters with bump buttons
- Overlapping inhibitive or pile-on functions

### EFFECTS

- Up to 600 level sensitive effects
- Programmable step times
- Effects may be loaded to cue or submaster
- Range editing of step values and attributes

### PORTS

- DMX512 in (5 pin XLR, male)
- DMX512 out- 3 independent patchable ports (5 pin XLR, female)
- DMX512 out- switch selectable 3 pin XLR to port A, B or C
- MIDI in/out/through (5 pin DIN)
- Remote go macro (9 pin D-Sub/DB9 female)
- Parallel printer port (25 pin D-Sub/DB25 female)
- VGA monitor outputs (high density 15 pin D-Sub/DB15 female)
- Hand held remote port (6 pin XLR female)
- Keyboard input (5 pin DIN)

### INTELLIGENT LIGHTING

- Controls any DMX512 device
- Control a variety of manufacturers' instruments simultaneously
- Pre-programmed library of popular fixtures
- User-definable attributes to custom create fixture personalities

### REAL TIME EVENT PROGRAMMABLE

- Up to 500 event capability options
- SMPTE via MIDI

CAT. NO.	DESCRIPTION
N2448-000	24/48 Theatrical/Intelligent Lighting Control Console. Midi In/Out/Thru, SMPTE via MIDI, DMX512, VGA, and 3 1/2" Disk Drive, 120V
N2448-00V	24/48 Theatrical/Intelligent Lighting Control Console. Midi In/Out/Thru, SMPTE via MIDI, DMX512, VGA, and 3 1/2" Disk Drive, 120V with 2nd Video installed
<b>ACCESSORIES</b>	
CTP-7-2021	Hand Held Remote for Innovator & Encore
CTP-7-5061	Innovator & MC 24/48 Dustcover
TAMON-F17	LCD Flat Screen Monitor, Black/Gray, 17"
TAMON-F19	LCD Flat Screen Monitor, Black/Gray, 19"
TAMDC-F17	Dustcover for 17" LCD Monitor
TAMDC-F19	Dustcover for 19" LCD Monitor

### LEVITON SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:
JOB NUMBER:	

### Leviton Manufacturing Co., Inc. Lighting Management Systems

20497 SW Teton Avenue, Portland, OR 97062

Telephone: 1-800-736-6682 • FAX: 503-404-5594 • Tech Line (6:00AM-4:00PM P.S.T. Monday-Friday): 1-800-959-6004

### Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 • Telephone: 1-800-469-7890 • FAX: 1-800-563-1853

### Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 • Tel. (+52) 55-5082-1040 • FAX: (+52) 5386-1797 • [www.leviton.com.mx](http://www.leviton.com.mx)

### Visit our Website at: [www.leviton.com/lms](http://www.leviton.com/lms)

© 2008 Leviton Manufacturing Co., Inc. All rights reserved. Subject to change without notice.

G-8014/B8-ak