

# Package ‘breedRBayes’

September 3, 2026

**Type** Package

**Title** ASReml-Style Formula Front-End for the BGLR Bayesian Engine

**Version** 0.0.0.9000

**Description** A formula-based interface, inspired by 'asreml' and 'sommer', for fitting Bayesian mixed models with the 'BGLR' engine. Supports genomic prediction (GBLUP), random-regression / reaction-norm models, multi-trait models and factor-analytic structures. Provides extraction of posterior chains, variance components, heritabilities as full posterior distributions, and Markov-chain convergence diagnostics.

**License** MIT + file LICENSE

**Encoding** UTF-8

**LazyData** false

**Depends** R (>= 4.1.0)

**Imports** BGLR,  
coda,  
RhpcBLASctl,  
stats,  
utils,  
ggplot2

**Suggests** SpATS,  
EnvRtype,  
RSpectra,  
parallel,  
testthat (>= 3.0.0),  
knitr,  
rmarkdown

**RoxygenNote** 7.3.2

**Roxygen** list(markdown = TRUE)

**Config/testthat/edition** 3

## Contents

|                               |    |
|-------------------------------|----|
| as_mcmc . . . . .             | 2  |
| bbglr . . . . .               | 2  |
| bbglr_control . . . . .       | 4  |
| gebv . . . . .                | 5  |
| heritability . . . . .        | 6  |
| legendre_basis . . . . .      | 6  |
| mcmc_diag . . . . .           | 7  |
| parse_model . . . . .         | 8  |
| plot_posterior . . . . .      | 8  |
| plot_trace . . . . .          | 9  |
| pr . . . . .                  | 9  |
| predict.breedRB_fit . . . . . | 10 |
| predict_pr . . . . .          | 12 |
| solution . . . . .            | 13 |
| solve_SNP . . . . .           | 14 |
| varcomp . . . . .             | 15 |

---

as\_mcmc

---

*Convert a fitted model's posterior draws to a coda object*


---

### Description

Reads the variance-component chains (and optionally the intercept  $\mu$ ) written by BGLR and returns them as a [coda::mcmc.list](#) (one component per chain), ready for [mcmc\\_diag\(\)](#) or coda/bayesplot functions.

### Usage

```
as_mcmc(x, ...)

## S3 method for class 'breedRB_fit'
as_mcmc(x, what = "varcomp", ...)
```

### Arguments

|      |                                                        |
|------|--------------------------------------------------------|
| x    | A breedRB_fit.                                         |
| ...  | Unused.                                                |
| what | Which quantities to return: any of "varcomp" and "mu". |

### Value

A [coda::mcmc.list](#).

---

|       |                                                                                    |
|-------|------------------------------------------------------------------------------------|
| bbglr | <i>Fit a Bayesian mixed model with the BGLR engine using asreml-style formulas</i> |
|-------|------------------------------------------------------------------------------------|

---

## Description

Fit a Bayesian mixed model with the BGLR engine using asreml-style formulas

## Usage

```
bbglr(
  fixed,
  random = NULL,
  residual = NULL,
  data,
  relmat = list(),
  control = bbglr_control(),
  ...
)
```

## Arguments

|          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| fixed    | Two-sided formula for the fixed/mean part, e.g. <code>yield ~ 1 + env</code> . Use <code>cbind(t1, t2) ~ ...</code> for a multi-trait model.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| random   | One-sided formula of random terms, e.g. <code>~ mrk(gen, M)</code> . Special functions: <code>mrk(f, M, method, rank)</code> genomic effect from a <b>marker matrix</b> <code>M</code> that automatically fits GBLUP or RR-BLUP, whichever is cheaper (method is "auto", "GBLUP" or "RRBLUP"; "auto" picks GBLUP when markers $\geq$ genotypes, else RR-BLUP — the two are prediction-equivalent). <code>rank</code> (GBLUP only, default all) keeps just the top-rank principal components of the genomic relationship — a low-rank / PC-GBLUP approximation that shrinks the design and, when <b>RSpectra</b> is installed, is computed straight from the markers without ever forming the $n \times n$ relationship matrix (much cheaper for many genotypes). A <code>mrk()</code> fit can score new genotypes with <code>predict.breedRB_fit()</code> and recover marker effects with <code>solve_SNP()</code> ; it is the recommended genomic term. <code>vm(f, K)</code> effect of factor <code>f</code> with a supplied covariance matrix <code>K</code> — use it for a kernel you already have and cannot rebuild from markers (pedigree A-matrix, environmic kernel, externally-computed G, or any custom kernel). <code>leg(x, n) / rr(x, n)</code> random regression of order <code>n</code> ; <code>fa(f, k) / rrc(f, k)</code> factor-analytic. Bare names are factors; <code>a:b</code> is an interaction. |
| residual | One-sided residual formula. <code>NULL/~ units</code> = homogeneous; <code>~ dsum(~units   env)</code> = heterogeneous residual variances by env.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| data     | A data frame.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| relmat   | Named list of matrices referenced by <code>mrk()</code> and <code>vm()</code> . For <code>mrk()</code> the entry is a marker matrix with genotypes in rows (row names = genotype IDs) and markers in columns, coded as <b>0/1/2 allele dosages</b> . Missing values are mean-imputed per                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |

marker and (near-)constant markers are dropped automatically. In GBLUP mode `mrk()` then builds the genomic relationship internally by VanRaden's method 1 ( $G = ZZ' / 2 \sum p_j q_j$ ) and adds a tiny diagonal ridge so  $G$  is always non-singular. For `vm()` the entry is a covariance / kernel matrix ( $K$ , not its inverse) — genomic, pedigree, environmic or any custom kernel — with row/column names matching the factor levels.

`control` A `bbglr_control()` object bundling the MCMC controls (`nIter`, `burnIn`, `thin`, `nChains`, `seed`, `saveAt`, `verbose`) and model hyperparameters (`exp_var_rank`, the explained-variance target for the genomic low-rank rotation).

`...` Individual `bbglr_control()` settings passed directly as a shortcut (e.g. `nIter = 20000`); they override the corresponding value in `control`.

### Value

An object of class `breedRB_fit`.

### See Also

`bbglr_control()` for the available control settings.

### Examples

```
G <- readRDS(system.file("extdata", "kinship.matrix.rds", package = "breedRBayes"))
dat <- read.csv(system.file("extdata", "data_soy.csv", package = "breedRBayes"))
fit <- bbglr(yield ~ 1 + env, random = ~ vm(gen, G), data = dat,
            relmat = list(G = G),
            control = bbglr_control(nIter = 2000, burnIn = 500, nChains = 2))
```

---

|                            |                                                  |
|----------------------------|--------------------------------------------------|
| <code>bbglr_control</code> | <i>Control settings for <code>bbglr()</code></i> |
|----------------------------|--------------------------------------------------|

---

### Description

Bundles the MCMC controls and model hyperparameters into a single object, so the main `bbglr()` call stays short. Pass it as `control = bbglr_control(...)`; any value left at its default is used as-is.

### Usage

```
bbglr_control(
  nIter = 5000,
  burnIn = 1000,
  thin = 5,
  nChains = 1,
  seed = 123,
  saveAt = NULL,
```

```

    verbose = TRUE,
    exp_var_rank = 0.99
  )

```

### Arguments

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| nIter, burnIn, thin | MCMC controls passed to <b>BGLR</b> : total iterations, burn-in, and thinning interval.                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| nChains             | Integer number of independent chains (distinct seeds). Enables Gelman-Rubin diagnostics when > 1.                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| seed                | Base random seed; chain c uses seed + c - 1.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| saveAt              | Directory for BGLR binary output. NULL (default) uses a fresh temporary directory.                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| verbose             | Logical; print BGLR progress.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| exp_var_rank        | Genomic low-rank control for GBLUP-style terms (mrk() in GBLUP mode and vm()). A number in (0, 1] keeps the smallest set of leading principal components of the genomic relationship that together explain at least this fraction of its total variance (default 0.99), giving a principled, self-scaling low-rank / PC-GBLUP fit that shrinks the design and speeds up sampling while retaining essentially all of the genetic signal. Set to 1 or NA to keep every (non-null) component. An explicit integer rank = inside mrk() overrides this for that term. |

### Value

A list of class `breedRB_control`.

### See Also

[bbglr\(\)](#)

### Examples

```
bbglr_control(nIter = 20000, burnIn = 5000, exp_var_rank = 0.95)
```

---

gebv

*Posterior genomic estimated breeding values (GEBV)*

---

### Description

**Deprecated.** Use [solution\(\)](#), which extracts posterior solutions for any term (genomic vm() BLUPs, plain random-factor BLUPs, and fixed effects). `gebv(fit, term)` is equivalent to `solution(fit, term, type = "random")` with the value column renamed `gebv`.

It still works for a `vm()` genomic term for now, mapping the ridge coefficients back through the PC rotation (`genetic value = PC %*% b`).

**Usage**

```
gebv(fit, term = NULL, prob = 0.95)
```

**Arguments**

|      |                                                                                                                                                  |
|------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| fit  | A breedRB_fit (single-trait).                                                                                                                    |
| term | Genetic term identifier (label or key). Defaults to the first vm() term. For a non-genomic random effect use <a href="#">solution()</a> instead. |
| prob | Central credible-interval mass (default 0.95).                                                                                                   |

**Value**

A data frame with ID, posterior gebv (mean), sd, lower, upper, ordered by decreasing gebv, with the pooled draws matrix (nDraws x nLevel) attached as attribute "draws".

**See Also**

[solution\(\)](#), the general replacement.

**Examples**

```
head(gebv(fit))
```

---

heritability

*Posterior distribution of heritability*

---

**Description**

Computes narrow-sense (genomic) heritability for every MCMC draw, returning the full posterior distribution rather than a single point estimate:

$$h^2 = \sigma_{genetic}^2 / (\sigma_{genetic}^2 + \sum \sigma_{other}^2 + \sigma_e^2).$$

**Usage**

```
heritability(fit, genetic = NULL, denominator = NULL, prob = 0.95)
```

**Arguments**

|             |                                                                                                                  |
|-------------|------------------------------------------------------------------------------------------------------------------|
| fit         | A breedRB_fit.                                                                                                   |
| genetic     | Character vector of genetic term identifiers (label or key) forming the numerator. Defaults to the vm() term(s). |
| denominator | Character vector of term identifiers summed in the denominator alongside varE. Defaults to all random terms.     |
| prob        | Central credible-interval mass (default 0.95).                                                                   |

### Value

A list of class `breedRB_h2`: summary (mean/median/sd/CI) and draws (posterior vector of  $h^2$ ).

### Examples

```
h2 <- heritability(fit); h2$summary; hist(h2$draws)
```

---

|                |                                                                      |
|----------------|----------------------------------------------------------------------|
| legendre_basis | <i>Orthogonal / orthonormal Legendre polynomial basis on [-1, 1]</i> |
|----------------|----------------------------------------------------------------------|

---

### Description

Constructs a Legendre polynomial basis evaluated at a numeric vector scaled to  $[-1, 1]$ , up to a specified order, using the three-term recurrence. Optionally returns the orthonormal basis.

### Usage

```
legendre_basis(x, order, orthonormal = FALSE)
```

### Arguments

`x` Numeric vector (already scaled to  $[-1, 1]$ ) where the basis is evaluated.  
`order` Integer. Maximum polynomial degree. Returns columns for degrees 0..order.  
`orthonormal` Logical. If TRUE, applies orthonormal scaling to each degree.

### Value

A numeric matrix  $\text{length}(x) \times (\text{order} + 1)$ ; column  $j$  is the degree  $j - 1$  polynomial.

### Examples

```
legendre_basis(seq(-1, 1, length.out = 5), order = 3)
```

---

|           |                                                                |
|-----------|----------------------------------------------------------------|
| mcmc_diag | <i>Markov-chain convergence diagnostics for a fitted model</i> |
|-----------|----------------------------------------------------------------|

---

### Description

Summarises convergence of the variance-component chains: effective sample size, Geweke's  $z$ , and (when the fit has  $>1$  chain) the Gelman-Rubin potential-scale-reduction factor ( $\hat{R}$ ).

### Usage

```
mcmc_diag(fit, what = "varcomp", plot = FALSE)
```

**Arguments**

|      |                                                                                                                                                                                                             |
|------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| fit  | A breedRB_fit.                                                                                                                                                                                              |
| what | Passed to <a href="#">as_mcmc()</a> (default "varcomp"; add "mu" to include the intercept).                                                                                                                 |
| plot | Logical. If TRUE, also render ggplot2 trace plots of the monitored chains (via <a href="#">plot_trace()</a> ) and attach the plot object to the returned data frame as the "plot" attribute. Default FALSE. |

**Value**

A data frame with one row per monitored parameter: param, n\_eff, geweke\_z, and Rhat (NA for single-chain fits). When plot = TRUE, the corresponding ggplot is attached as attr(., "plot").

**Examples**

```
mcmc_diag(fit)
d <- mcmc_diag(fit, plot = TRUE) # prints trace plots
attr(d, "plot")                 # the ggplot object
```

---

|             |                                                              |
|-------------|--------------------------------------------------------------|
| parse_model | <i>Parse asreml-style fixed / random / residual formulas</i> |
|-------------|--------------------------------------------------------------|

---

**Description**

Turns the three model formulas into an internal, engine-agnostic description used by [bbglr\(\)](#). Not usually called directly.

**Usage**

```
parse_model(fixed, random = NULL, residual = NULL)
```

**Arguments**

|          |                                                                                                                                                                                  |
|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| fixed    | Two-sided formula for the mean/fixed part, e.g. <code>yield ~ 1 + env</code> . Multi-trait models use <code>cbind(t1, t2) ~ ....</code>                                          |
| random   | One-sided formula for random terms, e.g. <code>~ vm(gen, G) + env:vm(gen, G)</code> . NULL for none.                                                                             |
| residual | One-sided residual formula. NULL (default) or <code>~ units</code> gives homogeneous residuals; <code>~ dsum(~units   env)</code> gives heterogeneous residual variances by env. |

**Value**

A breedRB\_terms list: response, fixed, random, residual.

**Examples**

```
parse_model(yield ~ 1 + env, ~ vm(gen, G))
```



---

|                |                                                                      |
|----------------|----------------------------------------------------------------------|
| plot_posterior | <i>Posterior density plot of variance components or heritability</i> |
|----------------|----------------------------------------------------------------------|

---

**Description**

Posterior density plot of variance components or heritability

**Usage**

```
plot_posterior(x, ...)

## S3 method for class 'breedRB_fit'
plot_posterior(x, ...)

## S3 method for class 'breedRB_h2'
plot_posterior(x, ...)
```

**Arguments**

|     |                                                             |
|-----|-------------------------------------------------------------|
| x   | A breedRB_fit (variance components) or a breedRB_h2 object. |
| ... | Unused.                                                     |

**Value**

A ggplot object.

---

|            |                                                     |
|------------|-----------------------------------------------------|
| plot_trace | <i>Trace plots of the variance-component chains</i> |
|------------|-----------------------------------------------------|

---

**Description**

Trace plots of the variance-component chains

**Usage**

```
plot_trace(fit, what = "varcomp")
```

**Arguments**

|      |                                       |
|------|---------------------------------------|
| fit  | A breedRB_fit.                        |
| what | Passed to <a href="#">as_mcmc()</a> . |

**Value**

A ggplot object (iteration on x, value on y, one panel per parameter, coloured by chain).

pr

*Posterior probability of ranking in the top fraction***Description**

For a model term, compute the posterior probability that each level ranks among the best threshold fraction of levels. Working from the pooled posterior draws (see [solution\(\)](#)), each MCMC draw is ranked independently and the top  $k = \text{round}(\text{threshold} \times n)$  levels are flagged; the reported probability is the fraction of draws in which a level is flagged. This is the Bayesian "probability of being in the top X" candidates by their whole posterior, not just their point estimate.

**Usage**

```
pr(fit, term = NULL, type = NULL, threshold = 0.2, higher = TRUE, pair = FALSE)
```

**Arguments**

|           |                                                                                                                                                                                                               |
|-----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| fit       | A <code>breedRB_fit</code> (single-trait).                                                                                                                                                                    |
| term      | Term identifier (label as written in the formula, e.g. "gen", or the internal key). If NULL, the first random term is used.                                                                                   |
| type      | Optional; one of "random" or "fixed", validated against the term's actual role. For a fixed term fitted with treatment contrasts the reference level is not among the coefficients and is therefore excluded. |
| threshold | Selected fraction in (0, 1); 0.20 = top 20%. Ignored when <code>pair = TRUE</code> .                                                                                                                          |
| higher    | Logical (default TRUE). If TRUE the "top" is the highest values (e.g. yield); set FALSE when smaller values are better. Ignored when <code>pair = TRUE</code> .                                               |
| pair      | Logical (default FALSE). If TRUE, return the pairwise table of posterior probabilities $P(A > B)$ for every pair of levels instead of the top-fraction summary.                                               |

**Details**

Because every draw is ranked on its own, adding the intercept `mu` would not change the ranking, so `pr()` is unaffected by centering.

**Value**

If `pair = FALSE`, a data frame with effect (level name), `solution` (posterior mean), and `prob` (posterior probability of ranking in the selected fraction), ordered by decreasing `prob`, with `k` and `threshold` attached as attributes. If `pair = TRUE`, a data frame with A, B, and `prob = P(A > B)` for every unordered pair, where A is the member with the larger posterior mean (so `prob >= 0.5` for well-separated pairs), ordered by decreasing `prob`.

**See Also**

[solution\(\)](#) for the underlying posterior draws.

## Examples

```
# probability each genotype is in the top 20%
pr(fit, term = "gen", type = "random", threshold = 0.20)
# pairwise probabilities P(A > B)
pr(fit, term = "gen", type = "random", pair = TRUE)
```

---

|                     |                                                                    |
|---------------------|--------------------------------------------------------------------|
| predict.breedRB_fit | <i>Predict genomic values for new genotypes from their markers</i> |
|---------------------|--------------------------------------------------------------------|

---

## Description

Scores genotypes that were **not** in the training data by combining the posterior marker effects with the new genotypes' marker calls:

$$\hat{g}_{new} = M_{c,new} b,$$

where  $M_{c,new}$  is  $M_{new}$  centred by the **training** column means (so the new genotypes sit on the same scale as the fitted breeding values) and  $b$  are the per-draw marker effects (read directly for a RR-BLUP fit, back-solved for a GBLUP fit — see [solve\\_SNP\(\)](#)). The full posterior is propagated, so every returned prediction carries a credible interval.

## Usage

```
## S3 method for class 'breedRB_fit'
predict(object, M_new, term = NULL, add_mu = TRUE, prob = 0.95, ...)
```

## Arguments

|        |                                                                                                                                                                                                                                                                                                                                                              |
|--------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| object | A breedRB_fit (single-trait) with a mrk() genomic term.                                                                                                                                                                                                                                                                                                      |
| M_new  | Marker matrix for the genotypes to predict: genotype IDs in the row names, markers in columns. Must contain every marker retained in the fit (extra columns are ignored; column order need not match). Missing calls are imputed with the training marker means. May include training genotypes, in which case the prediction reproduces their fitted value. |
| term   | Genomic term identifier (label or key). Defaults to the first genomic term.                                                                                                                                                                                                                                                                                  |
| add_mu | Logical (default TRUE). Add the model intercept mu to every draw, putting predictions on the overall-mean (phenotype) scale rather than the deviation scale. Done per posterior draw, so mu's uncertainty enters the interval.                                                                                                                               |
| prob   | Central credible-interval mass (default 0.95).                                                                                                                                                                                                                                                                                                               |
| ...    | Unused; for S3 compatibility.                                                                                                                                                                                                                                                                                                                                |

## Details

This requires a marker-based mrk() term. A vm() fit holds only a relationship matrix and cannot score genotypes outside it; refit the genomic term as mrk(gen, M) to enable prediction.

**Value**

A data frame with ID, prediction (posterior mean), sd, lower, upper, ordered by decreasing prediction, with the pooled draws matrix (nDraws x nGenotype) attached as attribute "draws".

**See Also**

[solve\\_SNP\(\)](#), [solution\(\)](#).

**Examples**

```
fit <- bbgblr(y ~ 1, random = ~ mrk(gen, M), data = dat, relmat = list(M = M))
pred <- predict(fit, M_new, add_mu = TRUE) # score unobserved genotypes
head(pred)
```

---

|            |                                                                                        |
|------------|----------------------------------------------------------------------------------------|
| predict_pr | <i>Posterior probability that new genotypes exceed a training-population threshold</i> |
|------------|----------------------------------------------------------------------------------------|

---

**Description**

Scores genotypes that were **not** in the training data (from their markers, via [predict.breedRB\\_fit\(\)](#)) and reports, for each, the posterior probability that its genomic value clears a bar defined by the **training population** — e.g. "probability this new line beats the top 10% of the training set".

**Usage**

```
predict_pr(
  fit,
  M_new,
  threshold = 0.1,
  term = NULL,
  higher = TRUE,
  add_mu = FALSE,
  prob = 0.95
)
```

**Arguments**

|           |                                                                                                                                                                                                              |
|-----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| fit       | A <a href="#">breedRB_fit</a> (single-trait) with a <a href="#">mrk()</a> genomic term.                                                                                                                      |
| M_new     | Marker matrix for the genotypes to score: genotype IDs in the row names, markers in columns (same requirements as <a href="#">predict.breedRB_fit()</a> ; missing calls are imputed with the training mean). |
| threshold | Training-population fraction in (0, 1) defining the bar; 0.10 = the top 10% of the training population (its 90th percentile when higher = TRUE).                                                             |
| term      | Genomic term identifier (label or key). Defaults to the first genomic term.                                                                                                                                  |

|        |                                                                                                                                                                                             |
|--------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| higher | Logical (default TRUE). If TRUE the bar is the upper threshold tail (larger is better, e.g. yield); set FALSE when smaller values are better (then it is the lower tail).                   |
| add_mu | Logical (default FALSE). Whether the reported prediction column is on the overall-mean scale (+ mu) or the deviation scale. Does not affect prob (the intercept cancels in the comparison). |
| prob   | Central credible-interval mass for the underlying prediction (default 0.95); affects only the internal prediction, not prob.                                                                |

### Details

The calculation is fully Bayesian and done per posterior draw: in each MCMC draw the bar is the corresponding quantile of the *training* genotypes' breeding values in that draw (so the threshold itself carries uncertainty), and the new genotype's predicted value in that same draw is compared against it. The reported probability is the fraction of draws the genotype clears the bar. Because the whole posterior is used, a new genotype with **more marker information** (a tighter predictive posterior) that sits above the bar earns a higher probability than an equally-ranked but more uncertain one — two lines with the same point prediction can have very different probabilities.

Requires a marker-based `mrk()` term (a `vm()` fit cannot score new genotypes). The probability is invariant to `add_mu`: the intercept shifts the new value and the training bar equally, so it cancels in the comparison.

### Value

A data frame with ID, prediction (posterior mean predicted value), sd (posterior SD of the prediction — the genotype's predictive uncertainty), and prob (posterior probability of clearing the training-population bar), ordered by decreasing prob. The pooled new-genotype draws are attached as attribute "draws", and the posterior-mean bar as attribute "cutoff".

### See Also

`predict.breedRB_fit()` for the point predictions, `pr()` for the in-sample analogue.

### Examples

```
fit <- bbgblr(yield ~ 1, random = ~ mrk(gen, M), data = dat, relmat = list(M = M))
# P(each new line beats the top 10% of the training population)
predict_pr(fit, M_new, threshold = 0.10)
```

## Description

Extracts the posterior distribution of the effect solutions for any term in a fitted model, pooled across chains:

- **Random terms** return BLUPs. A `vm()` genomic term is back-mapped through its principal-component rotation to per-genotype values (identical to `gebv()`); a plain random factor (fitted without a relationship matrix) returns one solution per level; random regression / covariate terms return one solution per basis coefficient.
- **Fixed terms** return the posterior of each estimable coefficient (treatment contrasts; the reference level is the implicit baseline at 0).

## Usage

```
solution(fit, term = NULL, type = NULL, prob = 0.95, add_mu = FALSE)
```

## Arguments

|                     |                                                                                                                                                                                                                                                                                                                                                           |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>fit</code>    | A <code>breedRB_fit</code> (single-trait).                                                                                                                                                                                                                                                                                                                |
| <code>term</code>   | Term identifier (the label as written in the formula, e.g. "gen" or "env", or the internal key). If <code>NULL</code> , the first random term is used.                                                                                                                                                                                                    |
| <code>type</code>   | Optional; one of "random" or "fixed". When supplied it is validated against the term's actual role (a mismatch is an error), which is a convenient guard when a name could be ambiguous.                                                                                                                                                                  |
| <code>prob</code>   | Central credible-interval mass (default 0.95).                                                                                                                                                                                                                                                                                                            |
| <code>add_mu</code> | Logical (default <code>FALSE</code> ). If <code>TRUE</code> , the model intercept <code>mu</code> is added to every draw, shifting the solutions onto the overall-mean scale (e.g. <code>BLUP + mu</code> ). Most useful for random BLUPs; the addition is done per posterior draw so the credible intervals account for uncertainty in <code>mu</code> . |

## Value

A data frame with `effect` (level / coefficient name), `solution` (posterior mean), `sd`, `lower`, `upper`. Random-term rows are ordered by decreasing `solution`; fixed-term rows keep design order. The pooled draws matrix (`nDraws` x `nEffect`) is attached as attribute "draws", and the resolved role as attribute "type".

## See Also

[gebv\(\)](#) for genomic breeding values from a `vm()` term.

## Examples

```
solution(fit, term = "gen", type = "random")           # random BLUPs (no G matrix)
solution(fit, term = "gen", type = "random", add_mu = TRUE) # BLUP + mu
solution(fit, term = "env", type = "fixed")           # fixed-effect estimates
```

solve\_SNP

*Marker (SNP) effects from a genomic model***Description**

Recovers the posterior distribution of per-marker allele-substitution effects  $b$  on the centred-marker scale, such that the genomic breeding values satisfy  $GEV = M_c b$  (where  $M_c$  is the column-centred marker matrix). This lets a **GBLUP** fit — which estimates breeding values rather than marker effects — be back-transformed to marker effects:

$$b = M_c^\top (M_c M_c^\top)^{-1} u$$

applied to every posterior draw of the breeding values  $u$ . For a **RR-BLUP** fit (`mrk()` chose RR-BLUP because genotypes outnumbered markers) the marker effects are estimated directly and are simply rescaled and returned.

**Usage**

```
solve_SNP(fit, M = NULL, term = NULL, prob = 0.95)
```

**Arguments**

|                   |                                                                                                                                                                                                                                                                                                                       |
|-------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>fit</code>  | A <code>breedRB_fit</code> (single-trait) with a <code>vm()</code> or <code>mrk()</code> genomic term.                                                                                                                                                                                                                |
| <code>M</code>    | Marker matrix with genotypes in rows (row names matching the genotype IDs) and markers in columns. Only needed to override the training markers when back-solving a GBLUP fit; for a <code>mrk()</code> fit the training markers stored in the fit are used automatically, and a RR-BLUP fit ignores <code>M</code> . |
| <code>term</code> | Genomic term identifier (label or key). Defaults to the first genomic term.                                                                                                                                                                                                                                           |
| <code>prob</code> | Central credible-interval mass (default 0.95).                                                                                                                                                                                                                                                                        |

**Details**

The back-transform requires  $M_c M_c^\top$  to be invertible, which holds when the number of markers is at least the number of genotypes — exactly the regime in which `mrk()` selects GBLUP.

**Value**

A data frame with `marker`, `effect` (posterior mean), `sd`, `lower`, `upper`, in marker (design) order, with the pooled draws matrix (`nDraws` x `nMarker`) attached as attribute `"draws"` and the fitted method as attribute `"method"`.

**See Also**

`predict.breedRB_fit()` to score new genotypes, `solution()`.

**Examples**

```
snp <- solve_SNP(fit)      # marker effects (back-solved for GBLUP, direct for RR-BLUP)
head(snp[order(-abs(snp$effect)), ])
```

---

varcomp

---

*Posterior variance components of a fitted model*


---

**Description**

Returns the posterior distribution and summaries of every random-term variance and the residual variance, pooling all chains.

**Usage**

```
varcomp(fit, prob = 0.95, draws = FALSE)
```

**Arguments**

|       |                                                                 |
|-------|-----------------------------------------------------------------|
| fit   | A breedRB_fit.                                                  |
| prob  | Central credible-interval mass (default 0.95).                  |
| draws | Logical; if TRUE also return the pooled posterior draws matrix. |

**Value**

A data frame of per-component summaries (term, mean, median, sd, lower, upper), with the pooled draws attached as attribute "draws" when draws = TRUE.

**Examples**

```
varcomp(fit)
```