

Bubble Sort and Linear Regression with MPI

Claudio Scheer¹ and Gabriell Araujo¹

¹Master's Degree in Computer Science - PUCRS
{claudio.scheer, grabriell.araujo}@edu.pucrs.br

October 14, 2020

asdfas w Include a title and one or two paragraphs describing what you plan to do. Tell what interviews, site visits, or other activity you plan. Be specific if you can. Include one good reference you plan to used. This is an example of how to include a citation.

0.1 Introduction

Include a title and one or two paragraphs describing what you plan to do. Tell what interviews, site visits, or other activity you plan. Be specific if you can. Include one good reference you plan to used. This is an example of how to include a citation.

0.2 Background

Give a background on your topic. Include references.

0.3 Results

Results of your interviews or observations. Use information and/or quotes from your interview or observations.

0.4 Discussion

Your comments or evaluation of interview or observations

0.5 Summary

Summarize your paper.

Appendices

Appendix A

Bubble Sort Source Code

```
1 #include <iostream>
2 #include <vector>
3
4 using namespace std;
5
6 namespace dataset {
7     vector<int> get_vector(int vector_size) {
8         vector<int> v;
9         for (int i = 0; i < vector_size; i++) {
10             v.push_back(vector_size - i);
11         }
12         return v;
13     }
14
15     vector<vector<int>> get_dataset(int number_vectors, int vector_size) {
16         vector<vector<int>> vectors;
17         vector<int> v = get_vector(vector_size);
18         for (int i = 0; i < number_vectors; i++) {
19             vectors.push_back(v);
20         }
21         return vectors;
22     }
23 } // namespace dataset
```

Listing A.1: Dataset generator

```
1 #include "dataset-generator.cpp"
2 #include <chrono>
3 #include <stdio>
4 #include <fstream>
5 #include <iostream>
6 #include <sstream>
7 #include <tuple>
8 #include <vector>
9
10 using namespace std;
11
12 vector<vector<int>> load_dataset(int number_vectors, int vector_size) {
13     chrono::steady_clock::time_point begin = chrono::steady_clock::now();
14     vector<vector<int>> vectors =
15         dataset::get_dataset(number_vectors, vector_size);
16     chrono::steady_clock::time_point end = chrono::steady_clock::now();
17     double total_time =
18         chrono::duration_cast<chrono::duration<double>>(end - begin).count();
19     cout << "Time load dataset (s): " << total_time << endl;
20     return vectors;
21 }
22
23 vector<int> bubble_sort(vector<int> v) {
24     int n = v.size();
25     int c = 0;
26     int temp;
27     int swapped = 1;
28
29     while ((c < (n - 1)) & swapped) {
30         swapped = 0;
31         for (int d = 0; d < n - c - 1; d++)
32             if (v.at(d) > v.at(d + 1)) {
33                 temp = v.at(d);
34                 v.at(d) = v.at(d + 1);
35                 v.at(d + 1) = temp;
36                 swapped = 1;
37             }
38     }
```

```
38         c++;
39     }
40
41     return v;
42 }
43
44 int main(int argc, char **argv) {
45     int number_vectors = atoi(argv[1]);
46     int vector_size = atoi(argv[2]);
47     vector<vector<int>> vectors = load_dataset(number_vectors, vector_size);
48
49     chrono::steady_clock::time_point begin = chrono::steady_clock::now();
50     for (int i = 0; i < vectors.size(); i++) {
51         vector<int> v = vectors.at(i);
52         vector<int> v_sorted = bubble_sort(v);
53     }
54     chrono::steady_clock::time_point end = chrono::steady_clock::now();
55     double total_time =
56         chrono::duration_cast<chrono::duration<double>>(end - begin).count();
57
58     cout << "Number vectors: " << number_vectors << endl;
59     cout << "Vector size: " << vector_size << endl;
60     cout << "Time sort (s): " << total_time << endl;
61     return 0;
62 }
```

Listing A.2: Bubble Sort Sequential

```
1 #include "dataset-generator.cpp"
2 #include <chrono>
3 #include <stdio>
4 #include <fstream>
5 #include <iostream>
6 #include <mpi.h>
7 #include <sstream>
8 #include <tuple>
9 #include <vector>
10
11 using namespace std;
12
13 vector<vector<int>> load_dataset(int number_vectors, int vector_size) {
14     chrono::steady_clock::time_point begin = chrono::steady_clock::now();
15     vector<vector<int>> vectors =
16         dataset::get_dataset(number_vectors, vector_size);
17     chrono::steady_clock::time_point end = chrono::steady_clock::now();
18     double total_time =
19         chrono::duration_cast<chrono::duration<double>>(end - begin).count();
20     cout << "Time load dataset (s): " << total_time << endl;
21     return vectors;
22 }
23
24 vector<int> bubble_sort(vector<int> v) {
25     int n = v.size();
26     int c = 0;
27     int temp;
28     int swapped = 1;
29
30     while ((c < (n - 1)) & swapped) {
31         swapped = 0;
32         for (int d = 0; d < n - c - 1; d++)
33             if (v.at(d) > v.at(d + 1)) {
34                 temp = v.at(d);
35                 v.at(d) = v.at(d + 1);
```

```

36         v.at(d + 1) = temp;
37         swapped = 1;
38     }
39     c++;
40 }
41
42 return v;
43 }
44
45 int main(int argc, char **argv) {
46     int number_vectors = atoi(argv[1]);
47     int vector_size = atoi(argv[2]);
48
49     int vector_tag = 1;
50     int kill_tag = 2;
51     int request_vector_tag = 3;
52
53     MPI_Status status;
54     int my_rank;
55     int num_processes;
56
57     MPI_Init(&argc, &argv);
58     MPI_Comm_rank(MPI_COMM_WORLD, &my_rank);
59     MPI_Comm_size(MPI_COMM_WORLD, &num_processes);
60
61     if (my_rank != 0) {
62         int master = 0;
63         int ask_for_message = 1;
64         int kill_flag = 0;
65         while (!kill_flag) {
66             if (ask_for_message) {
67                 // Will only send a new request when the last request was
68                 // already processed.
69                 MPI_Send(&ask_for_message, 1, MPI_INT, master,
70                     request_vector_tag, MPI_COMM_WORLD);
71                 ask_for_message = 0;
72             }
73             // Test whether the master submitted a new job.
74             int has_message = 0;
75             MPI_Iprobe(master, vector_tag, MPI_COMM_WORLD, &has_message,
76                 &status);
77             if (has_message) {
78                 vector<int> v;
79                 v.resize(vector_size);
80                 MPI_Recv(&v[0], vector_size, MPI_INT, master, vector_tag,
81                     MPI_COMM_WORLD, &status);
82
83                 vector<int> v_sorted = bubble_sort(v);
84                 MPI_Send(&v_sorted, vector_size, MPI_INT, master, vector_tag,
85                     MPI_COMM_WORLD);
86
87                 ask_for_message = 1;
88             }
89             // Check for a 'suicide' request.
90             MPI_Iprobe(master, kill_tag, MPI_COMM_WORLD, &kill_flag, &status);
91         }
92     } else {
93         vector<vector<int>> vectors = load_dataset(number_vectors, vector_size);
94
95         double begin = MPI_Wtime();
96
97         // Store async requests received from workers.
98         vector<MPI_Request> receive_requests(number_vectors);
99         vector<vector<int>> ordered_vectors(number_vectors);
100
101         int worker_request = 0;
102         for (int i = 0; i < vectors.size(); i++) {
103             vector<int> v = vectors.at(i);
104             MPI_Recv(&worker_request, 1, MPI_INT, MPI_ANY_SOURCE,
105                 request_vector_tag, MPI_COMM_WORLD, &status);
106             // Send the vector to the worker.
107             MPI_Send(&v, vector_size, MPI_INT, status.MPI_SOURCE, vector_tag,
108                 MPI_COMM_WORLD);
109
110             ordered_vectors[i].resize(vector_size);
111             MPI_Irecv(&ordered_vectors[i][0], vector_size, MPI_INT,
112                 status.MPI_SOURCE, vector_tag, MPI_COMM_WORLD,
113                 &receive_requests[i]);
114         }
115
116         // Wait for all requests.
117         for (int i = 0; i < vectors.size(); i++) {
118             MPI_Wait(&receive_requests.at(i), &status);
119         }
120
121         // Kill all workers.
122         int kill_value = 1;
123         for (int i = 1; i < num_processes; i++) {
124             MPI_Send(&kill_value, 1, MPI_INT, i, kill_tag, MPI_COMM_WORLD);
125         }
126
127         double end = MPI_Wtime();
128         double total_time = end - begin;
129
130         cout << "Number processes: " << num_processes << endl;
131         cout << "Number vectors: " << number_vectors << endl;
132         cout << "Vector size: " << vector_size << endl;
133         cout << "Time sort (s): " << total_time << endl;
134     }
135     MPI_Finalize();
136     return 0;
137 }
138

```

Listing A.3: Bubble Sort MPI

Appendix B

Linear Regression Source Code

```
1 #include <iostream>
2 #include <vector>
3
4 using namespace std;
5
6 namespace dataset {
7 vector<int> get_vector(int vector_size) {
8     vector<int> v;
9     for (int i = 0; i < vector_size; i++) {
10         v.push_back(vector_size - i);
11     }
12     return v;
13 }
14
15 vector<vector<int>> get_dataset(int number_vectors, int vector_size) {
16     vector<vector<int>> vectors;
17     vector<int> v = get_vector(vector_size);
18     for (int i = 0; i < number_vectors; i++) {
19         vectors.push_back(v);
20     }
21     return vectors;
22 }
23 } // namespace dataset
```

Listing B.1: Dataset generator

```
1 #include "dataset-generator.cpp"
2 #include <chrono>
3 #include <cstdio>
4 #include <fstream>
5 #include <iostream>
6 #include <sstream>
7 #include <tuple>
8 #include <vector>
9
10 using namespace std;
11
12 vector<dataset::Point> load_dataset(unsigned long long int number_points) {
13     chrono::steady_clock::time_point begin = chrono::steady_clock::now();
14     vector<dataset::Point> points = dataset::get_dataset(number_points);
15     chrono::steady_clock::time_point end = chrono::steady_clock::now();
16     double total_time = chrono::duration<double>(end - begin).count();
17     cout << "Time load dataset (s): " << total_time << endl;
18     return points;
19 }
20
21 tuple<double, double, double> execute_lr(vector<dataset::Point> points) {
22     chrono::steady_clock::time_point begin = chrono::steady_clock::now();
23
24     unsigned long long int x_sum = 0;
25     unsigned long long int y_sum = 0;
26     unsigned long long int x_squared_sum = 0;
27     unsigned long long int xy_sum = 0;
28     int n = (int)points.size();
29
30     for (unsigned long long int i = 0; i < n; i++) {
31         int x_aux = points.at(i).x;
32         int y_aux = points.at(i).y;
33
34         x_sum += x_aux;
35         y_sum += y_aux;
36     }
```

```
37         x_squared_sum += x_aux * x_aux;
38         xy_sum += x_aux * y_aux;
39     }
40
41     chrono::steady_clock::time_point end = chrono::steady_clock::now();
42     double total_time = chrono::duration<double>(end - begin).count();
43
44     double slope = ((double)(n * xy_sum - x_sum * y_sum)) /
45         ((double)(n * x_squared_sum - x_sum * x_sum));
46     double intercept = ((double)(y_sum - slope * x_sum)) / n;
47
48     return make_tuple(total_time, slope, intercept);
49 }
50
51 int main(int argc, char **argv) {
52     unsigned long long int number_points = atoll(argv[1]);
53     vector<dataset::Point> points = load_dataset(number_points);
54     tuple<double, double, double> results = execute_lr(points);
55
56     double total_time = get<0>(results);
57     double slope = get<1>(results);
58     double intercept = get<2>(results);
59     cout << "Time linear regression (s): " << total_time << endl;
60     cout << "Slope: " << slope << endl;
61     cout << "Intercept: " << intercept << endl;
62
63     return 0;
64 }
```

Listing B.2: Linear Regression Sequential

```
1 #include "dataset-generator.cpp"
2 #include <chrono>
3 #include <cstdio>
4 #include <fstream>
5 #include <iostream>
6 #include <mpi.h>
7 #include <sstream>
8 #include <tuple>
9 #include <vector>
10
11 using namespace std;
12
13 // Store the results from each worker.
14 struct RegressionSubResults {
15     unsigned long long int x_sum;
16     unsigned long long int y_sum;
17     unsigned long long int x_squared_sum;
18     unsigned long long int xy_sum;
19 };
20
21 vector<dataset::Point> load_dataset(unsigned long long int number_points) {
22     double begin = MPI_Wtime();
23     vector<dataset::Point> points = dataset::get_dataset(number_points);
24     double end = MPI_Wtime();
25     double total_time = end - begin;
26     cout << "Time load dataset (s): " << total_time << endl;
27     return points;
28 }
29
30 // Perform linear regression on the subvector.
31 RegressionSubResults execute_lr(vector<dataset::Point> points) {
```

```

32 unsigned long long int x_sum = 0;
33 unsigned long long int y_sum = 0;
34 unsigned long long int x_squared_sum = 0;
35 unsigned long long int xy_sum = 0;
36 int n = (int)points.size();
37
38 for (unsigned long long int i = 0; i < n; i++) {
39     int x_aux = points.at(i).x;
40     int y_aux = points.at(i).y;
41
42     x_sum += x_aux;
43     y_sum += y_aux;
44
45     x_squared_sum += x_aux * x_aux;
46     xy_sum += x_aux * y_aux;
47 }
48
49 return {
50     .x_sum = x_sum,
51     .y_sum = y_sum,
52     .x_squared_sum = x_squared_sum,
53     .xy_sum = xy_sum,
54 };
55 }
56
57 int main(int argc, char **argv) {
58     unsigned long long int number_points = atoll(argv[1]);
59     unsigned long long int granularity = atoll(argv[2]);
60
61     int vector_tag = 1;
62     int kill_tag = 2;
63     int request_vector_tag = 3;
64
65     int number_grains = number_points / granularity;
66     MPI_Status status;
67     int my_rank;
68     int num_processes;
69
70     MPI_Init(&argc, &argv);
71     MPI_Comm_rank(MPI_COMM_WORLD, &my_rank);
72     MPI_Comm_size(MPI_COMM_WORLD, &num_processes);
73
74     if ((number_points % granularity) > 0) {
75         // This avoids the need to deal with the last elements of the array.
76         cout << "Error: granularity must be a multiple of the number of points."
77         << endl;
78         MPI::COMM_WORLD.Abort(-1);
79     }
80
81     // Commit Point struct to MPI.
82     MPI_Datatype MPI_POINT_TYPE;
83     int block_lengths_point[2] = {1, 1};
84     MPI_Aint displacements_point[2] = {offsetof(dataset::Point, x),
85                                         offsetof(dataset::Point, y)};
86     MPI_Datatype types_point[2] = {MPI_INT, MPI_INT};
87     MPI_Type_create_struct(2, block_lengths_point, displacements_point,
88                           types_point, &MPI_POINT_TYPE);
89     MPI_Type_commit(&MPI_POINT_TYPE);
90
91     // Commit RegressionSubResults struct to MPI.
92     MPI_Datatype MPI_REGRESSION_SUB_RESULTS_TYPE;
93     int block_lengths_regression_sub_results[4] = {1, 1, 1, 1};
94     MPI_Aint displacements_regression_sub_results[4] = {
95         offsetof(RegressionSubResults, x_sum),
96         offsetof(RegressionSubResults, y_sum),
97         offsetof(RegressionSubResults, x_squared_sum),
98         offsetof(RegressionSubResults, xy_sum)};
99     MPI_Datatype types_regression_sub_results[4] = {
100     MPI_LONG_LONG_INT, MPI_LONG_LONG_INT, MPI_LONG_LONG_INT,
101     MPI_LONG_LONG_INT};
102     MPI_Type_create_struct(4, block_lengths_regression_sub_results,
103                           displacements_regression_sub_results,
104                           types_regression_sub_results,
105                           &MPI_REGRESSION_SUB_RESULTS_TYPE);
106     MPI_Type_commit(&MPI_REGRESSION_SUB_RESULTS_TYPE);
107
108     if (my_rank != 0) {
109         int master = 0;
110         int ask_for_message = 1;
111         int kill_flag = 0;
112         while (!kill_flag) {
113             if (ask_for_message) {
114                 // Will only send a new request when the last request was
115                 // already processed.
116                 MPI_Send(&ask_for_message, 1, MPI_INT, master,
117                         request_vector_tag, MPI_COMM_WORLD);
118                 ask_for_message = 0;
119             }
120             // Test whether the master submitted a new job.
121             int has_message = 0;
122             MPI_Iprobe(master, vector_tag, MPI_COMM_WORLD, &has_message,
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201 }

```

Listing B.3: Linear Regression MPI