



| [neilsedet](#) | [Logout](#)

[HOME](#) [TOP](#) [CATALOG](#) [CONTESTS](#) [GYM](#) [PROBLEMSET](#) [GROUPS](#) [RATING](#) [EDU](#) [API](#) [CALENDAR](#) [HELP](#) [RAYAN](#)

[PROBLEMS](#) [SUBMIT](#) [STATUS](#) [STANDINGS](#) [CUSTOM TEST](#)

## E1. Erase and Extend (Easy Version)

time limit per test: 2 seconds

memory limit per test: 256 megabytes

This is the easy version of the problem. The only difference is the constraints on  $n$  and  $k$ . You can make hacks only if all versions of the problem are solved.

You have a string  $s$ , and you can do two types of operations on it:

- Delete the last character of the string.
- Duplicate the string:  $s := s + s$ , where  $+$  denotes concatenation.

You can use each operation any number of times (possibly none).

Your task is to find the lexicographically smallest string of length exactly  $k$  that can be obtained by doing these operations on string  $s$ .

A string  $a$  is lexicographically smaller than a string  $b$  if and only if one of the following holds:

- $a$  is a prefix of  $b$ , but  $a \neq b$ ;
- In the first position where  $a$  and  $b$  differ, the string  $a$  has a letter that appears earlier in the alphabet than the corresponding letter in  $b$ .

### Input

The first line contains two integers  $n, k$  ( $1 \leq n, k \leq 5000$ ) — the length of the original string  $s$  and the length of the desired string.

The second line contains the string  $s$ , consisting of  $n$  lowercase English letters.

### Output

Print the lexicographically smallest string of length  $k$  that can be obtained by doing the operations on string  $s$ .

### Examples

<b>input</b>	<code>8 16</code>	<code>dbcadabc</code>	<a href="#">Copy</a>
<b>output</b>		<code>dbcadabcbcadabc</code>	<a href="#">Copy</a>
<b>input</b>	<code>4 5</code>	<code>abcd</code>	<a href="#">Copy</a>
<b>output</b>		<code>aaaaa</code>	<a href="#">Copy</a>

### Note

In the first test, it is optimal to make one duplication: "dbcadabc" → "dbcadabcbcadabc".

In the second test it is optimal to delete the last 3 characters, then duplicate the string 3 times, then delete the last 3 characters to make the string have length  $k$ .

### Codeforces Round 726 (Div. 2)

[Finished](#)

[Practice](#)



### → Virtual participation

Virtual contest is a way to take part in past contest, as close as possible to participation on time. It is supported only ICPC mode for virtual contests. If you've seen these problems, a virtual contest is not for you - solve these problems in the archive. If you just want to solve some problem from a contest, a virtual contest is not for you - solve this problem in the archive. Never use someone else's code, read the tutorials or communicate with other person during a virtual contest.

[Start virtual contest](#)

### → Clone Contest to Mashup

You can clone this contest to a mashup.

[Clone Contest](#)

### → Submit?

Language: [GNU G++17 7.3.0](#)

Choose file: [Choose File](#) No file chosen

[Submit](#)

### → Contest materials

- Announcement (en) [X](#)

- Tutorial (en) [X](#)

"abcd" → "abc" → "ab" → "a" → "aa" → "aaa" → "aaaa" → "aaaaaaaa" → "aaaaaaaa" → "aaaaaaaa" → "aaaaaaaa".

---

[Codeforces](#) (c) Copyright 2010-2025 Mike Mirzayanov  
The only programming contests Web 2.0 platform  
Server time: Aug/30/2025 01:01:51<sup>UTC-4</sup> (I2).  
Desktop version, switch to [mobile version](#).  
[Privacy Policy](#) | [Terms and Conditions](#)

Supported by

