

B. New Year and Ascent Sequence

time limit per test: 2 seconds
memory limit per test: 1024 megabytes

A sequence $a = [a_1, a_2, \dots, a_l]$ of length l has an **ascent** if there exists a pair of indices (i, j) such that $1 \leq i < j \leq l$ and $a_i < a_j$. For example, the sequence $[0, 2, 0, 2, 0]$ has an ascent because of the pair $(1, 4)$, but the sequence $[4, 3, 3, 3, 1]$ doesn't have an ascent.

Let's call a concatenation of sequences p and q the sequence that is obtained by writing down sequences p and q one right after another without changing the order. For example, the concatenation of the $[0, 2, 0, 2, 0]$ and $[4, 3, 3, 3, 1]$ is the sequence $[0, 2, 0, 2, 0, 4, 3, 3, 3, 1]$. The concatenation of sequences p and q is denoted as $p + q$.

Gyeonggeun thinks that sequences with ascents bring luck. Therefore, he wants to make many such sequences for the new year. Gyeonggeun has n sequences s_1, s_2, \dots, s_n which may have different lengths.

Gyeonggeun will consider all n^2 pairs of sequences s_x and s_y ($1 \leq x, y \leq n$), and will check if its concatenation $s_x + s_y$ has an ascent. Note that he may select the same sequence twice, and the order of selection matters.

Please count the number of pairs (x, y) of sequences s_1, s_2, \dots, s_n whose concatenation $s_x + s_y$ contains an ascent.

Input

The first line contains the number n ($1 \leq n \leq 100\,000$) denoting the number of sequences.

The next n lines contain the number l_i ($1 \leq l_i$) denoting the length of s_i , followed by l_i integers $s_{i,1}, s_{i,2}, \dots, s_{i,l_i}$ ($0 \leq s_{i,j} \leq 10^6$) denoting the sequence s_i .

It is guaranteed that the sum of all l_i does not exceed $100\,000$.

Output

Print a single integer, the number of pairs of sequences whose concatenation has an ascent.

Examples

input	Copy
5 1 1 1 1 1 2 1 4 1 3	
output	Copy
9	
input	Copy
3 4 2 0 2 0 6 9 9 8 8 7 7 1 6	
output	Copy
7	
input	Copy

[Hello 2020](#)
[Finished](#)
[Practice](#)

[→ Virtual participation](#)

Virtual contest is a way to take part in past contest, as close as possible to participation on time. It is supported only ICPC mode for virtual contests. If you've seen these problems, a virtual contest is not for you - solve these problems in the archive. If you just want to solve some problem from a contest, a virtual contest is not for you - solve this problem in the archive. Never use someone else's code, read the tutorials or communicate with other person during a virtual contest.

[Start virtual contest](#)
[→ Clone Contest to Mashup](#)

You can clone this contest to a mashup.

[Clone Contest](#)
[→ Submit?](#)

Language: [GNU G++17 7.3.0](#)

Choose file: [Choose File](#) No file chosen

[Submit](#)

[→ Contest materials](#)

- [Hello 2020 \(en\)](#)
- [Hello 2020 Editorial \(en\)](#)

```
10
3 62 24 39
1 17
1 99
1 60
1 64
1 30
2 79 29
2 20 73
2 85 37
1 100
```

output

Copy

72

Note

For the first example, the following 9 arrays have an ascent:

[1, 2], [1, 2], [1, 3], [1, 3], [1, 4], [1, 4], [2, 3], [2, 4], [3, 4]. Arrays with the same contents are counted as their occurrences.

[Codeforces](#) (c) Copyright 2010-2025 Mike Mirzayanov

The only programming contests Web 2.0 platform

Server time: Aug/30/2025 14:57:00^{UTC-4} (i2).

Desktop version, switch to [mobile version](#).

[Privacy Policy](#) | [Terms and Conditions](#)

Supported by

**ITMO**