

# Biax Experiment

For current calibrations – [gpfs/group/cjm38/default/Calibrations/](#)

*Revised: 30 Nov. 2021*

**Exp. Name:** p5555

**Operator(s):** clay

Temperature (°C):

Relative Humidity (%):

**Date/Time:** 2021-11-29

Hydraulics start: 1

Hydraulics end: 2

Data Logger/Control File:

## Purpose/Description:

Sample Block Used and Thickness with **no** Sample:

Material:
Particle Size, Distribution:
Benchtop Sample Thickness (mm):
Pre-Compaction Sample Thickness (mm):
Post-Compaction Sample Thickness (mm):

	Block 1	Block 2
Empty Block Weight (g)		
Weight of Material Used (g)		
Sample Block Weight (g)		
Weight of Gouge (g)		

## Load Cells:

Contact Area: 0.001 m<sup>2</sup>

Load cell name	Calibrations (mV/kN)	Target stress (MPa)	Init. Voltage	Volt. @ load
44mm Solid Horiz	100.123 (V/MPa): 0.1001	10	0	1.00123
44mm Solid Vert	100.123 (V/MPa): 0.1001	10	1	2.00123

## Vessel Pressures:

Calibrations (V/MPa)	Pressures (MPa)	Init. Voltage	Volt. @ load
44mm Solid Horiz	<i>PpA</i> : test	0	1.00123
44mm Solid Vert	<i>PpB</i> : test	1	2.00123
0.1456	<i>Pc</i> : test	1	2.00123

## Displacement Transducers

Name	Gain (mm/V)
Horiz. Load-point:	
Vert. Load-point	
Horiz. On-Board:	
Vert. On-Board:	

Horizontal Servo Settings	
P:	D <sub>atten</sub>
I:	Feedback:
D:	E-gain:
Vertical Servo Settings	
P:	D <sub>atten</sub>
I:	Feedback:
D:	E-gain:

Chilled water at HPS	Chiller Unit	Proc. water @ Chiller
1. Temp In (°F):	6. Panel Temp (°F):	10. Temp In (°F):
2. Pres. In (psi):	7. Panel Pres. (psi):	11. Pres. In (psi):
3. Temp Out (°F):	8. Near Pres. In (psi):	12. Temp Out (°F):
4. Pres. Out (psi):	9. Near Pres. Out (psi):	13. Pres. Out (psi):
5. Flow (lpm):		
Hyd. Power Supply (HPS)		
14. Tank Temp (°C):	15. Temp. Out (°C):	16. Pres. Out (psi):

## Experiment Notes

#