

CFNetwork

Generated by Doxygen 1.8.11

Contents

| | | |
|----------|---|-----------|
| 1 | License | 1 |
| 2 | Namespace Index | 3 |
| 2.1 | Namespace List | 3 |
| 3 | Hierarchical Index | 5 |
| 3.1 | Class Hierarchy | 5 |
| 4 | Class Index | 7 |
| 4.1 | Class List | 7 |
| 5 | File Index | 9 |
| 5.1 | File List | 9 |
| 6 | Namespace Documentation | 11 |
| 6.1 | CFNetwork Namespace Reference | 11 |
| 6.1.1 | Detailed Description | 11 |
| 6.1.2 | Enumeration Type Documentation | 12 |
| 6.1.2.1 | ConnectionFlow | 12 |
| 6.1.2.2 | SocketFamily | 12 |
| 6.1.3 | Function Documentation | 12 |
| 6.1.3.1 | parseAddress(const std::string &addr) | 12 |
| 6.1.4 | Variable Documentation | 12 |
| 6.1.4.1 | MAX_BYTES | 13 |

| | | |
|----------|--|-----------|
| 7 | Class Documentation | 15 |
| 7.1 | CFNetwork::Connection Class Reference | 15 |
| 7.1.1 | Detailed Description | 15 |
| 7.1.2 | Constructor & Destructor Documentation | 16 |
| 7.1.2.1 | Connection(const std::string &addr, int port) | 16 |
| 7.1.2.2 | Connection(const std::string &laddr, const std::string &raddr, int port, int socket) | 16 |
| 7.1.2.3 | ~Connection() | 16 |
| 7.1.3 | Member Function Documentation | 16 |
| 7.1.3.1 | getDescriptor() const | 16 |
| 7.1.3.2 | getFamily() const | 17 |
| 7.1.3.3 | getFlow() const | 17 |
| 7.1.3.4 | getListen() const | 17 |
| 7.1.3.5 | getPort() const | 17 |
| 7.1.3.6 | getRemote() const | 18 |
| 7.1.3.7 | read() const | 18 |
| 7.1.3.8 | valid() const | 18 |
| 7.1.3.9 | write(std::string data, bool newline=true) const | 18 |
| 7.1.4 | Member Data Documentation | 19 |
| 7.1.4.1 | family | 19 |
| 7.1.4.2 | flow | 19 |
| 7.1.4.3 | listen | 19 |
| 7.1.4.4 | port | 19 |
| 7.1.4.5 | remote | 19 |
| 7.1.4.6 | socket | 19 |
| 7.2 | CFNetwork::InvalidArgument Class Reference | 20 |
| 7.2.1 | Detailed Description | 20 |
| 7.3 | CFNetwork::Socket Class Reference | 20 |
| 7.3.1 | Detailed Description | 21 |
| 7.3.2 | Constructor & Destructor Documentation | 21 |
| 7.3.2.1 | Socket(const std::string &addr, int port) | 21 |

| | | |
|----------|--|-----------|
| 7.3.2.2 | ~Socket() | 21 |
| 7.3.3 | Member Function Documentation | 21 |
| 7.3.3.1 | accept() const | 21 |
| 7.3.3.2 | getDescriptor() const | 21 |
| 7.3.3.3 | getFamily() const | 22 |
| 7.3.3.4 | getHost() const | 22 |
| 7.3.3.5 | getPort() const | 22 |
| 7.3.3.6 | valid() const | 22 |
| 7.3.4 | Member Data Documentation | 23 |
| 7.3.4.1 | family | 23 |
| 7.3.4.2 | host | 23 |
| 7.3.4.3 | port | 23 |
| 7.3.4.4 | socket | 23 |
| 7.4 | CFNetwork::UnexpectedError Class Reference | 23 |
| 7.4.1 | Detailed Description | 23 |
| 8 | File Documentation | 25 |
| 8.1 | CFNetwork.cpp File Reference | 25 |
| 8.1.1 | Detailed Description | 25 |
| 8.2 | CFNetwork.hpp File Reference | 25 |
| 8.2.1 | Detailed Description | 26 |
| 8.3 | Connection.cpp File Reference | 26 |
| 8.3.1 | Detailed Description | 27 |
| 8.4 | Connection.hpp File Reference | 27 |
| 8.4.1 | Detailed Description | 27 |
| 8.5 | Socket.cpp File Reference | 28 |
| 8.5.1 | Detailed Description | 28 |
| 8.6 | Socket.hpp File Reference | 28 |
| 8.6.1 | Detailed Description | 28 |
| | Index | 29 |

Chapter 1

License

This program is free software: you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this program. If not, see <http://www.gnu.org/licenses/>.

Chapter 2

Namespace Index

2.1 Namespace List

Here is a list of all documented namespaces with brief descriptions:

| | |
|-------------------------------------|----|
| CFNetwork | 11 |
|-------------------------------------|----|

Chapter 3

Hierarchical Index

3.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

| | |
|--------------------------------------|----|
| CFNetwork::Connection | 15 |
| std::exception | |
| std::runtime_error | |
| CFNetwork::InvalidArgument | 20 |
| CFNetwork::UnexpectedError | 23 |
| CFNetwork::Socket | 20 |

Chapter 4

Class Index

4.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

| | |
|--|----|
| CFNetwork::Connection | 15 |
| CFNetwork::InvalidArgument | 20 |
| CFNetwork::Socket | 20 |
| CFNetwork::UnexpectedError | 23 |

Chapter 5

File Index

5.1 File List

Here is a list of all documented files with brief descriptions:

| | |
|--------------------------------|----|
| CFNetwork.cpp | 25 |
| CFNetwork.hpp | 25 |
| Connection.cpp | 26 |
| Connection.hpp | 27 |
| Socket.cpp | 28 |
| Socket.hpp | 28 |

Chapter 6

Namespace Documentation

6.1 CFNetwork Namespace Reference

Classes

- class [Connection](#)
- class [InvalidArgument](#)
- class [Socket](#)
- class [UnexpectedError](#)

Enumerations

- enum [ConnectionFlow](#) { [ConnectionFlow::Inbound](#), **Inbound**, [ConnectionFlow::Outbound](#), **Outbound** }
- enum [SocketFamily](#) { [SocketFamily::IPv4](#), **IPv4** = AF_INET, [SocketFamily::IPv6](#), **IPv6** = AF_INET6 }

Functions

- struct sockaddr_storage [parseAddress](#) (const std::string &addr)

Variables

- const int [MAX_BYTES](#) = 8192

6.1.1 Detailed Description

[CFNetwork](#) is a collection of utilities that simplifies the process of developing an application that will make use of the network

6.1.2 Enumeration Type Documentation

6.1.2.1 enum CFNetwork::ConnectionFlow [strong]

The `ConnectionFlow` enum is responsible for communicating whether or not a given `Connection` is setup for outbound connectivity or was received inbound from a `Socket` object

Enumerator

- Inbound** Represents an inbound `Connection`
- Outbound** Represents an outbound `Connection`

6.1.2.2 enum CFNetwork::SocketFamily [strong]

The `SocketFamily` enum is responsible for communicating which address family that a `Socket` object is using

Enumerator

- IPv4** Refers to the `AF_INET` socket family
- IPv6** Refers to the `AF_INET6` socket family

6.1.3 Function Documentation

6.1.3.1 struct sockaddr_storage CFNetwork::parseAddress (const std::string & addr)

Dynamically parse a `std::string` into a `sockaddr_storage` structure that is capable of being used in socket operations

The `struct sockaddr_storage` can be reinterpret cast into any of the following structures (after checking the `ss_family` attribute):

- `struct sockaddr`
- `struct sockaddr_in`
- `struct sockaddr_in6`

Exceptions

| | |
|---|--|
| <code><tt>InvalidArgument</tt></code> | on failure or when an unexpected address family is encountered |
|---|--|

Returns

`struct sockaddr_storage` containing the relevant information

6.1.4 Variable Documentation

6.1.4.1 CFNetwork::MAX_BYTES = 8192

The maximum number of bytes that should be contained within all buffers in this namespace's classes

Chapter 7

Class Documentation

7.1 CFNetwork::Connection Class Reference

```
#include <Connection.hpp>
```

Public Member Functions

- [Connection](#) (const std::string &addr, int [port](#))
- [Connection](#) (const std::string &laddr, const std::string &raddr, int [port](#), int [socket](#))
- [~Connection](#) ()
- int [getDescriptor](#) () const
- [SocketFamily](#) [getFamily](#) () const
- [ConnectionFlow](#) [getFlow](#) () const
- const std::string & [getListen](#) () const
- int [getPort](#) () const
- const std::string & [getRemote](#) () const
- std::string [read](#) () const
- bool [valid](#) () const
- void [write](#) (std::string data, bool newline=true) const

Protected Attributes

- [SocketFamily](#) [family](#) = [SocketFamily::IPv4](#)
- [ConnectionFlow](#) [flow](#) = [ConnectionFlow::Inbound](#)
- std::string [listen](#) = ""
- int [port](#) = 0
- std::string [remote](#) = "0.0.0.0"
- int [socket](#) = -1

7.1.1 Detailed Description

An object-oriented encapsulation for network connections

The [Connection](#) object is responsible for communication between two network endpoints. The object can be setup by accepting an incoming connection on a [Socket](#) object, or by explicitly making an outgoing connection to a given address and port

The [Connection](#) object is not copyable or assignable since it contains resources that do not lend themselves well to duplication

7.1.2 Constructor & Destructor Documentation

7.1.2.1 CFNetwork::Connection::Connection (const std::string & *addr*, int *port*)

[Connection](#) Constructor (outbound)

Allows for constructing a [Connection](#) object to an outbound endpoint

Parameters

| | |
|-------------|------------------------------------|
| <i>addr</i> | The address of the remote endpoint |
| <i>port</i> | The port of the remote endpoint |

7.1.2.2 CFNetwork::Connection::Connection (const std::string & *laddr*, const std::string & *raddr*, int *port*, int *socket*)

[Connection](#) Constructor (inbound)

Allows for constructing a [Connection](#) object from an inbound client file descriptor that was accepted by a listening socket

Parameters

| | |
|---------------|---|
| <i>laddr</i> | The address of the local listening socket |
| <i>raddr</i> | The address of the remote client |
| <i>port</i> | The port of the listening socket that received the client |
| <i>socket</i> | The file descriptor for the client |

7.1.2.3 CFNetwork::Connection::~~Connection ()

[Connection](#) Destructor

Upon destruction of a [Connection](#) object, close its associated file descriptor (if still valid)

7.1.3 Member Function Documentation

7.1.3.1 int CFNetwork::Connection::getDescriptor () const

Fetches the file descriptor of the [Connection](#) instance

The internal file descriptor can be used to perform more advanced actions that this class doesn't accommodate for

Returns

`int` representing a file descriptor

7.1.3.2 SocketFamily CFNetwork::Connection::getFamily () const

Fetches the address family of the [Connection](#) instance

See also

[SocketFamily](#) for more information on [socket](#) families

Returns

`SocketFamily` value describing the address family

7.1.3.3 ConnectionFlow CFNetwork::Connection::getFlow () const

Fetches the flow type of the [Connection](#) instance

See also

[ConnectionFlow](#) for more information on [flow](#) types

Returns

`ConnectionFlow` value describing the flow type

7.1.3.4 const std::string & CFNetwork::Connection::getListen () const

Fetches the listening address of the [Connection](#) instance

This method will produce a `std::string` of an IPv4/IPv6 address only (no IP addresses will be reverse resolved into hostnames)

In the context of an outbound [Connection](#), the resulting value will be an empty `std::string`

Returns

`std::string` containing the listening address

7.1.3.5 int CFNetwork::Connection::getPort () const

Fetches the port of the [Connection](#) instance

If the [Connection](#) represents an inbound client, the port will be that of the originating [Socket](#) listening port. For outbound connections, the port will be the original value provided during construction

Returns

`int` representing the port

7.1.3.6 `const std::string & CFNetwork::Connection::getRemote () const`

Fetches the remote address of the `Connection` instance

This method will produce a `std::string` of an IPv4/IPv6 address only (no IP addresses will be reverse resolved into hostnames)

Returns

`std::string` containing the remote peer's IP address

7.1.3.7 `std::string CFNetwork::Connection::read () const`

Attempts to read data from the internal file descriptor

Performs a blocking read on the internal file descriptor up to `MAX_BYTES - 1`. If there were zero bytes read then the `Connection` will be invalidated due to being reset by the remote peer

Exceptions

| | |
|---|--|
| <code><tt>InvalidArgument</tt></code> | if the <code>Connection</code> is invalid |
| <code><tt>UnexpectedError</tt></code> | if the <code>Connection</code> was reset by peer |

Returns

`std::string` containing the data that was read

7.1.3.8 `bool CFNetwork::Connection::valid () const`

Determines if the file descriptor is considered valid for read, write, or any other operations

A file descriptor is considered invalid if a call requesting its flags fails with the return value of `-1` or `errno` is set to `EBADF` (the provided argument is not an open file descriptor). If neither case is satisfied, the file descriptor is considered valid

See also

`fcntl()` For more information regarding this procedure's test

Returns

`true` if the file descriptor is valid, `false` otherwise

7.1.3.9 `void CFNetwork::Connection::write (std::string data, bool newline = true) const`

Attempts to write the provided data to the internal file descriptor

An optional newline character is inserted into the provided data by default, however this can be avoided using the appropriate parameter for this method.

Exceptions

| | |
|---|---|
| <code><tt>InvalidArgument</tt></code> | if the internal file descriptor is considered invalid |
|---|---|

Parameters

| | |
|----------------|---|
| <i>data</i> | <code>std::string</code> containing the contents to write |
| <i>newline</i> | Whether or not a newline character should be included |

7.1.4 Member Data Documentation

7.1.4.1 CFNetwork::Connection::family = **SocketFamily::IPv4** [protected]

Used to describe the socket family type of a [Connection](#)

7.1.4.2 CFNetwork::Connection::flow = **ConnectionFlow::Inbound** [protected]

Used to describe the connection flow direction of a [Connection](#)

7.1.4.3 CFNetwork::Connection::listen = "" [protected]

Holds the listening address associated with an inbound [Connection](#)

7.1.4.4 CFNetwork::Connection::port = 0 [protected]

Holds the listening port for an inbound [Connection](#) or the outbound port for an outbound [Connection](#)

7.1.4.5 CFNetwork::Connection::remote = "0.0.0.0" [protected]

Holds the remote address of a [Connection](#)

7.1.4.6 CFNetwork::Connection::socket = -1 [protected]

Holds the file descriptor associated with a [Connection](#)


The documentation for this class was generated from the following files:

- [Connection.hpp](#)
- [Connection.cpp](#)

7.2 CFNetwork::InvalidArgument Class Reference

```
#include <CFNetwork.hpp>
```

Inheritance diagram for CFNetwork::InvalidArgument:



7.2.1 Detailed Description

The `InvalidArgument` exception can be thrown by methods in the `CFNetwork` namespace when an invalid argument is provided. This is a non-critical exception, and can safely be caught.

The documentation for this class was generated from the following file:

- [CFNetwork.hpp](#)

7.3 CFNetwork::Socket Class Reference

```
#include <Socket.hpp>
```

Public Member Functions

- [Socket](#) (const std::string &addr, int [port](#))
- [~Socket](#) ()
- std::shared_ptr< [Connection](#) > [accept](#) () const
- int [getDescriptor](#) () const
- [SocketFamily](#) [getFamily](#) () const
- const std::string & [getHost](#) () const
- int [getPort](#) () const
- bool [valid](#) () const

Protected Attributes

- [SocketFamily](#) [family](#) = [SocketFamily::IPv4](#)
- std::string [host](#) = "0.0.0.0"
- int [port](#) = 0
- int [socket](#) = -1

7.3.1 Detailed Description

An object-oriented encapsulation for sockets

The [Socket](#) object is responsible for preparations in order to ultimately accept connections on a given listening address and port number

The [Socket](#) object is not copyable or assignable since it contains resources that do not lend themselves well to duplication

7.3.2 Constructor & Destructor Documentation

7.3.2.1 CFNetwork::Socket::Socket (const std::string & *addr*, int *port*)

[Socket](#) Constructor

Constructs a [Socket](#) object given a listening address/port and begins listening for clients

Parameters

| | |
|-------------|--|
| <i>addr</i> | std::string object containing the listen address |
| <i>port</i> | int containing the port number to listen on |

7.3.2.2 CFNetwork::Socket::~~Socket ()

[Socket](#) Destructor

Upon destruction of a [Socket](#) object, close its associated file descriptor

7.3.3 Member Function Documentation

7.3.3.1 std::shared_ptr< Connection > CFNetwork::Socket::accept () const

Accepts an incoming client and creates a [Connection](#) object for it

This method blocks execution until a client is accepted

Returns

[Connection](#) object representing the accepted client

7.3.3.2 int CFNetwork::Socket::getDescriptor () const

Fetches the file descriptor of the [Socket](#) instance

The internal file descriptor can be used to perform more advanced actions that this class doesn't accommodate for

Returns

int representing a file descriptor

7.3.3.3 `SocketFamily` `CFNetwork::Socket::getFamily () const`

Fetches the address family of the `Socket` instance

See also

`SocketFamily` for more information on `socket` families

Returns

`SocketFamily` value describing the address family

7.3.3.4 `const std::string & CFNetwork::Socket::getHost () const`

Fetches the listening address of the associated `Socket`

This method can produce a `std::string` of either an IPv4 address or an IPv6 address. This method will not produce hostnames

Returns

`std::string` of the listening address

7.3.3.5 `int CFNetwork::Socket::getPort () const`

Fetches the port of the `Socket` instance

The port should represent the value that the `Socket` was constructed with

Returns

`int` representing the port

7.3.3.6 `bool CFNetwork::Socket::valid () const`

Determines if the file descriptor is considered valid for read, write, or any other operations

A file descriptor is considered invalid if a call requesting its flags fails with the return value of `-1` or `errno` is set to `EBADF` (the provided argument is not an open file descriptor). If neither case is satisfied, the file descriptor is considered valid

See also

`fcntl()` For more information regarding this procedure's test

Returns

`true` if the file descriptor is valid, `false` otherwise

7.3.4 Member Data Documentation

7.3.4.1 CFNetwork::Socket::family = SocketFamily::IPv4 [protected]

Used to describe the socket family type of a [Socket](#)

7.3.4.2 CFNetwork::Socket::host = "0.0.0.0" [protected]

Holds the listening address associated with a [Socket](#)

7.3.4.3 CFNetwork::Socket::port = 0 [protected]

Holds the listening port associated with a [Socket](#)

7.3.4.4 CFNetwork::Socket::socket = -1 [protected]

Holds the file descriptor associated with a [Socket](#)


The documentation for this class was generated from the following files:

- [Socket.hpp](#)
- [Socket.cpp](#)

7.4 CFNetwork::UnexpectedError Class Reference

```
#include <CFNetwork.hpp>
```

Inheritance diagram for CFNetwork::UnexpectedError:



7.4.1 Detailed Description

The [UnexpectedError](#) exception can be thrown by methods in the [CFNetwork](#) namespace when an unexpected error is encountered. This is a non-critical exception, and can safely be caught

The documentation for this class was generated from the following file:

- [CFNetwork.hpp](#)

Chapter 8

File Documentation

8.1 CFNetwork.cpp File Reference

```
#include <cstring>
#include <netdb.h>
#include <string>
#include <sys/socket.h>
#include "CFNetwork.hpp"
```

Namespaces

- [CFNetwork](#)

Functions

- struct sockaddr_storage [CFNetwork::parseAddress](#) (const std::string &addr)

8.1.1 Detailed Description

Copyright

Copyright 2016 Clay Freeman. All rights reserved

License:

GNU Lesser General Public License v3 (LGPL-3.0)

Implementation source for the [CFNetwork](#) helper functions

8.2 CFNetwork.hpp File Reference

```
#include <stdexcept>
#include <string>
#include <sys/socket.h>
```

Classes

- class [CFNetwork::InvalidArgument](#)
- class [CFNetwork::UnexpectedError](#)

Namespaces

- [CFNetwork](#)

Enumerations

- enum [CFNetwork::ConnectionFlow](#) { [CFNetwork::ConnectionFlow::Inbound](#), **Inbound**, [CFNetwork::ConnectionFlow::Outbound](#), **Outbound** }
- enum [CFNetwork::SocketFamily](#) { [CFNetwork::SocketFamily::IPv4](#), **IPv4** = AF_INET, [CFNetwork::SocketFamily::IPv6](#), **IPv6** = AF_INET6 }

Functions

- struct sockaddr_storage [CFNetwork::parseAddress](#) (const std::string &addr)

Variables

- const int [CFNetwork::MAX_BYTES](#) = 8192

8.2.1 Detailed Description

Copyright

Copyright 2016 Clay Freeman. All rights reserved

License:

GNU Lesser General Public License v3 (LGPL-3.0)

Forward declaration of the [CFNetwork](#) namespace and related items

8.3 Connection.cpp File Reference

```
#include <arpa/inet.h>
#include <cstring>
#include <netinet/in.h>
#include <string>
#include <sys/errno.h>
#include <sys/fcntl.h>
#include <sys/socket.h>
#include <unistd.h>
#include "CFNetwork.hpp"
#include "Connection.hpp"
```


Namespaces

- [CFNetwork](#)

8.3.1 Detailed Description

Copyright

Copyright 2016 Clay Freeman. All rights reserved

License:

GNU Lesser General Public License v3 (LGPL-3.0)

Implementation source for the `Connection` object

8.4 Connection.hpp File Reference

```
#include <string>
#include "CFNetwork.hpp"
```

Classes

- class [CFNetwork::Connection](#)

Namespaces

- [CFNetwork](#)

8.4.1 Detailed Description

Copyright

Copyright 2016 Clay Freeman. All rights reserved

License:

GNU Lesser General Public License v3 (LGPL-3.0)

Implementation reference for the `Connection` object

8.5 Socket.cpp File Reference

```
#include <arpa/inet.h>
#include <memory>
#include <netinet/in.h>
#include <string>
#include <sys/errno.h>
#include <sys/fcntl.h>
#include <sys/socket.h>
#include <unistd.h>
#include "CFNetwork.hpp"
#include "Connection.hpp"
#include "Socket.hpp"
```

Namespaces

- [CFNetwork](#)

8.5.1 Detailed Description

Copyright

Copyright 2016 Clay Freeman. All rights reserved

License:

GNU Lesser General Public License v3 (LGPL-3.0)

Implementation source for the `Socket` object

8.6 Socket.hpp File Reference

```
#include <memory>
#include <string>
#include "CFNetwork.hpp"
```

Classes

- class [CFNetwork::Socket](#)

Namespaces

- [CFNetwork](#)

8.6.1 Detailed Description

Copyright

Copyright 2016 Clay Freeman. All rights reserved

License:

GNU Lesser General Public License v3 (LGPL-3.0)

Implementation reference for the `Socket` object

Index

- ~Connection
 - CFNetwork::Connection, [16](#)
- ~Socket
 - CFNetwork::Socket, [21](#)
- accept
 - CFNetwork::Socket, [21](#)
- CFNetwork, [11](#)
 - ConnectionFlow, [12](#)
 - IPv4, [12](#)
 - IPv6, [12](#)
 - Inbound, [12](#)
 - MAX_BYTES, [12](#)
 - Outbound, [12](#)
 - parseAddress, [12](#)
 - SocketFamily, [12](#)
- CFNetwork.cpp, [25](#)
- CFNetwork.hpp, [25](#)
- CFNetwork::Connection, [15](#)
 - ~Connection, [16](#)
 - Connection, [16](#)
 - family, [19](#)
 - flow, [19](#)
 - getDescriptor, [16](#)
 - getFamily, [16](#)
 - getFlow, [17](#)
 - getListen, [17](#)
 - getPort, [17](#)
 - getRemote, [17](#)
 - listen, [19](#)
 - port, [19](#)
 - read, [18](#)
 - remote, [19](#)
 - socket, [19](#)
 - valid, [18](#)
 - write, [18](#)
- CFNetwork::InvalidArgument, [20](#)
- CFNetwork::Socket, [20](#)
 - ~Socket, [21](#)
 - accept, [21](#)
 - family, [23](#)
 - getDescriptor, [21](#)
 - getFamily, [21](#)
 - getHost, [22](#)
 - getPort, [22](#)
 - host, [23](#)
 - port, [23](#)
 - Socket, [21](#)
 - socket, [23](#)
 - valid, [22](#)
- CFNetwork::UnexpectedError, [23](#)
- Connection
 - CFNetwork::Connection, [16](#)
- Connection.cpp, [26](#)
- Connection.hpp, [27](#)
- ConnectionFlow
 - CFNetwork, [12](#)
- family
 - CFNetwork::Connection, [19](#)
 - CFNetwork::Socket, [23](#)
- flow
 - CFNetwork::Connection, [19](#)
- getDescriptor
 - CFNetwork::Connection, [16](#)
 - CFNetwork::Socket, [21](#)
- getFamily
 - CFNetwork::Connection, [16](#)
 - CFNetwork::Socket, [21](#)
- getFlow
 - CFNetwork::Connection, [17](#)
- getHost
 - CFNetwork::Socket, [22](#)
- getListen
 - CFNetwork::Connection, [17](#)
- getPort
 - CFNetwork::Connection, [17](#)
 - CFNetwork::Socket, [22](#)
- getRemote
 - CFNetwork::Connection, [17](#)
- host
 - CFNetwork::Socket, [23](#)
- IPv4
 - CFNetwork, [12](#)
- IPv6
 - CFNetwork, [12](#)
- Inbound
 - CFNetwork, [12](#)
- listen
 - CFNetwork::Connection, [19](#)
- MAX_BYTES
 - CFNetwork, [12](#)
- Outbound
 - CFNetwork, [12](#)

- parseAddress
 - CFNetwork, [12](#)
- port
 - CFNetwork::Connection, [19](#)
 - CFNetwork::Socket, [23](#)
- read
 - CFNetwork::Connection, [18](#)
- remote
 - CFNetwork::Connection, [19](#)
- Socket
 - CFNetwork::Socket, [21](#)
- socket
 - CFNetwork::Connection, [19](#)
 - CFNetwork::Socket, [23](#)
- Socket.cpp, [28](#)
- Socket.hpp, [28](#)
- SocketFamily
 - CFNetwork, [12](#)
- valid
 - CFNetwork::Connection, [18](#)
 - CFNetwork::Socket, [22](#)
- write
 - CFNetwork::Connection, [18](#)