








Hashing

Cybersecurity
Cryptography Day 3



Today's Objectives

By the end of class, you will be able to:

-  Describe hashing and hash functions
-  Generate hashes on the command line using the CLI tools `md5sum` and `sha256sum`.
-  Discuss how hashing assists forensics investigations.
-  Crack password hashes with rainbow tables and hashcat.



Activity: Warm Up

In this activity, you'll review the cryptography concepts you've learned so far.

Instructions sent via Slack.

Suggested Time:
15 Minutes





Times Up! Let's Review.

Cryptography Warm-Up

Hashing and Data Integrity

Hashing

Hashing is used to generate a unique fingerprint for a piece of data.



Just as encryption turns plaintext into a ciphertext, hashes turn plaintext into a signature.



A hash function is a set of rules used to convert a plaintext into a signature



The hash of the string “example”: ddce269a1e3d054cae349621c198dd52



Even though has signatures are unintelligible (like cipher texts), they are used to protect **integrity**, not privacy.

Hashes to protect Integrity.

Hash functions have two properties that assist in Integrity protection.

Fixed-length output: Every hash output is the same length, regardless of plaintext input length.


The string “text” will output a hash the same length as a file as large as an OS.

Sensitivity to small change: changing a small bit in the input completely changes the hash output.

The hash output of “abcdefg” will be completely different from “abcdefj”.

Hashing

Note the fixed-length output and sensitivity to small changes.



Hash Use Cases

The following are some use cases for hashes:



Websites store hashes of passwords in their databases, rather than the plaintext password.




Antivirus scanners use hashes to “fingerprint” files.



Verify integrity and establish trust in records that underlie cryptocurrencies.



Confirm that a files was downloaded without corruption.



Instructor Demonstration

Generating Hsshes with the CLI



Activity: Inspecting and Generating Password Hashes

In this activity, you will md5sum and sha256sum to generate hashes of simple strings..*and more!*

Instructions sent via Slack.

Suggested Time:
15 Minutes





Times Up! Let's Review.

Inspecting and Generating Password Hashes



Activity: Hashes and Computer Forensics

In this activity, you will read an article about digital evidence in court cass and answer questions.

Suggested Time:
8 Minutes






Times Up! Let's Review.

Hashes and Computer Forensics

Rainbow Tables

Rainbow Tables

Although password hashes can not be inverted, they could still be cracked.
But it will take either a lot of time or a lot of disk space...



In the next activity, we'll look at how rainbow tables can be used to crack password hashes



Activity: Cracking Passwords with Rainbow Tables

In this activity, you will read an article about the function, purpose and limitation of rainbow tables, then answer corresponding questions.

Instructions sent via Slack.


Suggested Time:
8 Minutes





Times Up! Let's Review.

Rainbow Tables



Instructor Demonstration

Cracking Passwords with Hashcat



Activity: Hashcats

In this activity, you will identify the hash and hashcat flags for three files.

Instructions sent via Slack.

Suggested Time:
15 Minutes









Times Up! Let's Review.

Hashcat Activity

Today's Objectives

By the end of class, you will be able to:

-  Describe hashing and hash functions
-  Generate hashes on the command line using the CLI tools `md5sum` and `sha256sum`.
-  Discuss how hashing assists forensics investigations.
-  Crack password hashes with rainbow tables and hashcat.