HUBSAN MINI 7

Aircraft

Color	Black
Max Dimensions	Unfolded: 203*162*62mm Folded: 137*88*62mm Folded (with propellers): 137*94*62mm
Class	C0
Diagonal Wheelbase	220mm
Max Operating Current	16A
Max Ascent Speed	3m/s (N) / 4m/s (S) / 2m/s (F)
Maximum Descent Speed	3m/s (N) 3.5m/s (S) 1.52m/s (F)
Max Horizontal Flight Speed	Cinema Mode: 3m/s (F, sea level, no wind) Normal Mode: 10m/s (N, sea level, no wind) Sport Mode: 16m/s (S, sea level, no wind)
Max Takeoff Altitude	4000m
Max Wind Resistance	Level 5 (8.5-10.5 m/s)
Max Tilt Angle	40° (S) / 25° (N) / 15° (F)
Satellite Positioning System	Satellite Positioning System
Flight Time	38 mins (with 3000mAh standard battery, measured at low altitude, no wind, no recording, low-altitude flight)
Weight	<249g

Power System

Propeller	Model: Folding Propeller, Diameter 125.6mm Color: Black
ESC	Custom digital ESC, 4-in-1

Battery

Type	Lithium battery
Capacity	3000mAh (standard battery)
Nominal Voltage	3.6x2=7.2V
Charge Limit Voltage	8.4V
Charging Time	90 mins
Battery Weight	3000mAh (standard battery): 76g
Operating Temperature	0°C~50°C
Charging Temperature	0°C~40°C
Smart Battery Balancing	Supported
Smart Battery Management	Supported
Auto-Discharge Protection	Supported
Battery Warranty	12 months

Item Item

1-inch Image Sensor	1-inch CMOS Effective pixels: 48MP
Lens	FOV 84° Aperture f/1.8 Focus: 5m to infinityDistortion <1.5%
Max Video Encoding	4K@30fps
Video Recording	4K: 3840x2160@30fps
Electronic Shutter Speed	3-1/8000s
Night Mode	Supported
Vertical Screen Mode	Supported
Video Download	Wi-Fi 6E wireless fast transfer
Photo Format	JPEG
Video Format	MP4(H.264(MPEG-4 AVC)
Firmware Update	OTA
Supported Storage Card	Micro SD card, U3 or above, 16G/32G/64G/128G/1TB
Data Interface	TypeC-USB

Transmission System

Transmission Solution	SyncLeas 5.0
Max Signal Range	FCC:16km CE:16km; SRRC:16km
Average Bitrate	5Mbps
Transmission Latency	Within 250ms
Antenna	Built-in dual antenna
蓝牙	Supported
WIFI	Wi-Fi 6E Wireless Fast Transfer

Gimbal

Degrees of Freedom	3-axis
Max Control Speed (Pitch)	120°/s
Tilt Range	Pitch: -111.1° ~ +45° Roll: ±35°Yaw: ±35°

Flight Control

Flight Controller Version	Self-developed 3rd generation flight controller
Basic Flight Modes	Sport Mode / Normal Mode / Cinema Mode
Altitude Hold	TOF, barometer
Position Hold	optical flow, GPS
Unlock/Lock	Outer-eight stick movement
Fill Light	Supported, 0.5m~5m, auto light in low light
One-Key Takeoff Landing	Supported by APP and remote controller
Fail-Safe	Supported
Low Battery RTH	Supported
Home Visual Recognition (for landing pad)	Supported
Visual Tracking	3rd Generation Tracking Technology (ATVT 3.0)
Waypoint Fligh	Supported
Orbit Flight	Supported
Ray Flight	Supported
Hyperlapse	Supported
Auto Tail Slide	Supported
Motor Stall Protection	Supported
Firmware Update	App Online Update

Smart Screen Remote Controller

Color	Black
Model	HT55
Screen	5.5-inch display 1920×1080 resolution 2000nit brightness
Transmission Solution	SyncLeas 5.0
Max Signal Range	FCC:16km CE:16km; SRRC:16km
Buzzer	Supported
Built-in Battery	4500mAhx2
Operating Temperature	-10°C~70°C
Continuous Operating Time	6h
Positioning System	GPS+GLONASS+Galileo+BeiDou
Charging Time	3H
External Interfaces	Type-C USB、HDMI
Operating System	Android 10.0

Perception

Visual Perception	2nd generation visual obstacle avoidance algorithm
Home Visual Recognition (for landing pad)	Supported
Forward	Binocular vision, precision distance 0.5m~12m fluctuation <0.5m, detection range >15m
Backward	Binocular vision, precision distance 0.5m-8m Fluctuation <0.5m, detection range >12m
Downward	Monocular optical flow, TOF ranging, effective range 0.3m-5m, Fluctuation <0.1m
Visual Tracking	3rd generation tracking technology (ATVT 3.5)
Reverse Camera	Supported

APP

APP	X-Hubsan 3.0