




# FILL-RITE FR1200G\* Technical Specifications

## The Most Trusted Name in Pumps and Meters









| Pump                                |  |             |
|-------------------------------------|--|-------------|
| Type- rotary, diaphragm, gear, vane | Rotary Vane  |             |
| GPM in supplied configuration       | Up to 15   |             |
| GPM open flow - no hose or nozzle   | Up to 18.5   |             |
| By-pass pressure rating (psi) - Max | 16 psi   |             |
| Dry vac (in Hg)                     | 5  |             |
| Head- Max (Ft.)                     | 37   |             |
| Anti-siphon valve                   | None   |             |
| Inlet - Size / Thread               | 1" NPT   | 1" BSPP**   |
| Outlet – Size / Thread              | 3/4" NPT   | 3/4" BSPP** |
| Mount                               | 2" Bung NF   | 2" BSPP**   |
| Material -pump housing              | Cast Iron  |             |
| Material- wetted material           | BUNA-N   |             |
| Rotor material                      | Powdered Iron  |             |
| Rotor vane material                 | Sintered Bronze                                      |             |
| Compatible fluids                   | Diesel, gasoline, BioDiesel up to B20, E15, Kerosene |             |
| Strainer Mesh Size                  | 20 x 20  |             |
| Warranty                            | 2 Years  |             |

| Motor                            |                                     |
|----------------------------------|-------------------------------------|
| Power - AC 115, 230, 115/230 VAC | N/A                                 |
| HZ 50, 60, 50/60                 | N/A                                 |
| Power - DC 12, 24, 12/24         | 12                                  |
| HP (horsepower) rating           | 1/4 HP                              |
| Power cord length (feet)         | 18'                                 |
| Power cord gauge (AWG)           | 12 AWG                              |
| DC Power cord connectors         | NONE                                |
| Amps (FLA)                       | 20                                  |
| RPM                              | 2600                                |
| Duty cycle                       | 30 min.                             |
| Thermal protection switch        | Yes                                 |
| Circuit protection fuse          | NONE                                |
| Certification                    | UL, cUL Motor, ATEX, CE**,<br>ANZEx |


#### \*1200G Series pumps models: FR1204G, FR1210G, FR1211G, FR1205GE\*\*, FR1211GEL\*\*, FR1211GELA\*\*, FR1210GE\*\*, FR1210GEA\*\*

<sup>\*\*\*</sup> Specification will vary with specific model chosen.



<sup>\*\* &</sup>quot;E" models are CE Certified for use in Europe.

### **Performance Data**



## **Service Kit Information**

| Kit      | Description             | Parts   |
|----------|-------------------------|---|
| KIT120BD | BioDiesel Kit           | O-ring seal, bypass valve poppet, bypass cap seal, inlet seal         |
| KIT120RG | Rotor & Vane Kit        | Rotor cover, rotor, vanes, rotor key, O-ring seal, attaching hardware |
| KIT120JC | Junction Cover Kit      | Junction cover, seal  |
| KIT120SL | Seal Kit                | O-ring, shaft seals, retainer clip                                    |
| KIT120BV | By-Pass Service Kit     | Screen, bypass valve, valve spring, bypass cap. O-ring seal           |
| KIT120NB | Nozzle Boot Kit         | Nozzle boot, attaching hardware                                       |
| KIT120BG | Inlet Flange Kit        | Inlet flange (bung), attaching hardware, inlet seal, screen           |
| KIT120SG | Inlet Gasket and Screen | Gasket for inlet (bung) and screen                                    |
| KIT120SW | Switch Lever Kit        | Switch lever, mounting hardware                                       |

| Accessories                                |                          |
|--|--------------------------|
| Suction pipe material                      | N/A                      |
| Suction pipe length- extended/not extended | None                     |
| Nozzle- size                               | N/A***                   |
| Nozzle- manual / automatic                 | N/A***                   |
| Hose liquid materials compatibility        | Oil, Gasoline, Diesel*** |
| Hose diameter                              | 3/4"***                  |
| Hose length                                | N/A***                   |
| Hose static wire (Y/N)                     | N/A***                   |

| Logistics |                    |
|-----------|--------------------|
| UPC       | 0-89404-17578-1*** |
| Length    | 15.5"              |
| Width     | 10"                |
| Height    | 6.5"               |

\*1200G Series pumps models: FR1204G, FR1210G, FR1211G, FR1205GE\*\*, FR1211GEL\*\*, FR1211GELA\*\*, FR1210GE\*\*, FR1210GEA\*\*

<sup>\*\*\*</sup> Specification will vary with specific model chosen.



 $<sup>^{\</sup>star\star}$  "E" models are CE Certified for use in Europe.